

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 1 of 13

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

BISMUTH NITRATE

OTHER NAMES

Bi-N3-O9, Bi(NO3)3, "bismuth ternitrate", "bismuth trinitrate", "nitric acid, bismuth(3+) salt", "bismuth nitrate, hydrate (1:5)"

PROPER SHIPPING NAME

NITRATES, INORGANIC, N.O.S.
(contains bismuth nitrate)

PRODUCT USE

Used in preparation of other bismuth salts, bismuth lustre on tin, luminous paints and enamels, precipitation of alkaloids.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 2 of 13

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Oral) Category 5
Eye Irritation Category 2A
Oxidizing Solid Category 2
Respiratory Irritation Category 3
Skin Corrosion/Irritation Category 3



EMERGENCY OVERVIEW

HAZARD

DANGER
Determined by using GHS criteria:
H335 H273 H303 H316 H319
May cause respiratory irritation
May intensify fire; oxidizer
May be harmful if swallowed
Causes mild skin irritation
Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Wash hands thoroughly after handling.
Take any precaution to avoid mixing with combustible or incompatible materials.
Keep away from heat.

Response

If skin irritation occurs, seek medical advice/attention.
Wear eye/face protection.
If eye irritation persists, get medical advice/attention.
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

Store away from combustibles and incompatible materials

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 3 of 13

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
bismuth nitrate	10361-44-1	> 99

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.

- For advice, contact a Poisons Information Centre or a doctor.

Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

- Induce vomiting with fingers down the back of the of the throat, ONLY IF CONSCIOUS.

- Lean patient forward or place on left side (head-down position if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.

- If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided.

Further action will be the responsibility of the medical specialist.

- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.

- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

- Transport to hospital or doctor without delay.

- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.

- Flush skin and hair with running water (and soap if available).

- Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.

- Encourage patient to blow nose to ensure clear passage of breathing.

- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

The toxicity of nitrates and nitrites result from their vasodilating properties and their propensity to form methaemoglobin.

- Most produce a peak effect within 30 minutes.

- Clinical signs of cyanosis appear before other symptoms because of the dark

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 4 of 13

Section 4 - FIRST AID MEASURES

pigmentation of methaemoglobin.

- Initial attention should be directed towards improving oxygen delivery, with assisted ventilation, if necessary. Hyperbaric oxygen has not demonstrated conclusive benefits.
- Institute cardiac monitoring, especially in patients with coronary artery or pulmonary disease.
- Hypotension should respond to Trendelenburg's position and intravenous fluids; otherwise dopamine may be needed.
- Naloxone, glucose and thiamine should be given if a multiple ingestion is suspected.
- Decontaminate using Ipecac Syrup for alert patients or lavage for obtunded patients who present within 2-4 hours of ingestion.
- Symptomatic patients with methaemoglobin levels over 30% should receive methylene blue. (Cyanosis alone, is not an indication for treatment). The usual dose is 1-2 mg/kg of a 1% solution (10 mg/ml) IV over 5 minutes; repeat, using the same dose if symptoms of hypoxia fail to subside within 1 hour.

[Ellenhorn and Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker who has been exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
1. Methaemoglobin in blood	1.5% of haemoglobin	During or end of shift	B, NS, SQ

B: Background levels occur in specimens collected from subjects NOT exposed

NS: Non-specific determinant; also observed after exposure to other materials

SQ: Semi-quantitative determinant - Interpretation may be ambiguous; should be used as a screening test or confirmatory test.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Jets of water.
- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water course.
- Fight fire from a safe distance, with adequate cover.
- Extinguishers should be used only by trained personnel.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- If fire gets out of control withdraw personnel and warn against entry.
- Equipment should be thoroughly decontaminated after use.

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 5 of 13

Section 5 - FIRE FIGHTING MEASURES

FIRE/EXPLOSION HAZARD

- Will not burn but increases intensity of fire.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- Heat affected containers remain hazardous.
- Contact with combustibles such as wood, paper, oil or finely divided metal may produce spontaneous combustion or violent decomposition.
- May emit irritating, poisonous or corrosive fumes.

Decomposes on heating and produces toxic fumes of: nitrogen oxides (NO_x).

Personal Protective Equipment

Gloves, boots (chemical resistant).

Breathing apparatus - high vapour/dust levels only.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- No smoking, naked lights, ignition sources.
- Avoid all contact with any organic matter including fuel, solvents, sawdust, paper or cloth and other incompatible materials, as ignition may result.
- Avoid breathing dust or vapours and all contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with dry sand, earth, inert material or vermiculite.
- DO NOT use sawdust as fire may result.
- Scoop up solid residues and seal in labelled drums for disposal.
- Neutralise/decontaminate area.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus and protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- No smoking, flames or ignition sources.
- Increase ventilation.
- Contain spill with sand, earth or other clean, inert materials.
- NEVER USE organic absorbents such as sawdust, paper or cloth.
- Use spark-free and explosion-proof equipment.
- Collect any recoverable product into labelled containers for possible recycling.
- Avoid contamination with organic matter to prevent subsequent fire and explosion.
- DO NOT mix fresh with recovered material.
- Collect residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- Decontaminate equipment and launder all protective clothing before storage and re-use.
- If contamination of drains or waterways occurs advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 6 of 13

Section 6 - ACCIDENTAL RELEASE MEASURES

bismuth nitrate 500 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

bismuth nitrate 25 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

bismuth nitrate 4 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:

bismuth nitrate 1.25 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid personal contact and inhalation of dust, mist or vapours.
- Always wear protective equipment and wash off any spillage on clothing.
- Use in well ventilated areas, prevent accumulation of vapours.
- Keep material away from light, heat, ignition sources, flammables or combustibles.
- Keep dry and away from incompatible materials.
- Keep cool and below defined Control Temperature.
- Avoid friction, shock or containment.
- Use non-sparking equipment.
- Avoid physical damage to containers
- DO NOT repack or return unused portions to original container.
- Withdraw only sufficient material for immediate use.
- Contamination can cause VIOLENT DECOMPOSITION with intense heat and fire.
- Ensure proper rotation of stocks to limit decomposition and instability which may occur on long storage.
- When handling NEVER smoke, eat or drink.

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 7 of 13

Section 7 - HANDLING AND STORAGE

- Always wash hands with soap and water after handling.
- Use only good occupational work practice.
- Observe manufacturer's storing and handling directions.

SUITABLE CONTAINER

Glass container.
Plastic container.
Plastic drum.
Polylined drum.
• Check that containers are clearly labelled.
Packaging as recommended by manufacturer.

STORAGE INCOMPATIBILITY

Oxidising agents as a class are not necessarily combustible themselves, but can increase the risk and intensity of fire in many other substances.
Avoid storage with organic materials, reducing agents, combustible materials and metals such as iron and copper and their alloys.

STORAGE REQUIREMENTS

Keep dry.
• Store in original containers.
• Keep containers securely sealed as supplied.
• Store in a cool, well ventilated area.
• Keep dry.
• Store under cover and away from sunlight.
• Store away from flammable or combustible materials, debris and waste. Contact may cause fire or violent reaction.
• Store away from incompatible materials and foodstuff containers.
• DO NOT stack on wooden floors or pallets.
• Protect containers from physical damage.
• Check regularly for leaks.
• Observe manufacturer's storage and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- bismuth nitrate:

CAS:10361- 44- 1 CAS:10035- 06- 0 CAS:30880- 06- 9
CAS:35938- 70- 6 CAS:15008- 64- 7 CAS:14550- 88- 0
CAS:20394- 23- 4 CAS:13536- 44- 2

MATERIAL DATA

These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

Extensive concentrations of P.N.O.C.s may:

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 8 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- seriously reduce visibility,
- cause unpleasant deposits in the eyes, ears and nasal passages,
- contribute to skin or mucous membrane injury by chemical or mechanical action, per se, or by the rigorous skin cleansing procedures necessary for their removal. [ACGIH]


This limit does not apply:

- to brief exposures to higher concentrations
- nor does it apply to those substances that may cause physiological impairment at lower concentrations but for which a TLV has as yet to be determined.

This exposure standard applies to particles which

- are insoluble or poorly soluble* in water or, preferably, in aqueous lung fluid (if data is available) and
- have a low toxicity (i.e.. are not cytotoxic, genotoxic, or otherwise chemically reactive with lung tissue, and do not emit ionizing radiation, cause immune sensitization, or cause toxic effects other than by inflammation or by a mechanism of lung overload).

PERSONAL PROTECTION



EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Wear safety footwear.

OTHER

- Overalls.
- Eyewash unit.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 9 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 10 of 13

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Lustrous, clear, colourless, hygroscopic crystals with acid taste.
Slight nitric acid odour. Slowly decomposed by water to the subnitrate.
Soluble in dilute nitric acid, glycerol, dilute acids, including acetic acid and acetone. Practically insoluble in alcohol and ethyl acetate.

PHYSICAL PROPERTIES

Solid.
Mixes with water.
Contact with acids liberates toxic gas.

Molecular Weight: 485.11; (395.02
Melting Range (°C): Not available.
Solubility in water (g/L): Miscible
pH (1% solution): Not available
Volatile Component (%vol): Not applicable.
Relative Vapour Density (air=1): >1
Lower Explosive Limit (%): Not applicable
Autoignition Temp (°C): Not applicable
State: Divided solid

Boiling Range (°C): 75- 80 decomposes
Specific Gravity (water=1): 2.83
pH (as supplied): Not applicable
Vapour Pressure (kPa): Not applicable.
Evaporation Rate: Not applicable
Flash Point (°C): Not applicable
Upper Explosive Limit (%): Not applicable
Decomposition Temp (°C): Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable under normal handling conditions.
- Prolonged exposure to heat.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be damaging to the health of the individual.
Ingestion may result in nausea, abdominal irritation, pain and vomiting.
Absorbed bismuth salts permeate the body fluids and tissues and are excreted mainly in the urine but some bismuth is retained in tissues. It is deposited in the metaphyses of young bones and can pass the placenta into the foetus.

Effects of acute bismuth intoxication are gastro-intestinal disturbance, anorexia, headache, malaise, skin reactions, discolouration of mucous membranes and mild jaundice. Albuminuria (albumin in the urine) is an indication of kidney damage. Bismuth may cause a reverse encephalopathy (brain disease) that takes 2 to 10 weeks to reverse spontaneously.

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 11 of 13

Section 11 - TOXICOLOGICAL INFORMATION

EYE

Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.

Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

SKIN

Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Solution of material in moisture on the skin, or perspiration, may increase irritant effects.

Open cuts, abraded or irritated skin should not be exposed to this material.

INHALED

Limited evidence exists, or practical experience predicts, that the material produces irritation of the respiratory system in a significant number of individuals following inhalation.

Although inhalation is not thought to produce harmful effects (as classified under EC Directives), the material may still produce health damage, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally confined to doses producing mortality rather than those producing morbidity (disease, ill-health).

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and inhalation of generated dusts.

Symptoms of chronic bismuth toxicity in humans consist of decreased appetite, weakness, rheumatic pain, diarrhoea, fever, foul breath, gingivitis and dermatitis. A blue line of the gums, the "bismuth line", may persist for years after exposure has ceased. Jaundice and conjunctival haemorrhage are rare, but have been reported. Bismuth neuropathy (kidney damage), with proteinuria may occur. The kidney is the site of highest concentration with liver concentrations being significantly lower. Renal failure may be reversible if treated early but anuria and death have occurred.

TOXICITY AND IRRITATION

TOXICITY

for pentahydrate:

IRRITATION

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 12 of 13

Section 11 - TOXICOLOGICAL INFORMATION

Oral (rat) LD50: 4042 mg/kg

Nil Reported

Section 12 - ECOLOGICAL INFORMATION

No data for bismuth nitrate.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible. Special hazard may exist - specialist advice may be required.
- Consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury or incinerate residue at an approved site.
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
- Puncture containers to prevent re-use and bury at an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: OXIDIZING AGENT
HAZCHEM: 1[Z]

UNDG:

Dangerous Goods Class:	5.1	Subrisk:	None
UN Number:	1477	Packing Group:	II
Shipping Name: NITRATES, INORGANIC, N.O.S. (contains bismuth nitrate)			

Air Transport IATA:

ICAO/IATA Class:	5.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1477	Packing Group:	II
ERG Code:	5L		
Shipping name: NITRATES, INORGANIC, N.O.S. (contains bismuth nitrate)			

Maritime Transport IMDG:

IMDG Class:	5.1	IMDG Subrisk:	None
UN Number:	1477	Packing Group:	II
EMS Number:	F- A, S- Q		
Shipping name: NITRATES, INORGANIC, N.O.S. (contains bismuth nitrate)			

continued...

BISMUTH NITRATE

GHS Safety Data Sheet

Version No : 2.0

Page 13 of 13

Section 15 - REGULATORY INFORMATION

REGULATIONS

No regulations applicable

No data available for bismuth nitrate as CAS: 10361-44-1, CAS: 10035-06-0, CAS: 30880-06-9, CAS: 35938-70-6, CAS: 15008-64-7, CAS: 14550-88-0, CAS: 20394-23-4, CAS: 13536-44-2.

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
bismuth nitrate	10361- 44- 1, 10035- 06- 0, 30880- 06- 9, 35938- 70- 6, 15008- 64- 7, 14550- 88- 0, 20394- 23- 4, 13536- 44- 2

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 12-May-2018