

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 1 of 18

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

HYDROCHLORIC ACID 35-38%

OTHER NAMES

HCl, "hydrochloric acid 28-37%", "Convol analytical reagent", "spirits of salts", "spirits of salt", "chlorohydric acid gas", "muriatic acid", "hydrogen chloride aqueous solution", hydrochloride

PROPER SHIPPING NAME

HYDROCHLORIC ACID

PRODUCT USE

For pickling and heavy duty cleaning of metal parts; rust and scale removal.
The production of chlorides; neutralising bases; a laboratory reagent.
For hydrolyzing starch and proteins in preparations for food.
As a catalyst and solvent in organic synthesis.
As "spirits of salts" for cleaning of lime and masonry from new brickwork.
As flux or flux component for soldering; manufacture of "killed spirits".

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 2 of 18

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Inhalation) Category 2

Acute Toxicity (Oral) Category 4

Metal Corrosion Category 1

Skin Corrosion/Irritation Category 1B



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:

H330 H302 H290 H314

Fatal if inhaled

Harmful if swallowed

May be corrosive to metals

Causes severe skin burns and eye damage

PRECAUTIONARY STATEMENTS

Prevention

Wear protective gloves/clothing and eye/face protection.

Wash hands thoroughly after handling.

Wear respiratory protection.

Do not breathe dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well ventilated area.

Do not eat, drink or smoke when using this product.

Do not breathe dust or mist.

Wash thoroughly after handling.

Response

Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Keep container tightly closed.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Specific treatment: refer to Label or MSDS.

If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower.

Absorb spillage to prevent material damage.

Immediately call a POISON CENTER or doctor/physician.

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 3 of 18

Section 2 - HAZARDS IDENTIFICATION

Storage

Store in a corrosive resistant container with a resistant liner.
Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
hydrogen chloride	7647-01-0	30-35
water	7732-18-5	65-70

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
- Immediately flush body and clothes with large amounts of water, using safety shower if available.
 - Quickly remove all contaminated clothing, including footwear.
 - Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
 - Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 4 of 18

Section 4 - FIRST AID MEASURES

- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

Treat symptomatically.

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology].

If exposure has been severe and/or symptoms marked, observation in hospital for 48 hours should be considered due to possibility of delayed pulmonary oedema.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 5 of 18

Section 5 - FIRE FIGHTING MEASURES

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
 - Not considered to be a significant fire risk.
 - Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - May emit corrosive, poisonous fumes. May emit acrid smoke.
- Decomposition may produce toxic fumes of: hydrogen chloride.

FIRE INCOMPATIBILITY

None known.

Personal Protective Equipment

Breathing apparatus.
Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Chemical Class:acidic compounds, inorganic

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
LAND SPILL - SMALL				
foamed glass - pillows	1	throw	pitchfork	R, P, DGC, RT
expanded mineral - particulate	2	shovel	shovel	R, I, W, P, DGC
foamed glass -	2	shovel	shovel	R, W, P, DGC

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 6 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

particulate

LAND SPILL - MEDIUM

expanded mineral - particulate	1	blower	skiploader	R, I, W, P, DGC
foamed glass- particulate	2	blower	skiploader	R, W, P, DGC
foamed glass - particulate	3	throw	skiploader	R, W, P, DGC

Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT: Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

hydrochloric acid 150 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

hydrochloric acid 20 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

hydrochloric acid 3 ppm

The threshold concentration below which most people will experience no appreciable risk of health effects:

hydrochloric acid 0.5 ppm

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 7 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.
 - Avoid smoking, naked lights or ignition sources.
 - Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 - Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately. Launder contaminated clothing before re-use.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- DO NOT use aluminium or galvanised containers.
- Lined metal can, lined metal pail/ can.
 - Plastic pail.
 - Polyliner drum.
 - Packing as recommended by manufacturer.
 - Check all containers are clearly labelled and free from leaks.

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 8 of 18

Section 7 - HANDLING AND STORAGE

STORAGE INCOMPATIBILITY

Reacts vigorously with alkalis.

Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.

- Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.

- Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts.

- Neutralisation can generate dangerously large amounts of heat in small spaces.

- The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.

- The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.

- Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.

- Inorganic acids can initiate the polymerisation of certain classes of organic compounds.

- Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.

- Inorganic acids generate flammable and/or toxic gases in contact with dithiocarbamates, isocyanates, mercaptans, nitrides, nitriles, sulfides, and strong reducing agents.

Additional gas-generating reactions occur with sulfites, nitrites, thiosulfates (to give H₂S and SO₃), dithionites (SO₂), and even carbonates.

- Acids often catalyse (increase the rate of) chemical reactions.

Avoid storage with metals, metal oxides, hydroxides, amines, carbonates, alkaline materials, acetic anhydride, cyanides, sulphides, sulphites, phosphides, acetylides, borides, carbides, silicides, vinyl acetate, formaldehyde and potassium permanganate.

Reacts with zinc, brass, galvanised iron, aluminium, copper and copper alloys.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- | | | |
|----------------------|-----------------|-------------------------------------|
| • hydrochloric acid: | CAS:7647- 01- 0 | CAS:7698- 05- 7 |
| • hydrogen chloride: | CAS:7647- 01- 0 | CAS:7698- 05- 7 |
| • water: | CAS:7732- 18- 5 | CAS:558440- 53- 2 CAS:558440- 22- 5 |

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
hydrochloric acid		50
hydrogen chloride		50

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 9 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ODOUR SAFETY FACTOR (OSF)

OSF=1.3 (HYDROGEN CHLORIDE)

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

MATERIAL DATA

Odour Threshold Value: 0.262 ppm (detection), 10.06 ppm (recognition)

NOTE: Detector tubes for hydrochloric acid, measuring in excess of 1 ppm, are available commercially.

Hydrogen chloride is a strong irritant to the eyes, mucous membranes and skin. Chronic exposure produces a corrosive action on the teeth. Reports of respiratory irritation following short-term exposure at 5 ppm have lead to the recommended TLV-C. There is no indication that skin contact with hydrogen chloride elicits systemic poisoning and a skin designation has not been applied.

Exposure of humans to hydrogen chloride at 50 to 100 ppm for 1 hour is reported to be barely tolerable; 35 ppm caused irritation of the throat on short exposure and 10 ppm was the maximal concentration for prolonged exposure. It has been stated that hydrogen chloride at concentrations of 5 ppm is immediately irritating.

Toxic effects of hydrochloric acid

Concentration

Clinical effects

0.067 - 0.267 ppm
changes in respiratory pattern
5 ppm
10 ppm

Reported range of odour thresholds and
No organic damage
Irritation; work undisturbed

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet


Version No:3

Page 10 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

10-50 ppm	Work difficult but possible
35 ppm	Short exposure irritation of the throat
50-100 ppm	Exposure for 1 h barely tolerable
1000-2000 ppm	Brief exposure dangerous; laryngospasm
1300-2000 ppm	Lethal after a few minutes

PERSONAL PROTECTION



EYE

- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Elbow length PVC gloves.

When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection: hydrochloric acid

Protective Material CPI *.

BUTYL
BUTYL/NEOPRENE
HYPALON

A
A
A

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 11 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

NEOPRENE	A
NEOPRENE/NATURAL	A
NITRILE+PVC	A
PE/EVAL/PE	A
SARANEX- 23	A
VITON/NEOPRENE	A
PVC	A
NITRILE	A
NATURAL RUBBER	B
NATURAL+NEOPRENE	B
NAT+NEOPR+NITRILE	C

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	B- AUS P	-
1000	50	-	B- AUS P
5000	50	Airline *	-
5000	100	-	B- 2 P
10000	100	-	B- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 12 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air). aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	Air Speed: 0.25- 0.5 m/s (50- 100 f/min.) 0.5- 1 m/s (100- 200 f/min.) 1- 2.5 m/s (200- 500 f/min.) 2.5- 10 m/s (500- 2000 f/min.)
---	--

Within each range the appropriate value depends on:

Lower end of the range 1: Room air currents minimal or favourable to capture 2: Contaminants of low toxicity or of nuisance value only. 3: Intermittent, low production. 4: Large hood or large air mass in motion	Upper end of the range 1: Disturbing room air currents 2: Contaminants of high toxicity 3: High production, heavy use 4: Small hood- local control only
--	---

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear to light yellow (orange tint for inhibited grades) fuming corrosive liquid with sharp, suffocating odour.
CARE: mixes with water but generates heat, may cause dangerous boiling.
Concentrate and solutions are acidic and strongly corrosive.
Material is a solution of corrosive hydrogen chloride gas in water.
Commercial grades contain 28-37% hydrogen chloride HCl and at room temperature slowly gives off significant levels of acidic HCl gas.
Odour becomes disagreeable at 5-10 ppm.

continued...

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 13 of 18

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Liquid.
Mixes with water.
Corrosive.
Acid.
Toxic or noxious vapours/gas.

Molecular Weight: Not applicable.
Melting Range (°C): > - 74
Solubility in water (g/L): Miscible
pH (1% solution): 1.2
Volatile Component (%vol): approx. 100
Relative Vapour Density (air=1): 1.3
Lower Explosive Limit (%): Not applicable.
Autoignition Temp (°C): Not available.
State: Liquid

Boiling Range (°C): > 50
Specific Gravity (water=1): 1.14- 1.19
pH (as supplied): 0.9
Vapour Pressure (kPa): < 25 @ 25 C
Evaporation Rate: Slow
Flash Point (°C): Not combustible
Upper Explosive Limit (%): Not applicable.
Decomposition Temp (°C): Not Available
Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

Contact with alkaline material liberates heat.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.

Ingestion of acidic corrosives may produce circumoral burns with a distinct discolouration of the mucous membranes of the mouth, throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. Oedema of the epiglottis may produce respiratory distress and possibly, asphyxia. Nausea, vomiting, diarrhoea and a pronounced thirst may occur. More severe exposures may produce a vomitus containing fresh or dark blood and large shreds of mucosa. Shock, with marked hypotension, weak and rapid pulse, shallow respiration and clammy skin may be symptomatic of the exposure. Circulatory collapse may, if left untreated, result in renal failure. Severe cases may show gastric and oesophageal perforation with peritonitis, fever and abdominal rigidity. Stricture of the oesophageal, gastric and pyloric sphincter may occur as within several weeks or may be delayed for years. Death may be rapid and often results from asphyxia, circulatory collapse or aspiration of even minute amounts. Delayed deaths may be due to peritonitis, severe nephritis or pneumonia. Coma and convulsions may be terminal.

Accidental ingestion of the material may be damaging to the health of the individual.

EYE

The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.

continued...

HYDROCHLORIC ACID 35-38% (1.18)

Section 11 - TOXICOLOGICAL INFORMATION

When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.

Direct eye contact with acid corrosives may produce pain, lachrymation, photophobia and burns. Mild burns of the epithelia generally recover rapidly and completely. Severe burns produce long-lasting and possible irreversible damage. The appearance of the burn may not be apparent for several weeks after the initial contact. The cornea may ultimately become deeply vascularised and opaque resulting in blindness.

The material may be irritating to the eye, with prolonged contact causing inflammation.

Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

The material can produce chemical burns following direct contact with the skin.

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects.

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation.

In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Acidic corrosives produce respiratory tract irritation with coughing, choking and mucous membrane damage. Symptoms of exposure may include dizziness, headache, nausea and weakness. In more severe exposures, pulmonary oedema may be evident either immediately or after a latent period of 5-72 hours. Symptoms of pulmonary oedema include a tightness in the chest, dyspnoea, frothy sputum and cyanosis. Examination may reveal hypotension, a weak and rapid pulse and moist rates. Death, due to anoxia, may occur several hours after onset of the pulmonary oedema.

Inhalation of quantities of liquid mist may be extremely hazardous, even lethal due to spasm, extreme irritation of larynx and bronchi, chemical pneumonitis and pulmonary oedema.

CHRONIC HEALTH EFFECTS

Repeated or prolonged exposure to acids may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue.

Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of

HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 15 of 18

Section 11 - TOXICOLOGICAL INFORMATION

preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Repeated exposure to low vapour concentrations can cause skin tenderness, bleeding of the nose and gums, chronic bronchitis, gastritis.

TOXICITY AND IRRITATION

TOXICITY

Unreported (man) LDLo: 81 mg/kg

Inhalation (human) LCLo: 1300 ppm/30 min

Inhalation (human) LCLo: 3000 ppm/5 min

Inhalation (rat) LC50: 3124 ppm/1h

Oral (rat) LD50: 900 mg/kg

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

IRRITATION

Eye (rabbit): 5mg/30s - Mild

Section 12 - ECOLOGICAL INFORMATION

Hazardous Air Pollutant: Yes

Fish LC50 (96hr.) (mg/l): 0.282

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Ecotoxicity

Fish LC100 (24 h): trout 10 mg/l

TLm (96 h): mosquito fish 282 ppm (fresh water)

LC50: goldfish 178 mg/l

Shrimp LC50 (48 h): 100 - 330 ppm (salt water)

Starfish LC50 (48 h): 100 - 330 mg/l

Cockle LC50 (48 h): 330 - 1000 mg/l

[Hach]

Hydrogen chloride in water dissociates almost completely, releasing hydrogen and chloride ions; the hydrogen ions are captured by water to produce hydronium ions.

Hydrochloric acid infiltrates soil, the rate dependent on moisture content. During soil transport, hydrochloric acid dissolves soil components.

Drinking water standard:

chloride: 400 mg/l (UK max.)

250 mg/l (WHO guideline)

continued...

HYDROCHLORIC ACID 35-38% (1.18)

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 - Treat and neutralise at an approved treatment plant. Treatment should involve : Neutralisation with soda-ash or soda-lime followed by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material).
 - Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.
 - Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

WASTE DISPOSAL PROCEDURES

- Wear protective clothing, nitrile rubber gloves, eye protection and a self contained breathing apparatus to control personal contact from hydrochloric acid. In a well ventilated area, add the hydrochloric acid to cold water. Neutralise the contents with soda ash or calcium carbonate. Wash the solution into the drain. Dispose of any recoverable solid with normal refuse [Armour 1996].

SPILLAGE DISPOSAL

- Clear area of personnel. Wear protective clothing, nitrile rubber gloves, eye protection and breathing apparatus to control personal contact from hydrochloric acid. Cover the spill with a 1:1:1 mixture by weight of calcium carbonate or sodium carbonate, bentonite and sand. Scoop the absorbed hydrochloric acid mixture into a container and transfer to a well ventilated area. Add the mixture to a container of cold water. Neutralise with sodium carbonate, and decant the solution into the drain. Discard any recoverable solid with normal refuse [Armour 1996].

Section 14 - TRANSPORTATION INFORMATION



HYDROCHLORIC ACID 35-38% (1.18)

GHS Safety Data Sheet

Version No:3

Page 17 of 18

Section 14 - TRANSPORTATION INFORMATION

Labels Required: CORROSIVE
HAZCHEM: 2R

UNDG:

Dangerous Goods Class:	8	Subrisk:	None
UN Number:	1789	Packing Group:	II
Shipping Name: HYDROCHLORIC ACID			

Air Transport IATA:

ICAO/IATA Class:	8	ICAO/IATA Subrisk:	None
UN/ID Number:	1789	Packing Group:	II
ERG Code:	8L		
Shipping name: HYDROCHLORIC ACID			

Maritime Transport IMDG:

IMDG Class:	8	IMDG Subrisk:	None
UN Number:	1789	Packing Group:	II
EMS Number:	F- A, S- B		
Shipping name: HYDROCHLORIC ACID			

Section 15 - REGULATORY INFORMATION

REGULATIONS

hydrochloric acid (CAS: 7647-01-0) is found on the following regulatory lists;

- CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP
- IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
- International Agency for Research on Cancer (IARC) Carcinogens
- International Council of Chemical Associations (ICCA) - High Production Volume List
- International Maritime Dangerous Goods Requirements (IMDG Code) - Goods Forbidden for Transport
- OECD Representative List of High Production Volume (HPV) Chemicals
- United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control - Table II
- WHO Guidelines for Drinking-water Quality - Chemicals for which guideline values have not been established

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
water	7732- 18- 5, 558440- 53- 2, 558440- 22- 5

continued...

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 16-Aug-2017