

SODIUM CHLORIDE

GHS Safety Data Sheet

Version No:2

Page 1 of 11

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

SODIUM CHLORIDE

OTHER NAMES

NaCl, "common salt", halite, rocksalt, "rock salt", "sea salt", saline, salt, "Saxa table salt", "dendritis white crystal", "Natrii chloridum", "solar salt", "vacuum salt", "PDV salt", "butter salt", "Merck 10241", "Sigma S9625", APS, "Chem-Supply sodium chloride", "LR SL046", "BP SP046", "AR SA046", "Selby sodium chloride", "Pronalys BSPSL944", "TG ST046", "FG SP046", "Salt water softener granular sodium ST180", "All Purpose Purex Salt", "Canning and Pickling Salt", "Culinox 999 Chemical Grade Salt", "Culinox 999 Food Grade Salt", "Evaporated Granulated Salt", "Fine Mixing Salt", "H.G. Blending Salt", "Industrial Grade Solar Salt", "Kleer Fine Salt", "Kleer Granulated Salt", "Mill Run Salt", "Purex Salt", "Purex Select Salt", "Reagent Grade sodium chloride", "Refined Sea Salt", "Rock Pretzel Salt", "Rock Salt for making Ice Cream", Safe-T-Salt, "Sevice Pack Salt", "Ship n'Store Rock Salt", "USP sodium chloride", "White Crystal Rock salt", "White Crystal Solar Salt", "White Crystals Water Softening Solar Salt"

PRODUCT USE

As a source of chlorine and sodium.
 In the curing of hides; in glazing of pottery; in metallurgy.
 Preservative for a wide range of packaged foods.
 Minor use as household food seasoning. Laboratory reagent.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,
 248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



continued...

SODIUM CHLORIDE

GHS Safety Data Sheet

Version No:2

Page 2 of 11

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Oral) Category 5
Eye Irritation Category 2B
Skin Corrosion/Irritation Category 3

EMERGENCY OVERVIEW

HAZARD

WARNING
Determined by using GHS criteria:
H303 H316 H320
May be harmful if swallowed
Causes mild skin irritation
Causes eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Wash hands thoroughly after handling.

Response

If skin irritation occurs, seek medical advice/attention.
If eye irritation persists, get medical advice/attention.
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
sodium chloride	7647-14-5	>99

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - If pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.

continued...

SODIUM CHLORIDE

GHS Safety Data Sheet

Version No:2

Page 3 of 11

Section 4 - FIRST AID MEASURES

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
 - Not considered a significant fire risk, however containers may burn.
- Decomposition may produce toxic fumes of: hydrogen chloride, metal oxides.
May emit poisonous fumes.
May emit corrosive fumes.

FIRE INCOMPATIBILITY

None known.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing dust and contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- Use dry clean up procedures and avoid generating dust.
- Sweep up, shovel up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

Moderate hazard.

- CAUTION: Advise personnel in area.
- Alert Emergency Services and tell them location and nature of hazard.

continued...

SODIUM CHLORIDE

GHS Safety Data Sheet

Version No:2

Page 4 of 11

Section 6 - ACCIDENTAL RELEASE MEASURES

- Control personal contact by wearing protective clothing.
- Prevent, by any means available, spillage from entering drains or water courses.
- Recover product wherever possible.
- IF DRY: Use dry clean up procedures and avoid generating dust. Collect residues and place in sealed plastic bags or other containers for disposal. IF WET: Vacuum/shovel up and place in labelled containers for disposal.
- ALWAYS: Wash area down with large amounts of water and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise Emergency Services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

sodium chloride 500 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

sodium chloride 300 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

sodium chloride 40 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:

sodium chloride 15 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

continued...

SODIUM CHLORIDE

GHS Safety Data Sheet

Version No:2

Page 5 of 11

Section 7 - HANDLING AND STORAGE

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Food grade materials must be protected from all possible contaminants. Metals and their oxides or salts may react violently with chlorine trifluoride. Chlorine trifluoride is a hypergolic oxidiser. It ignites on contact (without external source of heat or ignition) with recognised fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition. The state of subdivision may affect the results.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ + + + + +

+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- sodium chloride: CAS:7647- 14- 5

MATERIAL DATA

It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no -observable-effect-levels (NOEL) are used to determine these limits where human results

continued...

SODIUM CHLORIDE


Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids.

- polychloroprene
- nitrile rubber
- butyl rubber
- fluorocautchouc
- polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity,
- are important in the selection of gloves.

SODIUM CHLORIDE

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

" Forsberg Clothing Performance Index" .

The effect(s) of the following substance(s) are taken into account in the computer- generated selection: sodium chloride

Protective Material CPI *.

NATURAL RUBBER	A
NATURAL+NEOPRENE	A
NITRILE	A

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult

your

Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

· Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.

· If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered.

Such protection might consist of:

- (a): particle dust respirators, if necessary, combined with an absorption cartridge;
- (b): filter respirators with absorption cartridge or canister of the right type;
- (c): fresh-air hoods or masks.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

continued...

SODIUM CHLORIDE

GHS Safety Data Sheet

Version No:2

Page 8 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Type of Contaminant:

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

Air Speed:

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only.
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Odourless, colourless, transparent crystals or white crystalline powder; completely soluble in water (2.165 g/cc).
Available as Rocksalt (crude), Technical, Pure, Food grade, BP grades; also solar salt, vacuum salt, sea salt and common salt.
A saturated solution of solar salt is approximately pH 8 and vacuum salt is pH 9.5 - 11.0

PHYSICAL PROPERTIES

Solid.
Mixes with water.

Molecular Weight: 58.44
Melting Range (°C): 801
Solubility in water (g/L): Miscible
pH (1% solution): Not available
Volatile Component (%vol): Not applicable.
Relative Vapour Density (air=1): Not available.
Lower Explosive Limit (%): Not applicable
Autoignition Temp (°C): Not applicable
State: Divided solid

Boiling Range (°C): 1413
Specific Gravity (water=1): 2.165
pH (as supplied): 6.7- 7.3
Vapour Pressure (kPa): Negligible @ 25
Evaporation Rate: Not applicable
Flash Point (°C): Not Applicable
Upper Explosive Limit (%): Not applicable
Decomposition Temp (°C): Not applicable
Viscosity: Not Applicable

continued...

SODIUM CHLORIDE

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health).

Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Use in food and as food additive, indicates high degree of tolerance.

EYE

Limited evidence or practical experience suggests, that the material may cause moderate eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged exposure may cause moderate inflammation (similar to windburn) characterised by a temporary redness of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

SKIN

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

The material may produce mild skin irritation; limited evidence or practical experience suggests, that the material either:

- produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or
- produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.

Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (non allergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Contact with cuts, abraded skin is painful, but this is transient.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

SODIUM CHLORIDE

GHS Safety Data Sheet

Version No:2

Page 10 of 11

Section 11 - TOXICOLOGICAL INFORMATION

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long term exposure to high dust concentrations may cause changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron penetrating and remaining in the lung. A prime symptom is breathlessness. Lung shadows show on X-ray.

TOXICITY AND IRRITATION

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 3000 mg/kg

Oral (human) TDLo: 12357 mg/kg/23d

Intravenous (Mouse) LD50: 645 mg/kg

Oral (Human) TDLo: 12357 mg/kg

Subcutaneous (Rat) LD: 3500 mg/kg

Intraperitoneal (Mouse) LD50: 2602 mg/kg

Intravenous (Rabbit) LD: 1100 mg/kg

Subcutaneous (Guinea pig) LD: 2160 mg/kg

Intravenous (Guinea pig) LD: 300 mg/kg

Intraperitoneal (Rat) LD50: 2600 mg/kg

IRRITATION

Skin (rabbit): 500 mg/24h - Mild

Eye (rabbit): 10 mg - Moderate

Skin : Mild

Eye : Moderate

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

Oral Lowest Toxic Dose (Human): 8.2 mg/kg Eye (rabbit):100 mg/24h - moderate

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

TLm 96 > 1000 ppm

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,
IMDG

continued...

SODIUM CHLORIDE

GHS Safety Data Sheet

Version No:2

Page 11 of 11

Section 14 - TRANSPORTATION INFORMATION

Section 15 - REGULATORY INFORMATION

REGULATIONS

sodium chloride (CAS: 7647-14-5) is found on the following regulatory lists;
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

MSDS SECTION CHANGES

The following table displays the version number of and date on which each section was last changed.

Section Name	Version	Date	Section Name	Version	Date	Section Name	Version	Date
First Aid (skin)	2	25- May- 2007	Storage (suitable container)	2	25- May- 2007	Acute Health (eye)	2	25- May- 2007
First Aid (swallowed)	2	25- May- 2007	Engineering Control	2	25- May- 2007	Acute Health (inhaled)	2	25- May- 2007
Fire Fighter (fire incompatibility)	2	25- May- 2007	Exposure Standard	2	25- May- 2007	Acute Health (skin)	2	25- May- 2007
Fire Fighter (fire/explosion hazard)	2	25- May- 2007	Personal Protection (eye)	2	25- May- 2007	Acute Health (swallowed)	2	25- May- 2007
Spills (major)	2	25- May- 2007	Personal Protection (hands/feet)	2	25- May- 2007	Chronic Health	2	25- May- 2007
Spills (minor)	2	25- May- 2007	Personal Protection (other)	2	25- May- 2007	Toxicity and Irritation (Irritation)	2	25- May- 2007
Handling Procedure	2	25- May- 2007	Appearance	2	25- May- 2007	Toxicity and Irritation (Other)	2	25- May- 2007
Storage (storage incompatibility)	2	25- May- 2007	Physical Properties	2	25- May- 2007	Toxicity and Irritation (Toxicity Figure)	2	25- May- 2007
Storage (storage requirement)	2	25- May- 2007	19	2	25- May- 2007	Environmental	2	25- May- 2007

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 25-May-2018