



SODIUM MOLYBDATE

GHS Safety Data Sheet

Version No:5

Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

SODIUM MOLYBDATE

OTHER NAMES

Mo-O₄.2Na, Na₂MoO₄, "molybdic acid, disodium salt", "disodium molybdate", "sodium molybdate (VI)", "sodium molybdate (VI)", "sodium molybdate, anhydrous", "molybdate (MoO₄)₂-, disodium", "EEC Number:2315517", "Catalog Number: 1041", "J.T. Baker 3764", Mallinckrodt, 7782

PRODUCT USE

As a reagent in analytical chemistry, reagent for alkaloid testing.
In metal finishing, brightening agent for zinc plating. Corrosion inhibitor.
Additive as trace element for fertilizers and in animal feed supplements.
Used in production of molybdate inorganic and organic toners, pigments.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,
248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Oral) Category 5

EMERGENCY OVERVIEW

continued...

SODIUM MOLYBDATE

GHS Safety Data Sheet

Version No:5

Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

HAZARD

WARNING

Determined by using GHS criteria:

H303

May be harmful if swallowed

PRECAUTIONARY STATEMENTS

Response

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
sodium molybdate	7631-95-0	> 98

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

· IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.

· For advice, contact a Poisons Information Centre or a doctor.

Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

· Induce vomiting with fingers down the back of the of the throat, ONLY IF CONSCIOUS.

· Lean patient forward or place on left side (head-down position if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

· In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.

· If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided.

Further action will be the responsibility of the medical specialist.

· If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.

EYE

If this product comes in contact with the eyes:

· Immediately hold eyelids apart and flush the eye continuously with running water.

· Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

· Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

· Transport to hospital or doctor without delay.

· Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

· Immediately remove all contaminated clothing, including footwear.

· Flush skin and hair with running water (and soap if available).

· Seek medical attention in event of irritation.

INHALED

· If dust is inhaled, remove from contaminated area.

continued...

SODIUM MOLYBDATE

GHS Safety Data Sheet

Version No:5

Page 3 of 10

Section 4 - FIRST AID MEASURES

- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

There is no restriction on the type of extinguisher which may be used.

- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

Alert Fire Brigade and tell them location and nature of hazard.

- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.

Use fire fighting procedures suitable for surrounding area.

Use water delivered as a fine spray to control the fire and cool adjacent area.

DO NOT approach containers suspected to be hot.

If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

Decomposes on heating and produces toxic fumes of:

metal oxides.

FIRE INCOMPATIBILITY

Avoid contamination with strong oxidising agents as ignition may result.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

Clean up all spills immediately.

Wear impervious gloves and safety glasses.

Avoid contact with skin and eyes.

Use dry clean up procedures and avoid generating dust.

Place in suitable containers for disposal.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment and dust respirator.
- Prevent spillage from entering drains, sewers or water courses.
- Recover product wherever possible. Avoid generating dust.
- Sweep / shovel up.
- If required, wet with water to prevent dusting.
- Put residues in labelled plastic bags or other containers for disposal.
- Wash area down with large quantity of water and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

continued...

SODIUM MOLYBDATE

GHS Safety Data Sheet

Version No:5

Page 4 of 10

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

sodium molybdate 200 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

sodium molybdate 200 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

sodium molybdate 3.5 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:

sodium molybdate 3.5 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

Avoid generating and breathing dust.

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

Multi-ply paper bag with sealed plastic liner or heavy gauge plastic bag.

NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse. Check that all containers are clearly labelled and free from leaks. Packing as recommended by manufacturer.

STORAGE INCOMPATIBILITY

Avoid storage with oxidisers, alkali metals e.g. sodium, potassium, lithium.
and.

common metals and their alloys.

Explodes on contact with molten magnesium.

continued...

SODIUM MOLYBDATE

GHS Safety Data Sheet

Version No:5

Page 5 of 10

Section 7 - HANDLING AND STORAGE

Violent reaction with interhalogens.
Incandescent reaction with hot sodium, potassium or lithium.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ + + + + +

+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

• sodium molybdate:

CAS:7631- 95- 0 CAS:10102- 40- 6

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
sodium molybdate	1, 000	

MATERIAL DATA

An increased incidence of non-specific symptoms including headache, weakness, fatigue, anorexia and joint and muscle weakness has been reported to occur in mining and metallurgy workers exposed to 60-600 mg (as Mo). Some investigators have attributed gout and elevated uric acid concentration found in some Armenians to result from exposures to Armenian soils rich in molybdenum, whilst exposure has been implicated as a cause of bone disease amongst Indians. "These involvements are speculative". [US National Research Council]. As far as it is known, the recommended TLV-TWA incorporates a large margin of safety against potential pulmonary or systemic effects.

PERSONAL PROTECTION



continued...

SODIUM MOLYBDATE

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear general protective gloves: i.e. Disposable polythene gloves or Cotton gloves or Light weight rubber gloves, with Barrier cream preferably Safety footwear.

OTHER

- Overalls.
- Eyewash unit.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Use in a well-ventilated area.

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
 - (a): particle dust respirators, if necessary, combined with an absorption cartridge;
 - (b): filter respirators with absorption cartridge or canister of the right type;
 - (c): fresh-air hoods or masks
- Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.

continued...

SODIUM MOLYBDATE

GHS Safety Data Sheet

Version No:5

Page 7 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Type of Contaminant:
direct spray, spray painting in shallow booths,
drum filling, conveyer loading, crusher dusts,
gas discharge (active generation into zone of
rapid air motion)
grinding, abrasive blasting, tumbling, high
speed wheel generated dusts (released at high
initial velocity into zone of very high rapid
air motion).

Air Speed:
1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range
1: Room air currents minimal or favourable to
capture
2: Contaminants of low toxicity or of nuisance
value only
3: Intermittent, low production.
4: Large hood or large air mass in motion

Upper end of the range
1: Disturbing room air currents
2: Contaminants of high toxicity
3: High production, heavy use
4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Small white odourless scales or flakes; very soluble in water.
Available as dihydrate CAS 10102-40-6, and anhydrous CAS 7631-95-0.
Readily soluble, solubility = 56% @ 20C and 84% @ 100C.

PHYSICAL PROPERTIES

Solid.
Mixes with water.

Molecular Weight: 205.92 anhydrous
Melting Range (°C): 687
Solubility in water (g/L): Soluble
pH (1% solution): 9- 10 (5% soln.)
Volatile Component (%vol): Nil
Relative Vapour Density (air=1): Not available.
Lower Explosive Limit (%): Not applicable
Autoignition Temp (°C): Not applicable
State: Divided solid

Boiling Range (°C): Not applicable.
Specific Gravity (water=1): 3.28
pH (as supplied): Not applicable
Vapour Pressure (kPa): Negligible
Evaporation Rate: Non Vol. @ 38C
Flash Point (°C): Non Combustible
Upper Explosive Limit (%): Not applicable
Decomposition Temp (°C): Not available.
Viscosity: Not available

continued...

SODIUM MOLYBDATE

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health).

Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Considered an unlikely route of entry in commercial/industrial environments.

The material is highly discomforting.

and.

harmful.

if swallowed.

Ingestion may result in nausea, abdominal irritation, pain and vomiting.

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

The dust may be highly discomforting.

to the eyes.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

The material is moderately discomforting.

to the skin.

if exposure is prolonged.

Open cuts, abraded or irritated skin should not be exposed to this material.

The material may accentuate any pre-existing skin condition.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

The dust may be highly discomforting.

to the upper respiratory tract.

if inhaled.

SODIUM MOLYBDATE

GHS Safety Data Sheet

Version No:5

Page 9 of 10

Section 11 - TOXICOLOGICAL INFORMATION

and may be.
harmful.

if exposure is prolonged.

Bronchial and alveolar exudate are apparent in animals exposed to molybdenum by inhalation. Molybdenum fume may produce bronchial irritation and moderate fatty changes in liver and kidney.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and inhalation of generated dusts.

Cattle, rabbits, and chicks on high dietary levels of molybdenum exhibited deformities of joints of the extremities. Chronic exposure of workers in Russian molybdenum-copper plant resulted in a fall in the albumin/globulin ratio owing to a rise in globulins (particularly alpha-globulins) which is interpreted as evidence of liver dysfunction with hyperbilirubinaemia. Hepatotoxic effects are also found in animals given molybdenum salts with a rise in alpha-globulin levels, hypoalbuminaemia and increased serum bilirubin reported. Other reported biochemical effects include an early depletive effect on tissue nicotinamide nucleotides, hyperaminoaciduria, reduction in red blood cell life-span and hyper-thyroidism. Industrial exposure to some insoluble molybdenum compounds is thought to have resulted in an increased incidence of weakness, fatigue, anorexia, headache and joint and muscular pain. Animals exposed to certain insoluble molybdenum compounds show anorexia, diarrhoea, weight loss, listlessness, and liver and kidney damage. Molybdenum disturbs bone metabolism, giving rise to lameness, bone joint abnormalities, osteoporosis and high serum phosphatase levels. Low molybdenum intake has been attributed to the high incidence of oesophageal cancer in South Africa among the Bantu of Transkei, in China and in Russia. Under the conditions of a 2-year inhalation study* there was equivocal evidence of carcinogenic activity of molybdenum trioxide in male rats, male mice and female mice based on a marginally significant positive trend of alveolar/bronchiolar adenoma or carcinoma. There was no evidence of carcinogenic activity in female rats exposed to 10, 30 and 100 mg/m³. Exposure of male and female rats to molybdenum trioxide by inhalation resulted in increased incidences of chronic alveolar inflammation, hyaline degeneration of the olfactory epithelium (females), hyaline degeneration of the respiratory epithelium and squamous metaplasia of the epiglottis. Exposure of female and male mice to molybdenum trioxide resulted in an increased incidence of metaplasia of the alveolar epithelium, histiocyte cellular inflammation (males), hyaline degeneration of the respiratory epithelium, hyaline degeneration of the olfactory epithelium (females), squamous metaplasia of the epiglottis, and hyperplasia of the larynx. Molybdenum trioxide was not mutagenic in any of five strains of Salmonella typhimurium and did not induce sister chromatid exchanges or chromosomal aberrations in cultured Chinese hamster ovary cells in vitro. All tests were conducted with or without S9 metabolic activation enzymes. National Toxicology Program: Technical Report Series 462, April 1997.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

No data

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

continued...

SODIUM MOLYBDATE

GHS Safety Data Sheet

Version No:5

Page 10 of 10

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,
IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

sodium molybdate (CAS: 7631-95-0) is found on the following regulatory lists;
OECD Representative List of High Production Volume (HPV) Chemicals

sodium molybdate (CAS: 10102-40-6) is found on the following regulatory lists;
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
sodium molybdate	7631- 95- 0, 10102- 40- 6

MSDS SECTION CHANGES

The following table displays the version number of and date on which each section was last changed.

Section Name	Version	Date	Section Name	Version	Date	Section Name	Version	Date
Fire Fighter (fire/explosion hazard)	4	29- Jul- 2005	Acute Health (eye)	4	29- Jul- 2005	Acute Health (swallowed)	4	29- Jul- 2005
Storage (storage incompatibility)	5	16- Aug- 2006	Acute Health (inhaled)	4	29- Jul- 2005	Toxicity and Irritation (Other)	4	29- Jul- 2005
Appearance	5	16- Aug- 2006	Acute Health (skin)	4	29- Jul- 2005			

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 16-Aug-2017