

GHS Safety Data Sheet

Version No:2.0 Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

AMMONIUM IODIDE

OTHER NAMES

NH4I, "iodide of ammonia"

PRODUCT USE

Laboratory reagent. Photographic chemicals. Used in medicine as an expectorant.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315-317, T.V. INDUSTRIAL ESTATE,


248, WORLI,

MUMBAI- 400030.INDIA. technical@sdfine.com

Telephone: 91- 22- 24959898 Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HAZARD

Not hazardous

No hazards determined by using GHS criteria

GHS Safety Data Sheet

Version No:2.0 Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

PRECAUTIONARY STATEMENTS

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME ammonium iodide 12027-06-4 >99 certain grades may contain stabiliser as ammonium hypophosphite 1

Section 4 - FIRST AID MEASURES

SWALLOWED

- · Immediately give a glass of water.
- · First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with the eyes:

- · Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- · If pain persists or recurs seek medical attention.
- · Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- · Flush skin and hair with running water (and soap if available).
- · Seek medical attention in event of irritation.

INHALED

- · If dust is inhaled, remove from contaminated area.
- · Encourage patient to blow nose to ensure clear passage of breathing.
- · If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

Prolonged absorption of iodides may produce "iodism" - skin rash, runing nose, headache, and irritation of mucous membranes. Severe cases may show pimples, boils, hives, blisters, anemia, weight loss and general depression.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

· There is no restriction on the type of extinguisher which may be used.

FIRE FIGHTING

Alert Fire Brigade and tell them location and nature of hazard.

· Wear breathing apparatus plus protective gloves.

GHS Safety Data Sheet

Version No:2.0 Page 3 of 10

Section 5 - FIRE FIGHTING MEASURES

· Prevent, by any means available, spillage from entering drains or water courses.

Use fire fighting procedures suitable for surrounding area.

Cool fire exposed containers with water spray from a protected location.

DO NOT approach containers suspected to be hot.

If safe to do so, remove containers from path of fire.

Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

Non combustible.

Not considered to be a significant fire risk.

Decomposes on heating and produces acrid and toxic fumes of: ammonia and iodine.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- · Clean up all spills immediately.
- · Avoid contact with skin and eyes.
- · Wear impervious gloves and safety glasses.
- · Use dry clean up procedures and avoid generating dust.
- · Sweep up or
- · Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- · Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

- · Clear area of personnel and move upwind.
- · Alert Fire Brigade and tell them location and nature of hazard.
- · Control personal contact by using protective equipment and dust respirator.
- · Prevent spillage from entering drains, sewers or water courses.
- · Avoid generating dust.
- · Sweep, shovel up. Recover product wherever possible.
- · Put residues in labelled plastic bags or other containers for disposal.
- · If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

ammonium iodide 150 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

ammonium iodide 30 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

GHS Safety Data Sheet

Version No:2.0 Page 4 of 10

Section 6 - ACCIDENTAL RELEASE MEASURES

ammonium iodide 4 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects: ammonium iodide 1.5 ma/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+) >= 0.1% Toxic (T) >= 3.0% R50 >= 0.25% Corrosive (C) >= 5.0%

>= 2.5% R51 >= 10% else

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS













May be stored together +:

May be stored together with specific preventions 0:

Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- · Limit all unnecessary personal contact.
- · Wear protective clothing when risk of exposure occurs.
- · Use in a well-ventilated area.
- · When handling DO NOT eat, drink or smoke.
- · Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- · Use good occupational work practice.
- · Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER

Packaging as recommended by manufacturer.

· Check that containers are clearly labelled.

Glass container.

Plastic container.

Multi-ply woven plastic or paper bag with sealed plastic liner

NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse.

Polylined drum.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

GHS Safety Data Sheet

Version No:2.0 Page 5 of 10

Section 7 - HANDLING AND STORAGE

STORAGE REQUIREMENTS

Observe manufacturer's storing and handling recommendations.

Store in original containers.

Keep containers securely sealed.

Keep dry.

Store in a well-ventilated area.

Store in a cool area and away from sunlight.

Store away from incompatible materials.

Store away from oxidising materials.

Protect containers against physical damage.

Check regularly for spills and leaks.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

ammonium iodide:

CAS:12027- 06- 4 CAS:130604- 19- 2

MATERIAL DATA

These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- · the architecture of the air spaces remain intact,
- · scar tissue (collagen) is not synthesised to any degree.
- · tissue reaction is potentially reversible.

Extensive concentrations of P.N.O.C.s may:

- · seriously reduce visibility,
- · cause unpleasant deposits in the eyes, ears and nasal passages,
- · contribute to skin or mucous membrane injury by chemical or mechanical action, per se, or by the rigorous skin cleansing procedures necessary for their removal. [ACGIH] This limit does not apply:
- · to brief exposures to higher concentrations
- · nor does it apply to those substances that may cause physiological impairment at lower concentrations but for which a TLV has as yet to be determined.

This exposure standard applies to particles which

- · are insoluble or poorly soluble* in water or, preferably, in aqueous lung fluid (if data is available) and
- have a low toxicity (i.e., are not cytotoxic, genotoxic, or otherwise chemically reactive with lung tissue, and do not emit ionizing radiation, cause immune sensitization, or cause toxic effects other than by inflammation or by a mechanism of lung overload).

PERSONAL PROTECTION

GHS Safety Data Sheet

Version No:2.0 Page 6 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION







EYE

- · Safety glasses.
- · Safety glasses with side shields.
- · Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear general protective gloves: i.e. Disposable polythene gloves or Cotton gloves or Light weight rubber gloves, with Barrier cream preferably Safety footwear.

OTHER

Overalls.

- · Impervious protective clothing.
- · Barrier cream.
- · Eyewash unit.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*		PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

^{* -} Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your

Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air

GHS Safety Data Sheet Version No:2.0 Page 7 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

solvent, vapours, degreasing etc., evaporating

from tank (in still air)

aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) direct spray, spray painting in shallow booths,

drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of

rapid air motion)

grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

Air Speed:

0.25- 0.5 m/s (50- 100 f/min)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance

value only

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

White crystals or powder; dissolves in water. Hygroscopic.

Saline, somewhat bitter taste.

Material quickly yellows and browns on exposure to light and air.

PHYSICAL PROPERTIES

Solid.

Mixes with water.

Molecular Weight: 144.96 Boiling Range (°C): 220

continued...

GHS Safety Data Sheet

Version No:2.0 Page 8 of 10

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Melting Range (°C): 551 decomposes Solubility in water (g/L): Miscible

pH (1% solution): 4.6

Volatile Component (%vol): <1 water

Relative Vapour Density (air=1): Not applicable Lower Explosive Limit (%): Not applicable Autoignition Temp (°C): Not applicable

State: Divided solid

Specific Gravity (water=1): 2.51 pH (as supplied): Not applicable Vapour Pressure (kPa): Negligible Evaporation Rate: Not applicable Flash Point (°C): Not applicable

Upper Explosive Limit (%): Not applicable Decomposition Temp (°C): Not available.

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- · Presence of incompatible materials.
- · Product is considered stable.
- · Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

The dust may produce eye discomfort causing transient smarting, blinking.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Open cuts, abraded or irritated skin should not be exposed to this material.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

GHS Safety Data Sheet

Version No:2.0 Page 9 of 10

Section 11 - TOXICOLOGICAL INFORMATION

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by inhalation of generated dust and skin/eye contact.

lodine and iodides may produce goitre and hypothyroidism as well as hyperthyroidism. A mild toxic syndrome resulting from chronic iodide overdose and from repeated administration of small amounts of iodine ("iodism") is characterised by salivation, coryza, sneezing, conjunctivitis, headache, fever, laryngitis, bronchitis, stomatitis, parotitis (iodine mumps), and various skin rashes (iododerma*, thrombotic thrombocytopenic purpura). Swelling and inflammation of the throat, irritated and swollen eyes and pulmonary oedema may also occur. Oedema of the glottis, necessitating tracheotomy has been reported. Occasional use of iodides for asthma in pregnancy has resulted in foetal death, severe goiter, hypothyroidism and the cretinoid appearance of the new-born. *lododerma may vary from mild erythema and acneform eruptions to urticaria and suppurative or haemorrhagic rashes.

TOXICITY AND IRRITATION

None available.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

Section 12 - ECOLOGICAL INFORMATION

No data for ammonium iodide.

Section 13 - DISPOSAL CONSIDERATIONS

- · Recycle wherever possible or consult manufacturer for recycling options.
- · Consult State Land Waste Management Authority for disposal.
- · Bury residue in an authorised landfill.
- · Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

No regulations applicable

No data available for ammonium iodide as CAS: 12027-06-4, CAS: 130604-19-2.

GHS Safety Data Sheet

Version No:2.0

Page 10 of 10

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name ammonium iodide

CAS 12027- 06- 4, 130604- 19- 2

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 30-Mar-2018