

## GLYCEROL ABT. 87%

GHS Safety Data Sheet

Version No:9

Page 1 of 11

### Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT NAME

GLYCEROL

#### OTHER NAMES

C3-H8-O3, glycerin, "glycerin, anhydrous", "glycerin, synthetic", glyceritol, "glycyl alcohol", "1, 2, 3-propanetriol", "1, 2, 3-propanetriol", trihydroxypropane, "1, 2, 3-trihydroxypropane", "1, 2, 3-trihydroxypropane"

#### PRODUCT USE

As solvent, humectant, plasticiser, emollient, sweetener; in the manufacture of nitroglycerol (explosive), cosmetics, liquid soaps, liqueurs, confectioneries, blacking, printing and copying inks and lubricants. It is also used in the manufacture of elastic glues, lead oxide cements; to keep fabrics pliable; to preserve printing on cotton; for printing rollers; to keep frost from windshields; as antifreeze in automobiles, gas meters and hydraulic jacks, in shock absorber fluids. In fermentation nutrients in production of antibiotics.

#### SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

#### HAZARD RATINGS



continued...

# GLYCEROL ABT. 87%

GHS Safety Data Sheet

Version No:9

Page 2 of 11

---

## Section 2 - HAZARDS IDENTIFICATION

---

### GHS Classification

Acute Toxicity (Oral) Category 5  
Eye Irritation Category 2B  
Skin Corrosion/Irritation Category 3

### EMERGENCY OVERVIEW

#### HAZARD

WARNING  
Determined by using GHS criteria:  
H303 H316 H320  
May be harmful if swallowed  
Causes mild skin irritation  
Causes eye irritation

#### PRECAUTIONARY STATEMENTS

##### Prevention

Wash hands thoroughly after handling.

##### Response

If skin irritation occurs, seek medical advice/attention.  
If eye irritation persists, get medical advice/attention.  
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

| NAME     | CAS RN  | %    |
|----------|---------|------|
| glycerol | 56-81-5 | > 96 |

---

## Section 4 - FIRST AID MEASURES

---

### SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

### EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - If pain persists or recurs seek medical attention.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

continued...

# GLYCEROL ABT. 87%

GHS Safety Data Sheet

Version No:9

Page 3 of 11

## Section 4 - FIRST AID MEASURES

---

### SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

### NOTES TO PHYSICIAN

Treat symptomatically.

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

### FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO<sub>2</sub>), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

### FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

### Personal Protective Equipment

Gloves, boots (chemical resistant).

continued...

# GLYCEROL ABT. 87%

GHS Safety Data Sheet

Version No:9

Page 4 of 11

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### EMERGENCY PROCEDURES

#### MINOR SPILLS

Slippery when spilt.

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

#### MAJOR SPILLS

Slippery when spilt.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

### EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

glycerol      500 mg/m<sup>3</sup>

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

glycerol      50 mg/m<sup>3</sup>

other than mild, transient adverse effects without perceiving a clearly defined odour is:

glycerol      30 mg/m<sup>3</sup>

The threshold concentration below which most people will experience no appreciable risk of health effects:

glycerol      15 mg/m<sup>3</sup>

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

|                 |         |           |         |
|-----------------|---------|-----------|---------|
| Very Toxic (T+) | >= 0.1% | Toxic (T) | >= 3.0% |
|-----------------|---------|-----------|---------|

continued...

# GLYCEROL ABT. 87%

GHS Safety Data Sheet

Version No:9  
Page 5 of 11

## Section 6 - ACCIDENTAL RELEASE MEASURES

R50                       $\geq 0.25\%$                       Corrosive (C)                       $\geq 5.0\%$   
R51                       $\geq 2.5\%$   
else                       $\geq 10\%$   
where percentage is percentage of ingredient found in the mixture

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together  
O: May be stored together with specific precautions  
X: Must not be stored together

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
  - Wear protective clothing when risk of exposure occurs.
  - Use in a well-ventilated area.
  - Prevent concentration in hollows and sumps.
  - DO NOT enter confined spaces until atmosphere has been checked.
  - Avoid smoking, naked lights or ignition sources.
  - Avoid contact with incompatible materials.
  - When handling, DO NOT eat, drink or smoke.
  - Keep containers securely sealed when not in use.
  - Avoid physical damage to containers.
  - Always wash hands with soap and water after handling.
  - Work clothes should be laundered separately.
  - Use good occupational work practice.
  - Observe manufacturer's storing and handling recommendations.
  - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
- DO NOT allow clothing wet with material to stay in contact with skin.

### SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.  
Avoid reaction with strong oxidising agents such as chromium trioxide, acetic anhydride, chromium oxides, calcium oxychloride, alkali metal hydrides, potassium chlorate and potassium permanganate as an explosive or violent reaction may occur.

continued...

# GLYCEROL ABT. 87%

## Section 7 - HANDLING AND STORAGE

### STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

The following materials had no OELs on our records

- glycerol:

CAS:56- 81- 5 CAS:78630- 16- 7 CAS:37228- 54- 9  
CAS:30049- 52- 6 CAS:29796- 42- 7 CAS:8013- 25- 0  
CAS:75398- 78- 6

### MATERIAL DATA

The mist is considered to be a nuisance particulate which appears to have little adverse effect on the lung and does not produce significant organic disease or toxic effects. OSHA concluded that this limit would protect the worker from kidney damage and perhaps, testicular effects.

### PERSONAL PROTECTION



### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

### OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.

continued...

# GLYCEROL ABT. 87%

GHS Safety Data Sheet

Version No:9  
Page 7 of 11

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Skin cleansing cream.
- Eye wash unit.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult

your

Occupational Health and Safety Advisor.

### ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

solvent, vapours, degreasing etc., evaporating from tank (in still air).

aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)

grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

Air Speed:

0.25- 0.5 m/s (50- 100 f/min)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

continued...

# GLYCEROL ABT. 87%

GHS Safety Data Sheet

Version No:9

Page 8 of 11

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

### APPEARANCE

Oily, colourless, odourless liquid, with syrupy, sweet taste. Miscible with water and alcohol. Insoluble in benzene, ether, chloroform, fixed and volatile oils. Absorbs water from the air. Also absorbs hydrogen sulphide, hydrogen cyanide and sulphur dioxide.

### PHYSICAL PROPERTIES

Liquid.

Mixes with water.

Molecular Weight: 92.1

Melting Range (°C): 18

Solubility in water (g/L): Miscible

pH (1% solution): 7 approx.

Volatile Component (%vol): Nil @ 38 C.

Relative Vapour Density (air=1): 3.17

Lower Explosive Limit (%): 3

Autoignition Temp (°C): 370

State: Liquid

Boiling Range (°C): 290

Specific Gravity (water=1): 1.2- 1.3 @ 20 C

pH (as supplied): Not applicable

Vapour Pressure (kPa): 0.003 @ 50 C

Evaporation Rate: Non Volatile

Flash Point (°C): 160

Upper Explosive Limit (%): 19

Decomposition Temp (°C): >280

Viscosity: Not Available

log Kow (Sangster 1997): - 1.76

log Kow: -2.66- -2.47

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

---

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

## Section 11 - TOXICOLOGICAL INFORMATION

---

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

continued...



## Section 11 - TOXICOLOGICAL INFORMATION

---

### EYE

Limited evidence or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

### SKIN

The material may produce mild skin irritation; limited evidence or practical experience suggests, that the material either:

- produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or
- produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.

Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (non allergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

### INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Not normally a hazard due to non-volatile nature of product.

### CHRONIC HEALTH EFFECTS

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Glyceryl triesters (triglycerides), following ingestion, are metabolised to monoglycerides, free fatty acids and glycerol, all of which are absorbed in the intestinal mucosa and undergo further metabolism. Little or no acute, subchronic or chronic oral toxicity was seen in animal studies unless levels approached a significant percentage of calorific intake. Subcutaneous injections of tricaprylin in rats over a five-week period caused granulomatous reaction characterised by oil deposits surrounded by macrophages. Diets containing substantial levels of tributyrin produced gastric lesions in rats fed for 3-35 weeks; the irritative effect of the substance was thought to be the cause of tissue damage.

Dermal application was not associated with significant irritation in rabbit skin; ocular exposures were, at most, mildly irritating to rabbit eyes. No evidence of sensitisation or photosensitisation was seen in a guinea pig maximisation test. Most of the genotoxicity test systems were negative. Tricaprylin, trioctanoin and triolein have been used, historically, as vehicles in carcinogenicity testing of other chemicals. In one study, subcutaneous injection of tricaprylin, in newborn mice, produced more tumours in lymphoid tissue than were seen in untreated animals whereas, in another study,

continued...

# GLYCEROL ABT. 87%

## Section 11 - TOXICOLOGICAL INFORMATION

subcutaneous or intraperitoneal injection in 4- to 6-week old female mice produced no tumours. Trioctanoin injected subcutaneously in hamster produced no tumours; when injected intraperitoneally in pregnant rats there was an increase in mammary tumours among the off-spring but similar studies in pregnant hamsters and rabbits showed no tumours in the off-spring.

The National Toxicological Program conducted a 2-year study in rats given tricaprylin by gavage. The treatment was associated with a statistically significant dose-related increase in pancreatic acinar cell hyperplasia and adenoma but there were no acinar carcinomas.

Tricaprylin is not teratogenic to mice or rats but some reproductive effects were seen in rabbits. A low level of foetal eye abnormalities and a small percentage of abnormal sperm were reported in mice injected with trioctanoin.

### TOXICITY AND IRRITATION

#### TOXICITY

Oral (Rat) LD50: 12600 mg/kg

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

#### IRRITATION

## Section 12 - ECOLOGICAL INFORMATION

|                             |             |
|-----------------------------|-------------|
| Algae IC50 (72hr.) (mg/l):  | 2900- 10000 |
| log Kow (Sangster 1997):    | - 1.76      |
| log Pow (Verschueren 1983): | 1.07692307  |
| BOD5:                       | 51%         |
| COD:                        | 95%         |
| ThOD:                       | 93%         |

DO NOT discharge into sewer or waterways.

log Kow: -2.66- -2.47

BOD 5 if unstated: 0.617-0.87,31-51%

COD: 1.16,82-95%

ThOD: 1.217-1.56

Completely biodegradable.

Fish LC50: >5000 mg/l

Algae IC50: >2900 mg/l

Bacteria EC50: .10000 mg/l (Pseudomonas putida)

## Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

# GLYCEROL ABT. 87%

GHS Safety Data Sheet

Version No:9  
Page 11 of 11

---

## Section 14 - TRANSPORTATION INFORMATION

---

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,  
IMDG

---

## Section 15 - REGULATORY INFORMATION

---

### REGULATIONS

glycerol (CAS: 56-81-5) is found on the following regulatory lists;  
CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food  
in General, Unless Otherwise Specified, in Accordance with GMP  
IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances  
International Council of Chemical Associations (ICCA) - High Production Volume List  
OECD Representative List of High Production Volume (HPV) Chemicals

No data available for glycerol as CAS: 78630-16-7, CAS: 37228-54-9, CAS: 30049-52-6, CAS:  
29796-42-7, CAS: 8013-25-0, CAS: 75398-78-6.

---

## Section 16 - OTHER INFORMATION

---

### INGREDIENTS WITH MULTIPLE CAS NUMBERS

| Ingredient Name | CAS                                                                                              |
|-----------------|--------------------------------------------------------------------------------------------------|
| glycerol        | 56- 81- 5, 78630- 16- 7, 37228 - 54- 9, 30049-<br>52- 6, 29796- 42- 7, 8013- 25- 0, 75398- 78- 6 |

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 14-Mar-2018