

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 1 of 16

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

METHYLENE CHLORIDE

OTHER NAMES

C-H₂-Cl₂, dichloromethane, "methylene bichloride", "methylene dichloride", "methane dichloride", "

PROPER SHIPPING NAME

DICHLOROMETHANE

PRODUCT USE

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing.

Before starting consider control of exposure by mechanical ventilation.

Solvent for cellulose acetate, plastics and fats.

Component of degreasing agents, cleaning fluids and paint removers.

A blowing agent in foams, as an aerosol propellant, and a cooling solvent.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 2 of 16

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Oral) Category 4
Carcinogen Category 2
Eye Irritation Category 2B
Reproductive Toxicity Category 1B
Respiratory Irritation Category 3
Skin Corrosion/Irritation Category 2



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:
H335 H302 H315 H320 H351 H360
May cause respiratory irritation
Harmful if swallowed
Causes skin irritation
Causes eye irritation
Suspected of causing cancer
May damage fertility

PRECAUTIONARY STATEMENTS

Prevention

Do not handle until all safety precautions have been read and understood.
Use personal protective equipment as required.
Wash thoroughly after handling.
Obtain special instructions before use.
Do not eat, drink or smoke when using this product.
Wash hands thoroughly after handling.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical attention advice.
If eye irritation persists, get medical advice/attention.
If skin irritation occurs, seek medical advice/attention.
Remove/Take off immediately all contaminated clothing
Specific treatment: refer to Label or MSDS.
IF ON SKIN: Gently wash with plenty of soap and water.
Wash/Decontaminate removed clothing before reuse.

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 3 of 16

Section 2 - HAZARDS IDENTIFICATION

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
methylene chloride	75-09-2	> 99

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

- If swallowed do NOT induce vomiting.
 - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 - Observe the patient carefully.
 - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 - Seek medical advice.
- Avoid giving milk or oils.
Avoid giving alcohol.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 4 of 16

Section 4 - FIRST AID MEASURES

- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.

DO NOT administer sympathomimetic drugs as they may cause ventricular arrhythmias.

For acute or short term repeated exposures to methylene chloride:

- Methylene chloride is well absorbed by the lung. An 8 hour exposure to 250 ppm causes carboxyhaemoglobin levels to exceed 8%. Physical exertion and smoke produce an additive effect.

- The lungs exhale most of the absorbed dose unchanged. Between 1/4 and 1/3 is metabolised to carbon monoxide / dioxide. 5 hours of 100% oxygen is required, typically, to reduce the carboxyhaemoglobin level from 13% to 7.5%.

- As with inhalation and ingestion of the hydrocarbons support of respiration and monitoring for dysrhythmias are the first steps toward stabilisation.

- Small ingestions require only dilution with water or milk. Patients who have ingested more than several swallows may benefit from Ipecac Syrup/lavage, charcoal or cathartics. No data is available to support the efficacy of these treatments.

[Ellenhorn and Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

Determinant	Index	Sampling Time	Comments
1. Methaemoglobin in blood	1.5% of haemoglobin	During or end of shift	B, NS, SQ

B: Background levels occur in specimens collected from subjects NOT exposed.

NS: Non-specific determinant; Also seen after exposure to other materials

SQ: Semi-quantitative determinant - Interpretation may be ambiguous; should be used as a screening test or confirmatory test.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Water spray or fog.

Foam.

Dry chemical powder.

Carbon dioxide.

FIRE FIGHTING

Alert Fire Brigade and tell them location and nature of hazard.

- Wear breathing apparatus plus protective gloves.

- Prevent, by any means available, spillage from entering drains or water courses.

Use water delivered as a fine spray to control the fire and cool adjacent area.

Cool fire exposed containers with water spray from a protected location.

DO NOT approach containers suspected to be hot.

If safe to do so, remove containers from path of fire.

Fight fire from a safe distance, with adequate cover.

FIRE/EXPLOSION HAZARD

- Non flammable liquid.

- However vapour will burn when in contact with high temperature flame.

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 5 of 16

Section 5 - FIRE FIGHTING MEASURES

- Ignition ceases on removal of flame.
- May form a flammable / explosive mixture in an oxygen enriched atmosphere
- Heating may cause expansion/vapourisation with violent rupture of containers
- Decomposes on heating and produces corrosive fumes of hydrochloric acid, carbon monoxide and small amounts of toxic phosgene.

FIRE INCOMPATIBILITY

Avoid contact with strong acids strong alkalis and strong oxidisers.

May react violently with.

aluminium and magnesium powdered metals and alkali metals e.g. sodium, potassium, lithium.

Dissolves most plastics and synthetic fibres.

Personal Protective Equipment

Breathing apparatus.

Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

Clean up all spills immediately.

Avoid breathing vapours and contact with skin and eyes.

Wear protective clothing, impervious gloves and safety glasses.

Wipe up and absorb small quantities with vermiculite or other absorbent material.

Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

- Wear breathing apparatus plus protective gloves.

- Prevent, by any means available, spillage from entering drains or water courses.

Shut off all possible sources of ignition and increase ventilation.

Stop leak if safe to do so.

Contain spill with sand, earth or vermiculite.

Use only spark-free shovels and explosion proof equipment.

Reclaim solvent for recycling at an approved site.

Absorb remaining product with sand, earth or vermiculite.

Collect residues and seal in labelled drums for disposal.

Wash spill area with detergent and water.

After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.

If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

methylene chloride 4000 ppm

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 6 of 16

Section 6 - ACCIDENTAL RELEASE MEASURES

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:
methylene chloride 750 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:
methylene chloride 200 ppm

The threshold concentration below which most people will experience no appreciable risk of health effects:
methylene chloride 25 ppm


American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

Use good occupational work practice. Observe manufacturer's storing and handling recommendations.

Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

Avoid all personal contact, including inhalation.

Avoid generating and breathing mist.

Wear protective clothing when risk of exposure occurs.

Avoid smoking, naked lights or ignition sources.

Use in a well-ventilated area.

until atmosphere has been checked.

Avoid contact with incompatible materials.

DO NOT spray directly on humans, exposed food or food utensils.

When handling, DO NOT eat, drink or smoke.

Keep containers securely sealed when not in use.

Avoid physical damage to containers.

Always wash hands with soap and water after handling. Work clothes should be laundered separately.

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 7 of 16

Section 7 - HANDLING AND STORAGE

SUITABLE CONTAINER

Packaging as recommended by manufacturer.

· Check that containers are clearly labelled.

Metal can.

Metal drum.

STORAGE INCOMPATIBILITY

Segregate from strong oxidisers strong alkalis.

aluminium and magnesium powdered metals and alkali metals e.g. sodium, potassium, lithium.

Segregate from alcohol, water.

In the presence of moisture and at higher temperatures material breaks down generating hydrochloric acid, which may corrode and perforate containers.

STORAGE REQUIREMENTS

Observe manufacturer's storing and handling recommendations.

Store in original containers.

Keep containers securely sealed.

Store in a cool, dry and well-ventilated area.

Store away from incompatible materials.

Store away from foodstuff containers.

DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

Protect containers against physical damage.

Check regularly for spills and leaks.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
methylene chloride		2,000

MATERIAL DATA

Odour Threshold Value: 158 ppm (detection), 227 ppm (recognition)

NOTE: Detector tubes for methylene chloride, measuring in excess of 25 ppm are commercially available. Long-term measurements (4 hrs) may be conducted to detect concentrations exceeding 13 ppm.

Exposure at or below the recommended TLV-TWA (and in the absence of occupational exposure to carbon monoxide) is thought to minimise the potential for liver injury and to provide protection against the possible weak carcinogenic effects which have been demonstrated in laboratory rats and mice. Enhancement of tumours of the lung, liver, salivary glands and mammary tissue in rodent studies has lead NIOSH to recommend a more conservative outcome. The ACGIH however concludes that in the absence of documentation of health-related injuries at higher exposures after a long history of methylene chloride use and a number of epidemiologic studies, the recommended TLV-TWA provides an adequate margin of safety. Concentration effects:

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 8 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Concentration	Clinical effects

>300 ppm	Sweet odour
500-1000 ppm (1-2 h)	Unpleasant odour, slight anaesthetic effects,
headache, light-headedness, eye irritation	
and elevated COHb concentration	
2300 ppm (5 min.)	Odour strong, intensely irritating; dizziness
7200 ppm (8-16 min)	Paraesthesia, tachycardia
>50000 ppm	Immediately life-threatening

PERSONAL PROTECTION



EYE

- Chemical goggles.
- Safety glasses with side shields.
- Full face shield.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- Barrier cream and PVA gloves or Viton gloves or Wear chemical protective gloves, eg. PVC.
- Wear safety footwear.
- DO NOT use this product to clean the skin.

OTHER

- Overalls and Plastic apron.
- Impervious protective clothing.
 - Eyewash unit.
- Ensure there is ready access to a safety shower.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:
"Forsberg Clothing Performance Index".
The effect(s) of the following substance(s) are taken into account in the computer-generated selection: methylene chloride

Protective Material CPI *.

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 9 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

PE/EVAL/PE	A
PVA	A
TEFLON	B
VITON	C
VITON/BUTYL	C
VITON/CHLOROBUTYL	C
CPE	C
BUTYL	C
NATURAL RUBBER	C
NEOPRENE	C

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AX- AUS	-
1000	50	-	AX- AUS
5000	50	Airline *	-
5000	100	-	AX- 2
10000	100	-	AX- 3
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Use in a well-ventilated area.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

Air Speed:

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 10 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. In confined spaces where there is inadequate ventilation, wear full-face air supplied breathing apparatus.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless non flammable liquid; does not mix with water. Highly volatile.
Has a penetrating, ether-like odour. Mixes with alcohol, organic solvents.

PHYSICAL PROPERTIES

Liquid.

Molecular Weight: 84.93
Melting Range (°C): - 97
Solubility in water (g/L): 2.0%
pH (1% solution): Not applicable.
Volatile Component (%vol): 100
Relative Vapour Density (air=1): 2.93

Boiling Range (°C): 40
Specific Gravity (water=1): 1.32
pH (as supplied): Not applicable
Vapour Pressure (kPa): 46.5 @20C
Evaporation Rate: >1 BuAc=1
Flash Point (°C): Not applicable

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 11 of 16

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Lower Explosive Limit (%): 14- oxygen rich
Autoignition Temp (°C): 662
State: Liquid

Upper Explosive Limit (%): 22- oxygen rich
Decomposition Temp (°C): Not available
Viscosity: Not available

log Kow (Prager 1995): 1.25
log Kow: 1.25

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Considered an unlikely route of entry in commercial/industrial environments.

EYE

Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 12 of 16

Section 11 - TOXICOLOGICAL INFORMATION

Toxic effects may result from skin absorption.

Bare unprotected skin should not be exposed to this material.

The material may accentuate any pre-existing skin condition.

The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis.

Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. Prolonged contact is unlikely, given the severity of response, but repeated exposures may produce severe ulceration.

INHALED

Inhalation may produce health damage*.

Limited evidence exists, or practical experience predicts, that the material produces irritation of the respiratory system in a significant number of individuals following inhalation.

Inhalation hazard is increased at higher temperatures.

At high concentrations most of the absorbed methylene chloride (dichloromethane) is exhaled unchanged; the remainder is metabolised to carbon monoxide, carbon dioxide and inorganic chloride. Inhalation may produce fatigue, weakness, sleepiness, light-headedness, chills, nausea, diarrhoea and abdominal pain. The lowest published lethal dose is 20,000 ppm for 20 hours. The body metabolises methylene chloride to carbon monoxide and adds to the body burden of carboxyhaemoglobin (COHb) contributed by other sources. The increase in COHb is related to the magnitude of vapour exposure and duration. Serious poisoning can occur without raised COHb concentrations, although these raised concentrations may persist for several hours. Central nervous system (CNS) effects are thought to be due to methylene chloride itself or methylene chloride in combination with other sources of COHb, rather than the COHb metabolite. The raised COHb concentrations are not usually expected to produce adverse effects in healthy individuals but may be cause for concern in individuals with cardiovascular disease. Encephalopathy (brain injury) has been reported after repeated exposure. Angina, myocardial infarction, cardiac arrhythmias and cardiac arrest have also been reported, although the cardiovascular system is not generally a target for methylene chloride toxicity.

Hypotension, shock and metabolic acidosis may also occur as a result of overexposure.

Respiratory failure may develop, secondary to CNS depression, in severe cases.

Inhalation exposure may cause susceptible individuals to show change in heart beat rhythm i.e. cardiac arrhythmia. Exposures must be terminated.

Acute intoxication by halogenated aliphatic hydrocarbons appears to take place over two stages. Signs of a reversible narcosis are evident in the first stage and in the second stage signs of injury to organs may become evident, a single organ alone is (almost) never involved.

Depression of the central nervous system is the most outstanding effect of most halogenated aliphatic hydrocarbons. Inebriation and excitation, passing into narcosis, is a typical reaction. In severe acute exposures there is always a danger of death from respiratory failure or cardiac arrest due to a tendency to make the heart more susceptible to catecholamines (adrenalin).

CHRONIC HEALTH EFFECTS

On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Principal routes of exposure are usually by.

skin contact/absorption and inhalation of vapour.

Methylene chloride is stored in body fat and is metabolised to carbon monoxide which

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 13 of 16

Section 11 - TOXICOLOGICAL INFORMATION

increases and sustains carboxyhaemoglobin levels in the blood, reducing its oxygen carrying capacity. Smokers with already high carboxyhaemoglobin levels may show increased effects of exposure.

Methylene chloride exposures cause liver and kidney damage in animals and this justifies consideration before exposing persons with a history of impaired liver function and/or renal disorders.

Chronic exposure may produce central nervous system damage including confusion, delusions, slurred speech, memory impairment, anxiety, focal seizures, encephalopathy and visual and auditory hallucinations. These effects are probably due to chronic carbon monoxide poisoning resulting from methylene chloride metabolism.

Two epidemiological studies of workers exposed to methylene chloride have been published. An excess in pancreatic tumours was noted in one study. Chronic exposure to methylene chloride (approximately 30-120 ppm TWA) did not appear to increase the risk of deaths arising from lung cancer or cardiovascular disease. A study from Zeneca's Central Toxicology Laboratory added further support to the claim that solvent methylene chloride is not a human carcinogen. This study supported a previous finding by the European Centre of Ecology and Toxicology (ECETOC) that methylene chloride induced-cancers, previously identified in mice, were a consequence of a unique metabolic pathway found only in mice.

TOXICITY AND IRRITATION

TOXICITY

Oral (human) LDLo: 357 mg/kg

Oral (rat) LD50: 1600 mg/kg

Inhalation (human) TCLo: 500 ppm/ 8 hr

Inhalation (rat) LC50: 88000 mg/m³/30 m

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

Inhalation (human) TCLo: 500 ppm/ 1 y - I Eye(rabbit): 10 mg - mild

IRRITATION

Skin (rabbit): 810 mg/24hr- SEVERE

Skin (rabbit): 100mg/24hr- Moderate

Eye(rabbit): 162 mg - Moderate

Eye(rabbit): 500 mg/24hr - Mild

Section 12 - ECOLOGICAL INFORMATION

Fish LC50 (96hr.) (mg/l):	147.6- 193
Daphnia magna EC50 (48hr.) (mg/l):	224
BCF<100:	5
log Kow (Prager 1995):	1.25
Half- life Soil - High (hours):	672
Half- life Soil - Low (hours):	168
Half- life Air - High (hours):	4584
Half- life Air - Low (hours):	458
Half- life Surface water - High (hours):	672
Half- life Surface water - Low (hours):	168
Half- life Ground water - High (hours):	1344
Half- life Ground water - Low (hours):	336
Aqueous biodegradation - Aerobic - High (hours):	672
Aqueous biodegradation - Aerobic - Low (hours):	168
Aqueous biodegradation - Anaerobic - High (hours):	2688
Aqueous biodegradation - Anaerobic - Low (hours):	672
Aqueous biodegradation - Removal secondary treatment - High (hours):	94.50%
Photolysis maximum light absorption - High (nano- m):	250
Photolysis maximum light absorption - Low (nano- m):	220
Photooxidation half- life air - High (hours):	4584
Photooxidation half- life air - Low (hours):	458

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 14 of 16

Section 12 - ECOLOGICAL INFORMATION

First order hydrolysis half- life (hours):

704 YR

The UK Department of Environment have established that methylene chloride is not a greenhouse gas and the Organisation for Economic Cooperation and Development (OECD) in a Monograph have affirmed that there was no single international view that risk reduction measures are required for the solvent. The Monograph suggests that alternatives may pose a greater risk to the environment.

In the atmosphere methylene chloride degrades by reaction with photochemically produced hydroxy radicals (half-life 6 months). Methylene chloride rapidly volatilises from water and soil to the atmosphere (estimated half-life for volatilisation from water 3-5.6 hours). In soil methylene chloride may partially leach to ground water. It is not expected to bioaccumulate or bioconcentrate in the food chain.

Drinking Water Standards:

hydrocarbon total: 10 ug/l (UK max)

dichloromethane: 20 ug/l (WHO guideline)

Soil Guidelines: Dutch Criteria: detection threshold (target)

20 mg/kg (intervention)

Air Quality Standards:

3 mg/m³ averaging time 24 hours (WHO guideline).

log Kow: 1.25

log Koc: 1.68

log Kom: 1.44

Henry's atm m³ /mol: 2.68E-03

BCF: 5

Section 13 - DISPOSAL CONSIDERATIONS

Recycle wherever possible.

Consult manufacturer for recycling options.

Consult State Land Waste Management Authority for disposal.

Reclaim solvent at an approved site.

Evaporate or incinerate residue at an approved site.

Recycle containers if possible, or dispose of in an authorised landfill.

WASTE DISPOSAL PROCEDURES

- Collect and package the recoverable quantities of dichloromethane in a labelled solvent container for incineration [Armour 1996].

SPILLAGE DISPOSAL

- Shut off all ignition sources and clear area of personnel. Wear breathing apparatus, nitrile rubber gloves and a protective clothing to control personal contact from dichloromethane. Cover the area of the spill with a 1:1:1 mixture by weight of sodium carbonate or calcium carbonate, bentonite and sand. Collect the absorbed mixture and place in a container. Package the contents for incineration [Armour 1996].

continued...

DICHLOROMETHANE

GHS Safety Data Sheet

Version No:1

Page 15 of 16

Section 14 - TRANSPORTATION INFORMATION



Labels Required: TOXIC
HAZCHEM: 2Z

UNDG:

Dangerous Goods Class:	6.1	Subrisk:	None
UN Number:	1593	Packing Group:	III
Shipping Name: DICHLOROMETHANE			

Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	None
UN/ID Number:	1593	Packing Group:	III
ERG Code:	6L		
Shipping name: DICHLOROMETHANE			

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	None
UN Number:	1593	Packing Group:	III
EMS Number:	F- A, S- A		
Shipping name: DICHLOROMETHANE			

Section 15 - REGULATORY INFORMATION

REGULATIONS

methylene chloride (CAS: 75-09-2) is found on the following regulatory lists;
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
International Agency for Research on Cancer (IARC) Carcinogens
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals
WHO Guidelines for Drinking-water Quality - Chemicals for which guideline values have not been established
WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water

continued...

DICHLOROMETHANE

Section 16 - OTHER INFORMATION

REPRODUCTIVE HEALTH GUIDELINES

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for the reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

#32org

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
methylene chloride	2.4 mg/m ³	100	R	14	-

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive
American Industrial Hygiene Association Journal 57: 641-649 (1996).

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 16-Aug-2017