SILICON STANDARD SOLUTION 1000 MG/L

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME
SILICON STANDARD SOLUTION 1000 MG/L

OTHER NAMES
"laboratory reagent", "AAS silicon standard", "1000ppm Si calibration"

PRODUCT USE
Laboratory reagent, standard for Si in atomic spectroscopy.

SUPPLIER
Company: S D FINE - CHEM LIMITED
Address:
315- 317, T.V.IND.ESTATE,
248 WORLI ROAD,
MUMBAI- 400 030, INDIA
technical@sdfine.com
Telephone: 91- 22 24959898
Telephone: 91- 22 24959899
Fax: 91- 22 24937232

Section 2 - HAZARDS IDENTIFICATION

HAZARD RATINGS

GHS Classification

Acute Toxicity (Dermal) Category 4
Acute Toxicity (Inhalation) Category 4
Acute Toxicity (Oral) Category 4

continued...

EMERGENCY OVERVIEW

HAZARD
WARNING
Determined by using GHS criteria:
H302 H312 H332
Harmful if swallowed
Harmful in contact with skin
Harmful if inhaled

PRECAUTIONARY STATEMENTS

Prevention
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

Response
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
Rinse mouth.
Wash contaminated clothing before reuse.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
ammonium fluorosilicate	16919-19-0	6.34
nitric acid	7697-37-2	NOT SPEC
water	7732-18-5	NOT SPEC

Section 4 - FIRST AID MEASURES

SWALLOWED
■ If poisoning occurs, contact a doctor or Poisons Information Centre.

EYE
■ If this product comes in contact with the eyes:
• Immediately hold eyelids apart and flush the eye continuously with running water.
• Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
• Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
• Transport to hospital or doctor without delay.
• Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN
■ If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.

INHALED
• If fumes or combustion products are inhaled remove from contaminated area.
• Lay patient down. Keep warm and rested.

continued...

- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

■ For acute or short term repeated exposures to fluorides:
- Fluoride absorption from gastro-intestinal tract may be retarded by calcium salts, milk or antacids.
- Fluoride particulates or fume may be absorbed through the respiratory tract with 20-30% deposited at alveolar level.
- Peak serum levels are reached 30 mins. post-exposure; 50% appears in the urine within 24 hours.
- For acute poisoning (endotracheal intubation if inadequate tidal volume), monitor breathing and evaluate/monitor blood pressure and pulse frequently since shock may supervene with little warning. Monitor ECG immediately; watch for arrhythmias and evidence of Q-T prolongation or T-wave changes. Maintain monitor. Treat shock vigorously with isotonic saline (in 5% glucose) to restore blood volume and enhance renal excretion.
- Where evidence of hypocalcaemic or normocalcaemic tetany exists, calcium gluconate (10 ml of a 10% solution) is injected to avoid tachycardia.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
Fluorides in urine	3 mg/gm creatinine	Prior to shift	B, NS
	10mg/gm creatinine	End of shift	B, NS

B: Background levels occur in specimens collected from subjects NOT exposed

NS: Non-specific determinant; also observed after exposure to other exposures.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

■ There is no restriction on the type of extinguisher which may be used.

FIRE FIGHTING

- Use water delivered as a fine spray to control fire and cool adjacent area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered a significant fire risk, however containers may burn.

Decomposition may produce toxic fumes of: nitrogen oxides (NOx) and hydrogen fluoride.

FIRE INCOMPATIBILITY

■ Avoid reaction with strong alkalis.

continued...

PERSONAL PROTECTION

Glasses:	Gloves:	Respirator:
Safety Glasses.	PVC chemical resistant type.	Particulate

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING
- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER
- Packaging as recommended by manufacturer.
- Check that containers are clearly labelled.
- Glass container is suitable for laboratory quantities.

STORAGE INCOMPATIBILITY
- Segregate from strong acids and strong alkalis.

STORAGE REQUIREMENTS
Treat as a high purity analytical standard solution.
Do not return any unused solution to the Stock bottle.
- Store in original containers.

continued...

• Keep containers securely sealed.
• Store in a cool, dry, well-ventilated area.
• Store away from incompatible materials and foodstuff containers.
• Protect containers against physical damage and check regularly for leaks.
• Observe manufacturer's storing and handling recommendations.
Limited shelf life

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

+	X	+	X	X	+

+: May be stored together
O: May be stored together with specific preventions
X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA mg/m³
Australia Exposure Standards	ammonium fluorosilicate (Fluorides (as F))	2.5

The following materials had no OELs on our records
• water: CAS:7732- 18- 5

MATERIAL DATA
SILICON STANDARD SOLUTION 1000 MG/L:
■ None assigned. Refer to individual constituents.

AMMONIUM FLUOROSILICATE:
■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.
OSHA (USA) concluded that exposure to sensory irritants can:
• cause inflammation
• cause increased susceptibility to other irritants and infectious agents
• lead to permanent injury or dysfunction
• permit greater absorption of hazardous substances and
• acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.
For fluorides:

continued...

Based on a study in which the threshold for minimum increase in bone density due to fluoride exposure was 3.38 mg/m3 (as fluoride), the present TLV-TWA has been adopted to prevent irritant effects and disabling bone changes. There is also support for the proposition that occupational exposure below the TLV will have no adverse effect on pregnant women or off-spring. IARC has classified fluorides in drinking water as Group 3 carcinogens; i.e. Not classifiable as to its carcinogenicity to humans. Equivocal evidence of carcinogenic activity (osteosarcoma) has been found in male rats administered sodium fluoride in drinking water. (0-175 ppm) Evidence was not found in female rats or in male or female mice.

WATER:
■ No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION





EYE
■ None under normal operating conditions.
OTHERWISE: • Safety glasses.

HANDS/FEET
• Polyethylene gloves.
• PVC gloves.
• Neoprene rubber gloves.

OTHER
■ Operators should be trained in procedures for safe use of this material.
None under normal operating conditions.
OTHERWISE:.
Overalls.
Laboratory coat.

RESPIRATOR
■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	- AUS P	-
1000	50	-	- AUS P
5000	50	Airline *	-
5000	100	-	- 2 P
10000	100	-	- 3 P
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult your

continued...

Occupational Health and Safety Advisor.

ENGINEERING CONTROLS
■ Use in a well-ventilated area.
General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE
Clear, colourless, odourless liquid. Mixes with water.
Nominal concentration is 10,000 micrograms per mL of silicon (Si) as diammonium silicofluoride $(NH_4)_2SiF_6$ in water.

continued...

PHYSICAL PROPERTIES
Liquid.
Mixes with water.

State	Liquid	Molecular Weight	28.09 Si
Melting Range (°C)	Not available	Boiling Range (°C)	100 approx
Solubility in water (g/L)	Miscible	Flash Point (°C)	Not applicable
pH (1% solution)	Not available	Decomposition Temp (°C)	Not available
pH (as supplied)	7 est.	Autoignition Temp (°C)	Not applicable
Vapour Pressure (kPa)	as water	Upper Explosive Limit (%)	Not applicable
Specific Gravity (water=1)	1.0	Lower Explosive Limit (%)	Not applicable
Relative Vapour Density (air=1)	Not available	Volatile Component (%vol)	Not available
Evaporation Rate	Not available		

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY
• Presence of incompatible materials.
• Product is considered stable.
• Hazardous polymerisation will not occur.
For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED
■ Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
■ Fluoride causes severe loss of calcium in the blood, with symptoms appearing several hours later including painful and rigid muscle contractions of the limbs. Cardiovascular collapse can occur and may cause death with increased heart rate and other heart rhythm irregularities. The brain and kidneys may be affected. Other toxic effects include headache, increased saliva output, jerking of the eyeball and dilated pupils, lethargy, stupor, coma and rarely, convulsions.
■ Large doses of ammonia or injected ammonium salts may produce diarrhoea and may be sufficiently absorbed to produce increased production of urine and systemic poisoning. Symptoms include weakening of facial muscle, tremor, anxiety, reduced muscle and limb control.

EYE
■ Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN
■ Skin contact with the material may be harmful; systemic effects may result following absorption.
■ The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED
■ The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of the material, especially for prolonged periods, may produce respiratory

continued...

discomfort and occasionally, distress.

CHRONIC HEALTH EFFECTS
■ Principal routes of exposure are usually by skin contact, eye contact and inhalation of vapour/spray mist. Extended exposure to inorganic fluorides causes fluorosis, which includes signs of joint pain and stiffness, tooth discolouration, nausea and vomiting, loss of appetite, diarrhoea or constipation, weight loss, anaemia, weakness and general unwellness. There may also be frequent urination and thirst. Redness, itchiness and allergy-like inflammation of the skin and mouth cavity can occur. The central nervous system may be involved.

TOXICITY AND IRRITATION
■ Not available. Refer to individual constituents.

AMMONIUM FLUOROSILICATE:
■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY	IRRITATION
Oral (rat) LDLo: 100 mg/kg	Nil Reported

WATER:
■ No significant acute toxicological data identified in literature search.

CARCINOGEN

Fluorides (inorganic, used in drinking-water)	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

AMMONIUM FLUOROSILICATE:
■ Although small amounts of fluorides are conceded to have beneficial effects, two forms of chronic toxic effect, dental fluorosis and skeletal fluorosis may be caused by excessive intake over long periods.
Fluorides are absorbed by humans following inhalation of workplace and ambient air that has been contaminated, ingestion of drinking water and foods and dermal contact.

Both hydrogen fluoride and particulate fluorides will be transported in the atmosphere and deposited on land or water by wet and dry deposition. Non-volatile inorganic fluoride particulates are removed from the atmosphere via condensation or nucleation processes. Fluorides adsorbed on particulate matter in the atmosphere are generally stable and are not readily hydrolysed, although they may be degraded by radiation if they persist in the atmosphere. Fluorine and the silicon fluorides (fluosilicates, silicofluorides) are hydrolysed in the atmosphere to form hydrogen fluoride. Hydrogen fluoride may combine with water vapour to produce an aerosol or fog of aqueous hydrofluoric acid. Based upon available data, inorganic fluoride compounds, with the exception of sulfur hexafluoride, are not expected to remain in the troposphere for long periods or to migrate to the stratosphere. Estimates of the residence time of sulfur hexafluoride in the atmosphere range from 500 to several thousand years. Fluoride in aerosols can be transported over large distances by wind or as a result of atmospheric turbulence. The distance travelled is determined by the deposition velocity of both the gaseous hydrogen fluoride and the fluorides in particulate form. Atmospheric fluorides may be transported to soils and surface waters through both wet and dry deposition processes.

Fluorides undergo transformations in soil and water, forming complexes and binding strongly to soil and sediment.

continued...

In water, the transport and transformation of inorganic fluorides are influenced by pH, water hardness and the presence of ion-exchange materials such as clays. In natural water, fluoride forms strong complexes with aluminum in water, and fluorine chemistry in water is largely regulated by aluminum concentration and pH. Below pH 5, fluoride is almost entirely complexed with aluminum and consequently, the concentration of free F- is low. As the pH increases, Al-OH complexes dominate over Al-F complexes and the free F- levels increase. Fluoride forms stable complexes with calcium and magnesium, which are present in sea water. Calcium carbonate precipitation dominates the removal of dissolved fluoride from sea water. The residence time for fluoride in ocean sediment is calculated to be 2?3 million years. Fluorosilicic acid and hydrofluoric acid in high aquatic concentrations such as may be found in industrial waste ponds may volatilise, releasing silicon tetrafluoride and hydrogen fluoride into the atmosphere.

Solubilisation of inorganic fluorides from minerals may also be enhanced by the presence of ion-exchange materials (e.g., bentonite clays and humic acid). Once dissolved, inorganic fluorides remain in solution under conditions of low pH and hardness and in the presence of ion-exchange material. Soluble inorganic fluorides may also form aerosols at the air?water interface or vaporise into the atmosphere whereas undissolved species generally undergo sedimentation.

Factors that influence the mobility of inorganic fluorides in soil are pH and the formation of aluminium and calcium complexes In more acidic soils, concentrations of inorganic fluoride were considerably higher in the deeper horizons. The low affinity of fluorides for organic material results in leaching from the more acidic surface horizon and increased retention by clay minerals and silts in the more alkaline, deeper horizons. The maximum adsorption of fluoride to soil was reported to occur at pH 5.5. In acidic soils with pH below 6, most of the fluoride is in complexes with either aluminium or iron. Fluoride in alkaline soils at pH 6.5 and above is almost completely fixed in soils as calcium fluoride, if sufficient calcium carbonate is available.
Fluoride is extremely immobile in soil, as determined by lysimeter experiments.
Populations living in areas with high fluoride levels in groundwater may be exposed to higher levels of fluorides in their drinking water or in beverages prepared with the water. Among these populations, outdoor laborers, people living in hot climates, and people with polydipsia will generally have the greatest daily intake of fluorides because they consume greater amounts of water.
Foods characteristically high in fluoride content are certain types of fish and seafood (1.9?28.5 mg/kg), especially those types in which the bones are consumed, bone products such as bone meal and gelatin, and tea, which contains approximately 0.52 mg fluoride/cup

Fluoride is mainly absorbed by the body in the form of hydrogen fluoride, which has a pKa of 3.45. That is, when ionic fluoride enters the acidic environment of the stomach lumen, it is largely converted into hydrogen fluoride. Most of the fluoride that is not absorbed from the stomach will be rapidly absorbed from the small intestine.

Fluorides have been shown to accumulate in animals that consume fluoride-containing foliage accumulation is primarily in skeletal tissue and therefore, it is unlikely that fluoride will biomagnify up the food chain.

.

■ In air ammonia is persistent whilst, in water, it biodegrades rapidly to nitrate, producing a high oxygen demand. Ammonia is strongly adsorbed to soil. Ammonia is non-persistent in water (half-life 2 days) and is moderately toxic to fish under normal temperature and pH conditions. Ammonia is harmful to aquatic life at low concentrations but does not concentrate in the food chain.
Drinking Water Standards:
0.5 mg/l (UK max.)
1.5 mg/l (WHO Levels)
Soil Guidelines: none available.
Air Quality Standards: none available.
■ DO NOT discharge into sewer or waterways.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
water	LOW		LOW	HIGH

continued...

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:
- None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS
Regulations for ingredients

ammonium fluorosilicate (CAS: 16919-19-0,1309-32-6) is found on the following regulatory lists;
"Australia Hazardous Substances","Australia Inventory of Chemical Substances (AICS)"

water (CAS: 7732-18-5) is found on the following regulatory lists;
"Australia Inventory of Chemical Substances (AICS)","IMO IBC Code Chapter 18: List of products to which the Code does not apply","OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Silicon Standard Solution 1000 mg/L (CW: 5504-76)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
ammonium fluorosilicate	16919- 19- 0, 1309- 32- 6

EXPOSURE STANDARD FOR MIXTURES

■ "Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

■ Composite Exposure Standard for Mixture (TWA) :100 mg/m³.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

continued...

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 31-Oct-2017