

ALUMINIUM STANDARD SOLUTION (1000 mg/L)

GHS Safety Data Sheet

Version No:2.0
Page 1 of 12

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

ALUMINIUM STANDARD SOLUTION (1000mg/L)

OTHER NAMES

"standard solution of aluminium", "AAS standard solution for Al", "ICP standard for Al³⁺", "spectrometric standard solution", "laboratory reagent"

PRODUCT USE

Laboratory reagent, standard solution of known ionic concentration.
Further diluted before use as calibration solution.

SUPPLIER

Company: S D FINE - CHEM LIMITED

Address:

315- 317, T.V.IND.ESTATE,

248 WORLI ROAD,

MUMBAI- 400 030, INDIA

technical@sdfine.com


Telephone: 91- 22 24959898

Telephone: 91- 22 24959899

Fax: 91- 22 24937232

Section 2 - HAZARDS IDENTIFICATION

HAZARD RATINGS



GHS Classification

Acute Toxicity (Inhalation) Category 3

Eye Irritation Category 2A

Serious Eye Damage Category 1

Skin Corrosion/Irritation Category 2

ALUMINIUM STANDARD SOLUTION (1000mg/L)

GHS Safety Data Sheet

Version No:2.0

Page 2 of 12

Section 2 - HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:

H331 H315 H315 H318 H319

Toxic if inhaled

Causes skin irritation

Causes skin irritation

Causes serious eye damage

Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Call a POISON CENTER or doctor/physician.

If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
aluminium nitrate	13473-90-0	1
nitric acid	7697-37-2	NOT SPEC
water	7732-18-5	NOT SPEC

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

continued...

ALUMINIUM STANDARD SOLUTION (1000 mg/L)

GHS Safety Data Sheet

Version No:2.0

Page 3 of 12

Section 4 - FIRST AID MEASURES

EYE

- If this product comes in contact with the eyes:
 - Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
 - Not considered a significant fire risk, however containers may burn.
- Decomposes on heating and produces toxic fumes of nitrogen oxides (NO_x).

FIRE INCOMPATIBILITY

- None known.

PERSONAL PROTECTION

Glasses:	Gloves:	Respirator:
Not normally required.	When handling larger quantities:	Type AE- P Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Wipe up.

continued...

ALUMINIUM STANDARD SOLUTION (1000mg/L)

GHS Safety Data Sheet

Version No:2.0

Page 4 of 12

Section 6 - ACCIDENTAL RELEASE MEASURES

Place in clean drum then flush area with water.

MAJOR SPILLS

- Minor hazard.
- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER

- Packaging as recommended by manufacturer.
- Check that containers are clearly labelled.
- Glass container is suitable for laboratory quantities.

STORAGE INCOMPATIBILITY

- Segregate from strong acids and strong alkalis.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

continued...

ALUMINIUM STANDARD SOLUTION (1000mg/L)

GHS Safety Data Sheet

Version No:2.0
Page 5 of 12

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
Australia Exposure Standards	aluminium nitrate (Aluminium, soluble salts (as Al))		2		
Australia Exposure Standards	nitric acid (Nitric acid)	2	5.2	4	10

The following materials had no OELs on our records

- water:

CAS:7732- 18- 5

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
nitric acid		25

MATERIAL DATA

BIOLAB ALUMINIUM STANDARD SOLUTION (10000 PPM):

- None assigned. Refer to individual constituents.

ALUMINIUM NITRATE:

■ The TLV is based on the exposures to aluminium chloride and the amount of hydrolysed acid and the corresponding acid TLV to provide the same degree of freedom from irritation. Workers chronically exposed to aluminium dusts and fumes have developed severe pulmonary reactions including fibrosis, emphysema and pneumothorax. A much rarer encephalopathy has also been described.

NITRIC ACID:

- For nitric acid:

Odour Threshold Value: 0.27 ppm (detection)




NOTE: Detector tubes for nitric acid, measuring in excess of 5 ppm, are commercially available.

The TLV-TWA is protective against corrosion of the skin, tissue and other membranes, against irritation to the eyes and mucous membranes, and against acute pulmonary oedema or chronic obstructive lung disease. It is not clear whether the TLV-TWA and STEL values will prevent potentiation of the toxicity of inhaled nitrogen dioxide.

WATER:

- No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION



EYE

- No special equipment for minor exposure i.e. when handling small quantities.

• OTHERWISE:

- Safety glasses with side shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A

continued...

ALUMINIUM STANDARD SOLUTION (1000mg/L)

GHS Safety Data Sheet

Version No:2.0

Page 6 of 12

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

■ No special equipment needed when handling small quantities.

OTHERWISE: Wear general protective gloves, eg. light weight rubber gloves.

OTHER

■ Laboratory coat.

• Eyewash unit.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AE- AUS P	-
1000	50	-	AE- AUS P
5000	50	Airline *	-
5000	100	-	AE- 2 P
10000	100	-	AE- 3 P
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ None under normal operating conditions.

Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear, colourless, odourless liquid; mixes with water.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

State	Liquid	Molecular Weight	Not applicable
Melting Range (°C)	<0	Boiling Range (°C)	100 approx.
Solubility in water (g/L)	Miscible	Flash Point (°C)	Not applicable
pH (1% solution)	>1	Decomposition Temp (°C)	Not available

continued...

ALUMINIUM STANDARD SOLUTION (1000 mg/L)

GHS Safety Data Sheet

Version No:2.0

Page 7 of 12

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

pH (as supplied)	Not available	Autoignition Temp (°C)	Not applicable
Vapour Pressure (kPa)	2.33 as water	Upper Explosive Limit (%)	Not applicable
Specific Gravity (water=1)	1.0 approx.	Lower Explosive Limit (%)	Not applicable
Relative Vapour Density (air=1)	Not available	Volatile Component (%vol)	Not available
Evaporation Rate	As for water.		

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Product is considered stable and hazardous polymerisation will not occur.
For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.
- Considered an unlikely route of entry in commercial/industrial environments.

EYE

- This material can cause eye irritation and damage in some persons.

SKIN

- This material can cause inflammation of the skin on contact in some persons.
- Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

INHALED

- The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
- Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

- Primary route of exposure is usually by skin contact/eye contact.
As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

TOXICITY AND IRRITATION

- Not available. Refer to individual constituents.

ALUMINIUM NITRATE:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

IRRITATION

continued...

ALUMINIUM STANDARD SOLUTION (1000mg/L)

GHS Safety Data Sheet

Version No:2.0

Page 8 of 12

Section 11 - TOXICOLOGICAL INFORMATION

Oral (rat) LD50: 3654 mg/kg

Oral (Rat) LD50: 204 mg/kg

Oral (Mouse) LD50: 370 mg/kg

Intraperitoneal (Rat) LD50: 901 mg/kg

Intraperitoneal (Mouse) LD50: 1587 mg/kg

■ The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

Skin (rabbit): 500mg - Mild

Eye (rabbit): 100mg - SEVERE

NITRIC ACID:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 430 mg/kg

Inhalation (rat) LC50: 2500 ppm/1h * * DuPont

Unreported (man) LDLo: 110 mg/kg

Inhalation (Cat) LC: 500 mg/m³/4h

Inhalation (Rat) LC50: 130 mg/m³/4h

Oral (Human) LD: 430 mg/kg

Inhalation (Cat) TCLo: 300 mg/m³/2h

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

Oral (?) LD50: 50-500 mg/kg *

[Various Manufacturers]

IRRITATION

Nil Reported

WATER:

■ No significant acute toxicological data identified in literature search.

CARCINOGEN

Nitrate or nitrite (ingested) under conditions that result in endogenous nitrosation

International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs

Group

2A

continued...

ALUMINIUM STANDARD SOLUTION (1000mg/L)

GHS Safety Data Sheet

Version No:2.0
Page 9 of 12

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

NITRIC ACID:

ALUMINIUM NITRATE:

- DO NOT discharge into sewer or waterways.

ALUMINIUM NITRATE:

- Toxic to aquatic organisms.

■ Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

■ The nitrates are of environmental concern because of their high water solubility and consequent leaching, diffusion, and environmental mobility in soil and water. Nitrate can contaminate groundwater to unacceptable levels. Nitrite is formed from nitrate or ammonium ion by micro-organisms in soil, water, sewage and the alimentary tract. The concern with nitrate in the environment is related to its conversion to nitrite.

Methaemoglobinaemia is caused following exposure to high levels of nitrite and produces difficulties in oxygen transport in the blood. Thousands of cases involving poisoning of infants, particularly in rural areas, have been reported as a result of drinking nitrate rich well-water.

Other concerns deriving from exposure to environmental nitrates relate to the production of nitrosamines following the reaction of food nitrites and secondary amines. Other nitroso-compounds may result following reaction with nitrites and amides, ureas, carbamates and other nitrogenous compounds. Nitrosamines produce liver damage, haemorrhagic lung lesions, convulsions and coma in rats, and teratogenic effects in experimental animals.

The N-nitroso class of compounds include potent carcinogens and mutagens: induction of tumors by single doses of N-nitroso compounds testify to this.

- For aluminium and its compounds and salts:

Environmental fate:

Aluminium occurs in the environment in the form of silicates, oxides and hydroxides, combined with other elements such as sodium, fluorine and arsenic complexes with organic matter.

Acidification of soils releases aluminium as a transportable solution. Mobilisation of aluminium by acid rain results in aluminium becoming available for plant uptake.

As an element, aluminum cannot be degraded in the environment, but may undergo various precipitation or ligand exchange reactions. Aluminum in compounds has only one oxidation state (+3), and would not undergo oxidation-reduction reactions under environmental conditions. Aluminum can be complexed by various ligands present in the environment (e.g., fulvic and humic acids). The solubility of aluminum in the environment will depend on the ligands present and the pH.

The trivalent aluminum ion is surrounded by six water molecules in solution. The hydrated aluminum ion, $[Al(H_2O)_6]^{3+}$, undergoes hydrolysis, in which a stepwise deprotonation of the coordinated water ligands forms bound hydroxide ligands (e.g., $[Al(H_2O)_5(OH)]^{2+}$, $[Al(H_2O)_4(OH)_2]^+$). The speciation of aluminum in water is pH dependent. The hydrated trivalent aluminum ion is the predominant form at pH levels below 4. Between pH 5 and 6, the predominant hydrolysis products are $Al(OH)_2^+$ and $Al(OH)_2^+$, while the solid $Al(OH)_3$ is most prevalent between pH 5.2 and 8.8. The soluble species $Al(OH)_4^-$ is the predominant species above pH 9, and is the only species present above pH 10. Polymeric aluminum hydroxides appear between pH 4.7 and 10.5, and increase in size until they are transformed into colloidal particles of amorphous $Al(OH)_3$, which crystallise to gibbsite in acid waters. Polymerisation is affected by the presence of dissolved silica; when enough silica is present, aluminum is precipitated as poorly crystallised clay mineral species.

Hydroxyaluminum compounds are considered amphoteric (e.g., they can act as both acids and bases in solution). Because of this property, aluminum hydroxides can act as buffers and resist pH changes within the narrow pH range of 4-5.

Monomeric aluminum compounds, typified by aluminum fluoride, chloride, and sulfate, are considered reactive or labile compounds, whereas polymeric aluminum species react much more slowly in the environment. Aluminum has a stronger attraction for fluoride in an acidic environment compared to other inorganic ligand.

The adsorption of aluminum onto clay surfaces can be a significant factor in controlling aluminum mobility in the environment, and these adsorption reactions, measured in one study at pH 3.0-4.1, have been observed to be very rapid. However, clays may act either as a sink or a source for soluble aluminum depending on the degree of aluminum saturation on the clay surface.

continued...

ALUMINIUM STANDARD SOLUTION (1000mg/L)

GHS Safety Data Sheet

Version No:2.0

Page 10 of 12

Section 12 - ECOLOGICAL INFORMATION

Within the pH range of 5-6, aluminum complexes with phosphate and is removed from solution. Because phosphate is a necessary nutrient in ecological systems, this immobilization of both aluminum and phosphate may result in depleted nutrient states in surface water.

Plant species and cultivars of the same species differ considerably in their ability to take up and translocate aluminum to above-ground parts. Tea leaves may contain very high concentrations of aluminum, >5,000 mg/kg in old leaves. Other plants that may contain high levels of aluminum include Lycopodium (Lycopodiaceae), a few ferns, Symplocos (Symplocaceae), and Orites (Proteaceae). Aluminum is often taken up and concentrated in root tissue. In sub-alpine ecosystems, the large root biomass of the Douglas fir, *Abies amabilis*, takes up aluminum and immobilizes it, preventing large accumulation in above-ground tissue. It is unclear to what extent aluminum is taken up into root food crops and leafy vegetables. An uptake factor (concentration of aluminum in the plant/concentration of aluminum in soil) of 0.004 for leafy vegetables and 0.00065 for fruits and tubers has been reported, but the pH and plant species from which these uptake factors were derived are unclear. Based upon these values, however, it is clear that aluminum is not taken up in plants from soil, but is instead biodiluted.

Aluminum concentrations in rainbow trout from an alum-treated lake, an untreated lake, and a hatchery were highest in gill tissue and lowest in muscle. Aluminum residue analyses in brook trout have shown that whole-body aluminum content decreases as the fish advance from larvae to juveniles. These results imply that the aging larvae begin to decrease their rate of aluminum uptake, to eliminate aluminum at a rate that exceeds uptake, or to maintain approximately the same amount of aluminum while the body mass increases. The decline in whole-body aluminum residues in juvenile brook trout may be related to growth and dilution by edible muscle tissue that accumulated less aluminum than did the other tissues.

The greatest fraction of the gill-associated aluminum was not sorbed to the gill tissue, but to the gill mucus. It is thought that mucus appears to retard aluminum transport from solution to the membrane surface, thus delaying the acute biological response of the fish. It has been reported that concentrations of aluminum in whole-body tissue of the Atlantic salmon exposed to high concentrations of aluminum ranging from 3 ug/g (for fish exposed to 33 ug/L) to 96 ug/g (for fish exposed to 264 ug/L) at pH 5.5. After 60 days of exposure, BCFs ranged from 76 to 190 and were directly related to the aluminum exposure concentration. In acidic waters (pH 4.6-5.3) with low concentrations of calcium (0.5-1.5 mg Ca/L), labile aluminum between 25 and 75 ug/L is toxic. Because aluminum is toxic to many aquatic species, it is not bioaccumulated to a significant degree (BCF <300) in most fish and shellfish; therefore, consumption of contaminated fish does not appear to be a significant source of aluminum exposure in humans.

Bioconcentration of aluminum has also been reported for several aquatic invertebrate species. BCF values ranging from 0.13 to 0.5 in the whole-body were reported for the snail. Bioconcentration of aluminum has also been reported for aquatic insects.

Ecotoxicity:

Freshwater species pH >6.5

Fish: Acute LC50 (48-96 h) 5 spp: 0.6 (*Salmo salar*) - 106 mg/L; Chronic NOEC (8-28 d): 7 spp, NOEC, 0.034-7.1 mg/L. The lowest measured chronic figure was an 8-d LC50 of 0.17 mg/L for *Micropterus* sp.

Amphibian: Acute LC50 (4 d): *Bufo americanus*, 0.86-1.66 mg/L; Chronic LC50 (8-d) 2.28 mg/L

Crustaceans LC50 (48 h): 1 sp 2.3-36.9 mg/L; Chronic NOEC (7-28 d) 3 spp, 0.136-1.72 mg/L

Algae EC50 (96 h): population growth, 0.46-0.57 mg/L; 2 spp, chronic NOEC, 0.8-2.0 mg/L

Freshwater species pH <6.5 (all between pH 4.5 and 6.0)

Fish LC50 (24-96 h): 4 spp, 0.015 (*S. trutta*) - 4.2 mg/L; chronic data on *Salmo trutta*, LC50 (21-42 d) 0.015-0.105 mg/L

Amphibians LC50 (4-5 d): 2 spp, 0.540-2.670 mg/L (absolute range 0.40-5.2 mg/L)

Alga: 1 sp NOEC growth 2.0 mg/L

Among freshwater aquatic plants, single-celled plants are generally the most sensitive to aluminium. Fish are generally more sensitive to aluminium than aquatic invertebrates. Aluminium is a gill toxicant to fish, causing both ionoregulatory and respiratory effects.

The bioavailability and toxicity of aluminium is generally greatest in acid solutions. Aluminium in acid habitats has been observed to be toxic to fish and phytoplankton. Aluminium is generally more toxic over the pH range 4.4-5.4, with a maximum toxicity occurring around pH 5.0-5.2. The inorganic single unit aluminium species ($\text{Al}(\text{OH})_2^+$) is thought to be the most toxic. Under very acid conditions, the toxic effects of the high H^+ concentration appear to be more important than the effects of low concentrations of aluminium; at approximately neutral pH values, the toxicity of aluminium is greatly reduced. The solubility of aluminium is also enhanced under alkaline conditions, due to its amphoteric character, and some researchers found that the acute toxicity of aluminium increased from pH 7 to pH 9. However, the opposite relationship was found in other studies. The uptake and toxicity of aluminium in freshwater organisms generally decreases with increasing water hardness under acidic, neutral and alkaline conditions. Complexing agents such as fluoride,

continued...

ALUMINIUM STANDARD SOLUTION (1000mg/L)

GHS Safety Data Sheet

Version No:2.0

Page 11 of 12

Section 12 - ECOLOGICAL INFORMATION

citrate and humic substances reduce the availability of aluminium to organisms, resulting in lower toxicity. Silicon can also reduce aluminium toxicity to fish.

Drinking Water Standards:

aluminium: 200 ug/l (UK max.)

200 ug/l (WHO guideline)

chloride: 400 mg/l (UK max.)

250 mg/l (WHO guideline)

fluoride: 1.5 mg/l (UK max.)

1.5 mg/l (WHO guideline)

nitrate: 50 mg/l (UK max.)

50 mg/l (WHO guideline)

sulfate: 250 mg/l (UK max.)

Soil Guideline: none available.

Air Quality Standards: none available.

NITRIC ACID:

■ For oxides of nitrogen:

Environmental fate

Oxides of nitrogen are part of the biogeochemical cycling of nitrogen, and are found in air, soil and water. In the atmosphere, oxides of nitrogen are rapidly oxidised to nitrogen dioxide (half-life about 50 days), which dissolves in water to produce dilute nitric acid and precipitates in rain. An increased rate of formation of oxides of nitrogen therefore contributes to 'acid rain'.

In the stratosphere, oxides of nitrogen play a crucial role in maintaining the level of ozone. Ozone is formed through the photochemical reaction of nitrogen dioxide and oxygen. However, too little nitrogen dioxide results in too little ozone being formed. On the other hand, too much nitric oxide reduces the level of ozone because of an increase in the reaction of ozone to convert nitric oxide to nitrogen dioxide. In the lower atmosphere, oxides of nitrogen play a major role in the formation of photochemical smog in a complex set of reactions that lead to the formation of a variety of nitrated organic compounds (from volatile organic matter) and excessive levels of ozone.

Environmental transport The oxides of nitrogen travel as gases through soil and the atmosphere, and in solution in water in soils, rivers and lakes, and rain and snow.

■ Prevent, by any means available, spillage from entering drains or water courses.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
aluminium nitrate	LOW		LOW	HIGH
nitric acid			LOW	
water	LOW		LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Treat and neutralise at an effluent treatment plant.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

☐ None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: UN, IATA, IMDG

continued...

ALUMINIUM STANDARD SOLUTION (1000mg/L)

GHS Safety Data Sheet

Version No:2.0

Page 12 of 12

Section 14 - TRANSPORTATION INFORMATION

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

aluminium nitrate (CAS: 13473-90-0,7784-27-2,60945-31-5,35343-90-9,25749-23-9,59454-18-1) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)"

nitric acid (CAS: 7697-37-2) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

water (CAS: 7732-18-5) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Aluminium Standard Solution (1000mg/L) (54760)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
aluminium nitrate	13473- 90- 0, 7784- 27- 2, 60945- 31- 5, 35343- 90- 9, 25749- 23- 9, 59454- 18- 1

EXPOSURE STANDARD FOR MIXTURES

■ "Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

■ Composite Exposure Standard for Mixture (TWA) :100 mg/m³.

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by using available literature references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 16-Jun-2018