

STANDARD SOLUTION "CERTISOL" ICP TUNGSTEN 1000 MG/L IN HNO3 NIST TRACEABLE.

GHS Safety Data Sheet

Version No:3.1.1.1

Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

STANDARD SOLUTION "CERTISOL" ICP TUNGSTEN 1000 MG/L IN HNO3 NIST TRACEABLE

OTHER NAMES

"tungsten standard solution", "analytical reagent"

PROPER SHIPPING NAME

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.(contains hydrofluoric acid)

PRODUCT USE

Analytical reagent.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V.Ind.Estate,

248, Worli Road,

Mumbai- 400030, India

www.sdfine.com

Telephone: 91- 22 24959898/99

Fax: 91- 22 2493 7232

Email: technical@sdfine.com

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity Category 3

Acute Toxicity Category 2

Acute Toxicity Category 3

Metal Corrosion Category 1

Serious Eye Damage Category 1

Skin Corrosion/Irritation Category 1A

**EMERGENCY OVERVIEW****HAZARD**

DANGER

Determined by using GHS criteria

H290	May be corrosive to metals.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H330	Fatal if inhaled.

continued...

PRECAUTIONARY STATEMENTS**Prevention**

Code	Phrase
P234	Keep only in original container.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well- ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.

Response

Code	Phrase
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P320	Specific treatment is urgent (see MSDS).
P330	Rinse mouth.
P361	Remove/Take off immediately all contaminated clothing.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.

Storage

Code	Phrase
P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P405	Store locked up.
P406	Store in corrosive resistant container or with a resistant inner liner.

Disposal

Code	Phrase
P501	Dispose of contents/container to ...

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
nitric acid	7697-37-2	2
tungsten	7440-33-7	0.1
hydrofluoric acid	7664-39-3	1
water	7732-18-5	balance

Section 4 - FIRST AID MEASURES**SWALLOWED**

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.

SKIN

- If there is evidence of severe skin irritation or skin burns:
 - Avoid further contact. Immediately remove contaminated clothing, including footwear.
 - Flush skin under running water for 15 minutes.
 - Avoiding contamination of the hands, massage calcium gluconate gel into affected areas, pay particular attention to creases in skin.
 - Contact the Poisons Information Centre.

INHALED

- For massive exposures:
 - If dusts, vapours, aerosols, fumes or combustion products are inhaled, remove from contaminated area.
 - Lay patient down.
 - Keep warm and rested.
 - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - If fumes or combustion products are inhaled remove from contaminated area.
 - Lay patient down. Keep warm and rested.
 - Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
 - Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- For acute or short term repeated exposures to strong acids:
 - Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
 - Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
 - Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
 - Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- Heating may cause expansion or decomposition leading to violent rupture of containers.

FIRE INCOMPATIBILITY

- None known.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.

Section 6 - ACCIDENTAL RELEASE MEASURES

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.

SUITABLE CONTAINER

- DO NOT use aluminium or galvanised containers.
- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.

STORAGE INCOMPATIBILITY

- Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.
- Avoid strong bases.
- Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.
- Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts - neutralisation can generate dangerously large amounts of heat in small spaces.
- The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.
- The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³
India Permissible Levels of Certain Chemical Substances in Work Environment	nitric acid (Nitric acid)	2	5	4	10		
India Permissible Levels of Certain Chemical Substances in Work Environment	hydrofluoric acid (Hydrogen fluoride (as F))					3	2.5

The following materials had no OELs on our records

- tungsten:
- water:

CAS:7440- 33- 7
CAS:7732- 18- 5

continued...

ODOUR SAFETY FACTOR (OSF)

OSF=71 (hydrofluoric acid)

■ Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

MATERIAL DATA

HIGH-PURITY 1000UG/ML TUNGSTEN IN 2% HNO3 + 1% HF:

■ None assigned. Refer to individual constituents.

NITRIC ACID:

■ For nitric acid:

Odour Threshold Value: 0.27 ppm (detection)

NOTE: Detector tubes for nitric acid, measuring in excess of 5 ppm, are commercially available.

The TLV-TWA is protective against corrosion of the skin, tissue and other membranes, against irritation to the eyes and mucous membranes, and against acute pulmonary oedema or chronic obstructive lung disease.

TUNGSTEN:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat.

Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

Insoluble tungsten compounds include all those for which water solubility is listed as insoluble or less than 0.01 gm/100 cc water. The recommended TLV-TWA and STEL reflects the reported physiologic activity of insoluble compounds of tungsten.

HYDROFLUORIC ACID:

■ Odour Threshold for hydrogen fluoride: 0.042 ppm

NOTE: Detector tubes for hydrogen fluoride, measuring in excess of 1.5 ppm, are available commercially. Long-term measurements (8 hrs) may be conducted to detect concentrations exceeding 0.25 ppm.

Hydrogen fluoride is a primary irritant which as a gas causes severe respiratory irritation and as a liquid which causes severe and painful burns to the skin and eyes.

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

WATER:

- No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION



RESPIRATOR

- Type ABE-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure
- Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- Alternatively a gas mask may replace splash goggles and face shields.

HANDS/FEET

- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- Elbow length PVC gloves.
- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.

ENGINEERING CONTROLS

- Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear colourless liquid almost odourless to a faint pungent odour; mixes with water.

PHYSICAL PROPERTIES

Mixes with water.
Corrosive.
Acid.
Toxic or noxious vapours/gas.

State	LIQUID	Molecular Weight	Not applicable
Melting Range (°C)	Not available	Viscosity	Not Available
Boiling Range (°C)	100 approx	Solubility in water (g/L)	Miscible
Flash Point (°C)	Not applicable	pH (1% solution)	Not available
Decomposition Temp (°C)	Not available	pH (as supplied)	0.9
Autoignition Temp (°C)	Not applicable	Vapour Pressure (kPa)	Not available
Upper Explosive Limit (%)	Not applicable	Specific Gravity (water=1)	1.0 approx
Lower Explosive Limit (%)	Not applicable	Relative Vapour Density (air=1)	Not available
Volatile Component (%vol)	Not available	Evaporation Rate	Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION**CONDITIONS CONTRIBUTING TO INSTABILITY**

- Contact with alkaline material liberates heat.
 - Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION**Health hazard summary table:**

Acute toxicity	Acute Tox. (dermal) 3 Acute Tox. (inhal) 2 Acute Tox. (oral) 3
Skin corrosion/irritation	Skin Corr. 1 A
Serious eye damage/irritation	Eye Dam. 1
Respiratory or skin sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Not applicable
Reproductive toxicity	Not applicable
STOT- single exposure	Not applicable
STOT- repeated exposure	Not applicable
Aspiration hazard	Not applicable

POTENTIAL HEALTH EFFECTS**ACUTE HEALTH EFFECTS****SWALLOWED**

- Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual.
 - Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident.
 - If given orally, tungsten can accumulate in the spleen, kidney and liver.
- Symptoms of poisoning include diarrhoea, stoppage of breathing and circulatory collapse leading to death.
- Fluoride causes severe loss of calcium in the blood, with symptoms appearing several hours later including painful and rigid muscle contractions of the limbs.
- Cardiovascular collapse can occur and may cause death with increased heart rate and other heart rhythm irregularities.

EYE

- If applied to the eyes, this material causes severe eye damage.
 - Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns.
- Mild burns of the epithelia generally recover rapidly and completely.
- The vapour may produce pronounced discomfort of the eyes when present at higher concentrations and this generally gives warning

continued...

of excessive exposure and the need for control measures to ensure safe working conditions.

SKIN

- Skin contact with the material may produce toxic effects; systemic effects may result following absorption.
- Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
- Fluorides are easily absorbed through the skin and cause death of soft tissue and erode bone. Healing is delayed and death of tissue may continue to spread beneath skin.
- This material can cause inflammation of the skin on contact in some persons.

INHALED

- Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects.
- The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness.
- Acute effects of fluoride inhalation include irritation of nose and throat, coughing and chest discomfort. A single acute over-exposure may even cause nose bleed.

CHRONIC HEALTH EFFECTS

- Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs. Chronic exposure may inflame the skin or conjunctiva. Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Hydrogen fluoride easily penetrates the skin and causes destruction and corrosion of the bone and underlying tissue. Ingestion causes severe pains and burns in the mouth and throat and blood calcium levels are dangerously reduced. Symptoms include spasm and twitching of the muscles, high fever, convulsions and general extreme pain. Inhalation may cause corrosion of the throat, nose and lungs, leading to severe inflammation and lung swelling.

TOXICITY AND IRRITATION

- Not available. Refer to individual constituents.

CARCINOGEN

hydrofluoric acid	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3	Not classifiable as to its carcinogenicity to humans
-------------------	---	-------	---	--

SKIN

nitric acid	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	3C
-------------	--	-------------------------------	----

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
nitric acid	No Data Available	No Data Available	LOW	No Data Available
tungsten	No Data Available	No Data Available	No Data Available	No Data Available

continued...

Section 12 - ECOLOGICAL INFORMATION

hydrofluoric acid	No Data Available	No Data Available	LOW	No Data Available
-------------------	-------------------	-------------------	-----	-------------------

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 - Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
 - Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.
 - Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: CORROSIVE

HAZCHEM:

2X

Land Transport UNDG:

Class or division:	8	Subsidiary risk:	None
UN No.:	3264	UN packing group:	II
Shipping Name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains hydrofluoric acid)			

Air Transport IATA:

ICAO/IATA Class:	8	ICAO/IATA Subrisk:	None
UN/ID Number:	3264	Packing Group:	II
Special provisions:	A3A803		

Shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains hydrofluoric acid)

Maritime Transport IMDG:

IMDG Class:	8	IMDG Subrisk:	None
UN Number:	3264	Packing Group:	II
EMS Number:	F- A, S- B	Special provisions:	274

Limited Quantities: 1 L

Shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains hydrofluoric acid)

Section 15 - REGULATORY INFORMATION

REGULATIONS

continued...

Regulations for ingredients**nitric acid (CAS: 7697-37-2) is found on the following regulatory lists;**

"FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "India Hazardous Wastes (Management, Handling and Transboundary Movement) Rules - Schedule 2: List of Wastes Constituents with Concentration Limits", "India Manufacture, Storage and Import of Hazardous Chemical Rules - Schedule 1: List of Hazardous and Toxic Chemicals", "India Permissible Levels of Certain Chemical Substances in Work Environment", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD List of High Production Volume (HPV) Chemicals"

tungsten (CAS: 7440-33-7) is found on the following regulatory lists;

"FisherTransport Information", "India Manufacture, Storage and Import of Hazardous Chemical Rules - Schedule 1: List of Hazardous and Toxic Chemicals", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information"

hydrofluoric acid (CAS: 7664-39-3) is found on the following regulatory lists;

"FisherTransport Information", "India Chemical Accidents Rules - Schedule 1: List of Hazardous Chemicals", "India Chemical Accidents Rules - Schedule 3: Named Chemicals", "India Hazardous Wastes (Management, Handling and Transboundary Movement) Rules - Schedule 2: List of Wastes Constituents with Concentration Limits", "India Manufacture, Storage and Import of Hazardous Chemical Rules - Schedule 1: List of Hazardous and Toxic Chemicals", "India Manufacture, Storage and Import of Hazardous Chemical Rules - Schedule 3: List of Hazardous Chemicals for Application of Rules 5 and 7 to 15", "India Permissible Levels of Certain Chemical Substances in Work Environment", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information", "The Australia Group Export Control List: Chemical Weapons Precursors", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

water (CAS: 7732-18-5) is found on the following regulatory lists;

"IMO IBC Code Chapter 18: List of products to which the Code does not apply", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information"

No data for High-Purity 1000ug/ml Tungsten in 2% HNO3 + 1% HF (CW: 4539-28)

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 15-Apr-2018