

INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3
Page 1 of 14

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

INDIUM 1000MG/L STANDARD SOLUTION

OTHER NAMES

"indium standard solution"

PROPER SHIPPING NAME

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.(contains nitric acid)

PRODUCT USE

General laboratory reagent; spectroscopic calibration solution for cerium.

SUPPLIER

Company: S D FINE - CHEM LIMITED

Address:

315- 317, T.V.IND.ESTATE,

248 WORLI ROAD,

MUMBAI- 400 030, INDIA

technical@sdfine.com


Telephone: 91- 22 24959898

Telephone: 91- 22 24959899

Fax: 91- 22 24937232

Section 2 - HAZARDS IDENTIFICATION

HAZARD RATINGS



GHS Classification

Acute Toxicity (Inhalation) Category 3

Eye Irritation Category 2A

Metal Corrosion Category 1

Respiratory Irritation Category 3

Serious Eye Damage Category 1

Skin Corrosion/Irritation Category 2

continued...

INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3

Page 2 of 14

Section 2 - HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:

H335 H331 H315 H290 H315 H318 H319

May cause respiratory irritation

Toxic if inhaled

Causes skin irritation

May be corrosive to metals

Causes skin irritation

Causes serious eye damage

Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Keep only in original container.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Call a POISON CENTER or doctor/physician.

Call a POISON CENTER or doctor/physician if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Absorb spillage to prevent material damage.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Store in corrosive resistant container or with a resistant inner liner.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
nitric acid	7697-37-2	NOT SPEC
indium(III) nitrate	13465-14-0	0.1
water	7732-18-5	NOT SPEC

continued...

Section 4 - FIRST AID MEASURES

SWALLOWED

- If poisoning occurs, contact a doctor or Poisons Information Centre.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

- Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible liquid.
- Will not burn, but heat produces highly toxic fumes/vapours.

FIRE INCOMPATIBILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES


MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Minor hazard.
- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

PROTECTIVE ACTIONS FOR SPILL



From IERG (Canada/Australia)

Isolation Distance	25 metres
Downwind Protection Distance	250 metres
IERG Number	37

FOOTNOTES

- 1 PROTECTIVE ACTION ZONE is defined as the area in which people are at risk of harmful exposure. This zone assumes that random changes in wind direction confines the vapour plume to an area within 30 degrees on either side of the predominant wind direction, resulting in a crosswind protective action distance equal to the downwind protective action distance.
- 2 PROTECTIVE ACTIONS should be initiated to the extent possible, beginning with those closest to the spill

and working away from the site in the downwind direction. Within the protective action zone a level of vapour concentration may exist resulting in nearly all unprotected persons becoming incapacitated and unable to take protective action and/or incurring serious or irreversible health effects.

3 INITIAL ISOLATION ZONE is determined as an area, including upwind of the incident, within which a high probability of localised wind reversal may expose nearly all persons without appropriate protection to life-threatening concentrations of the material.

4 SMALL SPILLS involve a leaking package of 200 litres (55 US gallons) or less, such as a drum (jerrican or box with inner containers). Larger packages leaking less than 200 litres and compressed gas leaking from a small cylinder are also considered "small spills".

LARGE SPILLS involve many small leaking packages or a leaking package of greater than 200 litres, such as a cargo tank, portable tank or a "one-tonne" compressed gas cylinder.

5 Guide 154 is taken from the US DOT emergency response guide book.

6 IERG information is derived from CANUTEC - Transport Canada.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Packaging as recommended by manufacturer.
- Check that containers are clearly labelled.
- Glass container is suitable for laboratory quantities.

STORAGE INCOMPATIBILITY

- Segregate from.
metals and alkalies.

STORAGE REQUIREMENTS

- Store in original containers.
 - Keep containers securely sealed.
 - Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storing and handling recommendations.
- Store between 15-25 degC.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3

Page 6 of 14

Section 7 - HANDLING AND STORAGE

+: May be stored together
O: May be stored together with specific precautions
X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
Australia Exposure Standards	nitric acid (Nitric acid)	2	5.2	4	10

The following materials had no OELs on our records

• water: CAS:7732- 18- 5

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
nitric acid		25

MATERIAL DATA

INDIUM 1000MG/L STANDARD SOLUTION

Not available

NITRIC ACID:

- For nitric acid:

Odour Threshold Value: 0.27 ppm (detection)

NOTE: Detector tubes for nitric acid, measuring in excess of 5 ppm, are commercially available.

The TLV-TWA is protective against corrosion of the skin, tissue and other membranes, against irritation to the eyes and mucous membranes, and against acute pulmonary oedema or chronic obstructive lung disease. It is not clear whether the TLV-TWA and STEL values will prevent potentiation of the toxicity of inhaled nitrogen dioxide.




INDIUM(III) NITRATE:

■ The character and severity of injury produced by indium salts (particularly pulmonary toxicity) has led to a recommendation for a relatively low value of the TLV-TWA.

WATER:

- No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION



EYE

- Safety glasses.
- Safety glasses with side shields.

continued...

INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3

Page 7 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- PVC gloves.

OTHER

- No special equipment needed when handling small quantities

OTHERWISE:

- Overalls
- Eyewash unit.

RESPIRATOR

- Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AE- AUS P	-
1000	50	-	AE- AUS P
5000	50	Airline *	-
5000	100	-	AE- 2 P
10000	100	-	AE- 3 P
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:
solvent, vapours, degreasing etc., evaporating from tank (in still air)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)

Air Speed:
0.25- 0.5 m/s (50- 100 f/min)

0.5- 1 m/s (100- 200 f/min.)

continued...

INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3
Page 8 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

1- 2.5 m/s (200- 500 f/min)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless, almost odourless liquid; mixes with water.
Solution pH low to maintain cerium (III) stability.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.
Corrosive.

State	Liquid	Molecular Weight	Not applicable.
Melting Range (°C)	Not available	Viscosity	Not available
Boiling Range (°C)	Not available	Solubility in water (g/L)	Miscible
Flash Point (°C)	Not applicable	pH (1% solution)	Not available
Decomposition Temp (°C)	Not available	pH (as supplied)	< 1
Autoignition Temp (°C)	Not available.	Vapour Pressure (kPa)	Not available
Upper Explosive Limit (%)	Not applicable.	Specific Gravity (water=1)	1.02
Lower Explosive Limit (%)	Not applicable.	Relative Vapour Density (air=1)	Not available
Volatile Component (%vol)	Not available	Evaporation Rate	Not available

continued...

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Product is considered stable and hazardous polymerisation will not occur.
For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS**ACUTE HEALTH EFFECTS****SWALLOWED**

- Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.
- Considered an unlikely route of entry in commercial/industrial environments.

EYE

- This material can cause eye irritation and damage in some persons.
- The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

- This material can cause inflammation of the skin on contact in some persons.
- Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.
- The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

INHALED

- If inhaled, this material can irritate the throat and lungs of some persons.
- Although inhalation is not thought to produce harmful effects (as classified under EC Directives), the material may still produce health damage, especially where pre-existing organ (e.g. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally confined to doses producing mortality rather than those producing morbidity (disease, ill-health).
- Inhalation hazard is increased at higher temperatures.
- The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function.

CHRONIC HEALTH EFFECTS

- Principal routes of exposure are usually by skin contact/eye contact with the liquid.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

TOXICITY AND IRRITATION

- None assigned. Refer to individual constituents.

NITRIC ACID:

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3

Page 10 of 14

Section 11 - TOXICOLOGICAL INFORMATION

TOXICITY

Oral (human) LDLo: 430 mg/kg
Inhalation (rat) LC50: 2500 ppm/1h * * DuPont
Unreported (man) LDLo: 110 mg/kg
Inhalation (Cat) LC: 500 mg/m³/4h
Inhalation (Rat) LC50: 130 mg/m³/4h
Oral (Human) LD: 430 mg/kg
Inhalation (Cat) TCLo: 300 mg/m³/2h

IRRITATION

Nil Reported

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

Oral (?) LD50: 50-500 mg/kg *

[Various Manufacturers]

INDIUM(III) NITRATE:

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (mouse) LD50: 3300 mg/kg

IRRITATION

Skin (mammal): 500 mg SEVERE

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. Post-implantation mortality, foetolethality, specific developmental abnormalities to the musculoskeletal system recorded.

WATER:

■ No significant acute toxicological data identified in literature search.

CARCINOGEN

continued...

INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3

Page 11 of 14

Section 11 - TOXICOLOGICAL INFORMATION

Nitrate or nitrite (ingested) under conditions that result in endogenous nitrosation

International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs

Group

2A

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

INDIUM(III) NITRATE:

NITRIC ACID:

- DO NOT discharge into sewer or waterways.

INDIUM 1000MG/L STANDARD SOLUTION

Marine Pollutant: Not Determined

NITRIC ACID:

- For oxides of nitrogen:

Environmental fate

Oxides of nitrogen are part of the biogeochemical cycling of nitrogen, and are found in air, soil and water. In the atmosphere, oxides of nitrogen are rapidly oxidised to nitrogen dioxide (half-life about 50 days), which dissolves in water to produce dilute nitric acid and precipitates in rain. An increased rate of formation of oxides of nitrogen therefore contributes to 'acid rain'.

In the stratosphere, oxides of nitrogen play a crucial role in maintaining the level of ozone. Ozone is formed through the photochemical reaction of nitrogen dioxide and oxygen. However, too little nitrogen dioxide results in too little ozone being formed. On the other hand, too much nitric oxide reduces the level of ozone because of an increase in the reaction of ozone to convert nitric oxide to nitrogen dioxide.

In the lower atmosphere, oxides of nitrogen play a major role in the formation of photochemical smog in a complex set of reactions that lead to the formation of a variety of nitrated organic compounds (from volatile organic matter) and excessive levels of ozone.

Environmental transport The oxides of nitrogen travel as gases through soil and the atmosphere, and in solution in water in soils, rivers and lakes, and rain and snow.

- Prevent, by any means available, spillage from entering drains or water courses.

INDIUM(III) NITRATE:

- Harmful to aquatic organisms.

■ Metal-containing inorganic substances generally have negligible vapour pressure and are not expected to partition to air. Once released to surface waters and moist soils their fate depends on solubility and dissociation in water. Environmental processes (such as oxidation and the presence of acids or bases) may transform insoluble metals to more soluble ionic forms. Microbiological processes may also transform insoluble metals to more soluble forms. Such ionic species may bind to dissolved ligands or sorb to solid particles in aquatic or aqueous media. A significant proportion of dissolved/ sorbed metals will end up in sediments through the settling of suspended particles. The remaining metal ions can then be taken up by aquatic organisms.

When released to dry soil most metals will exhibit limited mobility and remain in the upper layer; some will leach locally into ground water and/ or surface water ecosystems when soaked by rain or melt ice.

Environmental processes may also be important in changing solubilities.

Even though many metals show few toxic effects at physiological pHs, transformation may introduce new or magnified effects.

A metal ion is considered infinitely persistent because it cannot degrade further.

The current state of science does not allow for an unambiguous interpretation of various measures of bioaccumulation.

The counter-ion may also create health and environmental concerns once isolated from the metal. Under normal physiological conditions the counter-ion may be essentially insoluble and may not be bioavailable.

Environmental processes may enhance bioavailability.

continued...

INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3

Page 12 of 14

Section 12 - ECOLOGICAL INFORMATION

■ The nitrates are of environmental concern because of their high water solubility and consequent leaching, diffusion, and environmental mobility in soil and water. Nitrate can contaminate groundwater to unacceptable levels. Nitrite is formed from nitrate or ammonium ion by micro-organisms in soil, water, sewage and the alimentary tract. The concern with nitrate in the environment is related to its conversion to nitrite.

Methaemoglobinaemia is caused following exposure to high levels of nitrite and produces difficulties in oxygen transport in the blood. Thousands of cases involving poisoning of infants, particularly in rural areas, have been reported as a result of drinking nitrate rich well-water.

Other concerns deriving from exposure to environmental nitrates relate to the production of nitrosamines following the reaction of food nitrites and secondary amines. Other nitroso-compounds may result following reaction with nitrites and amides, ureas, carbamates and other nitrogenous compounds. Nitrosamines produce liver damage, haemorrhagic lung lesions, convulsions and coma in rats, and teratogenic effects in experimental animals.

The N-nitroso class of compounds include potent carcinogens and mutagens: induction of tumors by single doses of N-nitroso compounds testify to this.

■ Indium is used in LCD-displays, batteries and electronics. The most important route of dispersal to the environment is through solid waste and residuals from waste incineration.

No data is currently available environmental toxicity of indium, and, consequently, the possible environmental impacts of indium can not be assessed. However, due to the low consumption of indium and the low concentrations found in waste, the actual risk of adverse effects on environment and health is considered to be low.

The information on the environmental properties of indium is sparse. It is expected that its environmental properties are similar to the properties of gallium.

Distribution of indium in the soil between particle-bound and mobile forms of the element is not known.

Indium is probably found as hydroxides, whose solubility depends on the pH.

$\text{In}(\text{OH})_2^+$ and $\text{In}(\text{OH})_3^+$ are the typical compounds in the aquatic environment. It is possible that indium is biologically reactive and can form stable complexes with nitrogen and sulfur in living organic material. In the aquatic environment, indium is expected to be assimilated by e.g. algae. A fraction will, however, be sorbed on particulate matter.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
nitric acid			LOW	
indium(III) nitrate	LOW		LOW	HIGH
water	LOW		LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Treat and neutralise at an effluent treatment plant.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: CORROSIVE

continued...

INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3

Page 13 of 14

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

□ 2X

Land Transport UNDG:

Class or division:	8	Subsidiary risk:	None
UN No.:	3264	UN packing group:	III
Shipping Name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains nitric acid)			

Air Transport IATA:

ICAO/IATA Class:	8	ICAO/IATA Subrisk:	None
UN/ID Number:	3264	Packing Group:	III
Special provisions:	A3		
Shipping Name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. *(CONTAINS NITRIC ACID)			

Maritime Transport IMDG:

IMDG Class:	8	IMDG Subrisk:	None
UN Number:	3264	Packing Group:	III
EMS Number:	F- A, S- B	Special provisions:	223 274 944
Limited Quantities:	5 L	Marine Pollutant:	Not Determined
Shipping Name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (contains nitric acid)			

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

nitric acid (CAS: 7697-37-2) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP) - Schedule 6", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals"

indium(III) nitrate (CAS: 13465-14-0, 13770-61-1) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)"

water (CAS: 7732-18-5) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "OECD Representative List of High Production Volume (HPV) Chemicals"

No data for Indium 1000MG/L Standard Solution

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
indium(III) nitrate	13465- 14- 0, 13770- 61- 1

EXPOSURE STANDARD FOR MIXTURES

- "Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:
- Composite Exposure Standard for Mixture (TWA) :100 mg/m³.

continued...

INDIUM 1000MG/L STANDARD SOLUTION

GHS Safety Data Sheet

Version No:3

Page 14 of 14

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by using available literature references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 19-Feb-2018