

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 1 of 18

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

BUTANE-2-ONE

OTHER NAMES

C4-H8-O, CH₃COC₂H₅, CH₃COCH₂CH₃, 2-butanone, 2-butanone, "ethyl methyl ketone", "methyl acetone", butan-2-one, butan-2-one,

PROPER SHIPPING NAME

ETHYL METHYL KETONE (METHYL ETHYL KETONE)

PRODUCT USE

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing.

Before starting consider control of exposure by mechanical ventilation.

WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.

As a solvent in lacquers, thinners, solvent cements, adhesives, glues, in paint removers, nail polish removers, nail polish and cleaning solvents.

In the manufacture of smokeless gunpowder and colourless synthetic resins.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 2 of 18

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Oral) Category 5
Eye Irritation Category 2A
Flammable Liquid Category 2
Respiratory Irritation Category 3
Skin Corrosion/Irritation Category 3



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:
H335 H225 H303 H316 H319
May cause respiratory irritation
Highly flammable liquid and vapour
May be harmful if swallowed
Causes mild skin irritation
Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Use only non-sparking tools.
Take precautionary measures against static discharge
Wash hands thoroughly after handling.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment
Keep away from heat/sparks/open flame - No smoking.
Keep container tightly closed.
Wear protective gloves and eye/face protection.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
If eye irritation persists, get medical advice/attention.
Wear eye/face protection.
If skin irritation occurs, seek medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower.
In case of fire, use alcohol-type foam for extinction.

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 3 of 18

Section 2 - HAZARDS IDENTIFICATION

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
methyl ethyl ketone	78-93-3	>99

Section 4 - FIRST AID MEASURES

SWALLOWED

If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 4 of 18

Section 4 - FIRST AID MEASURES

is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.
for simple ketones:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5mL/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Give activated charcoal.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Consider intubation at first sign of upper airway obstruction resulting from oedema.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
 - Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
 - Consult a toxicologist as necessary.
- BRONSTEIN, A.C. and CURRANCE, P.L.
EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 5 of 18

Section 5 - FIRE FIGHTING MEASURES

- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Fight fire from a safe distance, with adequate cover.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control the fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat, flame and/or oxidisers.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Personal Protective Equipment

Breathing apparatus.
Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

Chemical Class: ketones

For release onto land: recommended sorbents listed in order of priority.

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 6 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
LAND SPILL - SMALL				
cross- linked polymer - particulate	1	shovel	shovel	R, W, SS
cross- linked polymer - pillow	1	throw	pitchfork	R, DGC, RT
sorbent clay - particulate	2	shovel	shovel	R, I, P
wood fiber - pillow	3	throw	pitchfork	R, P, DGC, RT
treated wood fiber - pillow	3	throw	pitchfork	DGC, RT
foamed glass - pillow	4	throw	pitchfork	R, P, DGC, RT

LAND SPILL - MEDIUM

cross- linked polymer - particulate	1	blower	skiploader	R, W, SS
cross- linked polymer - pillow	2	throw	skiploader	R, DGC, RT
sorbent clay - particulate	3	blower	skiploader	R, I, P
polypropylene - particulate	3	blower	skiploader	R, SS, DGC
expanded mineral - particulate	4	blower	skiploader	R, I, W, P, DGC
polypropylene - mat	4	throw	skiploader	DGC, RT

Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT:Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 7 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse /absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

methyl ethyl ketone 3000 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

methyl ethyl ketone 300 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

methyl ethyl ketone 300 ppm

The threshold concentration below which most people will experience no appreciable risk of health effects:

methyl ethyl ketone 200 ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 8 of 18

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

Contains low boiling substance:

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.

- Check for bulging containers.
 - Vent periodically
 - Always release caps or seals slowly to ensure slow dissipation of vapours.
 - Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - Prevent concentration in hollows and sumps.
 - DO NOT enter confined spaces until atmosphere has been checked.
 - Avoid smoking, naked lights, heat or ignition sources.
 - When handling, DO NOT eat, drink or smoke.
 - Vapour may ignite on pumping or pouring due to static electricity.
 - DO NOT use plastic buckets.
 - Earth and secure metal containers when dispensing or pouring product.
 - Use spark-free tools when handling.
 - Avoid contact with incompatible materials.
 - Keep containers securely sealed.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
 - (i) : Removable head packaging;
 - (ii) : Cans with friction closures and
 - (iii) : low pressure tubes and cartridges may be used.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 9 of 18

Section 7 - HANDLING AND STORAGE

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.
Avoid strong bases.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- methyl ethyl ketone:

CAS:78- 93- 3 CAS:135311- 02- 3

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
methyl ethyl ketone		3, 000 [Unch]

ODOUR SAFETY FACTOR (OSF)

OSF=28 (METHYL ETHYL KETONE)

MATERIAL DATA

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 10 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Odour Threshold Value: Variously reported as 2 ppm and 4.8 ppm
Odour threshold: 2 ppm (detection); 5 ppm (recognition)
25 ppm (easy recognition); 300 ppm IRRITATING
Exposures at or below the recommended TLV-TWA are thought to prevent injurious systemic effects and to minimise objections to odour and irritation. Where synergism or potentiation may occur stringent control of the primary toxin (e.g. n-hexane or methyl butyl ketone) is desirable and additional consideration should be given to lowering MEK exposures.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection: methyl ethyl ketone

Protective Material CPI *.

BUTYL	A
PE/EVAL/PE	A
TEFLON	A
PVA	B

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 11 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

BUTYL/NEOPRENE	B
SARANEX- 23	C
NEOPRENE/NATURAL	C
HYPALON	C
NITRILE+PVC	C
NATURAL+NEOPRENE	C
VITON/NEOPRENE	C
NATURAL RUBBER	C
PVC	C
NEOPRENE	C
NITRILE	C

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS	-
1000	50	-	A- AUS
5000	50	Airline *	-
5000	100	-	A- 2
10000	100	-	A- 3
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:
solvent, vapours, degreasing etc., evaporating

Air Speed:
0.25- 0.5 m/s (50- 100 f/min.)

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 12 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

from tank (in still air).

aerosols, fumes from pouring operations,

intermittent container filling, low speed

conveyer transfers, welding, spray drift,

plating acid fumes, pickling (released at low

velocity into zone of active generation)

direct spray, spray painting in shallow booths,

drum filling, conveyer loading, crusher dusts,

gas discharge (active generation into zone of

rapid air motion)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Attacks, softens and may dissolve.

Thin colourless highly flammable liquid; partly mixes with water (27.5%).

Less soluble at higher temperatures. Solubility of water in MEK: 12.5% at 25 deg. C.

Penetrating, sharp smell. Very volatile and vapour is heavier than air.

Mixes with alcohol, ether and hydrocarbon solvents, petrol, turps etc.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

Molecular Weight: 72.12

Melting Range (°C): - 85.9

Solubility in water (g/L): Partly miscible

pH (1% solution): Not applicable

Volatile Component (%vol): 100

Relative Vapour Density (air=1): 2.4 @ 20 C

Lower Explosive Limit (%): 1.8

Boiling Range (°C): 78- 80

Specific Gravity (water=1): 0.81 @ 20 C

pH (as supplied): Not applicable

Vapour Pressure (kPa): 9.5 @ 20 C

Evaporation Rate: 5.7 Fast BuAc=1

Flash Point (°C): - 6.7 closed cup

Upper Explosive Limit (%): 12.0

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 13 of 18

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Autoignition Temp (°C): 474
State: Liquid

Decomposition Temp (°C): Not available
Viscosity: Not Available

log Kow (Prager 1995): 0.26- 0.29
log Kow (Sangster 1997): 0.29
log Kow: 0.26-0.69

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Product is considered stable under normal handling conditions.
 - Stable under normal storage conditions.
 - Hazardous polymerization will not occur.
- Segregate from strong oxidisers.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result.

(ICSC13733).

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health).

Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.

Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

The vapour when concentrated has pronounced eye irritation effects and this gives some warning of high vapour concentrations. If eye irritation occurs seek to reduce exposure with available control measures, or evacuate area.

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material may produce moderate skin irritation; limited evidence or practical

continued...

experience suggests, that the material either:

- produces moderate inflammation of the skin in a substantial number of individuals following direct contact and/or
- produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.

Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

INHALED

Inhalation may produce health damage*.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation.

In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Exposure to ketone vapours may produce nose, throat and mucous membrane irritation. High concentrations of vapour may produce central nervous system depression characterised by headache, vertigo, loss of coordination, narcosis and cardiorespiratory failure. Some ketones produce neurological disorders (polyneuropathy) characterised by bilateral symmetrical paresthesia and muscle weakness primarily in the legs and arms.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing.

Before starting consider control of exposure by mechanical ventilation.

CHRONIC HEALTH EFFECTS

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 15 of 18

Section 11 - TOXICOLOGICAL INFORMATION

irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

The material is considered to have a low order of toxicity; however methyl ethyl ketone is often used in combination with other solvents and the toxic effects of the mix may be greater than either solvent alone.

Combinations of n-hexane with methyl ethyl ketone and also methyl n-butyl ketone with methyl ethyl ketone show increase in peripheral neuropathy, a progressive disorder of nerves of extremities.

Combinations with chloroform also show increase in toxicity.

TOXICITY AND IRRITATION

TOXICITY

Oral (rat) LD50: 2737 mg/kg

Inhalation (human) TClO: 100 ppm/5 m

Inhalation (rat) LD50: 23500 mg/m³/8 hr

Dermal (rabbit) LD50: 6480 mg/kg

Inhalation (man) TClO: 10 mg/m³/6 hr - Mild

Inhalation (rat) LC50: 50100 mg/m³/8 hr

Dermal (rabbit) LD50: 20000 mg/kg

IRRITATION

Eye (human): 350 ppm - Irritant

Eye (rabbit): 80 mg - Irritant

Skin (rabbit): 402 mg/24 hr - Mild

Skin (rabbit): 13.78mg/24 hr Open

Section 12 - ECOLOGICAL INFORMATION

Hazardous Air Pollutant:	Yes
Fish LC50 (96hr.) (mg/l):	1690- 5640
Algae IC50 (72hr.) (mg/l):	110- 4300
log Kow (Prager 1995):	0.26- 0.29
log Kow (Sangster 1997):	0.29
log Pow (Verschuereen 1983):	0.26
BOD5:	1.92
COD:	2.2
ThOD:	2.44
Half- life Soil - High (hours):	168
Half- life Soil - Low (hours):	24
Half- life Air - High (hours):	642
Half- life Air - Low (hours):	64.2
Half- life Surface water - High (hours):	168
Half- life Surface water - Low (hours):	24
Half- life Ground water - High (hours):	336
Half- life Ground water - Low (hours):	48
Aqueous biodegradation - Aerobic - High (hours):	168
Aqueous biodegradation - Aerobic - Low (hours):	24
Aqueous biodegradation - Anaerobic - High (hours):	672
Aqueous biodegradation - Anaerobic - Low (hours):	96
Aqueous biodegradation - Removal secondary treatment - High (hours):	100%

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 16 of 18

Section 12 - ECOLOGICAL INFORMATION

Aqueous biodegradation - Removal secondary treatment - Low (hours):	86%
Photooxidation half- life water - High (hours):	7.10E+05
Photooxidation half- life water - Low (hours):	1.80E+04
Photooxidation half- life air - High (hours):	642
Photooxidation half- life air - Low (hours):	64.2
First order hydrolysis half- life (hours):	>50 YR

DO NOT discharge into sewer or waterways.

log Kow: 0.26-0.69

log Koc: 0.69

Koc: 34

Half-life (hr) air: 2.3

Half-life (hr) H₂O surface water: 72-288

Henry's atm m³ /mol: 1.05E-05

BOD 5 if unstated: 1.5-2.24,46%

COD: 2.2-2.31,100%

ThOD: 2.44

BCF: 1

Toxicity Fish: LC50(96)13.16-277.8mg/L

Toxicity invertebrate: LD0 1g/L

Bioaccumulation: not sig

Anaerobic effects: some degrad

Effects on algae and plankton: algae LD0 125mg/L

Degradation Biological: sig

processes Abiotic: photox,RxnOH*,hydrl photol/deg notsig

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID

HAZCHEM: 2[Y]E

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 17 of 18

Section 14 - TRANSPORTATION INFORMATION

UNDG:

Dangerous Goods Class:	3	Subrisk:	None
UN Number:	1193	Packing Group:	II
Shipping Name:ETHYL METHYL KETONE (METHYL ETHYL KETONE)			

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1193	Packing Group:	II
ERG Code:	3L		
Shipping name:ETHYL METHYL KETONE (METHYL ETHYL KETONE)			

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1193	Packing Group:	II
EMS Number:	F- E, S- D		
Shipping name:ETHYL METHYL KETONE (METHYL ETHYL KETONE)			

Section 15 - REGULATORY INFORMATION

REGULATIONS

methyl ethyl ketone (CAS: 78-93-3) is found on the following regulatory lists;
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
OECD Representative List of High Production Volume (HPV) Chemicals
United Nations List of Precursors and Chemicals Frequently used in the Illicit
Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control -
Table II

No data available for methyl ethyl ketone as CAS: 135311-02-3.

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
methyl ethyl ketone	78- 93- 3, 135311- 02- 3

REPRODUCTIVE HEALTH GUIDELINES

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for the reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

continued...

BUTAN-2-ONE

GHS Safety Data Sheet

Version No:5

Page 18 of 18

Section 16 - OTHER INFORMATION

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
methyl ethyl ketone	590 mg/m3	NA	NA	NA	Yes

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive
American Industrial Hygiene Association Journal 57: 641-649 (1996).

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 9-Nov-2017