

BUFFER SOLUTION PH 4.0 (25°C) NIST TRACEABLE

GHS Safety data sheet

Version No:4
Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

BUFFER SOLUTION PH 4.0 (25°C) NIST TRACEABLE

OTHER NAMES

"laboratory reagent"

PRODUCT USE

General laboratory reagent.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.

technical@sdfine.com






Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS

Flammability
Toxicity
Body Contact
Reactivity
Chronic



SCALE: Min/Nil=0

Low=1

Moderate=2

High=3

Extreme=4

Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HAZARD

Not hazardous

No hazards determined by using GHS criteria

PRECAUTIONARY STATEMENTS

continued...

BUFFER SOLUTION PH 4.0 (25°C) NIST TRACEABLE

Version No:4
Page 2 of 8

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
additives nonhazardous		NotSpec
water	7732-18-5	>60

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

- If this product comes in contact with eyes:
- Wash out immediately with water.
 - If irritation continues, seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin or hair contact occurs:
- Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.

continued...

BUFFER SOLUTION PH 4.0 (25°C) NIST TRACEABLE

Version No:4

Page 3 of 8

Section 5 - FIRE FIGHTING MEASURES

- May emit acrid smoke.

FIRE INCOMPATIBILITY

None known.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Minor hazard.

- Clear area of personnel.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment as required.
- Prevent spillage from entering drains or water ways.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.
- Wash area and prevent runoff into drains or waterways.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

water 500 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

water 500 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

water 500 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:

water 500 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

continued...

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid contamination of water, foodstuffs, feed or seed.

STORAGE REQUIREMENTS

- Store in original containers.
 - Keep containers securely sealed.
 - Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storing and handling recommendations.
- Store between 15 and 25 degC.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ + + + + +

+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- water: CAS:7732- 18- 5

BUFFER SOLUTION PH 4.0 (25°C) NIST TRACEABLE

Version No:4

Page 5 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

MATERIAL DATA


Not available. Refer to individual constituents.

INGREDIENT DATA

WATER:

No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves.

OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:
solvent, vapours, degreasing etc., evaporating

Air Speed:
0.25- 0.5 m/s (50- 100 f/min)

continued...

BUFFER SOLUTION PH 4.0 (25°C) NIST TRACEABLE

Version No:4
Page 6 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

from tank (in still air)	
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Liquid; mixes with water.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

Molecular Weight: Not Applicable	Boiling Range (°C): Not Available
Melting Range (°C): Not Available	Specific Gravity (water=1): 1.0 approx
Solubility in water (g/L): Miscible	pH (as supplied): 7
pH (1% solution): Not Available	Vapour Pressure (kPa): Not Available
Volatile Component (%vol): Not Available	Evaporation Rate: Not Available
Relative Vapour Density (air=1): Not Available	Flash Point (°C): Not Applicable
Lower Explosive Limit (%): Not Applicable	Upper Explosive Limit (%): Not Applicable
Autoignition Temp (°C): Not Applicable	Decomposition Temp (°C): Not Available
State: Liquid	Viscosity: Not Available

continued...

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

Not normally a hazard due to non-volatile nature of product.
The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

WATER:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.
No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

No data for Buffer Solution pH 4.0 (Phosphate).

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,
IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

Buffer Solution pH 4.0 (Phosphate) (CAS: None):
No regulations applicable

water (CAS: 7732-18-5) is found on the following regulatory lists;
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 24-Sep-2017