

PAN INDICATOR IN ETHANOL

GHS Safety Data Sheet

Version No:2.0
Page 2 of 8

Section 2 - HAZARDS IDENTIFICATION

Determined by using GHS criteria

H225	Highly flammable liquid and vapour.
H303	May be harmful if swallowed
H316	Causes mild skin irritation
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H402	Harmful to aquatic life

PRECAUTIONARY STATEMENTS

Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion- proof electrical/ventilating/lighting/ ... /equipment
P242	Use only non- sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well- ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/ attention.
P337+P313	If eye irritation persists: Get medical advice/attention.

Storage

P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P403+P235	Store in a well- ventilated place. Keep cool.
P405	Store locked up.

Disposal

P501	Dispose of contents/container to ...
------	--------------------------------------

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
ethanol	64-17-5	99.9
1- (2- pyridylazo)- 2- naphthol	85-85-8	0.1

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.

continued...

PAN INDICATOR IN ETHANOL

GHS Safety Data Sheet

Version No:2.0
Page 3 of 8

Section 4 - FIRST AID MEASURES

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- For acute or short term repeated exposures to ethanol:
- Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
- Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
- Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
- Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
 - May be violently or explosively reactive.
 - Wear breathing apparatus plus protective gloves.
 - Prevent, by any means available, spillage from entering drains or water course.
- When any large container (including road and rail tankers) is involved in a fire, consider evacuation by 500 metres in all directions.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat, flame and/or oxidisers.
 - Vapour forms an explosive mixture with air.
 - Severe explosion hazard, in the form of vapour, when exposed to flame or spark.
- Decomposes on heating and produces toxic fumes of: carbon dioxide (CO₂).

FIRE INCOMPATIBILITY

- Avoid contamination with strong oxidising agents as ignition may result.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.

continued...

PAN INDICATOR IN ETHANOL

GHS Safety Data Sheet

Version No:2.0

Page 4 of 8

Section 6 - ACCIDENTAL RELEASE MEASURES

- Wear breathing apparatus plus protective gloves.
Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- Glass container is suitable for laboratory quantities or Plastic container Plastic drum.
Plastic container may be used only if approved for use with flammable solvents.

STORAGE INCOMPATIBILITY

- Avoid storage with oxidisers.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³
South Africa Hazardous Chemical Substances - Recommended Limits	ethanol (Ethyl alcohol)	1000	1900
South Africa Occupational Exposure Limits for Airborne Pollutants	ethanol (Ethanol)	1000	1900

The following materials had no OELs on our records

- 1- (2- pyridylazo)- 2- naphthol: CAS:85- 85- 8

MATERIAL DATA

1-(2-PYRIDYLAZO)-2-NAPHTHOL:

ETHANOL:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

PAN INDICATOR IN ETHANOL:

- None assigned. Refer to individual constituents.

ETHANOL:

- For ethanol:
Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects. Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness.

1-(2-PYRIDYLAZO)-2-NAPHTHOL:

- It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.
At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal

continued...

PAN INDICATOR IN ETHANOL

GHS Safety Data Sheet

Version No:2.0

Page 5 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

experiments or clinical experience).

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

PERSONAL PROTECTION



RESPIRATOR

•Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.

ENGINEERING CONTROLS

- Use in a well-ventilated area.

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless flammable liquid with sweet, fragrant odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

State	Liquid	Molecular Weight	Not applicable
Melting Range (°C)	- 117.3	Viscosity	Not Available
Boiling Range (°C)	78.3	Solubility in water (g/L)	Miscible
Flash Point (°C)	13	pH (1% solution)	Not available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°C)	365	Vapour Pressure (kPa)	5.8
Upper Explosive Limit (%)	19	Specific Gravity (water=1)	0.8
Lower Explosive Limit (%)	3.3	Relative Vapour Density (air=1)	1.9

continued...

PAN INDICATOR IN ETHANOL

GHS Safety Data Sheet

Version No:2.0
Page 6 of 8

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Volatile Component (%vol)	100	Evaporation Rate	2.53 BuAc=1
---------------------------	-----	------------------	-------------

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Ingestion of ethanol may produce nausea, vomiting, gastrointestinal bleeding, abdominal pain and diarrhoea.

Systemic effects:

--	--

 Blood concentration:
Effects:

EYE

- The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

- The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis.

INHALED

- Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination.
- Inhalation hazard is increased at higher temperatures.
- If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

CHRONIC HEALTH EFFECTS

- Long-term exposure to ethanol may result in progressive liver damage with fibrosis or may exacerbate liver injury caused by other agents.
- Repeated ingestion of ethanol by pregnant women may adversely affect the central nervous system of the developing foetus, producing effects collectively described as foetal alcohol syndrome.
- Consumption of ethanol (in alcoholic beverages) may be linked to the development of Type I hypersensitivities in a small number of individuals.

TOXICITY AND IRRITATION

- Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

ethanol 96 hr LC50 (100) mg/L Fathead minnow Fish Source: Experimental

This material and its container must be disposed of as hazardous waste.

continued...

PAN INDICATOR IN ETHANOL

GHS Safety Data Sheet

Version No:2.0
Page 7 of 8

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
ethanol	LOW	MED	LOW	HIGH
1- (2- pyridylazo)- 2- naphthol	HIGH	No Data Available	LOW	LOW

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID

HAZCHEM:

•2YE

Land Transport UNDG:

Class or division:	3	Subsidiary risk:	None
UN No.:	1170	UN packing group:	II
Shipping Name:ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)			

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1170	Packing Group:	II
Special provisions:	A3		

Shipping name:ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1170	Packing Group:	II
EMS Number:	F- E, S- D	Special provisions:	144
Limited Quantities:	1 L		

Shipping name:ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

ethanol (CAS: 64-17-5) is found on the following regulatory lists;

"FEMA Generally Recognized as Safe (GRAS) Flavoring Substances 23 - Examples of FEMA GRAS Substances with Non-Flavor Functions",
"GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances",
"IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Air Transport Association (IATA) Dangerous Goods Regulations", "International

continued...

PAN INDICATOR IN ETHANOL

GHS Safety Data Sheet

Version No:2.0
Page 8 of 8

Section 15 - REGULATORY INFORMATION

Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway", "South Africa Hazardous Chemical Substances - Recommended Limits", "South Africa List of classification and labelling of chemicals in accordance with the Globally Harmonized System (GHS)", "South Africa Occupational Exposure Limits for Airborne Pollutants", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Competition (German)", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Particular Sports (English)", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Particular Sports (French)", "World Anti-Doping Agency - The 2009 Prohibited List World Anti-Doping Code - Substances Prohibited in Particular Sports (Korean)"

1-(2-pyridylazo)-2-naphthol (CAS: 85-85-8) is found on the following regulatory lists;

"GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards"

No data for PAN indicator in ethanol (CW: 24-8933)

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 21-Sep-2017