

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 1 of 13

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

BARIUM PEROXIDE

OTHER NAMES

Ba-O₂, "barium dioxide", "barium superoxide", "barium binoxide"

PROPER SHIPPING NAME

BARIUM PEROXIDE

PRODUCT USE

Bleaching, decolourising glass, thermal welding of aluminium, manufacture of hydrogen peroxide, oxidising agent, dyeing textiles.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Inhalation) Category 4

Acute Toxicity (Oral) Category 4

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 2 of 13

Section 2 - HAZARDS IDENTIFICATION

Eye Irritation Category 2A
Oxidizing Solid Category 2
Respiratory Irritation Category 3
Skin Corrosion/Irritation Category 3



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:
H335 H273 H332 H302 H316 H319

May cause respiratory irritation

May intensify fire; oxidizer

Harmful if inhaled

Harmful if swallowed

Causes mild skin irritation

Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Wash hands thoroughly after handling.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well ventilated area.

Do not eat, drink or smoke when using this product.

Take any precaution to avoid mixing with combustible or incompatible materials.

Keep away from heat.

Response

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists, get medical advice/attention.

Specific treatment: refer to Label or MSDS.

Wear eye/face protection.

Call a POISON CENTER or doctor/physician if you feel unwell.

If skin irritation occurs, seek medical advice/attention.

Storage

Store away from combustibles and incompatible materials

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 3 of 13

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
barium peroxide	1304-29-6	>99

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.

- For advice, contact a Poisons Information Centre or a doctor.

Where Medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:

- Induce vomiting with fingers down the back of the of the throat, ONLY IF CONSCIOUS.

- Lean patient forward or place on left side (head-down position if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.

- If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist.

- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.

- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

- Transport to hospital or doctor without delay.

- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.

- Flush skin and hair with running water (and soap if available).

- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.

- Lay patient down. Keep warm and rested.

- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.

- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

- Transport to hospital, or doctor, without delay.

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 4 of 13

Section 4 - FIRST AID MEASURES

NOTES TO PHYSICIAN

- After ingestion of barium acid salts, severe gastro-intestinal irritation followed by muscle twitching, progressive flaccid paralysis and severe hypokalemia and hypertension, occurs.
- Respiratory failure, renal failure and occasional cardiac dysrhythmias may result from an acute ingestion.
- Use sodium sulfate as a cathartic. Add 5-10 gm of sodium sulfate to lavage solution or as fluid supplement to Ipecac syrup (the sulfate salt is not absorbed)
- Monitor cardiac rhythm and serum potassium closely to establish the trend over the first 24 hours. Large doses of potassium may be needed to correct the hypokalemia.
- Administer generous amounts of fluid replacement but monitor the urine and serum for evidence of renal failure. [Ellenhorn and Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Jets of water.
- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Fight fire from a safe distance, with adequate cover.
- Extinguishers should be used only by trained personnel.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- If fire gets out of control withdraw personnel and warn against entry.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Will not burn but increases intensity of fire.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- Heat affected containers remain hazardous.
- Contact with combustibles such as wood, paper, oil or finely divided metal may produce spontaneous combustion or violent decomposition.
- May emit irritating, poisonous or corrosive fumes.

Personal Protective Equipment

Gloves, boots (chemical resistant).
Breathing apparatus.

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 5 of 13

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- No smoking, naked lights, ignition sources.
- Avoid all contact with any organic matter including fuel, solvents, sawdust, paper or cloth and other incompatible materials, as ignition may result.
- Avoid breathing dust or vapours and all contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with dry sand, earth, inert material or vermiculite.
- DO NOT use sawdust as fire may result.
- Scoop up solid residues and seal in labelled drums for disposal.
- Neutralise/decontaminate area.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus and protective gloves.
- Prevent, by any means available, spillage from entering drains or water courses.
- No smoking, flames or ignition sources.
- Increase ventilation.
- Contain spill with sand, earth or other clean, inert materials.
- NEVER USE organic absorbents such as sawdust, paper or cloth.
- Use spark-free and explosion-proof equipment.
- Collect any recoverable product into labelled containers for possible recycling.
- Avoid contamination with organic matter to prevent subsequent fire and explosion.
- DO NOT mix fresh with recovered material.
- Collect residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- Decontaminate equipment and launder protective clothing before storage and re-use.
- If contamination of drains or waterways occurs advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

barium peroxide 7.5 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

barium peroxide 1.5 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

barium peroxide 0.6 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:

barium peroxide 0.6 mg/m³

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 6 of 13

Section 6 - ACCIDENTAL RELEASE MEASURES

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid personal contact and inhalation of dust, mist or vapours.
- Always wear protective equipment and wash off any spillage on clothing.
- Use in well ventilated areas, prevent accumulation of vapours.
- Keep material away from light, heat, ignition sources, flammables or combustibles.
- Keep dry and away from incompatible materials.
- Keep cool and below defined Control Temperature.
- Avoid friction, shock or containment.
- Use non-sparking equipment.
- Avoid physical damage to containers
- DO NOT repack or return unused portions to original container.
- Withdraw only sufficient material for immediate use.
- Contamination can cause VIOLENT DECOMPOSITION with intense heat and fire.
- Ensure proper rotation of stocks to limit decomposition and instability which may occur on long storage.
- When handling NEVER smoke, eat or drink.
- Always wash hands with soap and water after handling.
- Use only good occupational work practice.
- Observe manufacturer's storing and handling directions.

SUITABLE CONTAINER

Glass container.

- Polyethylene or polypropylene container.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid storage with organic materials, combustible materials, most common metals and strong reducing agents.

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 7 of 13

Section 7 - HANDLING AND STORAGE

STORAGE REQUIREMENTS

- Store in original containers in an isolated/detached store away from other materials.
- Keep containers securely sealed as supplied.
- WARNING: Gradual decomposition during storage in sealed containers may lead to a large pressure build-up and subsequent explosion.
- No smoking, naked lights, heat or ignition sources.
- Store under cover and away from sunlight.
- Always store below 35 deg.C
- Store away from flammable or combustible materials, debris and waste.
- Store away from incompatible materials and foodstuffs containers.
- DO NOT stack on wooden floors or wooden pallets.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
- Observe manufacturer's storage and handling recommendations.
- Keep locked up.
- Restrictions may apply on quantities and to other materials permitted in the same location.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- barium peroxide:

CAS:1304- 29- 6 CAS:55396- 27- 5 CAS:16678- 58- 3 CAS:61233- 09- 8

MATERIAL DATA

The recommended TLV-TWA is based on satisfactory results achieved while employing an internal limit for barium nitrate at a national laboratory. It is not known what degree of added safety this limit incorporates.

PERSONAL PROTECTION



EYE

- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure,

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 8 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Wear safety footwear.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
 - (a): particle dust respirators, if necessary, combined with an absorption cartridge;
 - (b): filter respirators with absorption cartridge or canister of the right type;
 - (c): fresh-air hoods or masks
- Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.

Type of Contaminant:
direct spray, spray painting in shallow booths,
drum filling, conveyer loading, crusher dusts,

Air Speed:
1- 2.5 m/s (200- 500 f/min.)

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 9 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

gas discharge (active generation into zone of rapid air motion)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Greyish-white powder; slightly soluble in water (0.1-1.0%).

PHYSICAL PROPERTIES

Solid.

Does not mix with water.

Sinks in water.

Molecular Weight: 169.34

Melting Range (°C): 450

Solubility in water (g/L): Partly miscible

pH (1% solution): Not available

Volatile Component (%vol): Not applicable

Relative Vapour Density (air=1): Not applicable

Lower Explosive Limit (%): Not applicable

Autoignition Temp (°C): Not applicable

State: Divided solid

Boiling Range (°C): Not available.

Specific Gravity (water=1): 4.96

pH (as supplied): Not applicable

Vapour Pressure (kPa): Not applicable

Evaporation Rate: Not applicable

Flash Point (°C): Not applicable

Upper Explosive Limit (%): Not applicable

Decomposition Temp (°C): Not available

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 10 of 13

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Unstable under normal storage, requires special storage conditions.
- Prolonged exposure to heat above control temperature.
- Presence of shock and/or friction.
- Hazardous decomposition will occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Ingestion of soluble barium compounds may result in ulceration of the mucous membranes of the gastrointestinal tract, tightness in the muscles of the face and neck, gastroenteritis, vomiting, diarrhoea, muscular tremors and paralysis, anxiety, weakness, laboured breathing, cardiac irregularity due to contractions of smooth, striated and cardiac muscles (often violent and painful), slow irregular pulse, hypertension, convulsions and respiratory failure.

EYE

Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.

Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

SKIN

Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 11 of 13

Section 11 - TOXICOLOGICAL INFORMATION

INHALED

Limited evidence exists, or practical experience predicts, that the material produces irritation of the respiratory system in a significant number of individuals following inhalation.

Barium fumes are respiratory irritants. Over-exposure to barium dusts and fume may result in rhinitis, frontal headache, wheezing, laryngeal spasm, salivation and anorexia. Long term effects include nervous disorders and adverse effects on the heart, circulatory system and musculature. Heavy exposures may result in a benign pneumoconiosis.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and inhalation of generated dusts.

Workers exposed to barium compounds have been reported to show an increased incidence of hypertension, irritation of the respiratory system, and damage to the spleen, liver and bone marrow. Long term exposure to some barium compounds (especially inorganic species) may produce a condition known as baritosis, a form of benign pneumoconiosis. X-ray may show this when no other abnormal signs are present.

Symptoms of pneumoconiosis may include a progressive dry cough, shortness of breath on exertion, increased chest expansion, weakness and weight loss. As the disease progresses the cough produces a stringy mucous, vital capacity decreases further and shortness of breath becomes more severe. Pneumoconiosis is the accumulation of dusts in the lungs and the tissue reaction in its presence. Barium sulfate produces noncollagenous pneumoconiosis identified by minimal stromal reaction, consisting mainly of reticulin fibres, an intact alveolar architecture and is potentially reversible. Miners of ores containing barium sulfate do not show symptoms, abnormal physical signs, an incapacity to work, diminished lung function, an increased likelihood of developing pulmonary or other bronchial infections or other thoracic disease despite the fact that particulate matter may have been retained in the lungs for many years.

TOXICITY AND IRRITATION

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

No data for barium peroxide.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible. Special hazard may exist - specialist advice may be required.
- Consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury or incinerate residue at an approved site.
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
- Puncture containers to prevent re-use and bury at an authorised landfill.

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 12 of 13

Section 14 - TRANSPORTATION INFORMATION



Labels Required: OXIDIZING AGENT, TOXIC
HAZCHEM: 2Y

UNDG:

Dangerous Goods Class: 5.1
UN Number: 1449
Shipping Name: BARIUM PEROXIDE

Subrisk: 6.1
Packing Group: II

Air Transport IATA:

ICAO/IATA Class: 5.1
UN/ID Number: 1449
ERG Code: 5P
Shipping name: BARIUM PEROXIDE

ICAO/IATA Subrisk: 6.1
Packing Group: II

Maritime Transport IMDG:

IMDG Class: 5.1
UN Number: 1449
EMS Number: F- G, S- Q
Shipping name: BARIUM PEROXIDE

IMDG Subrisk: 6.1
Packing Group: II

Section 15 - REGULATORY INFORMATION

REGULATIONS

No regulations applicable
No data available for barium peroxide as CAS: 1304-29-6, CAS: 55396-27-5, CAS: 16678-58-3, CAS: 61233-09-8.

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
barium peroxide	1304- 29- 6, 55396- 27- 5, 16678- 58- 3, 61233- 09- 8

continued...

BARIUM PEROXIDE

GHS Safety Data Sheet

Version No:2.0

Page 13 of 13

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 28-Dec-2017