

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 1 of 11

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

2-BROMO-2-METHYLPROPANE

OTHER NAMES

C4-H9-Br, (CH₃)₂CHCH₂Br, "propane, 2-bromo-2-methyl", "propane, 2-bromo-2-methyl", 2-bromoisobutane, 2-bromoisobutane, "tert-butyl bromide", trimethylbromomethane, "butyl bromide", bromomethylpropane

PROPER SHIPPING NAME

BROMOMETHYLPROPANES

PRODUCT USE

Used in organic syntheses.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Flammable Liquid Category 2

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 2 of 11

Section 2 - HAZARDS IDENTIFICATION

Respiratory Effects Category 3



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:

H336 H225

May cause drowsiness and dizziness

Highly flammable liquid and vapour

PRECAUTIONARY STATEMENTS

Prevention

Take precautionary measures against static discharge

Use explosion-proof electrical/ventilating/lighting/equipment

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Keep away from heat/sparks/open flame - No smoking.

Keep container tightly closed.

Wear protective gloves and eye/face protection.

Response

If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
2- bromo- 2- methylpropane	507-19-7	99.9

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

· If swallowed do NOT induce vomiting.

· If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

· Observe the patient carefully.

· Never give liquid to a person showing signs of being sleepy or with reduced awareness;

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 3 of 11

Section 4 - FIRST AID MEASURES

i.e. becoming unconscious

- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

- Seek medical advice.

Avoid giving milk or oils.

Avoid giving alcohol.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.

- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

- Transport to hospital or doctor without delay.

- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.

- Flush skin and hair with running water (and soap if available).

- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.

- Lay patient down. Keep warm and rested.

- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.

- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.

- Dry chemical powder.

- BCF (where regulations permit).

- Carbon dioxide.

- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.

- May be violently or explosively reactive.

- Wear full body protective clothing with breathing apparatus.

- Prevent, by any means available, spillage from entering drains or water course.

- Consider evacuation (or protect in place).

- Fight fire from a safe distance, with adequate cover.

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 4 of 11

Section 5 - FIRE FIGHTING MEASURES

- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat, flame and/or oxidisers.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Other combustion products include: hydrogen bromide.

FIRE INCOMPATIBILITY

Avoid contamination with strong oxidising agents, particularly peroxides, perchlorates, etc. as violent decomposition / detonation may result.

Personal Protective Equipment

Breathing apparatus.
Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse /absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 5 of 11

Section 6 - ACCIDENTAL RELEASE MEASURES

- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- When handling, DO NOT eat, drink or smoke.
- Vapour may ignite on pumping or pouring due to static electricity.
- DO NOT use plastic buckets.
- Earth and secure metal containers when dispensing or pouring product.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- Keep containers securely sealed.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 6 of 11

Section 7 - HANDLING AND STORAGE

- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- 2-bromo-2-methylpropane:


CAS:507-19-7

MATERIAL DATA

CEL TWA: 0.06 ppm, 0.5 mg/m³

[compare OEL (Russia): for 1-bromo-3-methylbutane]

PERSONAL PROTECTION



EYE

- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Nitrile gloves.

Neoprene gloves.

Safety footwear.

DO NOT use this product to clean the skin.

OTHER

- Overalls.
- Eyewash unit.
- Barrier cream.
- Skin cleansing cream.

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 7 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATOR

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	A- AUS	-	A- PAPR- AUS
50 x ES	-	A- AUS	-
100 x ES	-	A- 2	A- PAPR- 2 ^

^ - Full-face.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Use in a well-ventilated area.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50- 100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 8 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless liquid; does not mix well with water.

At 210 deg C. changes to isobutyl bromide.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Sinks in water.

Molecular Weight: 137.03

Melting Range (°C): - 20

Solubility in water (g/L): Immiscible

pH (1% solution): Not applicable.

Volatile Component (%vol): 100

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): Not available

Autoignition Temp (°C): Not available

State: Liquid

Boiling Range (°C): 72- 74

Specific Gravity (water=1): 1.189

pH (as supplied): Not applicable

Vapour Pressure (kPa): Not available

Evaporation Rate: Not available

Flash Point (°C): 18.33

Upper Explosive Limit (%): Not available

Decomposition Temp (°C): Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 9 of 11

Section 11 - TOXICOLOGICAL INFORMATION

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Considered an unlikely route of entry in commercial/industrial environments.

Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material is not thought to be a skin irritant (i.e. is unlikely to produce irritant dermatitis as described in EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Toxic effects may result from skin absorption.

INHALED

Inhalation may produce health damage*.

The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation, of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

Depression of the central nervous system is the most outstanding effect of most halogenated aliphatic hydrocarbons. Inebriation and excitation, passing into narcosis, is a typical reaction. In severe acute exposures there is always a danger of death from respiratory failure or cardiac arrest due to a tendency to make the heart more susceptible to catecholamines (adrenalin).

In the case of iodised and brominated compounds, exposure effects cannot be described by simple central nervous system depression produced by other halogenated aliphatic hydrocarbons. Headache, nausea, ataxia (loss of muscle co-ordination), tremors, speech difficulties, visual disturbances, convulsions, paralysis, delirium, mania and apathy are all evidence of additional effects.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 10 of 11

Section 11 - TOXICOLOGICAL INFORMATION

TOXICITY AND IRRITATION

TOXICITY

Intraperitoneal (rat) LD50: 1250 mg/kg

Intraperitoneal (mouse) LD50: 4400 mg/kg

IRRITATION

Nil Reported

Section 12 - ECOLOGICAL INFORMATION

No data for 2-bromo-2-methylpropane.

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID
HAZCHEM: 2[Y]E

UNDG:

Dangerous Goods Class: 3
UN Number: 2342
Shipping Name: BROMOMETHYLPROPANES

Subrisk: None
Packing Group: II

Air Transport IATA:

ICAO/IATA Class: 3
UN/ID Number: 2342
ERG Code: 3L
Shipping name: BROMOMETHYLPROPANES

ICAO/IATA Subrisk: None
Packing Group: II

Maritime Transport IMDG:

IMDG Class: 3
UN Number: 2342
EMS Number: F- E, S- D
Shipping name: BROMOMETHYLPROPANES

IMDG Subrisk: None
Packing Group: II

continued...

2-BROMO-2-METHYLPROPANE

GHS Safety Data Sheet

Version No:2.0

Page 11 of 11

Section 15 - REGULATORY INFORMATION

REGULATIONS

No regulations applicable

No data available for 2-bromo-2-methylpropane as CAS: 507-19-7.

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 12-May-2018