

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0
Page 1 of 18

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

N-BUTANOL

OTHER NAMES

C4-H10-O, CH3-CH2-CH2-CH2-OH, butanol, 1-butanol, 1-butanol, butan-1-ol, butan-1-ol, "n-butyl alcohol", "n-butyl alcohol", 1-hydroxybutane, 1-hydroxybutane, "propyl methanol", propylcarbinol, methylopropane, "butyric propylcarbinol"

PROPER SHIPPING NAME

BUTANOLS


PRODUCT USE

A solvent for waxes, resins, shellac, varnish, polymers etc..
Manufacture of lacquers, enamels, thinners, solvent blends, rayon.
In the preparation of butyl esters, especially butyl acetate.

SUPPLIER

Company: S D FINE- CHEM LIMITED
Address:
315- 317, T.V. INDUSTRIAL ESTATE,
248, WORLI,
MUMBAI- 400030.INDIA.
technical@sdfine.com
Telephone: 91- 22- 24959898
Telephone: 91- 22- 24959899
Fax: 91- 22- 24937232

HAZARD RATINGS



BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 2 of 18

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Inhalation) Category 4

Acute Toxicity (Oral) Category 4

Flammable Liquid Category 3

Respiratory Irritation Category 3

Serious Eye Damage Category 1

Skin Corrosion/Irritation Category 2



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:

H335 H226 H332 H302 H315 H318

May cause respiratory irritation

Flammable liquid and vapour

Harmful if inhaled

Harmful if swallowed

Causes skin irritation

Causes serious eye damage

PRECAUTIONARY STATEMENTS

Prevention

Do not eat, drink or smoke when using this product.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Wash hands thoroughly after handling.

Wash thoroughly after handling.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well ventilated area.

Wear protective gloves and eye/face protection.

Keep container tightly closed.

Keep away from heat/sparks/open flame - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment

Take precautionary measures against static discharge

Response

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a POISON CENTER or doctor/physician.

Wear eye/face protection.

continued...

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 3 of 18

Section 2 - HAZARDS IDENTIFICATION

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

If eye irritation persists, get medical advice/attention.

IF ON SKIN: Gently wash with plenty of soap and water.

Specific treatment: refer to Label or MSDS.

In case of fire, use alcohol-type foam for extinction.

If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower.

If skin irritation occurs, seek medical advice/attention.

Wash/Decontaminate removed clothing before reuse.

Remove/Take off immediately all contaminated clothing

Call a POISON CENTER or doctor/physician if you feel unwell.

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
n- butanol	71-36-3	95-99.4

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
 - If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
 - Observe the patient carefully.
 - Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 - Seek medical advice.
- Avoid giving milk or oils.
Avoid giving alcohol.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

continued...

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 4 of 18

Section 4 - FIRST AID MEASURES

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

To treat poisoning by the higher aliphatic alcohols:

- Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.
- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5)

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for shock.
- Monitor and treat, where necessary, for pulmonary oedema.
- Anticipate and treat, where necessary, for seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Give activated charcoal.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Treat seizures with diazepam.

continued...

BUTAN-1-OL

- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- Acidosis may respond to hyperventilation and bicarbonate therapy.
- Haemodialysis might be considered in patients with severe intoxication.
- Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
 - Moderate fire hazard when exposed to heat or flame.
 - Vapour forms an explosive mixture with air.
 - Moderate explosion hazard when exposed to heat or flame.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 6 of 18

Section 5 - FIRE FIGHTING MEASURES

burning organic material.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Personal Protective Equipment

Breathing apparatus.
Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

Slippery when spilt.

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

Chemical Class: alcohols and glycols

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
LAND SPILL - SMALL				
cross- linked polymer - particulate	1	shovel	shovel	R, W, SS
cross- linked polymer - pillow	1	throw	pitchfork	R, DGC, RT
sorbent clay - particulate	2	shovel	shovel	R, I, P
wood fiber - pillow	3	throw	pitchfork	R, P, DGC, RT
treated wood fiber - pillow	3	throw	pitchfork	DGC, RT
foamed glass - pillow	4	throw	pichfork	R, P, DGC, RT
LAND SPILL - MEDIUM				
cross- linked polymer -	1	blower	skiploader	R, W, SS

continued...

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 7 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

particulate polypropylene - particulate	2	blower	skiploader	W, SS, DGC
sorbent clay - particulate	2	blower	skiploader	R, I, W, P, DGC
polypropylene - mat	3	throw	skiploader	DGC, RT
expanded mineral - particulate	3	blower	skiploader	R, I, W, P, DGC
polyurethane - mat	4	throw	skiploader	DGC, RT

Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT: Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988.

Slippery when spilt.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

n-butanol 1400 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

n-butanol 50 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

n-butanol 50 ppm

continued...

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 8 of 18

Section 6 - ACCIDENTAL RELEASE MEASURES

The threshold concentration below which most people will experience no appreciable risk of health effects:
n-butanol 50 ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of overexposure occurs.
 - Use in a well-ventilated area.
 - Prevent concentration in hollows and sumps.
 - DO NOT enter confined spaces until atmosphere has been checked.
 - Avoid smoking, naked lights or ignition sources.
 - Avoid generation of static electricity.
 - DO NOT use plastic buckets.
 - Earth all lines and equipment.
 - Use spark-free tools when handling.
 - Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 - Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
- DO NOT allow clothing wet with material to stay in contact with skin.

continued...

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 9 of 18

Section 7 - HANDLING AND STORAGE

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
 - (i) : Removable head packaging;
 - (ii) : Cans with friction closures and
 - (iii) : low pressure tubes and cartridges may be used.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

Avoid reaction with.

Avoid storage with strong acids, acid chlorides, acid anhydrides, oxidising agents.

Incompatible with aluminium. DO NOT heat above 49 deg. C. in aluminium equipment.

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- n- butanol:

CAS:71- 36- 3 CAS:220713- 25- 7 CAS:42031- 19- 6
CAS:107569- 51- 7

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
n- butanol		1, 400 [LEL]

NOTES

Values marked LEL indicate that the IDLH was based on 10% of the lower explosive limit for safety considerations even though the relevant toxicological data indicated that irreversible health effects or impairment of escape existed only at higher concentrations.

continued...

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 10 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ODOUR SAFETY FACTOR (OSF)

OSF=60 (n-BUTANOL)

MATERIAL DATA

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

Odour Threshold Value: 0.12-3.4 ppm (detection), 1.0-3.5 ppm (recognition)

NOTE: Detector tubes for n-butanol, measuring in excess of 5 ppm are commercially available.

Exposure at or below the TLV-TWA is thought to provide protection against hearing loss due to vestibular and auditory nerve damage in younger workers and to protect against the significant risk of headache and irritation.

25 ppm may produce mild irritation of the respiratory tract

50 ppm may produce headache and vertigo.

Higher concentrations may produce marked irritation, sore throat, coughing, nausea, shortness of breath, pulmonary injury and central nervous system depression characterised by headache, dizziness, dullness and drowsiness.


6000 ppm may produce giddiness, prostration, narcosis, ataxia, and death.

PERSONAL PROTECTION

continued...

BUTAN-1-OL

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.
For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:
solvent, vapours, degreasing etc., evaporating from tank (in still air).
aerosols, fumes from pouring operations,

Air Speed:
0.25- 0.5 m/s (50- 100 f/min.)
0.5- 1 m/s (100- 200 f/min.)

continued...

BUTAN-1-OL

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

intermittent container filling, low speed
conveyer transfers, welding, spray drift,
plating acid fumes, pickling (released at low
velocity into zone of active generation)
direct spray, spray painting in shallow booths,
drum filling, conveyer loading, crusher dusts,
gas discharge (active generation into zone of
rapid air motion)

1- 2.5 m/s (200- 500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only.
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless flammable liquid with a strong, distinctive odour; mixes with water. Mixes with alcohol, ether and aromatic / aliphatic solvents.
Burns with a luminous flame. Odour similar to that of fusel oil, but weaker.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

Molecular Weight: 74.14
Melting Range (°C): - 89.5
Solubility in water (g/L): Miscible
pH (1% solution): Not available.
Volatile Component (%vol): >99
Relative Vapour Density (air=1): 2.55 @ 20 C
Lower Explosive Limit (%): 1.4
Autoignition Temp (°C): 355- 365
State: Liquid

Boiling Range (°C): 117.2
Specific Gravity (water=1): 0.81 @ 20 C
pH (as supplied): Not applicable
Vapour Pressure (kPa): 0.73 @ 20 C
Evaporation Rate: Not available
Flash Point (°C): 29 (Abel)
Upper Explosive Limit (%): 11.2
Decomposition Temp (°C): Not Available
Viscosity: Not Available

log Kow (Prager 1995): 0.88
log Kow (Sangster 1997): 0.84

continued...

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 13 of 18

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

log Kow: 0.88

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
-

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

Effects on the nervous system characterise over-exposure to higher aliphatic alcohols. These include headache, muscle weakness, giddiness, ataxia, (loss of muscle coordination), confusion, delirium and coma. Gastrointestinal effects may include nausea, vomiting and diarrhoea. In the absence of effective treatment, respiratory arrest is the most common cause of death in animals acutely poisoned by the higher alcohols. Aspiration of liquid alcohols produces an especially toxic response as they are able to penetrate deeply in the lung where they are absorbed and may produce pulmonary injury. Those possessing lower viscosity elicit a greater response. The result is a high blood level and prompt death at doses otherwise tolerated by ingestion without aspiration. As a general observation, alcohols are more powerful central nervous system depressants than their aliphatic analogues. In sequence of decreasing depressant potential, tertiary alcohols with multiple substituent OH groups are more potent than secondary alcohols, which, in turn, are more potent than primary alcohols. The potential for overall systemic toxicity increases with molecular weight, principally because the water solubility is diminished and lipophilicity is increased.

Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.

EYE

When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

continued...

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either

- produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or
- produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.

Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

INHALED

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation.

In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Exposure to aliphatic alcohols with more than 3 carbons may produce central nervous system effects such as headache, dizziness, drowsiness, muscle weakness, delirium, CNS depression, coma, seizure, and neurobehavioural changes. Symptoms are more acute with higher alcohols. Respiratory tract involvement may produce irritation of the mucosa, respiratory insufficiency, respiratory depression secondary to CNS depression, pulmonary oedema, chemical pneumonitis and bronchitis. Cardiovascular involvement may result in arrhythmias and hypotension. Gastrointestinal effects may include nausea and vomiting. Kidney and liver damage may result following massive exposures. The alcohols are potential irritants being, generally, stronger irritants than similar organic structures that lack functional groups (e.g. alkanes) but are much less irritating than the corresponding amines, aldehydes or ketones. Alcohols and glycols (diols) rarely represent serious hazards in the workplace, because their vapour concentrations are usually less than the levels which produce significant irritation which, in turn, produce significant central nervous system effects as well.

BUTAN-1-OL

Section 11 - TOXICOLOGICAL INFORMATION

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

CHRONIC HEALTH EFFECTS

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

Serious systemic effects from exposure to n-butanol in the form of auditory and vestibular nerve damage have been reported amongst workers in France and Mexico. Audiologic impairment was produced in workers exposed to 80 ppm n-butanol with unprotected noise exposure. Workers exposed over a 15 year period (1929-1944) exhibited severe vertigo and vertiges gravis. Workers exposed from 3-11 years without personal protective equipment from noise experienced greater hearing loss (hypoacusia) in direct relation to exposure time when compared to a control group exposed to industrial noise of 90-100 dB but with n-butanol exposure. Average hearing loss was not large but the workers had central frequencies of 21.98 dB (11.59 dB minimum and 32.30 dB maximum) with a mean widening of the break between 3000 and 4000 Hz of 42.22 dB. There was a tendency of the averages to decrease as the frequencies moved away from the central zone. Affected workers were aged from 20-39 years. [ACGIH Documentation of TLVs]

TOXICITY AND IRRITATION

TOXICITY

Oral (rat) LD50: 790 mg/kg

Inhalation (human) TCLo: 25 ppm

Inhalation (rat) LC50: 8000 ppm/4h

Dermal (rabbit) LD50: 3400 mg/kg

Inhalation (human) TCLo: 86000 mg/m³

IRRITATION

Skin (rabbit): 405 mg/24h- Moderate

Eye (human): 50 ppm - Irritant

Eye (rabbit): 1.6 mg- SEVERE

Eye (rabbit): 24 mg/24h- SEVERE

BUTAN-1-OL

Section 12 - ECOLOGICAL INFORMATION

Fish LC50 (96hr.) (mg/l):	1910- 1940
Daphnia magna EC50 (48hr.) (mg/l):	1983
Algae IC50 (72hr.) (mg/l):	650
log Kow (Prager 1995):	0.88
log Kow (Sangster 1997):	0.84
log Pow (Verschuereen 1983):	0.88
Half- life Soil - High (hours):	168
Half- life Soil - Low (hours):	24
Half- life Air - High (hours):	87.7
Half- life Air - Low (hours):	8.8
Half- life Surface water - High (hours):	168
Half- life Surface water - Low (hours):	24
Half- life Ground water - High (hours):	1296
Half- life Ground water - Low (hours):	48
Aqueous biodegradation - Aerobic - High (hours):	168
Aqueous biodegradation - Aerobic - Low (hours):	24
Aqueous biodegradation - Anaerobic - High (hours):	1296
Aqueous biodegradation - Anaerobic - Low (hours):	96
Aqueous biodegradation - Removal secondary treatment - High (hours):	99%
Aqueous biodegradation - Removal secondary treatment - Low (hours):	31%
Photooxidation half- life water - High (hours):	104000
Photooxidation half- life water - Low (hours):	2602
Photooxidation half- life air - High (hours):	87.7
Photooxidation half- life air - Low (hours):	8.8

DO NOT discharge into sewer or waterways.

log Kow: 0.88

Koc: 71.6

Half-life (hr) air: 5-52

Half-life (hr) H₂O surface water: 2.4-3022

Henry's atm m³ /mol: 5.57E-06

BOD 5 if unstated: 1.1-2.04,33%

COD: 1.9,92%

ThOD: 2.594

Toxicity Fish: LD100(24)1.4g/L,LC50(96)1.91g/L

Toxicity invertebrate: cell mult. inhib.8-650mg/L

Bioaccumulation: not sig

Nitrif. inhib.: 50% inhib at 8200mg/L

Effects on algae and plankton: cell mult. inhib.100-875mg/L

Degradation Biological: sig

processes Abiotic: RxnOH*

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material).

continued...

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 17 of 18

Section 13 - DISPOSAL CONSIDERATIONS

- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
 - Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID
HAZCHEM: 3[Y]

UNDG:

Dangerous Goods Class: 3
UN Number: 1120
Shipping Name: BUTANOLS

Subrisk: None
Packing Group: III

Air Transport IATA:

ICAO/IATA Class: 3
UN/ID Number: 1120
ERG Code: 3L
Shipping name: BUTANOLS

ICAO/IATA Subrisk: None
Packing Group: III

Maritime Transport IMDG:

IMDG Class: 3
UN Number: 1120
EMS Number: F- E, S- D
Shipping name: BUTANOLS

IMDG Subrisk: None
Packing Group: III

Section 15 - REGULATORY INFORMATION

REGULATIONS

n-butanol (CAS: 71-36-3) is found on the following regulatory lists;
IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

continued...

BUTAN-1-OL

GHS Safety Data Sheet

Version No:2.0

Page 18 of 18

Section 15 - REGULATORY INFORMATION

No data available for n-butanol as CAS: 220713-25-7, CAS: 42031-19-6, CAS: 107569-51-7.

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
n- butanol	71- 36- 3, 220713- 25- 7, 42031 - 19- 6, 107569- 51- 7

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 26-Mar-2018