



CALCIUM SULPHATE ANHYDROUS

GHS Safety Data Sheet

Version No:3

Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

CALCIUM SULFATE

OTHER NAMES

Ca-O4-S, CaSO₄, "sulphuric acid, calcium salt (1:1)", "sulfuric acid, calcium salt (1:1)", "anhydrous gypsum", "dried calcium sulphate", Annalin, Crysalba, Gibs, Thiolite, "calcined calcium sulphate", "calcined calcium sulfate", "as dihydrate", "sulfuric acid, calcium(2+) salt, dihydrate", "calcium (II) sulfate, dihydrate (1:1:2)", "calcium (II) sulfate, dihydrate (1:1:2)",

PRODUCT USE

Laboratory reagent for drying, desiccant.

Used as portland cement retarder; tile and plaster; source of sulphur and sulphuric acid; polishing powders; paints (white pigment, filler, drier); paper (size filler, surface coating); dyeing and calico printing.

Also used in metallurgy (reduction of zinc minerals); drying industrial gases, solids and many organic liquids; in granulated form as soil conditioner; quick-setting cements, moulds, and surgical casts; wallboard; food additive and desiccant.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.

technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS

continued...


CALCIUM SULPHATE ANHYDROUS

GHS Safety Data Sheet

Version No:3

Page 2 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION



Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HAZARD

Not hazardous
No hazards determined by using GHS criteria

PRECAUTIONARY STATEMENTS

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
calcium sulfate	7778-18-9	100

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - If pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.

continued...

CALCIUM SULPHATE ANHYDROUS

GHS Safety Data Sheet

Version No:3

Page 3 of 10

Section 4 - FIRST AID MEASURES

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
 - Not considered to be a significant fire risk, however containers may burn.
 - In a fire may decompose on heating and produce toxic / corrosive fumes.
- Decomposes on heating and produces toxic fumes of:
sulfur oxides (SO_x) and calcium oxide.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety glasses.
- Use dry clean up procedures and avoid generating dust.
- Sweep up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment and dust respirator.
- Prevent spillage from entering drains, sewers or water courses.

continued...

CALCIUM SULPHATE ANHYDROUS

GHS Safety Data Sheet

Version No:3

Page 4 of 10

Section 6 - ACCIDENTAL RELEASE MEASURES

- Recover product wherever possible. Avoid generating dust.
- Sweep / shovel up.
- If required, wet with water to prevent dusting.
- Put residues in labelled plastic bags or other containers for disposal.
- Wash area down with large quantity of water and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

calcium sulfate 250 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

calcium sulfate 50 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

calcium sulfate 30 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:

calcium sulfate 15 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ + + + + +

+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.

continued...

CALCIUM SULPHATE ANHYDROUS

GHS Safety Data Sheet

Version No:3

Page 5 of 10

Section 7 - HANDLING AND STORAGE

- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

Glass container.

Plastic container.

Multi-ply woven plastic or paper bag with sealed plastic liner

NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse.

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid storage with aluminium, diazomethane, phosphorus and acids.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.


Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

MATERIAL DATA

The TLV-TWA is thought to be protective against the significant risks of eye, skin and other physical irritation.

PERSONAL PROTECTION



continued...

CALCIUM SULPHATE ANHYDROUS

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.
Wear safety footwear.

OTHER

- Overalls.
- Barrier cream
- Eyewash unit.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:
solvent, vapours, degreasing etc., evaporating from tank (in still air).
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)

Air Speed:
0.25- 0.5 m/s (50- 100 f/min)
0.5- 1 m/s (100- 200 f/min.)

continued...

CALCIUM SULPHATE ANHYDROUS

GHS Safety Data Sheet

Version No:3

Page 7 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

White, odourless, tasteless powder or crystals. Very slightly soluble in water.

PHYSICAL PROPERTIES

Solid.

Does not mix with water.

Sinks in water.

Molecular Weight: 136.14

Melting Range (°C): 1450 (anhydrous)

Solubility in water (g/L): Partly miscible

pH (1% solution): Not applicable.

Volatile Component (%vol): 0

Relative Vapour Density (air=1): Not applicable.

Lower Explosive Limit (%): Not applicable

Autoignition Temp (°C): Not applicable

State: Divided solid

Boiling Range (°C): Not available.

Specific Gravity (water=1): 2.96 (anhydrous)

pH (as supplied): Not applicable

Vapour Pressure (kPa): Not applicable.

Evaporation Rate: Not applicable

Flash Point (°C): Not applicable

Upper Explosive Limit (%): Not applicable

Decomposition Temp (°C): 1425

Viscosity: Not available

continued...

CALCIUM SULPHATE ANHYDROUS

GHS Safety Data Sheet

Version No:3

Page 8 of 10

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). The dust may produce eye discomfort causing transient smarting, blinking.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting. Solution of material in moisture on the skin, or perspiration, may increase irritant effects.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and inhalation of generated dusts. As with any chemical product, contact with unprotected bare skin; inhalation of vapour,

continued...

CALCIUM SULPHATE ANHYDROUS

GHS Safety Data Sheet

Version No:3

Page 9 of 10

Section 11 - TOXICOLOGICAL INFORMATION

mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

TOXICITY AND IRRITATION

for dihydrate

[RTEC NO.: EW 4150000]

Inhalation (human) TCLo: 194000 mg/m³/10Y Nil reported
-Intermittent

Section 12 - ECOLOGICAL INFORMATION

No data

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,
IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

calcium sulfate (CAS: 7778-18-9) is found on the following regulatory lists;
CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals
United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II

calcium sulfate (CAS: 10101-41-4) is found on the following regulatory lists;
United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II

No data available for calcium sulfate as CAS: 99400-01-8, CAS: 326855-67-8, CAS: 151621-69-1, CAS: 146522-67-0, CAS: 23296-15-3.

continued...

CALCIUM SULPHATE ANHYDROUS

GHS Safety Data Sheet

Version No:3

Page 10 of 10

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name
calcium sulfate

CAS
7778- 18- 9, 10101- 41- 4, 99400- 01- 8, 326855-
67- 8, 151621- 69- 1, 146522- 67- 0, 23296- 15-
3

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 22-Jan-2018