

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 1 of 15

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

M-CHLOROTOLUENE

OTHER NAMES

3-chloro-l-methylbenzene, 3-chloro-l-methylbenzene, "3 chlorotoluene",
"m-tolyl chloride", "toluene, m-chloro",
"benzene, 1-chloro-3-methyl", monochlorotoluene, "chlorotoluene"

PROPER SHIPPING NAME

CHLOROTOLUENES

PRODUCT USE

Used as solvent and intermediate in manufacturer of organic chemicals and dyes.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 2 of 15

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Inhalation) Category 4
Chronic Aquatic Hazard Category 2
Flammable Liquid Category 3
Respiratory Irritation Category 3



EMERGENCY OVERVIEW

HAZARD

WARNING

Determined by using GHS criteria:
H335 H226 H332 H411

May cause respiratory irritation

Flammable liquid and vapour

Harmful if inhaled

Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS

Prevention

Use only non-sparking tools.

Take precautionary measures against static discharge

Use explosion-proof electrical/ventilating/lighting/equipment

Avoid breathing dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well ventilated area.

Ground/bond container and receiving equipment.

Keep away from heat/sparks/open flame - No smoking.

Keep container tightly closed.

Wear protective gloves and eye/face protection.

Response

Specific treatment: refer to Label or MSDS.

Call a POISON CENTER or doctor/physician if you feel unwell.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower.

In case of fire, use foam for extinction.

Disposal

Dispose of contents and container in accordance with relevant legislation.

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 3 of 15

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
m- chlorotoluene	108-41-8	>96
toluene	108-88-3	2 ap.

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

Treat symptomatically.

Do not give epinephrine or related drugs.

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 4 of 15

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
 - Moderate fire hazard when exposed to heat or flame.
 - Vapour forms an explosive mixture with air.
 - Moderate explosion hazard when exposed to heat or flame.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Decomposes on heating and produces acrid and toxic fumes of: hydrogen chloride.

Personal Protective Equipment

Breathing apparatus.
Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

- Pollutant - contain spillage.
- Clear area of personnel and move upwind.

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 5 of 15

Section 6 - ACCIDENTAL RELEASE MEASURES

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid generation of static electricity.
- DO NOT use plastic buckets.
- Earth all lines and equipment.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 6 of 15

Section 7 - HANDLING AND STORAGE

SUITABLE CONTAINER

- Metal can or drum
 - Packaging as recommended by manufacturer.
 - Check all containers are clearly labelled and free from leaks.
- Plastic containers may only be used if approved for flammable liquids.

STORAGE INCOMPATIBILITY

Avoid storage with oxidisers.

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- m- chlorotoluene: CAS:108- 41- 8
- toluene: CAS:108- 88- 3

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
toluene		500

ODOUR SAFETY FACTOR (OSF)

OSF=17 (TOLUENE)

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 7 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

E	<0.18	that the Exposure Standard is being reached As " D" for less than 10% of persons aware of being tested
---	-------	---

MATERIAL DATA

Not available for material.

Data for similar material only.

INGREDIENT DATA

TOLUENE:

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no -observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time -weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996).

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0


Page 8 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

E	<0.18	that the Exposure Standard is being reached As " D" for less than 10% of persons aware of being tested
---	-------	---

Odour Threshold Value: 0.16-6.7 (detection), 1.9-69 (recognition)
NOTE: Detector tubes measuring in excess of 5 ppm, are available.
High concentrations of toluene in the air produce depression of the central nervous system (CNS) in humans. Intentional toluene exposure (glue-sniffing) at maternally-intoxicating concentration has also produced birth defects. Foetotoxicity appears at levels associated with CNS narcosis and probably occurs only in those with chronic toluene-induced kidney failure. Exposure at or below the recommended TLV-TWA is thought to prevent transient headache and irritation, to provide a measure of safety for possible disturbances to human reproduction, the prevention of reductions in cognitive responses reported amongst humans inhaling greater than 40 ppm, and the significant risks of hepatotoxic, behavioural and nervous system effects (including impaired reaction time and incoordination). Although toluene/ethanol interactions are well recognised, the degree of protection afforded by the TLV-TWA among drinkers is not known.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Butyl rubber gloves.
Neoprene gloves.
PVC gloves.
Safety footwear.
DO NOT use this product to clean the skin.

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 9 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OTHER

- Overalls.
- Eyewash unit.
- Barrier cream.
- Skin cleansing cream.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Use in a well-ventilated area.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

solvent, vapours, degreasing etc., evaporating from tank (in still air).

aerosols, fumes from pouring operations,

intermittent container filling, low speed

conveyer transfers, welding, spray drift,

plating acid fumes, pickling (released at low velocity into zone of active generation)

direct spray, spray painting in shallow booths,

drum filling, conveyer loading, crusher dusts,

gas discharge (active generation into zone of rapid air motion)

grinding, abrasive blasting, tumbling, high

speed wheel generated dusts (released at high

initial velocity into zone of very high rapid air motion).

Air Speed:

0.25- 0.5 m/s (50- 100 f/min.)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 10 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. In confined spaces where there is inadequate ventilation, wear full-face air supplied breathing apparatus.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear, flammable liquid; does not mix with water.
Mixes with most organic solvents.
Vapour is heavier than air.

PHYSICAL PROPERTIES

Liquid.
Does not mix with water.
Sinks in water.

Molecular Weight: 126.7
Melting Range (°C): - 48
Solubility in water (g/L): Immiscible
pH (1% solution): Not applicable.
Volatile Component (%vol): 100
Relative Vapour Density (air=1): 40 approx.
Lower Explosive Limit (%): Not available.
Autoignition Temp (°C): Not available.
State: Liquid

Boiling Range (°C): 162
Specific Gravity (water=1): 1.070- 1.072@ 20C
pH (as supplied): Not applicable
Vapour Pressure (kPa): 0.4 @ 20 C
Evaporation Rate: Not available
Flash Point (°C): 51
Upper Explosive Limit (%): Not available.
Decomposition Temp (°C): Not available

log Kow : 3.28
log Kow (Sangster 1997): 2.73
log Kow: 2.1-3

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 11 of 15

Section 11 - TOXICOLOGICAL INFORMATION

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

Considered an unlikely route of entry in commercial/industrial environments.

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material is not thought to be a skin irritant (i.e. is unlikely to produce irritant dermatitis as described in EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Toxic effects may result from skin absorption.

INHALED

Limited evidence exists, or practical experience predicts, that the material produces irritation of the respiratory system in a significant number of individuals following inhalation.

Inhalation hazard is increased at higher temperatures.

Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

CHRONIC HEALTH EFFECTS

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Principal routes of exposure are usually by inhalation of vapour and skin contact/absorption.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

Prolonged or continuous skin contact with the liquid may cause defatting with drying, cracking, irritation and dermatitis following.

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 12 of 15

Section 11 - TOXICOLOGICAL INFORMATION

TOXICITY AND IRRITATION

None available.

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances

TOLUENE:

TOXICITY

Oral (human) LDLo: 50 mg/kg

Oral (rat) LD50: 636 mg/kg

Inhalation (human) TClO: 100 ppm

Inhalation (man) TClO: 200 ppm

Inhalation (rat) LC50: >26700 ppm/1h

Dermal (rabbit) LD50: 12124 mg/kg

IRRITATION

Skin (rabbit):20 mg/24h- Moderate

Skin (rabbit):500 mg - Moderate

Eye (rabbit):0.87 mg - Mild

Eye (rabbit): 2mg/24h - SEVERE

Eye (rabbit):100 mg/30sec - Mild

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant:Not Determined

log Kow : 3.28

Toxicity Fish: non tox at 50ppm

Toxicity invertebrate: cell mult. inhib.15->100mg/L

Bioaccumulation: little if any

Effects on algae and plankton: cell mult. inhib. algae >100mg/L

Refer to data for ingredients, which follows:

TOLUENE:

Hazardous Air Pollutant:

Yes

Fish LC50 (96hr.) (mg/l):

7.3- 22.8

BCF<100:

13.2 (EELS)

log Kow (Sangster 1997):

2.73

log Pow (Verschueren 1983):

2.69

BOD5:

5%

COD:

21%

ThOD:

3.13

Half- life Soil - High (hours):

528

Half- life Soil - Low (hours):

96

Half- life Air - High (hours):

104

Half- life Air - Low (hours):

10

Half- life Surface water - High (hours):

528

Half- life Surface water - Low (hours):

96

Half- life Ground water - High (hours):

672

Half- life Ground water - Low (hours):

168

Aqueous biodegradation - Aerobic - High (hours):

528

Aqueous biodegradation - Aerobic - Low (hours):

96

Aqueous biodegradation - Anaerobic - High (hours):

5040

Aqueous biodegradation - Anaerobic - Low (hours):

1344

Aqueous biodegradation - Removal secondary treatment - High (hours):

75%

Photolysis maximum light absorption - High (nano- m):

268

Photolysis maximum light absorption - Low (nano- m):

253.5

Photooxidation half- life water - High (hours):

1284

Photooxidation half- life water - Low (hours):

321

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 13 of 15

Section 12 - ECOLOGICAL INFORMATION

Photooxidation half- life air - High (hours):	104
Photooxidation half- life air - Low (hours):	10

The lower molecular weight hydrocarbons are expected to form a "slick" on the surface of waters after release in calm sea conditions. This is expected to evaporate and enter the atmosphere where it will be degraded through reaction with hydroxy radicals.

Some of the material will become associated with benthic sediments, and it is likely to be spread over a fairly wide area of sea floor. Marine sediments may be either aerobic or anaerobic. The material, in probability, is biodegradable, under aerobic conditions (isomerised olefins and alkenes show variable results). Evidence also suggests that the hydrocarbons may be degradable under anaerobic conditions although such degradation in benthic sediments may be a relatively slow process.

Under aerobic conditions the material will degrade to water and carbon dioxide, while under anaerobic processes it will produce water, methane and carbon dioxide.

Based on test results, as well as theoretical considerations, the potential for bioaccumulation may be high. Toxic effects are often observed in species such as blue mussel, daphnia, freshwater green algae, marine copepods and amphipods.

DO NOT discharge into sewer or waterways.

log Kow: 2.1-3

log Koc: 1.12-2.85

Koc: 37-250

log Kom: 1.39-2.89

Half-life (hr) air: 2.4-104

Half-life (hr) H₂O surface water: 5.55-528

Half-life (hr) H₂O ground: 168-2628

Half-life (hr) soil: <48-240

Henry's Pa m³ /mol: 518-694

Henry's atm m³ /mol: 5.94E-03

BOD 5 if unstated: 0.86-2.12,5%

COD: 0.7-2.52,21-27%

ThOD: 3.13

BCF: 1.67-380

Log BCF: 0.22-3.28

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 14 of 15

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID
HAZCHEM: 3[Y]E

UNDG:

Dangerous Goods Class:	3	Subrisk:	None
UN Number:	2238	Packing Group:	III
Shipping Name:CHLOROTOLUENES			

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	2238	Packing Group:	III
ERG Code:	3L		
Shipping name:CHLOROTOLUENES			

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	2238	Packing Group:	III
EMS Number:	F- E, S- D	Marine Pollutant:	Not Determined
Shipping name:CHLOROTOLUENES			

Section 15 - REGULATORY INFORMATION

REGULATIONS

m-chlorotoluene (CAS: 108-41-8) is found on the following regulatory lists;
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk

Section 16 - OTHER INFORMATION

REPRODUCTIVE HEALTH GUIDELINES

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level (LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

Ingredient	ORG	UF	Endpoi	CR	Adeq
------------	-----	----	--------	----	------

continued...

M-CHLOROTOLUENE

GHS Safety Data Sheet

Version No:2.0

Page 15 of 15

Section 16 - OTHER INFORMATION

toluene	9.6 mg/m3	10	nt D	NA	TLV -
---------	-----------	----	---------	----	----------

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996).

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 30-Mar-2018