

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 1 of 13

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

GAMMA-BUTYROLACTONE

OTHER NAMES

C4-H6-O2, "1, 4-butyrolactone", "1, 4-butyrolactone", "4-hydroxybutyric acid, gamma-lactone", "4-hydroxybutyric acid, gamma-lactone", "gamma butyrolactone", "gamma-hydroxybutyric acid lactone", "1, 2, 1, 4, 4-butanolide", "1, 2, 1, 4, 4-butanolide", "butyric acid lactone", 4-butyrolactone, 4-butyrolactone, "butyryl lactone", "4-deoxytetronic acid", "4-deoxytetronic acid", dihydro-2(3H)-furanone, "4-hydroxybutanoic acid lactone", "4-hydroxybutanoic acid lactone", "4-hydroxybutanoic acid, gamma-lactone", "4-hydroxybutanoic acid, gamma-lactone", "2(3H)-furanone, dihydro-", "gamma-hydroxybutyric acid cyclic ester", "4-hydroxybutyric acid lactone", "4-hydroxybutyric acid lactone"

PRODUCT USE

Catalyst for phenolic resins, intermediate for synthesis of butyric acid compounds, polyvinylpyrrolidone, methionine.

Solvent for acrylate and styrene polymers, ingredient of paint removers, spinning solvent, textile assistants and drilling oils.

Used in a model test for presynaptic dopaminergic activity for introduction of carboxypropyl sidechain. Found as a component of electrolyte solutions in batteries and capacitors.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.

technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS

continued...


Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 2 of 13

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Oral) Category 4

Eye Irritation Category 2A

Respiratory Effects Category 3



EMERGENCY OVERVIEW

HAZARD

WARNING

Determined by using GHS criteria:

H336 H302 H319

May cause drowsiness and dizziness

Harmful if swallowed

Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Wear eye/face protection.

If eye irritation persists, get medical advice/attention.

Specific treatment: refer to Label or MSDS.

Storage

Store locked up.

continued...

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 3 of 13

Section 2 - HAZARDS IDENTIFICATION

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
gamma- butyrolactone	96-48-0	99.5

Section 4 - FIRST AID MEASURES

SWALLOWED

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
 - For advice, contact a Poisons Information Centre or a doctor.
 - Urgent hospital treatment is likely to be needed.
 - In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
 - If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist.
 - If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.
 - Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
 - INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- NOTE: Wear a protective glove when inducing vomiting by mechanical means.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - If pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.
For poisons (where specific treatment regime is absent):

BASIC TREATMENT

continued...

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 4 of 13

Section 4 - FIRST AID MEASURES

-
- Establish a patent airway with suction where necessary.
 - Watch for signs of respiratory insufficiency and assist ventilation as necessary.
 - Administer oxygen by non-rebreather mask at 10 to 15 L/min.
 - Monitor and treat, where necessary, for pulmonary oedema .
 - Monitor and treat, where necessary, for shock.
 - Anticipate seizures .
 - DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

-
- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
 - Positive-pressure ventilation using a bag-valve mask might be of use.
 - Monitor and treat, where necessary, for arrhythmias.
 - Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
 - Drug therapy should be considered for pulmonary oedema.
 - Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
 - Treat seizures with diazepam.
 - Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.

continued...

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 5 of 13

Section 5 - FIRE FIGHTING MEASURES

- Mists containing combustible materials may be explosive.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Personal Protective Equipment

Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

Slippery when spilt.

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Slippery when spilt.

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

gamma-butyrolactone 500 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take

continued...

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 6 of 13

Section 6 - ACCIDENTAL RELEASE MEASURES

protective action is:
gamma-butyrolactone 40 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:
gamma-butyrolactone 6 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:
gamma-butyrolactone 2 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

DO NOT allow clothing wet with material to stay in contact with skin.

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

continued...

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 7 of 13

Section 7 - HANDLING AND STORAGE

SUITABLE CONTAINER

- Metal can or drum
 - Packaging as recommended by manufacturer.
 - Check all containers are clearly labelled and free from leaks.
- Do not use epoxy lined drums.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records


- gamma- butyrolactone:

CAS:96- 48- 0 CAS:187997- 16- 6

MATERIAL DATA

No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

continued...

Y-BUTYROLACTONE

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS/FEET

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS P	-
1000	50	-	A- AUS P
5000	50	Airline *	-
5000	100	-	A- 2 P
10000	100	-	A- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:
solvent, vapours, degreasing etc., evaporating from tank (in still air).
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low

Air Speed:
0.25- 0.5 m/s (50- 100 f/min)
0.5- 1 m/s (100- 200 f/min.)

continued...

Y-BUTYROLACTONE

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

velocity into zone of active generation) direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear, colourless, thin liquid; mixes with water. Pleasant odour.
Dissolves in alcohol, organic solvents in all proportions.
Flashpoint (Closed Cup): 93.3 deg. C.
Liquid; does not mix well with water.
Swallowing may result in intoxication and drowsiness with lowering of inhibitions and increased libido.
Side effects of treatment include abnormal muscular activity during the induction phase and nausea and vomiting. Bradycardia frequently occurs.
Emergence delirium has been reported. Respiration may be slowed and hypokalaemia has also been recorded.
Consumption of less than 1 gram of the material acts as a relaxant, causing a loss of muscle tone and reduced inhibitions. Consumption of 1 to 2 grams causes a strong feeling of relaxation and slows the heart rate and respiration. At this dosage level, the material also interferes with blood circulation, motor coordination, and balance. In stronger doses, 2 to 4 grams, pronounced interference with motor and speech control occurs. A coma-like sleep may be induced, requiring intubation to wake the user. When mixed with alcohol, the depressant effects of the material are enhanced. This can lead to respiratory depression, unconsciousness, coma, and overdose.

continued...

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 10 of 13

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Side effects associated with the material may include nausea, vomiting, delusions, depression, vertigo, hallucinations, seizures, respiratory distress, loss of consciousness, slowed heart rate, lowered blood pressure, amnesia, and coma. It can become addictive with sustained use.

Patients with a history of around-the-clock use of this material (every 2 to 4 hours) exhibit withdrawal symptoms including anxiety, insomnia, tremors, and episodes of tachycardia (abnormally fast heart rates), and may progress to delirium and agitation. Because it has a short duration of action and quickly leaves the user's system, withdrawal symptoms may occur within 1 to 6 hours of the last dose. These symptoms may last for many months.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

Molecular Weight: 86.10

Melting Range (°C): - 43

Solubility in water (g/L): Miscible

pH (1% solution): 4.5 (10%)

Volatile Component (%vol): 100

Relative Vapour Density (air=1): 3.0

Lower Explosive Limit (%): 1.4

Autoignition Temp (°C): Not available

State: Liquid

Boiling Range (°C): 206

Specific Gravity (water=1): 1.13 @ 25 C

pH (as supplied): Not applicable

Vapour Pressure (kPa): 0.06 @ 25 C

Evaporation Rate: V. Slow

Flash Point (°C): 98 (OC)

Upper Explosive Limit (%): 6.9

Decomposition Temp (°C): 455

Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.

EYE

Evidence exists, or practical experience predicts, that the material may cause severe eye irritation in a substantial number of individuals and/or may produce significant ocular

continued...

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 11 of 13

Section 11 - TOXICOLOGICAL INFORMATION

lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Eye contact may cause significant inflammation with pain. Corneal injury may occur; permanent impairment of vision may result unless treatment is prompt and adequate. Repeated or prolonged exposure to irritants may cause inflammation characterised by a temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material is not thought to be a skin irritant (i.e. is unlikely to produce irritant dermatitis as described in EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation.

INHALED

Inhalation hazard is increased at higher temperatures.

The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

CHRONIC HEALTH EFFECTS

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Gamma-butyrolactone is rapidly converted to gamma-hydroxybutyric acid by enzymes in the blood and liver of animals and humans. An equivocal response produced by the lactone, in carcinogenicity studies in rats, has been reported in terms of its ability to increase the incidence of pheochromocytomas in the renal medulla. Because of the rapid and extensive conversion of gamma-butyrolactone to the acid, the evaluation of the lactone was in fact an evaluation of gamma-hydroxybutyric acid.

In Scandinavia, some cases of poisoning in children have been reported after ingestion of small amounts (less than 8ml) of gamma-butyrolactone.

TOXICITY AND IRRITATION

TOXICITY

Oral (rat) LD50: 1540 mg/kg

Dermal (g.pig) LD50: >5000 mg/kg

IRRITATION

Skin (rabbit): non-irritating *

Eye (rabbit): SEVERE

* [Manuf. ISP]

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

continued...

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 12 of 13

Section 11 - TOXICOLOGICAL INFORMATION

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

Aquatic toxicity: 48hr LC50 (minnow): 100-500 mg/l

[ISP]

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.
- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

gamma-butyrolactone (CAS: 96-48-0) is found on the following regulatory lists;
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
International Agency for Research on Cancer (IARC) Carcinogens
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

No data available for gamma-butyrolactone as CAS: 187997-16-6.

continued...

Y-BUTYROLACTONE

GHS Safety Data Sheet

Version No:4

Page 13 of 13

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
gamma- butyrolactone	96- 48- 0, 187997- 16- 6

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 10-Nov-2017