

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 1 of 11

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

DIETHYL CARBONATE

OTHER NAMES

C5-H10-O3, (C2H5)2CO3, "carbonic acid diethyl ester", diethylcarbonate, "ethoxyformic anhydride", "ethyl carbonate", Diatol, Dec, Eufin

PROPER SHIPPING NAME

DIETHYL CARBONATE

PRODUCT USE

Solvent for nitrocellulose, cellulose ethers, many synthetic and natural resins; organic synthesis; adhering rare earths to cathodes.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Flammable Liquid Category 3

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 2 of 11

Section 2 - HAZARDS IDENTIFICATION

Reproductive Toxicity Category 1B
Respiratory Irritation Category 3



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:

H335 H226 H360

May cause respiratory irritation

Flammable liquid and vapour

May damage the unborn child

PRECAUTIONARY STATEMENTS

Prevention

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge

Use personal protective equipment as required.

Do not handle until all safety precautions have been read and understood.

Obtain special instructions before use.

Keep container tightly closed.

Keep away from heat/sparks/open flame - No smoking.

Wear protective gloves and eye/face protection.

Use explosion-proof electrical/ventilating/lighting/equipment

Response

If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower.

If exposed or concerned: Get medical attention advice.

In case of fire, use foam for extinction.

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
diethyl carbonate	105-58-8	> 99

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 3 of 11

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 4 of 11

Section 5 - FIRE FIGHTING MEASURES

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are flammable.
 - Moderate fire hazard when exposed to heat or flame.
 - Vapour forms an explosive mixture with air.
 - Moderate explosion hazard when exposed to heat or flame.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Other combustion products include: carbon dioxide (CO₂).

Personal Protective Equipment

Gloves, boots (chemical resistant).
Breathing apparatus.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 5 of 11

Section 6 - ACCIDENTAL RELEASE MEASURES

- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ X X X X +

+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid generation of static electricity.
- DO NOT use plastic buckets.
- Earth all lines and equipment.
- Use spark-free tools when handling.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

Glass container.

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Oxidising agents. Protect from moisture. Strong acids

Strong bases. Reducing agents.

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 6 of 11

Section 7 - HANDLING AND STORAGE

STORAGE REQUIREMENTS

- Store in original containers in approved flammable liquid storage area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- diethyl carbonate:

CAS:105- 58- 8

MATERIAL DATA

No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields; or as required,
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Wear safety footwear.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 7 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Ensure there is ready access to a safety shower.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult
your

Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

solvent, vapours, degreasing etc., evaporating
from tank (in still air).

aerosols, fumes from pouring operations,
intermittent container filling, low speed
conveyer transfers, welding, spray drift,
plating acid fumes, pickling (released at low
velocity into zone of active generation)

direct spray, spray painting in shallow booths,
drum filling, conveyer loading, crusher dusts,
gas discharge (active generation into zone of
rapid air motion)

grinding, abrasive blasting, tumbling, high
speed wheel generated dusts (released at high
initial velocity into zone of very high rapid
air motion).

Air Speed:

0.25- 0.5 m/s (50- 100 f/min)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to
capture

2: Contaminants of low toxicity or of nuisance
value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 8 of 11

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear colourless liquid with a mild, pleasant ether-like odour.
Does not mix with water. Mixes with alcohols, ketones, esters, aromatic hydrocarbons and some aliphatic solvents.
Moisture sensitive.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

Molecular Weight: 118.15

Melting Range (°C): - 43

Solubility in water (g/L): Immiscible

pH (1% solution): Not applicable.

Volatile Component (%vol): 100

Relative Vapour Density (air=1): 4.1

Lower Explosive Limit (%): Not available.

Autoignition Temp (°C): Not available.

State: Liquid

Boiling Range (°C): 126- 128

Specific Gravity (water=1): 0.98

pH (as supplied): Not applicable

Vapour Pressure (kPa): 1.33 @ 20 C.

Evaporation Rate: Not available

Flash Point (°C): 33

Upper Explosive Limit (%): Not available.

Decomposition Temp (°C): Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.

Considered an unlikely route of entry in commercial/industrial environments.

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 9 of 11

Section 11 - TOXICOLOGICAL INFORMATION

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

The vapour and liquid both produce eye discomfort. Tearing and reddening of the eyes are symptomatic of overexposure. Higher levels of vapour are generated with increased temperature and engineering controls should be introduced when any discomfort is experienced following exposure to mists or vapour.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

The liquid may produce skin discomfort following prolonged contact. Defatting and/or drying of the skin may lead to dermatitis.

INHALED

Limited evidence exists, or practical experience predicts, that the material produces irritation of the respiratory system in a significant number of individuals following inhalation.

Although inhalation is not thought to produce harmful effects (as classified under EC Directives), the material may still produce health damage, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally confined to doses producing mortality rather than those producing morbidity (disease, ill-health).

Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are usually by inhalation of vapour and skin contact/absorption.

No human exposure data available. For this reason health effects described are based on experience with chemically related materials.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

TOXICITY AND IRRITATION

TOXICITY

Oral (rat) LDLo: 15000 mg/kg

Equivocal tumorigen by RTECS criteria

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

IRRITATION

Nil Reported

Section 12 - ECOLOGICAL INFORMATION

No data for diethyl carbonate.

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 10 of 11

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID
HAZCHEM: 3Y

UNDG:

Dangerous Goods Class: 3
UN Number: 2366
Shipping Name: DIETHYL CARBONATE

Subrisk: None
Packing Group: III

Air Transport IATA:

ICAO/IATA Class: 3
UN/ID Number: 2366
ERG Code: 3L
Shipping name: DIETHYL CARBONATE

ICAO/IATA Subrisk: None
Packing Group: III

Maritime Transport IMDG:

IMDG Class: 3
UN Number: 2366
EMS Number: F- E, S- D
Shipping name: DIETHYL CARBONATE

IMDG Subrisk: None
Packing Group: III

Section 15 - REGULATORY INFORMATION

REGULATIONS

diethyl carbonate (CAS: 105-58-8) is found on the following regulatory lists;
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk

continued...

DIETHYL CARBONATE

GHS Safety Data Sheet

Version No:2.0

Page 11 of 11

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 28-Sep-2017