**GHS Safety Data Sheet** 

Version No:2.0 Page 1 of 9

#### Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

## **PRODUCT NAME**

GADOLINIUM(III) SULPHATE

## **OTHER NAMES**

Gd2-O12-S3, Gd2(SO4)3, "gadolinium(3+) sulphate", "sulfuric acid, gadolinium (3+) salt (3:2)"

## **PRODUCT USE**

Reagent; cryogenic research.

#### SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315-317, T.V. INDUSTRIAL ESTATE,


248, WORLI,

MUMBAI- 400030.INDIA. technical@sdfine.com

Telephone: 91- 22- 24959898 Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

#### **HAZARD RATINGS**



### **Section 2 - HAZARDS IDENTIFICATION**

## **EMERGENCY OVERVIEW**

## **HAZARD**

Not hazardous

No hazards determined by using GHS criteria

### **GHS Safety Data Sheet**

Version No:2.0

Page 2 of 9

## **Section 2 - HAZARDS IDENTIFICATION**

#### PRECAUTIONARY STATEMENTS

#### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS CAS RN % gadolinium(III) sulfate 13628-54-1 >98

#### **Section 4 - FIRST AID MEASURES**

#### **SWALLOWED**

NAME

- · If swallowed do NOT induce vomiting.
- · If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- · Observe the patient carefully.
- · Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- · Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- · Seek medical advice.

## EYE

If this product comes in contact with the eyes:

- · Immediately hold eyelids apart and flush the eye continuously with running water.
- · Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- · Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- · Transport to hospital or doctor without delay.
- · Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

#### SKIN

If skin contact occurs:

- · Immediately remove all contaminated clothing, including footwear.
- · Flush skin and hair with running water (and soap if available).
- · Seek medical attention in event of irritation.

#### **INHALED**

- · If dust is inhaled, remove from contaminated area.
- · Encourage patient to blow nose to ensure clear passage of breathing.
- · If irritation or discomfort persists seek medical attention.
- · If fumes or combustion products are inhaled remove from contaminated area.
- · Lay patient down. Keep warm and rested.
- · Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- · Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- · Transport to hospital, or doctor.

## **NOTES TO PHYSICIAN**

Treat symptomatically.

GHS Safety Data Sheet Version No:2.0

Page 3 of 9

### **Section 5 - FIRE FIGHTING MEASURES**

#### **EXTINGUISHING MEDIA**

- · Water spray or fog.
- · Foam.
- · Dry chemical powder.
- · BCF (where regulations permit).
- · Carbon dioxide.

#### FIRE FIGHTING

- · Alert Fire Brigade and tell them location and nature of hazard.
- · Wear breathing apparatus plus protective gloves for fire only.
- · Prevent, by any means available, spillage from entering drains or water courses.
- · Use fire fighting procedures suitable for surrounding area.
- · DO NOT approach containers suspected to be hot.
- · Cool fire exposed containers with water spray from a protected location.
- · If safe to do so, remove containers from path of fire.
- · Equipment should be thoroughly decontaminated after use.

## FIRE/EXPLOSION HAZARD

- · Non combustible.
- · Not considered a significant fire risk, however containers may burn.

Decomposition may produce toxic fumes of: sulfur oxides (SOx) and metal oxides.

## FIRE INCOMPATIBILITY

Avoid reaction with oxidising agents.

## **Section 6 - ACCIDENTAL RELEASE MEASURES**

#### **EMERGENCY PROCEDURES**

#### **MINOR SPILLS**

- · Clean up all spills immediately.
- · Avoid contact with skin and eyes.
- · Wear protective clothing, gloves, safety glasses and dust respirator.
- · Use dry clean up procedures and avoid generating dust.
- · Sweep up or
- · Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- · Place in clean drum then flush area with water.

#### **MAJOR SPILLS**

- · Clear area of personnel and move upwind.
- · Alert Fire Brigade and tell them location and nature of hazard.
- · Control personal contact by using protective equipment and dust respirator.
- · Prevent spillage from entering drains, sewers or water courses.
- · Avoid generating dust.
- · Sweep, shovel up. Recover product wherever possible.
- · Put residues in labelled plastic bags or other containers for disposal.
- · If contamination of drains or waterways occurs, advise emergency services.

## **GHS Safety Data Sheet**

Version No:2.0

Page 4 of 9

## **Section 6 - ACCIDENTAL RELEASE MEASURES**

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS













+

May be stored together

+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

### Section 7 - HANDLING AND STORAGE

## PROCEDURE FOR HANDLING

Avoid generating and breathing dust.

- · Limit all unnecessary personal contact.
- · Wear protective clothing when risk of exposure occurs.
- · Use in a well-ventilated area.
- · Avoid contact with incompatible materials.
- · When handling, DO NOT eat, drink or smoke.
- · Keep containers securely sealed when not in use.
- · Avoid physical damage to containers.
- · Always wash hands with soap and water after handling.
- · Work clothes should be laundered separately.
- · Use good occupational work practice.
- · Observe manufacturer's storing and handling recommendations.
- · Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

## SUITABLE CONTAINER

Glass container.

Plastic container.

- · Metal can or drum
- Packaging as recommended by manufacturer.
- · Check all containers are clearly labelled and free from leaks.

#### STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

#### STORAGE REQUIREMENTS

- · Store in original containers.
- · Keep containers securely sealed.
- · No smoking, naked lights or ignition sources.
- · Store in a cool, dry, well-ventilated area.
- · Store away from incompatible materials and foodstuff containers.
- · Protect containers against physical damage and check regularly for leaks.
- · Observe manufacturer's storing and handling recommendations.

**GHS Safety Data Sheet** 

Version No:2.0

Page 5 of 9

### Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **EXPOSURE CONTROLS**

The following materials had no OELs on our records

gadolinium(III) sulfate:

CAS:13628- 54- 1 CAS:13450- 87- 8

#### **MATERIAL DATA**

as gadolinium

CEL TWA: 1 mg/m3 (compare TLV-TWA yttrium)

Exposure to the vapours of some rare earth salts reportedly produces sensitivity to heat, itching and an increased perception of odour and taste. Other effects may include bronchiolitis, subacute bronchitis, acute transient chemical pneumonitis, focal hypertrophic emphysema, regional bronchiolar stricturing and cellular eosinophilia. In rare fatal cases of exposure to the rare-earth fluoride and/or oxide mixtures, delayed chemical hyperaemia has occurred. Lung granulomas have also been seen in experimental animals.

## PERSONAL PROTECTION







## EYE

- · Safety glasses with side shields
- · Chemical goggles.
- · Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

### HANDS/FEET

Wear general protective gloves: i.e. Disposable polythene gloves or Cotton gloves or Light weight rubber gloves, with Barrier cream preferably Safety footwear.

#### **OTHER**

- Overalls.
- · Barrier cream
- · Eyewash unit.

GHS Safety Data Sheet Version No:2.0
Page 6 of 9

#### Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

#### RESPIRATOR

Protection Factor Half- Face Respirator Full- Face Respirator Powered Air Respirator

10 x ES P1 Air- line\* -- PAPR- P1 - 50 x ES Air- line\*\* P2 PAPR- P2

100 x ES - P3 Air- line\*

100+ x ES - Air- line\*\* PAPR- P3

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult

your

Occupational Health and Safety Advisor.

#### **ENGINEERING CONTROLS**

Use in a well-ventilated area.

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: Air Speed:

solvent, vapours, degreasing etc., evaporating 0.25- 0.5 m/s (50- 100 f/min)

from tank (in still air).

aerosols, fumes from pouring operations, one of the container filling, low speed 0.5- 1 m/s (100- 200 f/min.)

conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts,

gas distinct the control of the cont

rapid air motion)

grinding, abrasive blasting, tumbling, high 2.5- 10 m/s speed wheel generated dusts (released at high initial velocity into zone of very high rapid

air motion).

2.5- 10 m/s (500- 2000 f/min.)

1- 2.5 m/s (200- 500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range Upper end of the range

1: Room air currents minimal or favourable to 1: Disturbing room air currents

capture

2: Contaminants of low toxicity or of nuisance 2: Contaminants of high toxicity

value only.

3: Intermittent, low production. 3: High production, heavy use

4: Large hood or large air mass in motion 4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction

<sup>\* -</sup> Negative pressure demand \*\* - Continuous flow.

## **GHS Safety Data Sheet**

Version No:2.0

Page 7 of 9

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

#### APPEARANCE

White crystalline hygroscopic solid; mixes with water. Becomes less soluble with increasing temperature. Loses water of hydration at 400 deg C.

## **PHYSICAL PROPERTIES**

Solid.

Mixes with water.

Molecular Weight: 746.81 (.8H2O) Melting Range (°C): Not available Solubility in water (g/L): Miscible pH (1% solution): Not applicable

Volatile Component (%vol): Not applicable. Relative Vapour Density (air=1): Not applicable.

Lower Explosive Limit (%): Not available. Autoignition Temp (°C): Not available.

State: Divided solid

Boiling Range (°C): Not applicable. Specific Gravity (water=1): 3.01 pH (as supplied): Not applicable Vapour Pressure (kPa): Not applicable. Evaporation Rate: Not applicable

Flash Point (°C): Not applicable

Upper Explosive Limit (%): Not available.

Decomposition Temp (°C): 500

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

## CONDITIONS CONTRIBUTING TO INSTABILITY

- · Presence of incompatible materials.
- · Product is considered stable.
- · Hazardous polymerisation will not occur.

#### Section 11 - TOXICOLOGICAL INFORMATION

## POTENTIAL HEALTH EFFECTS

### **ACUTE HEALTH EFFECTS**

#### **SWALLOWED**

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for

## **GHS Safety Data Sheet**

Version No:2.0 Page 8 of 9

## Section 11 - TOXICOLOGICAL INFORMATION

concern.

Sulfate salts are poorly absorbed from the gastro-intestinal tract but because of osmotic activity are able to draw water from the lumen to produce diarrhoea (purging). Sulfate ion usually has little toxicological potential.

#### EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

#### SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

#### INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Not normally a hazard due to non-volatile nature of product.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

#### **CHRONIC HEALTH EFFECTS**

Principal routes of exposure are usually by skin contact and inhalation of generated dust.

Gadolinium is a member of the so-called heavy-group (the yttriums) of the rare earths (or lanthanides). No occupational diseases or cases of poisoning in workers producing rare earth elements have been described. Lanthanides because of their high density can produce significant and lesions typically have little or no clinical importance. Occasional cases of suspected pneumoconiosis have however been reported. The toxicity of all elements in the yttrium group has been investigated in workers and animals alike. Effects on peripheral blood including a decrease haemoglobin and erythrocyte content and changes in the leucocyte formula have been recorded. Animal lungs show productive inflammation and a tendency to develop nodular or diffuse sclerosis following administration by intratracheal injection. The main risks to workers involved in the production of rare earths are due to dust inhalation.

### **TOXICITY AND IRRITATION**

No significant acute toxicological data identified in literature search.

#### **Section 12 - ECOLOGICAL INFORMATION**

No data for gadolinium(III) sulfate.

# GHS Safety Data Sheet Version No:2.0

Page 9 of 9

#### **Section 13 - DISPOSAL CONSIDERATIONS**

- · Recycle wherever possible or consult manufacturer for recycling options.
- · Consult State Land Waste Management Authority for disposal.
- · Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill. For small quantities;
- Carefully make a 5% of the solution in water or dilute acid controlling any vigorous exotherm or fumes by rate of addition and cooling.
- · Gradually add dilute ammonium hydroxide to pH 10.
- If precipitation does not occur adjust to pH 6 stopping when precipitation occurs.
- · Filter and remove solids to land-fill (subject to local regulation).

## **Section 14 - TRANSPORTATION INFORMATION**

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

#### **Section 15 - REGULATORY INFORMATION**

### **REGULATIONS**

No regulations applicable

No data available for gadolinium(III) sulfate as CAS: 13628-54-1, CAS: 13450-87-8.

#### **Section 16 - OTHER INFORMATION**

#### **INGREDIENTS WITH MULTIPLE CAS NUMBERS**

Ingredient Name gadolinium(III) sulfate

CAS

13628- 54- 1, 13450- 87 - 8

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 12-May-2018