



ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 1 of 15

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

ISOPROPYL ACETATE

OTHER NAMES

C5-H10-O2, CH3-COOCH(CH3)2, "acetic acid, isopropyl ester", "acetic acid, 1-methylethyl ester", "acetic acid, 2-acetoxyp propane, "2-propyl acetate"

PROPER SHIPPING NAME

ISOPROPYL ACETATE

PRODUCT USE

Solvent for nitrocellulose, resin gums, paints, lacquers and printing inks; organic syntheses, perfumery.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 2 of 15

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Eye Irritation Category 2A
Flammable Liquid Category 2
Respiratory Effects Category 3
Skin Corrosion/Irritation Category 3



EMERGENCY OVERVIEW

HAZARD

DANGER
Determined by using GHS criteria:
H336 H225 H316 H319
May cause drowsiness and dizziness
Highly flammable liquid and vapour
Causes mild skin irritation
Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Use only non-sparking tools.
Take precautionary measures against static discharge
Wash hands thoroughly after handling.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment
Keep away from heat/sparks/open flame - No smoking.
Keep container tightly closed.
Wear protective gloves and eye/face protection.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
If eye irritation persists, get medical advice/attention.
Wear eye/face protection.
If skin irritation occurs, seek medical advice/attention.
If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower.
In case of fire, use alcohol-type foam for extinction.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Disposal

Dispose of contents and container in accordance with relevant legislation.

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 3 of 15

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
isopropyl acetate	108-21-4	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

for simple esters:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 4 of 15

Section 4 - FIRST AID MEASURES

- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Give activated charcoal.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- Consult a toxicologist as necessary.

BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- Fight fire from a safe distance, with adequate cover.
- If safe, switch off electrical equipment until vapour fire hazard removed.

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 5 of 15

Section 5 - FIRE FIGHTING MEASURES

- Use water delivered as a fine spray to control the fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat, flame and/or oxidisers.
- Vapour may travel a considerable distance to source of ignition.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).

Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Personal Protective Equipment

Gloves, boots (chemical resistant).

Breathing apparatus.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Wipe up.
- Collect residues in a flammable waste container.

MAJOR SPILLS

Chemical Class: ester and ethers

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
LAND SPILL - SMALL				
cross- linked polymer - particulate	1	shovel	shovel	R, W, SS
cross- linked polymer - pillow sorbent clay -	1	throw	pitchfork	R, DGC, RT
	2	shovel	shovel	R, I, P

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 6 of 15

Section 6 - ACCIDENTAL RELEASE MEASURES

particulate wood fiber -	3	shovel	shovel	R, W, P, DGC
particulate wood fiber -	3	throw	pitchfork	R, P, DGC, RT
pillow treated wood fiber -	3	throw	pitchfork	DGC, RT
pillow				

LAND SPILL - MEDIUM

cross- linked polymer -	1	blower	skiploader	R, W, SS
particulate cross- linked polymer -	2	throw	skiploader	R, DGC, RT
pillow sorbent clay -	3	blower	skiploader	R, I, P
particulate polypropylene -	3	blower	skiploader	W, SS, DGC
particulate expanded mineral -	4	blower	skiploader	R, I, W, P, DGC
particulate wood fiber -	4	blower	skiploader	R, W, P, DGC
particulate				

Legend

DGC: Not effective where ground cover is dense

R; Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT: Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse /absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- If contamination of drains or waterways occurs, advise emergency services.

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 7 of 15

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

isopropyl acetate 1800 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

isopropyl acetate 310 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

isopropyl acetate 310 ppm

The threshold concentration below which most people will experience no appreciable risk of health effects:

isopropyl acetate 250 ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ X X X X +

+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights, heat or ignition sources.
- When handling, DO NOT eat, drink or smoke.
- Vapour may ignite on pumping or pouring due to static electricity.

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 8 of 15

Section 7 - HANDLING AND STORAGE

- DO NOT use plastic buckets.
 - Earth and secure metal containers when dispensing or pouring product.
 - Use spark-free tools when handling.
 - Avoid contact with incompatible materials.
 - Keep containers securely sealed.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

Glass container.

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C)
- (i) : Removable head packaging;
- (ii) : Cans with friction closures and
- (iii) : low pressure tubes and cartridges may be used.
- Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages
- In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE INCOMPATIBILITY

- Esters react with acids to liberate heat along with alcohols and acids.
 - Strong oxidising acids may cause a vigorous reaction with esters that is sufficiently exothermic to ignite the reaction products.
 - Heat is also generated by the interaction of esters with caustic solutions.
 - Flammable hydrogen is generated by mixing esters with alkali metals and hydrides.
 - Esters may be incompatible with aliphatic amines and nitrates.
- Avoid reaction with oxidising agents.
- Avoid strong acids, bases.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.
- Store away from incompatible materials in a cool, dry well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 9 of 15

Section 7 - HANDLING AND STORAGE

Heat and moisture sensitive.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- isopropyl acetate: CAS:108- 21- 4

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
isopropyl acetate		1, 800

ODOUR SAFETY FACTOR (OSF)

OSF=74 (ISOPROPYL ACETATE)

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

MATERIAL DATA

Odour Threshold Value: 0.50-34 ppm (detection), 0.91-41 ppm (recognition)

The TLV-TWA is thought to be protective against ocular and upper respiratory tract irritation. It must be noted however that one study demonstrated that the majority of subjects exposed at 200 ppm for 15 minutes experienced eye irritation.

PERSONAL PROTECTION

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 10 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS	-
1000	50	-	A- AUS
5000	50	Airline *	-
5000	100	-	A- 2
10000	100	-	A- 3
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

continued...

ISOPROPYL ACETATE

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

solvent, vapours, degreasing etc., evaporating from tank (in still air).

aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)

Air Speed:

0.25- 0.5 m/s (50- 100 f/min.)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear colourless liquid with aromatic odour; mixes with water (1:23),

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 12 of 15

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

alcohol, ether.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

Molecular Weight: 102.13

Melting Range (°C): - 73

Solubility in water (g/L): Miscible

pH (1% solution): Not applicable

Volatile Component (%vol): 100

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): 1.78

Autoignition Temp (°C): 460

State: Liquid

Boiling Range (°C): 89

Specific Gravity (water=1): 0.868

pH (as supplied): Not applicable

Vapour Pressure (kPa): 5.8 @ 20 C

Evaporation Rate: Fast

Flash Point (°C): 5.56

Upper Explosive Limit (%): 7.8

Decomposition Temp (°C): Not Available

Viscosity: Not Available

log Kow (Sangster 1997): 1.02

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result.
(ICSC13733).

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals. Repeated or prolonged eye contact may cause inflammation (similar to windburn) characterised by a temporary redness of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

continued...

ISOPROPYL ACETATE

Section 11 - TOXICOLOGICAL INFORMATION

SKIN

The material may produce mild skin irritation; limited evidence or practical experience suggests, that the material either:

- produces mild inflammation of the skin in a substantial number of individuals following direct contact, and/or
- produces significant, but mild, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.

Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (non allergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Inhalation hazard is increased at higher temperatures.

The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.

The main effects of simple aliphatic esters are narcosis and irritation and anaesthesia at higher concentrations. These effects become greater as the molecular weights and boiling points increase. Central nervous system depression, headache, drowsiness, dizziness, coma and neurobehavioral changes may also be symptomatic of overexposure. Respiratory tract involvement may produce mucous membrane irritation, dyspnea, and tachypnea, pharyngitis, bronchitis, pneumonitis and, in massive exposures, pulmonary oedema (which may be delayed). Gastrointestinal effects include nausea, vomiting, diarrhoea and abdominal cramps. Liver and kidney damage may result from massive exposures.

CHRONIC HEALTH EFFECTS

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

TOXICITY AND IRRITATION

TOXICITY

Inhalation (rat) LC50: 50600 mg/m³/8h

IRRITATION

Eye (human): 200 ppm/15m

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Section 11 - TOXICOLOGICAL INFORMATION

Oral (rabbit) LD50: 6946 mg/kg
Dermal (rabbit) LD50: >20000 mg/kg

Skin (rabbit): 500 mg/24h - Mild
Eye (rabbit): 500 mg Open
Eye (rabbit): 500 mg/24h - Mild

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

Section 12 - ECOLOGICAL INFORMATION

BOD5:	26%
Algae IC50 (72hr.) (mg/l):	165- 1400
log Kow (Sangster 1997):	1.02
BOD5:	12%
BOD20:	40%

DO NOT discharge into sewer or waterways.

Koc: 14.8

Half-life (hr) air: 100.8-124.8

Half-life (hr) H2O surface water: 6.1

Henry's atm m³ /mol: 2.81E-04

BOD 5 if unstated: 0.26,12.7%

BCF: 1.8

Toxicity Fish: LD50(24)>5000mg/L

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID
HAZCHEM: 3[Y]E

continued...

ISOPROPYL ACETATE

GHS Safety Data Sheet

Version No:4

Page 15 of 15

Section 14 - TRANSPORTATION INFORMATION

UNDG:

Dangerous Goods Class: 3
UN Number: 1220
Shipping Name: ISOPROPYL ACETATE

Subrisk: None
Packing Group: II

Air Transport IATA:

ICAO/IATA Class: 3
UN/ID Number: 1220
ERG Code: 3L
Shipping name: ISOPROPYL ACETATE

ICAO/IATA Subrisk: None
Packing Group: II

Maritime Transport IMDG:

IMDG Class: 3
UN Number: 1220
EMS Number: F- E, S- D
Shipping name: ISOPROPYL ACETATE

IMDG Subrisk: None
Packing Group: II

Section 15 - REGULATORY INFORMATION

REGULATIONS

isopropyl acetate (CAS: 108-21-4) is found on the following regulatory lists;
IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 8-Jul-2018