

THIOUREA

GHS Safety Data Sheet

Version No:3

Page 1 of 14

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

THIOUREA

OTHER NAMES

C-H4-N2-S, CS(NH2)2, 2-thiourea, thiocarbamide, isothiurea, pseudothiurea, sulourea, "thiocarbonic acid diamide", thiomocovina.

PROPER SHIPPING NAME

TOXIC SOLID, ORGANIC, N.O.S.

PRODUCT USE

Chemically reactive with various sulfhydryl oxidising agents and forms complexes and adducts with metallic salts and many organic compounds including proteins and certain hydrocarbons.

Used in the chemical, rubber, and petroleum industries, as a therapeutic agent, for photosensitive paper manufacture, as a flame retardant, as a dye intermediate, as a chelating agent in boiler water.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Oral) Category 3

continued...

THIOUREA

GHS Safety Data Sheet

Version No:3

Page 2 of 14

Section 2 - HAZARDS IDENTIFICATION

Carcinogen Category 2
Chronic Aquatic Hazard Category 2
Reproductive Toxicity Category 2
Skin Sensitizer Category 1



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:

H301 H317 H351 H361 H411

Toxic if swallowed

May cause allergic skin reaction

Suspected of causing cancer

Suspected of damaging the unborn child

Toxic to aquatic life with long lasting effects

PRECAUTIONARY STATEMENTS

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated clothing should not be allowed out of the workplace.

Use personal protective equipment as required.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Response

If exposed or concerned: Get medical attention advice.

If skin irritation or rash occurs, seek medical advice/attention.

Wash contaminated clothing before reuse.

Specific treatment: refer to Label or MSDS.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN: Gently wash with plenty of soap and water.

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
thiourea	62-56-6	>99

continued...

THIOUREA

Section 4 - FIRST AID MEASURES

SWALLOWED

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
 - For advice, contact a Poisons Information Centre or a doctor.
 - Urgent hospital treatment is likely to be needed.
 - In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
 - If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist.
 - If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.
 - Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
 - INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- NOTE: Wear a protective glove when inducing vomiting by mechanical means.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.
For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.

continued...

THIOUREA

Section 4 - FIRST AID MEASURES

- Anticipate seizures .
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Combustible solid which burns but propagates flame with difficulty.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.
- Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.
- Build-up of electrostatic charge may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.
- All movable parts coming in contact with this material should have a speed of less than 1-meter/sec.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), nitrogen oxides (NO_x), sulfur oxides (SO_x), hydrogen sulfide (H₂S), other pyrolysis products

THIOUREA

GHS Safety Data Sheet

Version No:3

Page 5 of 14

Section 5 - FIRE FIGHTING MEASURES

typical of burning organic material.
May emit poisonous fumes.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up waste regularly and abnormal spills immediately.
- Avoid breathing dust and contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- Use dry clean up procedures and avoid generating dust.
- Vacuum up or sweep up. NOTE: Vacuum cleaner must be fitted with an exhaust micro filter (HEPA type) (consider explosion-proof machines designed to be grounded during storage and use).
- Dampen with water to prevent dusting before sweeping.
- Place in suitable containers for disposal.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by all means available, spillage from entering drains or water courses.
- Consider evacuation (or protect in place).
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Contain or absorb spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

thiourea 125 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

thiourea 25 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

thiourea 10 mg/m³

continued...

THIOUREA

Section 6 - ACCIDENTAL RELEASE MEASURES

The threshold concentration below which most people will experience no appreciable risk of health effects:
thiourea 10 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Glass container.
- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Contact with acids produces toxic fumes.
- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

THIOUREA


GHS Safety Data Sheet

Version No:3

Page 7 of 14

Section 7 - HANDLING AND STORAGE

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

• thiourea:

CAS:62- 56- 6

MATERIAL DATA

OEL STEL (Russia): 0.3 mg/m³

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

NOTE: The material may produce skin sensitisation in predisposed individuals. Care must

continued...

THIOUREA

GHS Safety Data Sheet

Version No:3

Page 8 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

OTHER

- Overalls.
- Eyewash unit.
- Barrier cream.
- Skin cleansing cream.

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer-generated selection: thiourea

PE/EVAL/PE

A

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
 - (a): particle dust respirators, if necessary, combined with an absorption cartridge;
 - (b): filter respirators with absorption cartridge or canister of the right type;
 - (c): fresh-air hoods or masks
- Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.

Type of Contaminant:
direct spray, spray painting in shallow booths,

Air Speed:
1- 2.5 m/s (200- 500 f/min.)

continued...

THIOUREA

GHS Safety Data Sheet

Version No:3

Page 9 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Practically colourless crystals or needles. Strong sulfur smell.
Soluble in water, alcohol, and sparingly soluble in ether.
Sublimes in vacuum at 150-160 C.
A harmful substance Classified Xn, which is also shipped by laboratory chemical suppliers as UN 3077 Environmentally Hazardous Substance, N.O.S.
Class 9, Packing Group III, Hazchem = "Contain"
OR deregulated from the provisions of the ADG Code E.G. Orica THIOUREA.

PHYSICAL PROPERTIES

Mixes with water.

Molecular Weight: 76.12
Melting Range (°C): 182
Solubility in water (g/L): Miscible
pH (1% solution): Not available
Volatile Component (%vol): Nil @ 38C.
Relative Vapour Density (air=1): Not applicable.
Lower Explosive Limit (%): Not applicable.
Autoignition Temp (°C): Not applicable.
State: DIVIDED SOLID

Boiling Range (°C): Not applicable.
Specific Gravity (water=1): 1.41 @ 20
pH (as supplied): Not applicable
Vapour Pressure (kPa): Negligible
Evaporation Rate: Non Volatile
Flash Point (°C): > 182
Upper Explosive Limit (%): Not applicable.
Decomposition Temp (°C): Not Available
Viscosity: Not Applicable

log Kow (Prager 1995): - 1.02

continued...

THIOUREA

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual.

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. The material may produce foreign body irritation in certain individuals.

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Abrasive damage however, may result from prolonged exposures. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Skin sensitivity to thiourea derivatives has been demonstrated in several studies. Allergic contact dermatitis and photocontact dermatitis have been described. A Russian study published in 1970 reported that workers handling thiourea products showed ready penetration through the skin which lead to clinical evidence of destructive changes in the thyroid gland.

INHALED

Inhalation may produce health damage*.

Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.

The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of dusts, or fumes, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

CHRONIC HEALTH EFFECTS

On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory

continued...

THIOUREA

Section 11 - TOXICOLOGICAL INFORMATION

assessment.

Long term exposure to high dust concentrations may cause changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron penetrating and remaining in the lung. A prime symptom is breathlessness. Lung shadows show on X-ray.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

There exists limited evidence that shows that skin contact with the material is capable either of inducing a sensitisation reaction in a significant number of individuals, and/or of producing positive response in experimental animals.

On the basis, primarily, of animal experiments, the material may be regarded as carcinogenic to humans. There is sufficient evidence to provide a strong presumption that human exposure to the material may result in cancer on the basis of:

- appropriate long-term animal studies
- other relevant information.

Sensitisation may result in allergic dermatitis responses including rash, itching, hives or swelling of extremities.

The mechanism by which thioureas exert the antithyroid effect involves the inhibition of iodine uptake and activation by the thyroid. At low doses, a physiological and biological compensation mechanism maintains normal levels of circulating thyroid hormone. Prolonged exposure to high doses of thyroid inhibitors causes severe hypertrophy and hyperplasia resulting in reduced levels of circulating thyroid hormone. Positive mutagenic effects have been elicited by the use of several thiourea derivatives in various assays.

Teratogenic responses have been recorded with alkylated thioureas and ethylene thiourea in various species.

The material is a sensitizer in persons who exhibit photosensitivity.

Chronic exposure may result in damage to the blood, liver and thyroid.

Thiourea inhibits utilisation of iodine and has a haemolytic effect (impedes blood clotting).

Thiourea has produced goiter and bone marrow depression (anaemia, leukopenia, thrombocytopenia and agranulocytosis) in experimental animals.

When administered in the drinking water, thiourea induced thyroid adenomas and carcinomas in rats of both sexes and squamous cell carcinomas of the Zymbal gland in male rats. When administered in the diet, thiourea induced hepatocellular adenomas in rats.

TOXICITY AND IRRITATION

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (woman) TDLo: 1660 mg/kg/5W

Oral (rat) LD50: 125 mg/kg

Intraperitoneal (rat) LD50: 436 mg/kg

Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen [National Toxicology Program: U.S. Dep. of Health & Human Services 2002].

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Product:

Oral (rat) >5000 mg/kg

Dermal (rabbit) >2800 mg/kg [Orica]

Respiratory tract changes, multiple lung effects, haemorrhage, granulocytopenia, specific developmental abnormalities involving central nervous system, musculoskeletal system, endocrine system recorded.

IRRITATION

Eye (rabbit): 14%

THIOUREA

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant: Not Determined

Fish LC50 (96hr.) (mg/l):	100
Daphnia magna EC50 (48hr.) (mg/l):	1.8
BCF<100:	1
Water solubility (g/l):	9
log Kow (Prager 1995):	- 1.02
log Pow (Verschueren 1983):	2.50526315
BOD5:	0.013
COD:	0.84

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

Environmental Impact:

Aquatic organisms- LC50: 1.8 mg/L (Daphnia magna)

LC50: >100 mg/L (Pimephales promelas)

[ORICA]

BOD 5 if unstated: 0.013

COD: 0.84

Nitrif. inhib.: 50% inhib at 0.9mg/L

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 - Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)
 - Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
 - Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

WASTE DISPOSAL PROCEDURES

- Collect and package recoverable quantities of thiourea in a labelled container for incineration. For small quantities follow the spillage disposal procedure [Armour 1996].

SPILLAGE DISPOSAL

- Wear nitrile rubber gloves, protective clothing and goggles to control personal contact from thiourea. Work in a well ventilated area. Wash the area of the spill thoroughly with water and detergent. Add enough water to dissolve the

THIOUREA

GHS Safety Data Sheet

Version No:3

Page 13 of 14

Section 13 - DISPOSAL CONSIDERATIONS

solid. Add 100mL of household bleach (5% sodium hypochlorite solution) for each 1g of thiourea. Allow to stand overnight. Empty the liquid into the drain with water [Armour 1996].

Section 14 - TRANSPORTATION INFORMATION



Labels Required: TOXIC
HAZCHEM: 2X

UNDG:

Dangerous Goods Class:	6.1	Subrisk:	None
UN Number:	2811	Packing Group:	III
Shipping Name: TOXIC SOLID, ORGANIC, N.O.S.			

Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	None
UN/ID Number:	2811	Packing Group:	III
Special provisions:	A3áA5		
Shipping Name: TOXIC SOLID, ORGANIC N.O.S.			

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	None
UN Number:	2811	Packing Group:	III
EMS Number:	F- A, S- A	Special provisions:	223 274 944
Marine Pollutant:	Not Determined		
Shipping Name: TOXIC SOLID, ORGANIC, N.O.S.			

Section 15 - REGULATORY INFORMATION

REGULATIONS

thiourea (CAS: 62-56-6) is found on the following regulatory lists;
International Agency for Research on Cancer (IARC) Carcinogens
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied

continued...

THIOUREA

GHS Safety Data Sheet

Version No:3

Page 14 of 14

Section 16 - OTHER INFORMATION

of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 16-Aug-2017