

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet

Version No:3

Page 1 of 12

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

TRI-N-BUTYL PHOSPHATE

OTHER NAMES

C₁₂H₂₇PO₄, (C₄H₉)₃PO₄, TBP, "tri-n-butyl phosphate", "tri-n-butyl phosphate", "tri butyl phosphate", "trialkyl phosphate", "phosphoric acid tributyl ester"

PRODUCT USE

Plasticizer for cellulose esters, lacquers, plastic and vinyl resins.
In the manufacture of surface coatings and adhesives; in latex exterior paints and pigmented coatings. Solvent in extraction of metals.
Heat exchange medium, aircraft hydraulic fluid and pigment grinding agent.
Antifoaming agent.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,
248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Aquatic Hazard Category 2

Acute Toxicity (Oral) Category 4

Carcinogen Category 2

Eye Irritation Category 2B

Skin Corrosion/Irritation Category 2

continued...

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet

Version No:3

Page 2 of 12

Section 2 - HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW

HAZARD

WARNING

Determined by using GHS criteria:

H302 H315 H320 H351 H401

Harmful if swallowed

Causes skin irritation

Causes eye irritation

Suspected of causing cancer

Toxic to aquatic life

PRECAUTIONARY STATEMENTS

Prevention

Do not handle until all safety precautions have been read and understood.

Wash hands thoroughly after handling.

Wash thoroughly after handling.

Obtain special instructions before use.

Use personal protective equipment as required.

Do not eat, drink or smoke when using this product.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If exposed or concerned: Get medical attention advice.

If eye irritation persists, get medical advice/attention.

If skin irritation occurs, seek medical advice/attention.

Remove/Take off immediately all contaminated clothing

Specific treatment: refer to Label or MSDS.

IF ON SKIN: Gently wash with plenty of soap and water.

Wash/Decontaminate removed clothing before reuse.

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
tributyl phosphate	126-73-8	>99

continued...

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet

Version No:3

Page 3 of 12

Section 4 - FIRST AID MEASURES

SWALLOWED

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
 - For advice, contact a Poisons Information Centre or a doctor.
 - Urgent hospital treatment is likely to be needed.
 - In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
 - If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist.
 - If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.
 - Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
 - INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- NOTE: Wear a protective glove when inducing vomiting by mechanical means.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - If pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

All persons handling organic phosphorus ester materials regularly should undergo regular medical examination with special stress on the central nervous systems. Whilst atropine or pyridine-2-aldoxime methiodide (PAM) are beneficial antidotes for acute phosphate ester poisonings, they are of little value in reversing acute or chronic neurological damage due to phosphites and some types of aryl phosphate.

Rats given a single oral dose of labeled tributyl phosphate excreted 50, 10 and 6% of the dose in urine, exhaled air and faeces, respectively, within 24 hours. The substance appeared in all tissues within 30 minutes. Step-wise debutylation, through hydroxylated intermediates, gives rise to dibutyl hydrogen phosphate and butyl dihydrogen phosphate.

continued...

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet

Version No:3

Page 4 of 12

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), phosphorus oxides (PO_x), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Personal Protective Equipment

Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.

continued...

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet

Version No:3

Page 5 of 12

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

tributyl phosphate 30 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

tributyl phosphate 1 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

tributyl phosphate 0.6 ppm

The threshold concentration below which most people will experience no appreciable risk of health effects:

tributyl phosphate 0.46 ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - Prevent concentration in hollows and sumps.
 - DO NOT enter confined spaces until atmosphere has been checked.
 - Avoid smoking, naked lights or ignition sources.
 - Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 - Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

continued...

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet

Version No:3

Page 6 of 12

Section 7 - HANDLING AND STORAGE

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- tributyl phosphate: CAS:126- 73- 8

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
tributyl phosphate		30

MATERIAL DATA

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

continued...

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet


Version No:3

Page 7 of 12

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

An irritant of eyes, skin and mucous membranes in experimental animals, weak cholinesterase inhibitor with narcotic properties. The recommended value for TLV-TWA is identical to that of triphenyl phosphate measured as ppm. Exposure at or below this limit is thought to protect workers against the significant risk of anaesthetic effects and skin and eye irritation.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS	-
1000	50	-	A- AUS
5000	50	Airline *	-
5000	100	-	A- 2
10000	100	-	A- 3

continued...

TRI-N-BUTYL PHOSPHATE

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

100+

Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

solvent, vapours, degreasing etc., evaporating from tank (in still air).

aerosols, fumes from pouring operations,

intermittent container filling, low speed

conveyer transfers, welding, spray drift,

plating acid fumes, pickling (released at low velocity into zone of active generation)

direct spray, spray painting in shallow booths,

drum filling, conveyer loading, crusher dusts,

gas discharge (active generation into zone of rapid air motion)

grinding, abrasive blasting, tumbling, high

speed wheel generated dusts (released at high

initial velocity into zone of very high rapid air motion).

Air Speed:

0.25- 0.5 m/s (50- 100 f/min.)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only.

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

continued...

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet

Version No:3

Page 9 of 12

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless to pale liquid. Odourless. Slightly soluble in water (1g/l).
Soluble in alcohol, ether and benzene.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Floats on water.

Molecular Weight: 266.32

Melting Range (°C): - 80

Solubility in water (g/L): Immiscible

pH (1% solution): Not applicable

Volatile Component (%vol): Not available.

Relative Vapour Density (air=1): 9.2

Lower Explosive Limit (%): Not available.

Autoignition Temp (°C): >482

State: Liquid

Boiling Range (°C): 289

Specific Gravity (water=1): 0.98

pH (as supplied): Not applicable

Vapour Pressure (kPa): 1.83

Evaporation Rate: Not available

Flash Point (°C): 146

Upper Explosive Limit (%): Not available.

Decomposition Temp (°C): Not available

Viscosity: Not Available

log Kow: 2.5-4.0

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Ingestion may produce nausea, vomiting, anorexia, abdominal cramps, and diarrhoea.

Generalised symptoms produced by cholinesterase inhibitors may ensue following appreciable absorption.

Adverse effects associated with the administration of central nervous system stimulants include dyspnea, coughing, bronchospasm, and laryngospasm. Muscular involvement may produce symptoms ranging from fasciculation to spasticity or seizures. Headache, dizziness and confusion may also result as can hyperpyrexia or a sensation of warmth.

Other symptoms may include nausea, vomiting, diarrhoea and difficulty in urination.

Cardiovascular involvement may produce alterations in blood pressure or arrhythmia.

EYE

Evidence exists, or practical experience predicts, that the material may cause severe eye irritation in a substantial number of individuals and/or may produce significant ocular

continued...

TRI-N-BUTYL PHOSPHATE

Section 11 - TOXICOLOGICAL INFORMATION

lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Eye contact may cause significant inflammation with pain. Corneal injury may occur; permanent impairment of vision may result unless treatment is prompt and adequate. Repeated or prolonged exposure to irritants may cause inflammation characterised by a temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

Direct contact with the eyes may produce lachrymation (tears), twitching of the eyelids, miosis (contraction of the pupils) and ciliary muscle spasm mydriasis (dilation of the pupils). Absorption may produce generalised cholinesterase inhibition.

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

The material may accentuate any pre-existing dermatitis condition.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Localised sweating and fasciculation (small localised muscular contractions visible through the skin) may occur at sites of contact. Absorption may produce cholinesterase inhibition effects following delays of up to 2-3 hours (but generally not more than 12 hours).

INHALED

Inhalation may produce health damage*.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Inhalation hazard is increased at higher temperatures.

The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

The early warnings of poisonings associated with cholinesterase inhibition include nasal hyperaemia (localised engorgement with blood), watery discharge, chest discomfort, dyspnoea and wheezing due to increased bronchial secretions and bronchoconstriction. Other effects may include tearing, urination, chest pains, breathing difficulties, low blood pressure, irregular heartbeat, loss of reflexes, twitching, visual disturbances, dilated or pin-point pupils, convulsion, lung congestion, coma and heart-include ataxia, slurred speech, tremors of the tongue and eyelids, and eventual paralysis of the extremities and respiratory muscles. Fatalities in man are generally due to respiratory failure on the basis of central nervous system paralysis although cardiac arrest may also occur. Where cholinesterase inhibitors have been used as miotic eyedrops there has occasional evidence of toxic effects on the crystalline lens and obstruction of the nasolachrymal canals.

CHRONIC HEALTH EFFECTS

On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet

Version No:3

Page 11 of 12

Section 11 - TOXICOLOGICAL INFORMATION

assessment.

Repeated oral administration to rats produced pathological changes in the bladder epithelium.

TOXICITY AND IRRITATION

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Intraperitoneal (Rat) LD50: 251 mg/kg

Intravenous (Rat) LD: 100 mg/kg

Oral (Mouse) LD50: 1189 mg/kg [CCINFO]*

Inhalation (Mouse) LC50: 1300 mg/m³/4h

Intraperitoneal (Mouse) LD50: 159 mg/kg

Subcutaneous (Mouse) LD50: 764 mg/kg

The material may produce severe irritation to the eye causing pronounced inflammation.

Repeated or prolonged exposure to irritants may produce conjunctivitis.

IRRITATION

Skin (rabbit): 10 mg/24h - SEVERE

Eye (rabbit): 97 mg

Section 12 - ECOLOGICAL INFORMATION

Fish LC50 (96hr.) (mg/l): 5.0- 9.0

The principal problems of phosphate contamination of the environment relates to eutrophication processes in lakes and ponds. Phosphorus is an essential plant nutrient and is usually the limiting nutrient for blue-green algae. A lake undergoing eutrophication shows a rapid growth of algae in surface waters. Planktonic algae cause turbidity and flotation films. Shore algae cause ugly muddying, films and damage to reeds. Decay of these algae causes oxygen depletion in the deep water and shallow water near the shore. The process is self-perpetuating because anoxic conditions at the sediment/water interface causes the release of more adsorbed phosphates from the sediment. The growth of algae produces undesirable effects on the treatment of water for drinking purposes, on fisheries, and on the use of lakes for recreational purposes. Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

log Kow: 2.5-4.0

Toxicity Fish: TLm(?)20-40mg/L

Bioaccumulation: not sig

Nitrif. inhib.: nil at 100mg/L

Degradation Biological: little

processes Abiotic: nohydrol&photol,RxnOH*

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.
- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and MSDS and observe all notices

continued...

TRI-N-BUTYL PHOSPHATE

GHS Safety Data Sheet

Version No:3

Page 12 of 12

Section 13 - DISPOSAL CONSIDERATIONS

pertaining to the product.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,
IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

tributyl phosphate (CAS: 126-73-8) is found on the following regulatory lists;
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk
OECD Representative List of High Production Volume (HPV) Chemicals

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 9-Oct-2017