



HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

HYFLOSUPERCEL

OTHER NAMES

"diatomaceous earth absorbent", "BDH celite", "uncalcined diatomaceous earth silica - amorphous", diatomite, Silocel, Silocell, "Silosell (misspelling)"

PRODUCT USE

Used in filtration; as oil and grease absorbent; refractory back-up insulation.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



SCALE: Min/Nil=0 Low=1 Moderate=2 High=3 Extreme=4

Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HAZARD

Not hazardous

No hazards determined by using GHS criteria

continued...

HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

PRECAUTIONARY STATEMENTS

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
silica amorphous, diatomaceous earth	61790-53-2	100

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

continued...

HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 3 of 10

Section 5 - FIRE FIGHTING MEASURES

FIRE/EXPLOSION HAZARD

- Non combustible.
 - Not considered a significant fire risk, however containers may burn.
- Decomposition may produce toxic fumes of: silicon dioxide (SiO₂).

FIRE INCOMPATIBILITY

None known.

Personal Protective Equipment

Breathing apparatus.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety glasses.
- Use dry clean up procedures and avoid generating dust.
- Sweep up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment and dust respirator.
- Prevent spillage from entering drains, sewers or water courses.
- Avoid generating dust.
- Sweep, shovel up. Recover product wherever possible.
- Put residues in labelled plastic bags or other containers for disposal.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific preventions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

continued...

HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 4 of 10

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid contamination of water, foodstuffs, feed or seed.

Metals and their oxides or salts may react violently with chlorine trifluoride. Chlorine trifluoride is a hypergolic oxidiser. It ignites on contact (without external source of heat or ignition) with recognised fuels - contact with these materials, following an ambient or slightly elevated temperature, is often violent and may produce ignition. The state of subdivision may affect the results.

Avoid storage with magnesium and hydrofluoric acid.

Reacts with hydrofluoric acid to produce silicon tetrafluoride gas.

Reacts with xenon hexafluoride to produce explosive xenon trioxide.

In the presence of water and heat, forms an explosive mixture with magnesium.

Reacts exothermically with oxygen difluoride, and explosively with chlorine trifluoride.

These halogenated materials are not commonplace industrial materials.

Heating with alkali carbonates can produce a vigorous reaction

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

continued...

HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 5 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- silica amorphous, diatomaceous earth:

CAS:61790- 53- 2 CAS:57126- 63- 3 CAS:11139- 66- 5
CAS:12623- 98- 2 CAS:12750- 99- 1 CAS:29847- 98- 1
CAS:37264- 95- 2 CAS:37328- 66- 8 CAS:77108- 41- 9
CAS:37337- 67- 0 CAS:39421- 62- 0 CAS:50814- 24- 9
CAS:55839- 10- 6 CAS:192230- 56- 1
CAS:73158- 38- 0 CAS:68368- 75- 2 CAS:56748- 40- 4
CAS:57692- 84- 9 CAS:61970- 41- 0 CAS:81988- 94- 5
CAS:64060- 29- 3 CAS:67016- 73- 3
CAS:67417- 47- 4 CAS:39455- 02- 2 CAS:54990- 61- 3
CAS:54990- 62- 4 CAS:51109- 72- 9
CAS:53571- 43- 0 CAS:54511- 18- 1

MATERIAL DATA

Amorphous crystalline silica shows little potential for producing adverse effects on the lung and exposure standards should reflect intrinsic toxicity. Mixtures of diatomaceous earth and crystalline silica are treated in a different manner.

a particulate of low

PERSONAL PROTECTION



EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids.

- polychloroprene

continued...

HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 6 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- nitrile rubber
- butyl rubber
- fluorocautchouc
- polyvinyl chloride

Gloves should be examined for wear and/ or degradation constantly.

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity,
- are important in the selection of gloves.

OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

· Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.

· If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered.

Such protection might consist of:

- (a): particle dust respirators, if necessary, combined with an absorption cartridge;
- (b): filter respirators with absorption cartridge or canister of the right type;
- (c): fresh-air hoods or masks.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

direct spray, spray painting in shallow booths,
drum filling, conveyer loading, crusher dusts,
gas discharge (active generation into zone of
rapid air motion)
grinding, abrasive blasting, tumbling, high

Air Speed:

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

continued...

HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 7 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only.
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Grey/cream pebble-like solid or powder; insoluble in water.

The material is composed of skeletons of microscopic, prehistoric aquatic plants called diatoms. Its bulk density is only 0.15 to 0.45 g/cc due to large volume of void space within each diatom.

PHYSICAL PROPERTIES

Solid.

Does not mix with water.

Sinks in water.

Molecular Weight: Not applicable.

Melting Range (°C): Not available.

Solubility in water (g/L): Immiscible

pH (1% solution): Not applicable.

Volatile Component (%vol): Nil.

Relative Vapour Density (air=1): Not applicable.

Lower Explosive Limit (%): Not applicable

Autoignition Temp (°C): Not applicable

State: Divided solid

Boiling Range (°C): Not available.

Specific Gravity (water=1): 1.6- 2.0

pH (as supplied): Not applicable

Vapour Pressure (kPa): Not applicable.

Evaporation Rate: Non Volatile

Flash Point (°C): Not applicable

Upper Explosive Limit (%): Not applicable

Decomposition Temp (°C): Not available.

Viscosity: Not Applicable

continued...

HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 8 of 10

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

Presence of incompatible materials.

Product is considered stable and hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result. The material may produce foreign body irritation in certain individuals.

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation, of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Effects on lungs are significantly enhanced in the presence of respirable particles. Overexposure to respirable dust may produce wheezing, coughing and breathing difficulties leading to or symptomatic of impaired respiratory function.

CHRONIC HEALTH EFFECTS

Long term exposure to high dust concentrations may cause changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron penetrating and remaining in the lung. A prime symptom is breathlessness. Lung shadows show on X-ray.

continued...

HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 9 of 10

Section 11 - TOXICOLOGICAL INFORMATION

Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

The synthetic, amorphous silicas are believed to represent a very greatly reduced silicosis hazard compared to crystalline silicas.

Inhalation of dusts containing crystalline silicas may lead to silicosis, a disabling pulmonary fibrosis that takes many years to develop.

When heated to high temperature, amorphous silica can produce crystalline silica on cooling. Treat as a nuisance dust.

Discrepancies between various studies showing that fibrosis associated with chronic exposure to amorphous silica and those that do not may be explained by assuming that diatomaceous earth is either weakly fibrogenic or nonfibrogenic and that fibrosis is due to contamination by crystalline silica content.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

No data for silica amorphous, diatomaceous earth.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Management Authority for disposal.
- Bury residue in an authorised landfill.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

silica amorphous, diatomaceous earth (CAS: 61790-53-2) is found on the following regulatory lists;

OECD Representative List of High Production Volume (HPV) Chemicals

No data available for silica amorphous, diatomaceous earth as CAS: 57126-63-3, CAS: 11139-66-5, CAS: 12623-98-2, CAS: 12750-99-1, CAS: 29847-98-1, CAS: 37264-95-2, CAS: 37328-66-8, CAS: 77108-41-9, CAS: 37337-67-0, CAS: 39421-62-0, CAS: 50814-24-9, CAS: 55839-10-6,

continued...

HYFLOSUPERCEL

GHS Safety Data Sheet

Version No:2.0

Page 10 of 10

Section 15 - REGULATORY INFORMATION

CAS: 192230-56-1, CAS: 73158-38-0, CAS: 68368-75-2, CAS: 56748-40-4, CAS: 57692-84-9, CAS: 61970-41-0, CAS: 81988-94-5, CAS: 64060-29-3, CAS: 67016-73-3, CAS: 67417-47-4, CAS: 39455-02-2, CAS: 54990-61-3, CAS: 54990-62-4, CAS: 51109-72-9, CAS: 53571-43-0, CAS: 54511-18-1.

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
silica amorphous, diatomaceous earth	61790- 53 - 2, 57126- 63- 3, 11139- 66- 5, 12623- 98- 2, 12750- 99- 1, 29847- 98- 1, 37264- 95- 2, 37328 - 66- 8, 77108- 41- 9, 37337- 67- 0, 39421- 62- 0, 50814- 24- 9, 55839- 10- 6, 192230- 56- 1, 73158- 38- 0, 68368- 75- 2, 56748- 40- 4, 57692- 84- 9, 61970- 41- 0, 81988- 94- 5, 64060- 29- 3, 67016- 73- 3, 67417- 47- 4, 39455- 02- 2, 54990- 61- 3, 54990- 62- 4, 51109- 72- 9, 53571- 43- 0, 54511- 18- 1

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 30-Mar-2018