

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1
Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

GIEMSA'S STAINING SOLUTION

OTHER NAMES

"microscopy stain"

PROPER SHIPPING NAME

FLAMMABLE LIQUID, TOXIC, N.O.S.(contains methanol)

PRODUCT USE

■ Used according to manufacturer's directions.

Used in hospital and pathology hematology laboratories, usually for staining blood films only.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V.Ind.Estate,

248, Worli Road,

Mumbai- 400030, India

www.sdfine.com

Telephone: 91- 22 24959898/99

Fax: 91- 22 2493 7232

Email: technical@sdfine.com

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity Category 3

Acute Toxicity Category 2

Acute Toxicity Category 3

Aspiration Hazard Category 1

Eye Irritation Category 2A

Flammable Liquid Category 2

Skin Corrosion/Irritation Category 2

STOT - SE Category 3

STOT - SE Category 1



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria

H225

Highly flammable liquid and vapour.

H301

Toxic if swallowed.

continued...

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1

Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H370	Causes damage to organs.

PRECAUTIONARY STATEMENTS

Prevention

Code	Phrase
P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion- proof electrical/ventilating/lighting/ ... /equipment
P242	Use only non- sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well- ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.

Response

Code	Phrase
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+P311	IF exposed: Call a POISON CENTER or doctor/physician.
P310	Immediately call a POISON CENTER or doctor/physician.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P320	Specific treatment is urgent (see MSDS).
P330	Rinse mouth.
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P361	Remove/Take off immediately all contaminated clothing.
P362	Take off contaminated clothing and wash before re- use.
P363	Wash contaminated clothing before reuse.

Storage

Code	Phrase
P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P403+P235	Store in a well- ventilated place. Keep cool.
P405	Store locked up.

Disposal

Code	Phrase
P501	Dispose of contents/container to ...

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
methanol	67-56-1	40-60
glycerol	56-81-5	40-60
giemsa	61-73-4	0.75

continued...

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1

Page 3 of 10

Section 4 - FIRST AID MEASURES

SWALLOWED

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
- For advice, contact a Poisons Information Centre or a doctor.
- Urgent hospital treatment is likely to be needed.
- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.

SKIN

- If skin or hair contact occurs:
- Quickly but gently, wipe material off skin with a dry, clean cloth.
- Immediately remove all contaminated clothing, including footwear.
- Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
- Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Treat symptomatically.
- For acute and short term repeated exposures to methanol:
- Toxicity results from accumulation of formaldehyde/formic acid.
 - Clinical signs are usually limited to CNS, eyes and GI tract. Severe metabolic acidosis may produce dyspnea and profound systemic effects which may become intractable. All symptomatic patients should have arterial pH measured. Evaluate airway, breathing and circulation.
 - Stabilise obtunded patients by giving naloxone, glucose and thiamine.
 - Decontaminate with Ipecac or lavage for patients presenting 2 hours post-ingestion. Charcoal does not absorb well; the usefulness of cathartic is not established.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water may be an ineffective extinguishing media for methanol fires; static explosions are reported for aqueous solutions as dilute as 30%. Water may be used to cool containers.
- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
- Severe fire hazard when exposed to heat, flame and/or oxidisers.
- Vapour may travel a considerable distance to source of ignition.

continued...

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1

Page 4 of 10

Section 5 - FIRE FIGHTING MEASURES

- Heating may cause expansion or decomposition leading to violent rupture of containers.

Combustion products include: carbon dioxide (CO₂), formaldehyde, acrolein, other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
 - Clean up all spills immediately.
 - Avoid breathing vapours and contact with skin and eyes.
 - Control personal contact with the substance, by using protective equipment.
- Slippery when spilt.

MAJOR SPILLS

- Slippery when spilt.
- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear full body protective clothing with breathing apparatus.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.

STORAGE INCOMPATIBILITY

■ Glycerol:

- reacts violently with strong oxidisers, acetic anhydride, alkali metal hydrides, calcium hypochlorite, calcium oxychloride, chlorine, chromic anhydride, chromium oxides, ethylene oxide, hydrogen peroxide, phosphorous triiodide, potassium chlorate, potassium permanganate, potassium peroxide, silver perchlorate, sodium hydride, sodium peroxide, sodium triiodide, sodium tetrahydroborate, is incompatible with strong acids, caustics, aliphatic amines, isocyanates, uranium fluoride
- is able to polymerise above 145 C.

Methanol:

- reacts violently with strong oxidisers, acetyl bromide, alkyl aluminium salts, beryllium dihydride, bromine, chromic acid, 1-chloro-3,3-difluoro-2-methoxycyclopropene, cyanuric chloride, diethylzinc, isophthaloyl chloride, nitric acid, perchloric acid, potassium-tert-butoxide, potassium sulfur diimide, Raney nickel catalysts, 2,4,6-trichlorotriazine, triethylaluminium, 1,3,3-trifluoro-2-methoxycyclopropene
- is incompatible with strong acids, strong caustics, alkaline earth and alkali metals, aliphatic amines, acetaldehyde, benzoyl peroxide, 1,3-bis(di-n-cyclopentadienyl iron)-2-propen-1-one, calcium carbide, chloroform, chromic anhydride, chromium trioxide,

continued...

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1

Page 5 of 10

Section 7 - HANDLING AND STORAGE

dialkylzinc, dichlorine oxide, dichloromethane, ethylene oxide, hypochlorous acid, isocyanates, isopropyl chlorocarbonate, lithium tetrahydroaluminate, magnesium, methyl azide, nitrogen dioxide, palladium, pentafluoroguanidine, perchloryl fluoride, phosphorus pentasulfide, phosphorus trioxide, potassium, tangerine oil, triisobutylaluminium

- mixtures with lead perchlorate, sodium hypochlorite are explosive
- may react with metallic aluminium at high temperatures.

Alcohols

- are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.
- reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen
- react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
- should not be heated above 49 deg. C. when in contact with aluminium equipment.
- Avoid storage with reducing agents.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Notes
India Permissible Levels of Certain Chemical Substances in Work Environment	methanol (Methyl alcohol (Methanol))	200	260	250	310	Skin

The following materials had no OELs on our records

- glycerol: CAS:56- 81- 5
- methylene blue: CAS:61- 73- 4 CAS:7220- 79- 3

MATERIAL DATA

GIEMSA STAIN SOLUTION:

METHANOL:

- For methanol:

Odour Threshold Value: 4.2-5960 ppm (detection), 53.0-8940 ppm (recognition)

NOTE: Detector tubes for methanol, measuring in excess of 50 ppm, are commercially available.

Exposure at or below the recommended TLV-TWA is thought to substantially reduce the significant risk of headache, blurred vision and other ocular and systemic effects.

Odour Safety Factor (OSF)

OSF=2 (METHANOL).

GLYCEROL:

- Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat.

Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

The mist is considered to be a nuisance particulate which appears to have little adverse effect on the lung and does not produce significant organic disease or toxic effects. OSHA concluded that the nuisance particulate limit would protect the worker from kidney damage and perhaps, testicular effects.

METHYLENE BLUE:

■ These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

Extensive concentrations of P.N.O.C.s may:

continued...

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1

Page 6 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- seriously reduce visibility.

PERSONAL PROTECTION



RESPIRATOR

- Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Dar blue-purple flammable viscous liquid with an alcohol odour; mixes with water.

PHYSICAL PROPERTIES

Mixes with water.

Toxic or noxious vapours/gas.

continued...

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1

Page 7 of 10

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

State	LIQUID	Molecular Weight	Not applicable.
Melting Range (°C)	- 98	Viscosity	Not Available
Boiling Range (°C)	65	Solubility in water (g/L)	Miscible
Flash Point (°C)	11	pH (1% solution)	Not available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not available
Autoignition Temp (°C)	Not available	Vapour Pressure (kPa)	Not available
Upper Explosive Limit (%)	44	Specific Gravity (water=1)	1.18
Lower Explosive Limit (%)	5.5	Relative Vapour Density (air=1)	Not available
Volatile Component (%vol)	>50	Evaporation Rate	Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Static induced flash fires have happened when filling plastic containers with methanol / water solutions with as low as 30% methanol content.
 - Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

Health hazard summary table:

Acute toxicity	Acute Tox. (dermal) 3 Acute Tox. (inhal) 2 Acute Tox. (oral) 3
Skin corrosion/irritation	Skin Irrit. 2
Serious eye damage/irritation	Eye Irrit. 2A
Respiratory or skin sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Not applicable
Reproductive toxicity	Not applicable
STOT- single exposure	STOT SE 3 STOT SE 1
STOT- repeated exposure	Not applicable
Aspiration hazard	Asp. Tox. 1

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Strong evidence exists that exposure to the material may produce serious irreversible damage (other than carcinogenesis, mutagenesis and teratogenesis) following a single exposure by swallowing.

■ Methanol may produce a burning or painful sensation in the mouth, throat, chest, and stomach.

This may be accompanied by nausea, vomiting, headache, dizziness, shortness of breath, weakness, fatigue, leg cramps, restlessness, confusion, drunken behaviour, visual disturbance, drowsiness, coma and death.

EYE

■ There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation.

Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.

SKIN

■ There is strong evidence to suggest that this material, on a single contact with skin, can cause serious, irreversible damage of organs.

■ The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time.

Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

■ Open cuts, abraded or irritated skin should not be exposed to this material.

■ Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

continued...

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1

Page 8 of 10

Section 11 - TOXICOLOGICAL INFORMATION

- Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.

INHALED

- Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects.
- The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- There is strong evidence to suggest that this material can cause, if inhaled once, serious, irreversible damage of organs.
- Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.
- Minor but regular methanol exposures may effect the central nervous system, optic nerves and retinae. Symptoms may be delayed, with headache, fatigue, nausea, blurring of vision and double vision.

CHRONIC HEALTH EFFECTS

- Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. Liver and/or kidney injury may also result. Some individuals show severe eye damage following prolonged exposure to 800 ppm of the vapour.

TOXICITY AND IRRITATION

- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. At very high concentrations, evidence predicts that glycerol may cause tremor, irritation of the skin, eyes, digestive tract and airway. Otherwise it is of low toxicity. There is no significant evidence to suggest that it causes cancer, genetic, reproductive or developmental toxicity. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

SKIN

	India Permissible Levels of Certain Chemical Substances in Work Environment - Skin	Notes	Skin
methanol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
glycerol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	0

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
methanol	LOW	No Data Available	LOW	HIGH
glycerol	LOW	No Data Available	LOW	HIGH
methylene blue	No Data Available	No Data Available	LOW	No Data Available

continued...

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1
Page 9 of 10

Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.
- Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.
- A Hierarchy of Controls seems to be common - the user should investigate:
- Reduction.
 - DO NOT allow wash water from cleaning or process equipment to enter drains.
 - It may be necessary to collect all wash water for treatment before disposal.
 - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
 - Where in doubt contact the responsible authority.
 - Recycle wherever possible.
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 - Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
 - Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE LIQUID, TOXIC

HAZCHEM:

•3WE

Land Transport UNDG:

Class or division:	3	Subsidiary risk:	6.1
UN No.:	1992	UN packing group:	II
Shipping Name: FLAMMABLE LIQUID, TOXIC, N.O.S. (contains methanol)			

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	6.1
UN/ID Number:	1992	Packing Group:	II
Special provisions:	A3		

Shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (contains methanol)

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	6.1
UN Number:	1992	Packing Group:	II
EMS Number:	F- E, S- D	Special provisions:	274

Limited Quantities: 1 L
Shipping name: FLAMMABLE LIQUID, TOXIC, N.O.S. (contains methanol)

Section 15 - REGULATORY INFORMATION

REGULATIONS

continued...

GIEMSA'S STAINING SOLUTION

GHS Safety Data Sheet

Version No:4.1.1.1
Page 10 of 10

Section 15 - REGULATORY INFORMATION

Regulations for ingredients

methanol (CAS: 67-56-1) is found on the following regulatory lists;

"Acros Transport Information", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "India Chemical Accidents Rules - Schedule 1: List of Hazardous Chemicals", "India Chemical Accidents Rules - Schedule 2: Threshold Quantities", "India Chemical Accidents Rules - Schedule 3: Named Chemicals", "India Hazardous Wastes (Management, Handling and Transboundary Movement) Rules - Schedule 2: List of Wastes Constituents with Concentration Limits", "India Manufacture, Storage and Import of Hazardous Chemical Rules - Schedule 1: List of Hazardous and Toxic Chemicals", "India Manufacture, Storage and Import of Hazardous Chemical Rules - Schedule 2: Isolated storage at Installations other than those covered by Schedule 4", "India Manufacture, Storage and Import of Hazardous Chemical Rules - Schedule 3: List of Hazardous Chemicals for Application of Rules 5 and 7 to 15", "India Permissible Levels of Certain Chemical Substances in Work Environment", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments"

glycerol (CAS: 56-81-5) is found on the following regulatory lists;

"CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "India Hazardous Wastes (Management, Handling and Transboundary Movement) Rules - Schedule 2: List of Wastes Constituents with Concentration Limits", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "International Numbering System for Food Additives", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information"

methylene blue (CAS: 61-73-4,7220-79-3) is found on the following regulatory lists;

"FisherTransport Information", "India Hazardous Wastes (Management, Handling and Transboundary Movement) Rules - Schedule 2: List of Wastes Constituents with Concentration Limits", "Sigma-AldrichTransport Information"

No data for Giemsa Stain Solution (CW: 6552-88)

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
methylene blue	61- 73- 4	Xn; R22 N; R50/53

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
methylene blue	61- 73- 4, 7220- 79- 3

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as using available literature references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 6-Jul-2017