

GRAM'S IODINE STAINING SOLN. (M.S.)

GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 2 of 11

Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HAZARD

WARNING

Determined by using GHS criteria:

H317 H401

May cause allergic skin reaction

Toxic to aquatic life

PRECAUTIONARY STATEMENTS

Prevention

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated clothing should not be allowed out of the workplace.

Response

If skin irritation or rash occurs, seek medical advice/attention.

Wash contaminated clothing before reuse.

Specific treatment: refer to Label or MSDS.

IF ON SKIN: Gently wash with plenty of soap and water.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
potassium iodide	7681-11-0	0.1-1
iodine	7553-56-2	0.1-1
water	7732-18-5	>90

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

continued...

GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 3 of 11

Section 4 - FIRST AID MEASURES

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Use extinguishing media suitable for surrounding area.
- There is no restriction on the type of extinguisher which may be used.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.
- May emit acrid smoke.

Decomposition may produce toxic fumes of: hydrogen iodide, metal oxides.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

None known.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.

continued...

GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 4 of 11

Section 6 - ACCIDENTAL RELEASE MEASURES

- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

water 500 mg/m³

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

water 500 mg/m³

other than mild, transient adverse effects without perceiving a clearly defined odour is:

water 500 mg/m³

The threshold concentration below which most people will experience no appreciable risk of health effects:

water 500 mg/m³

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - Avoid contact with moisture.
 - Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 - Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately. Launder contaminated clothing before re-use.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

continued...

GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 5 of 11

Section 7 - HANDLING AND STORAGE

STORAGE INCOMPATIBILITY

None known.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together
O: May be stored together with specific precautions
X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- potassium iodide: CAS:7681- 11- 0
- iodine: CAS:7553- 56- 2
- water: CAS:7732- 18- 5

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
iodine		2

MATERIAL DATA

None assigned. Refer to individual constituents.

INGREDIENT DATA

POTASSIUM IODIDE:
Not available

IODINE:

Iodine is an intense irritant to the eyes, mucous membranes and skin and a respiratory irritant in animals. The no-effect concentration in humans for ocular and upper respiratory tract irritation is 0.1 ppm.

WATER:

No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION

continued...


GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 6 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear chemical protective gloves, eg. PVC.

Wear safety footwear or safety gumboots, eg. Rubber.

NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	B- AUS P	-
1000	50	-	B- AUS P
5000	50	Airline *	-
5000	100	-	B- 2 P
10000	100	-	B- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult
your

Occupational Health and Safety Advisor.

continued...

GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 7 of 11

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Amber liquid with iodine odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

Molecular Weight: Not applicable
Melting Range (°C): Not applicable
Solubility in water (g/L): Miscible

Boiling Range (°C): Not applicable
Specific Gravity (water=1): Not available
pH (as supplied): Not available

continued...

GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 8 of 11

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

pH (1% solution): Not available
Volatile Component (%vol): Not available
Relative Vapour Density (air=1): Not available
Lower Explosive Limit (%): Not applicable
Autoignition Temp (°C): Not applicable
State: Liquid

Vapour Pressure (kPa): Not available
Evaporation Rate: Not available
Flash Point (°C): Not applicable
Upper Explosive Limit (%): Not applicable
Decomposition Temp (°C): Not available
Viscosity: Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Not normally a hazard due to non-volatile nature of product.

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

CHRONIC HEALTH EFFECTS

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

There exists limited evidence that shows that skin contact with the material is capable

continued...

GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 9 of 11

Section 11 - TOXICOLOGICAL INFORMATION

either of inducing a sensitisation reaction in a significant number of individuals, and/or of producing positive response in experimental animals.
Iodine and iodides may produce goitre and hypothyroidism as well as hyperthyroidism. A mild toxic syndrome resulting from chronic iodide overdose and from repeated administration of small amounts of iodine ("iodism") is characterised by salivation, coryza, sneezing, conjunctivitis, headache, fever, laryngitis, bronchitis, stomatitis, parotitis (iodine mumps), and various skin rashes (iododerma*, thrombotic thrombocytopenic purpura). Swelling and inflammation of the throat, irritated and swollen eyes and pulmonary oedema may also occur. Oedema of the glottis, necessitating tracheotomy has been reported. Occasional use of iodides for asthma in pregnancy has resulted in foetal death, severe goiter, hypothyroidism and the cretinoid appearance of the new-born. *Iododerma may vary from mild erythema and acneform eruptions to urticaria and suppurative or haemorrhagic rashes.
Sensitisation may result in allergic dermatitis responses including rash, itching, hives or swelling of extremities.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

POTASSIUM IODIDE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (mouse) LDLo: 1862 mg/kg

IRRITATION

Nil Reported

IODINE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LD50: 30 mg/kg*

Oral (woman) TDLo: 26 mg/kg/1y - int *[BDH]

Oral (rat) LD50: 14000 mg/kg

Inhalation (rat) LCLo: 800 mg/m³/1h

IRRITATION

Nil Reported

WATER:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.
No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

Refer to data for ingredients, which follows:

POTASSIUM IODIDE:

Toxicity Fish: LC50(48)0.09-0.48mg/L

Toxicity invertebrate: LC50(48)0.8mg/L

Nitrif. inhib.: inhib at 0.05mg/L

IODINE:

The material is classified as an ecotoxin* because the Fish LC50 (96 hours) is less than or equal to 0.1 mg/l

* Classification of Substances as Ecotoxic (Dangerous to the Environment)

Appendix 8, Table 1

Compiler's Guide for the Preparation of International Chemical Safety Cards: 1993

continued...

GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 10 of 11

Section 12 - ECOLOGICAL INFORMATION

Commission of the European Communities.

Toxicity Fish: LC50(96)36-200mg/L

Nitrif. inhib.: slight inhib

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 - Dispose of by: Burial in a licenced land-fill or incineration in a licenced apparatus (after admixture with suitable combustible material).
 - Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
 - Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

Lugol's iodine solution (CAS: None):
No regulations applicable

iodine (CAS: 7553-56-2) is found on the following regulatory lists;
International Agency for Research on Cancer (IARC) Carcinogens
WHO Guidelines for Drinking-water Quality - Chemicals for which guideline values have not been established

water (CAS: 7732-18-5) is found on the following regulatory lists;
OECD Representative List of High Production Volume (HPV) Chemicals

No data available for potassium iodide as CAS: 7681-11-0.

Section 16 - OTHER INFORMATION

REPRODUCTIVE HEALTH GUIDELINES

Established occupational exposure limits frequently do not take into consideration reproductive end points that are clearly below the thresholds for other toxic effects. Occupational reproductive guidelines (ORGs) have been suggested as an additional standard. These have been established after a literature search for the reproductive no-observed-adverse effect-level (NOAEL) and the lowest-observed-adverse-effect-level

continued...

GRAM'S IODINE STAINING SOLN. (M.S.)

GHS Safety Data Sheet

Version No:3

Page 11 of 11

Section 16 - OTHER INFORMATION

(LOAEL). In addition the US EPA's procedures for risk assessment for hazard identification and dose-response assessment as applied by NIOSH were used in the creation of such limits. Uncertainty factors (UFs) have also been incorporated.

Ingredient	ORG	UF	Endpoint	CR	Adeq TLV
potassium iodide	1.0 mg/m ³	NA	NA	NA	Yes

These exposure guidelines have been derived from a screening level of risk assessment and should not be construed as unequivocally safe limits. ORGS represent an 8-hour time-weighted average unless specified otherwise.

CR = Cancer Risk/10000; UF = Uncertainty factor:

TLV believed to be adequate to protect reproductive health:

LOD: Limit of detection

Toxic endpoints have also been identified as:

D = Developmental; R = Reproductive; TC = Transplacental carcinogen

Jankovic J., Drake F.: A Screening Method for Occupational Reproductive

American Industrial Hygiene Association Journal 57: 641-649 (1996).

EXPOSURE STANDARD FOR MIXTURES

"Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

Composite Exposure Standard for Mixture (TWA) :100 mg/m³.

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 25-May-2018