

PHENYLCHLOROFORMATE

GHS SAFETY DATA SHEET

Version No:2.0
Page 1 of 12

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

PHENYLCHLOROFORMATE

OTHER NAMES

C7-H5-Cl-O2, ClCO2C6H5, "carbonochloridic acid, phenyl ester", "chloroformic acid phenyl ester", "formic acid, chloro-, phenyl ester", "phenyl chlorocarbonate"

PROPER SHIPPING NAME

PHENYL CHLOROFORMATE

PRODUCT USE

Intermediate.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,
248, WORLI,
MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Inhalation) Category 3

Acute Toxicity (Oral) Category 4

Flammable Liquid Category 4

Skin Corrosion/Irritation Category 1C

continued...

PHENYLCHLOROFORMATE

Page 2 of 12
Section 2 - HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by using GHS criteria:

H227 H331 H302 H314

Combustible Liquid

Toxic if inhaled

Harmful if swallowed

Causes severe skin burns and eye damage

PRECAUTIONARY STATEMENTS

Prevention

Do not breathe dust/fume/gas/mist/vapours/spray.

Keep away from flames and hot surfaces.

Do not breathe dust or mist.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use explosion-proof electrical/ventilating/lighting/equipment

Wear protective gloves/clothing and eye/face protection.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well ventilated area.

Wash thoroughly after handling.

Response

Call a POISON CENTER or doctor/physician if you feel unwell.

Immediately call a POISON CENTER or doctor/physician.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Keep container tightly closed.

If on skin or hair: remove/take off immediately all contaminated clothing. Rinse with water/shower.

In case of fire, use foam for extinction.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment: refer to Label or MSDS.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Storage

Store in a corrosive resistant container with a resistant inliner.

Store away from other materials

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

continued...

PHENYLCHLOROFORMATE

Page 3 of 12

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
phenylchloroformate	1885-14-9	>98
decomposes in water/moist air to give hydrogen chloride	7647-01-0	

Section 4 - FIRST AID MEASURES

SWALLOWED

Rinse mouth out with plenty of water.

For advice, contact a Poisons Information Centre or a doctor.

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Immediately flush body and clothes with large amounts of water, using safety shower if available.
- Quickly remove all contaminated clothing, including footwear.
- Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
- Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is

continued...

PHENYLCHLOROFORMATE

contraindicated by excessive swelling

- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
 - Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
 - Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).
- [Ellenhorn and Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Consider evacuation (or protect in place).
- Use water delivered as a fine spray to control fire and cool adjacent area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- May emit acrid smoke and corrosive fumes.

Decomposes on heating and produces toxic fumes of: carbon dioxide (CO₂), phosgene, hydrogen chloride and chlorine.

PHENYLCHLOROFORMATE

FIRE INCOMPATIBILITY

Avoid contamination with strong oxidising agents as ignition may result.
Reacts with metals producing flammable / explosive hydrogen gas.

Personal Protective Equipment

Breathing apparatus.
Chemical splash suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

DO NOT touch the spill material.

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

DO NOT touch the spill material.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+



+



+



+



+



+

+: May be stored together
O: May be stored together with specific precautions
X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.

continued...

PHENYLCHLOROFORMATE

- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing/handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

Glass container.

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

Contact with moisture or water may generate heat.

Segregate from alcohol, water.

Avoid strong bases.

Acyl halides tend to react violently with protic organic solvents, water, and the aprotic solvents, dimethylformamide and dimethyl sulfoxide. Their facile reaction with ethers is also potentially dangerous. In the absence of diluent or other effective control of reaction rate, sulfoxides may react violently or explosively with certain acyl halides. These violent reactions may be explained in terms of exothermic polymerisation of formaldehyde which is formed under a variety of conditions by interaction of the sulfoxide with reactive halides.

BREITHERICK L.: Handbook of Reactive Chemical Hazards.

May react with rust from corroded products.

STORAGE REQUIREMENTS

Keep dry.

- Store in original containers.
 - Keep containers securely sealed.
 - No smoking, naked lights or ignition sources.
 - Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storing and handling recommendations.
- NOTE: May develop pressure in containers; open carefully. Vent periodically.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- | | |
|------------------------|-----------------------------------|
| • phenylchloroformate: | CAS:1885- 14- 9 CAS:180273- 50- 1 |
| • hydrogen chloride: | CAS:7647- 01- 0 CAS:7698- 05- 7 |

continued...

PHENYLCHLOROFORMATE

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m3)	Revised IDLH Value (ppm)
hydrogen chloride		50

ODOUR SAFETY FACTOR (OSF)

OSF=1.3 (HYDROGEN CHLORIDE)

Exposed individuals are NOT reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

MATERIAL DATA

No exposure limits set by NOHSC or ACGIH.

INGREDIENT DATA

HYDROGEN CHLORIDE:

Odour Threshold Value: 0.262 ppm (detection), 10.06 ppm (recognition)

NOTE: Detector tubes for hydrochloric acid, measuring in excess of 1 ppm, are available commercially.

Hydrogen chloride is a strong irritant to the eyes, mucous membranes and skin. Chronic exposure produces a corrosive action on the teeth. Reports of respiratory irritation following short-term exposure at 5 ppm have lead to the recommended TLV-C. There is no indication that skin contact with hydrogen chloride elicits systemic poisoning and a skin designation has not been applied.

Exposure of humans to hydrogen chloride at 50 to 100 ppm for 1 hour is reported to be barely tolerable; 35 ppm caused irritation of the throat on short exposure and 10 ppm was the maximal concentration for prolonged exposure. It has been stated that hydrogen chloride at concentrations of 5 ppm is immediately irritating.

PERSONAL PROTECTION

PHENYLCHLOROFORMATE

Page 8 of 12

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION



EYE

- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

DO NOT handle directly. Wear gloves and use scoop / tongs / tools.
Elbow length PVC gloves.
Nitrile gloves.
PVC boots.

OTHER

- Overalls.
 - PVC Apron.
 - PVC protective suit may be required if exposure severe.
 - Eyewash unit.
 - Ensure there is ready access to a safety shower.
- Operators should be trained in procedures for safe use of this material.
Operators should be trained in correct use & maintenance of respirators.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	AB- AUS P	-
1000	50	-	AB- AUS P
5000	50	Airline *	-
5000	100	-	AB- 2 P
10000	100	-	AB- 3 P
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.
For further information consult your

continued...

PHENYLCHLOROFORMATE

Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50- 100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless liquid; decomposes in water and alkalies.

PHENYLCHLOROFORMATE

PHYSICAL PROPERTIES

Liquid.
Corrosive.
Acid.
Reacts violently with water.

Molecular Weight: 156.57
Melting Range (°C): Not available
Solubility in water (g/L): Reacts
pH (1% solution): Not available
Volatile Component (%vol): Not available
Relative Vapour Density (air=1): >1
Lower Explosive Limit (%): Not available
Autoignition Temp (°C): Not available
State: Liquid

Boiling Range (°C): 74- 75 (13 mm Hg)
Specific Gravity (water=1): 1.248
pH (as supplied): Not applicable
Vapour Pressure (kPa): 8.4 @ 20 C
Evaporation Rate: Not available
Flash Point (°C): 75
Upper Explosive Limit (%): Not available
Decomposition Temp (°C): Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.

Considered an unlikely route of entry in commercial/industrial environments.

EYE

The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.

When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material can produce chemical burns following direct contact with the skin.

Solution of material in moisture on the skin, or perspiration, may markedly increase skin corrosion and accelerate tissue destruction.

Toxic effects may result from skin absorption.

Bare unprotected skin should not be exposed to this material.

The material may cause skin irritation after prolonged or repeated exposure and may

PHENYLCHLOROFORMATE

Section 11 - TOXICOLOGICAL INFORMATION

produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

INHALED

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system in a substantial number of individuals following inhalation. Inhalation of quantities of liquid mist may be extremely hazardous, even lethal due to spasm, extreme irritation of larynx and bronchi, chemical pneumonitis and pulmonary oedema.

CHRONIC HEALTH EFFECTS

Considered toxic by all exposure routes.

Principal routes of exposure are usually by skin contact/absorption.

The material may accumulate in the human body and progressively cause tissue damage.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

TOXICITY AND IRRITATION

TOXICITY

Oral (rat) LD50: 1410 mg/kg

Dermal (rabbit) LD50: 3970 mg/kg

IRRITATION

Skin (rabbit): 500 mg/24h - Mild

Eye (rabbit): 0.05 mg/24h- SEVERE

HYDROGEN CHLORIDE:

TOXICITY

Inhalation (human) LCLo: 1300 ppm/30m

Inhalation (human) LCLo: 3000 ppm/5m

Inhalation (rat) LC50: 3124 ppm/60m

4701 ppm/30m

IRRITATION

Eye (rabbit): 5 mg/30s - Mild

Section 12 - ECOLOGICAL INFORMATION

No data for phenylchloroformate.

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: TOXIC,CORROSIVE
HAZCHEM: 2W

continued...

PHENYLCHLOROFORMATE

Page 12 of 12

Section 14 - TRANSPORTATION INFORMATION

UNDG:

Dangerous Goods Class:	6.1	Subrisk:	8
UN Number:	2746	Packing Group:	II
Shipping Name: PHENYL CHLOROFORMATE			

Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	8
UN/ID Number:	2746	Packing Group:	II
ERG Code:	6C		
Shipping name: PHENYL CHLOROFORMATE			

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	8
UN Number:	2746	Packing Group:	II
EMS Number:	F- A, S- B		
Shipping name: PHENYL CHLOROFORMATE			

Section 15 - REGULATORY INFORMATION

REGULATIONS

No regulations applicable
No data available for phenylchloroformate as CAS: 1885-14-9, CAS: 180273-50-1.

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
phenylchloroformate	1885- 14- 9	Xn; R22

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
phenylchloroformate	1885- 14- 9, 180273- 50- 1

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 12-May-2018