

2-BROMO-2-NITROPROPANE-1,3-DIOL

GHS SAFETY DATA SHEET

Version No:3
Page 1 of 15

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

2-BROMO-2-NITROPROPANE-1,3-DIOL

OTHER NAMES

C3-H6-Br-NO4, HOCH2CBr(NO2)CH2OH, "2-bromo-2-nitropropane-1, 3-diol", "2-bromo-2-nitropropane-1, 3-diol", "2-bromo-2-nitro-1, 3-propanediol", "2-bromo-2-nitro-1, 3-propanediol", beta-bromo-beta-nitrotrimethyleneglycol, preservative, "1, 3-propanediol, 2-bromo-2-nitro-", "1, 3-propanediol, 2-bromo-2-nitro-", "brominated nitroparaffin",

PROPER SHIPPING NAME

2-BROMO-2-NITROPROPANE-1,3-DIOL

PRODUCT USE

Bactericide, biocide preservative, antiseptic, cotton seed treatment.
Has been used as preservative in cosmetics and toiletries.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,
248, WORLI,
MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Aquatic Hazard Category 1
Acute Toxicity (Dermal) Category 4
Acute Toxicity (Oral) Category 3
Flammable Solid Category 2
Reproductive Toxicity Category 1B
Respiratory Irritation Category 3
Serious Eye Damage Category 1
Skin Corrosion/Irritation Category 2
Skin Sensitizer Category 1



EMERGENCY OVERVIEW

HAZARD

DANGER
Determined by using GHS criteria:
H335 H228 H301 H312 H315 H317 H360 H318 H400
May cause respiratory irritation
Flammable solid
Solid desensitised explosives: low hazard
Toxic if swallowed
Harmful in contact with skin
Causes skin irritation
May cause allergic skin reaction
May damage the unborn child
Causes serious eye damage
Very toxic to aquatic life

PRECAUTIONARY STATEMENTS

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.

continued...

2-BROMO-2-NITROPROPANE-1,3-DIOL

Wash hands thoroughly after handling.
Contaminated clothing should not be allowed out of the workplace.
Wash thoroughly after handling.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wear protective gloves/clothing
Keep away from heat/sparks/open flame - No smoking.
Wear protective gloves and eye/face protection.
Use personal protective equipment as required.
Do not eat, drink or smoke when using this product.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Wash contaminated clothing before reuse.
If exposed or concerned: Get medical attention advice.
If eye irritation persists, get medical advice/attention.
If skin irritation or rash occurs, seek medical advice/attention.
If skin irritation occurs, seek medical advice/attention.
Wear eye/face protection.
Call a POISON CENTER or doctor/physician if you feel unwell.
Remove/Take off immediately all contaminated clothing
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
Specific treatment: refer to Label or MSDS.
IF ON SKIN: Gently wash with plenty of soap and water.
Immediately call a POISON CENTER or doctor/physician.
Wash/Decontaminate removed clothing before reuse.

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
2- bromo- 2- nitropropan- 1, 3- diol	52-51-7	> 98

Section 4 - FIRST AID MEASURES

SWALLOWED

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
 - For advice, contact a Poisons Information Centre or a doctor.
 - Urgent hospital treatment is likely to be needed.
 - In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
 - If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided.
- Further action will be the responsibility of the medical specialist.

2-BROMO-2-NITROPROPANE-1,3-DIOL

- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS.
 - Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:
 - INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- NOTE: Wear a protective glove when inducing vomiting by mechanical means.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

Treat symptomatically.
For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- Anticipate seizures .
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.

2-BROMO-2-NITROPROPANE-1,3-DIOL

- Positive-pressure ventilation using a bag-valve mask might be of use.
 - Monitor and treat, where necessary, for arrhythmias.
 - Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
 - Drug therapy should be considered for pulmonary oedema.
 - Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
 - Treat seizures with diazepam.
 - Proparacaine hydrochloride should be used to assist eye irrigation.
- BRONSTEIN, A.C. and CURRANCE, P.L.
EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

For SMALL FIRES:

Dry chemical, CO₂, water spray or foam.

For LARGE FIRES:

Water-spray, fog or foam.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Fight fire from a safe distance, with adequate cover.
- If safe, switch off electrical equipment until vapour fire hazard removed.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Flammable solid which burns and propagates flame easily, even when partly wetted with water.
 - Any source of ignition, i.e. friction, heat, sparks or flame, may cause fire or explosion.
 - May burn fiercely
 - May form explosive mixtures with air.
 - May REIGNITE after fire is extinguished.
 - Containers may explode on heating.
 - Solids may melt and flow when heated or involved in a fire.
 - Runoff may pollute waterways.
 - Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.
 - Dry dust can be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport, thereby providing a source of ignition.
 - Decomposition products may be irritating, poisonous or corrosive.
- Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), aldehydes, hydrogen bromide, nitrogen oxides (NO_x), other pyrolysis products typical of burning

2-BROMO-2-NITROPROPANE-1,3-DIOL

organic material.

FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Personal Protective Equipment

Gas tight chemical resistant suit.
Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- DO NOT touch or walk through spilled material.
- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Prevent dust cloud.
- With clean shovel (preferably non-sparking) place material into clean, dry container and cover loosely.
- Move containers from spill area.
- Control personal contact by using protective equipment.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- DO NOT touch or walk through spilled material.
- Control personal contact by using protective equipment.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.
- Stop leak if safe to do so.
- Contain or cover with sand, earth or vermiculite.
- Use only spark-free shovels and explosion proof equipment.
- Collect recoverable product into labelled containers for recycling.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area with water and dike for later disposal; prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+



X



X



X



X



+

+: May be stored together

O: May be stored together with specific preventions

2-BROMO-2-NITROPROPANE-1,3-DIOL

Page 7 of 15

Section 6 - ACCIDENTAL RELEASE MEASURES

X: *Must not be stored together*

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid smoking, naked lights or ignition sources.
- When handling, DO NOT eat, drink or smoke.
- Avoid contact with incompatible materials.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Working clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing/handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

For low viscosity materials and solids:

Drums and jerricans must be of the non-removable head type.

Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C):

- Removable head packaging and
- cans with friction closures may be used.

-

Where combination packages are used, there must be sufficient inert absorbent material to absorb completely any leakage that may occur, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic. All combination packages for Packing group I and II must contain cushioning material.

STORAGE INCOMPATIBILITY

- Avoid oxidising agents, acids, acid chlorides, acid anhydrides.
- Avoid strong bases.

STORAGE REQUIREMENTS

FOR MINOR QUANTITIES:

- Store in an indoor fireproof cabinet or in a room of noncombustible construction.
- Provide adequate portable fire-extinguishers in or near the storage area.

FOR PACKAGE STORAGE:

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.

continued...

2-BROMO-2-NITROPROPANE-1,3-DIOL

- Store away from incompatible materials in a cool, dry, well ventilated area.
- Protect containers against physical damage and check regularly for leaks.
- Protect containers from exposure to weather and from direct sunlight unless: (a) the packages are of metal or plastic construction; (b) the packages are securely closed and not opened for any purpose while in the area where they are stored and (c) adequate precautions are taken to ensure that rain water, which might become contaminated by the dangerous goods, is collected and disposed of safely.
- Ensure proper stock-control measures are maintained to prevent prolonged storage of dangerous goods.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- 2- bromo- 2- nitropropan- 1, 3- diol: CAS:52- 51- 7 CAS:179733- 60- 9 CAS:133248- 96- 1

MATERIAL DATA

It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no -observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELS) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five -category system based on intensive odour, local irritation, and elimination half-life.

However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.


OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

2-BROMO-2-NITROPROPANE-1,3-DIOL

Designated H in List of MAK values: Danger of cutaneous absorption.
Absorption of such substances through the skin can pose an incomparably larger danger of toxicity than their inhalation. To avoid health risks when handling such substances, meticulous cleaning of the skin, hair and clothing is imperative.
MAK values, and categories and groups are those recommended within the Federal Republic of Germany.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Suitability and durability of glove type is dependent on usage. Factors such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity,

are important in the selection of gloves.
Wear physical protective gloves, eg. leather.
Wear safety footwear.

NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

OTHER

- Overalls.
- Eyewash unit.
- Barrier cream.
- Skin cleansing cream.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-

continued...

2-BROMO-2-NITROPROPANE-1,3-DIOL

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

100+ x ES	-	Air- line*	-
		Air- line**	PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
 - (a): particle dust respirators, if necessary, combined with an absorption cartridge;
 - (b): filter respirators with absorption cartridge or canister of the right type;
 - (c): fresh-air hoods or masks
- Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.

Type of Contaminant:	Air Speed:
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction

continued...

2-BROMO-2-NITROPROPANE-1,3-DIOL

Page 11 of 15

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

White or pale-yellow crystalline powder; soluble in water.
Soluble in alcohol and ethyl acetate. Soluble, with difficulty,
in chloroform, acetone, ether and benzene. Faint odour.

PHYSICAL PROPERTIES

Solid.

Mixes with water.

Molecular Weight: 200.01

Melting Range (°C): 130

Solubility in water (g/L): Miscible

pH (1% solution): 4.5- 7.0

Volatile Component (%vol): Negligible

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): Not available.

Autoignition Temp (°C): Not available.

State: Divided solid

Boiling Range (°C): Decomposes.

Specific Gravity (water=1): 1.10

pH (as supplied): Not applicable

Vapour Pressure (kPa): Negligible

Evaporation Rate: Not applicable

Flash Point (°C): Not available

Upper Explosive Limit (%): Not available.

Decomposition Temp (°C): >140

Viscosity: Not Applicable

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

continued...

EYE

When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.

SKIN

Skin contact with the material may be harmful; systemic effects may result following absorption.

The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either

- produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or
- produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period.

Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Solution of material in moisture on the skin, or perspiration, may increase irritant effects.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

The material is not thought to produce adverse health effects following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Long term exposure to high dust concentrations may cause changes in lung function (i.e. pneumoconiosis) caused by particles less than 0.5 micron penetrating and remaining in the lung. A prime symptom is breathlessness. Lung shadows show on X-ray.

There exists limited evidence that shows that skin contact with the material is capable either of inducing a sensitisation reaction in a significant number of individuals, and/or of producing positive response in experimental animals.

There is some evidence that human exposure to the material may result in developmental toxicity. This evidence is based on animal studies where effects have been observed in the absence of marked maternal toxicity, or at around the same dose levels as other toxic effects but which are not secondary non-specific consequences of the other toxic effects. Chronic intoxication with ionic bromides, historically, has resulted from medical use of bromides but not from environmental or occupational exposure; depression, hallucinosis, and schizophreniform psychosis can be seen in the absence of other signs of intoxication. Bromides may also induce sedation, irritability, agitation, delirium, memory loss, confusion, disorientation, forgetfulness (aphasias), dysarthria, weakness, fatigue, vertigo, stupor, coma, decreased appetite, nausea and vomiting, diarrhoea, hallucinations, an acne like rash on the face, legs and trunk (seen in 25-30% of case involving bromide ion), and a profuse discharge from the nostrils (coryza). Ataxia and generalised hyperreflexia have also been observed. Correlation of neurologic symptoms with blood levels of bromide is inexact. The use of substances such as brompheniramine, as antihistamines, largely reflect current day usage of bromides; ionic bromides have been largely withdrawn from therapeutic use due to their toxicity. Several cases of foetal abnormalities have been described in mothers who took large doses of bromides during pregnancy.

TOXICITY AND IRRITATION

TOXICITY

Oral (rat) LD50: 180 mg/kg
Inhalation (rat) LC50: >5000 mg/m³/6h
Dermal (rat) LD50: 1600 mg/kg
Intraperitoneal (Rat) LD50: 26 mg/kg
Subcutaneous (Rat) LD50: 170 mg/kg
Oral (Mouse) LD50: 270 mg/kg
Subcutaneous (Mouse) LD50: 116 mg/kg
Intravenous (Mouse) LD50: 48 mg/kg
Oral (Dog) LD50: 250 mg/kg

IRRITATION

Skin (human): 10 mg Moderate
Skin (rabbit): 500 mg/24h Mild
Skin (rabbit): 80 mg Moderate
Eye (rabbit): 5 mg

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder

2-BROMO-2-NITROPROPANE-1,3-DIOL

Page 14 of 15

Section 11 - TOXICOLOGICAL INFORMATION

is characterised by dyspnea, cough and mucus production.
Chemical with the aliphatic nitro group (-C-NO₂) have been added to a list of DNA
-reactive subgroups recognised by the National Toxicological Program (NTP, U.S. Dept
Health and Human Services) for possible carcinogenic activity.

Section 12 - ECOLOGICAL INFORMATION

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.
Wastes resulting from use of the product must be disposed of on site or at approved waste sites.
DO NOT discharge into sewer or waterways.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
 - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
 - Dispose of by: Burial in a licenced land-fill or Incineration in a licenced apparatus (after admixture with suitable combustible material)
 - Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.
 - Containers may still present a chemical hazard/ danger when empty.
 - Return to supplier for reuse/ recycling if possible.
- Otherwise:
- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
 - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: FLAMMABLE SOLID
HAZCHEM: None

UNDG:

Dangerous Goods Class:	4.1	Subrisk:	None
UN Number:	3241	Packing Group:	III
Shipping Name: 2-BROMO-2-NITROPROPANE-1,3-DIOL			

continued...

2-BROMO-2-NITROPROPANE-1,3-DIOL

Page 15 of 15

Section 14 - TRANSPORTATION INFORMATION

Air Transport IATA:

ICAO/IATA Class:	4.1	ICAO/IATA Subrisk:	None
UN/ID Number:	3241	Packing Group:	III
ERG Code:	3L		

Shipping name: 2-BROMO-2-NITROPROPANE-1,3-DIOL

Maritime Transport IMDG:

IMDG Class:	4.1	IMDG Subrisk:	None
UN Number:	3241	Packing Group:	III
EMS Number:	F- J, S- G		

Shipping name: 2-BROMO-2-NITROPROPANE-1,3-DIOL

Section 15 - REGULATORY INFORMATION

REGULATIONS

No regulations applicable
No data available for 2-bromo-2-nitropropan-1,3-diol as CAS: 52-51-7, CAS: 179733-60-9, CAS: 133248-96-1.

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
2- bromo- 2- nitropropan- 1, 3- diol	52- 51- 7, 179733- 60- 9, 133248- 96- 1

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 12-Jul-2018