

METHYL-M-HYDROXYBENZOATE

GHS SAFETY DATA SHEET

Version No:2.0
Page 1 of 9

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

METHYL 3-HYDROXYBENZOATE

OTHER NAMES

C8-H8-O3, OHC6H4CO2CH3, "hydroxybenzoic acid, methyl ester"

PRODUCT USE

Laboratory reagent.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Skin Sensitizer Category 1



continued...

METHYL-M-HYDROXYBENZOATE

EMERGENCY OVERVIEW

HAZARD

WARNING

Determined by Chemwatch using GHS criteria:

H317

May cause allergic skin reaction

PRECAUTIONARY STATEMENTS

Prevention

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated clothing should not be allowed out of the workplace.

Response

Wash contaminated clothing before reuse.

If skin irritation or rash occurs, seek medical advice/attention.

IF ON SKIN: Gently wash with plenty of soap and water.

Specific treatment: refer to Label or MSDS.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
methyl 3- hydroxybenzoate	19438-10-9	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves for fire only.
- Prevent, by any means available, spillage from entering drains or water courses.
- Use fire fighting procedures suitable for surrounding area.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Solid which exhibits difficult combustion or is difficult to ignite.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.
- Dry dust can also be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.
- Build-up of electrostatic charge may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.
- All movable parts coming in contact with this material should have a speed of less than 1-metre/sec.

FIRE INCOMPATIBILITY

Avoid contamination / mixing with oxidising agents as ignition may result.

Personal Protective Equipment

Gas tight chemical resistant suit.
Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear protective clothing, gloves, safety glasses and dust respirator.
- Use dry clean up procedures and avoid generating dust.
- Sweep up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place in clean drum then flush area with water.

METHYL-M-HYDROXYBENZOATE

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment and dust respirator.
- Prevent spillage from entering drains, sewers or water courses.
- Avoid generating dust.
- Sweep, shovel up. Recover product wherever possible.
- Put residues in labelled plastic bags or other containers for disposal.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



- +: May be stored together
O: May be stored together with specific precautions
X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid generating and breathing dust.
- Limit all unnecessary personal contact.
 - Wear protective clothing when risk of exposure occurs.
 - Use in a well-ventilated area.
 - Avoid contact with incompatible materials.
 - When handling, DO NOT eat, drink or smoke.
 - Keep containers securely sealed when not in use.
 - Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately.
 - Use good occupational work practice.
 - Observe manufacturer's storing and handling recommendations.
 - Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Glass container.
Plastic container.
Multi-ply woven plastic or paper bag with sealed plastic liner
NOTE: Bags should be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse.
- Check that containers are clearly labelled.
- Packaging as recommended by manufacturer.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.

METHYL-M-HYDROXYBENZOATE

- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- methyl 3- hydroxybenzoate: CAS:19438- 10- 9

MATERIAL DATA

These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

Extensive concentrations of P.N.O.C.s may:

- seriously reduce visibility,
- cause unpleasant deposits in the eyes, ears and nasal passages,
- contribute to skin or mucous membrane injury by chemical or mechanical action, per se, or by the rigorous skin cleansing procedures necessary for their removal. [ACGIH]

This limit does not apply:

- to brief exposures to higher concentrations
- nor does it apply to those substances that may cause physiological impairment at lower concentrations but for which a TLV has as yet to be determined.

This exposure standard applies to particles which

- are insoluble or poorly soluble* in water or, preferably, in aqueous lung fluid (if data is available) and
- have a low toxicity (i.e.. are not cytotoxic, genotoxic, or otherwise chemically reactive with lung tissue, and do not emit ionizing radiation, cause immune sensitization, or cause toxic effects other than by inflammation or by a mechanism of lung overload).

PERSONAL PROTECTION



EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure,

continued...

METHYL-M-HYDROXYBENZOATE

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear general protective gloves: i.e. Disposable polythene gloves or Cotton gloves or Light weight rubber gloves, with Barrier cream preferably Safety footwear.

OTHER

- Overalls.
- Barrier cream
- Eyewash unit.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Use in a well-ventilated area.

- Local exhaust ventilation is required where solids are handled as powders or crystals; even when particulates are relatively large, a certain proportion will be powdered by mutual friction.
- Exhaust ventilation should be designed to prevent accumulation and recirculation of particulates in the workplace.
- If in spite of local exhaust an adverse concentration of the substance in air could occur, respiratory protection should be considered. Such protection might consist of:
 - (a): particle dust respirators, if necessary, combined with an absorption cartridge;
 - (b): filter respirators with absorption cartridge or canister of the right type;
 - (c): fresh-air hoods or masks
- Build-up of electrostatic charge on the dust particle, may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to efficiently remove the contaminant.

Type of Contaminant:

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid

Air Speed:

1- 2.5 m/s (200- 500 f/min.)

2.5- 10 m/s (500- 2000 f/min.)

continued...

METHYL-M-HYDROXYBENZOATE

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

air motion).

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 4-10 m/s (800-2000 f/min) for extraction of crusher dusts generated 2 metres distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Colourless crystals or white crystalline powder. Odourless or faint characteristic odour; slight burning taste. Slightly soluble in water, benzene and carbon tetrachloride. Soluble in alcohol and ether.

PHYSICAL PROPERTIES

Solid.

Does not mix with water.

Molecular Weight: 152.16

Melting Range (°C): 72- 74

Solubility in water (g/L): Partly miscible

pH (1% solution): Not applicable.

Volatile Component (%vol): Negligible

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): Not available.

Autoignition Temp (°C): Not available.

State: Divided solid

Boiling Range (°C): 280- 281 (709 mm)

Specific Gravity (water=1): Not available

pH (as supplied): Not applicable

Vapour Pressure (kPa): Negligible

Evaporation Rate: Not applicable

Flash Point (°C): Not available

Upper Explosive Limit (%): Not available.

Decomposition Temp (°C): Not available.

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Although ingestion is not thought to produce harmful effects (as classified under EC Directives), the material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

Considered an unlikely route of entry in commercial/industrial environments.

EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Sensitisation may result in allergic dermatitis responses including rash, itching, hives or swelling of extremities.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Not normally a hazard due to non-volatile nature of product.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

There exists limited evidence that shows that skin contact with the material is capable either of inducing a sensitisation reaction in a significant number of individuals, and/or of producing positive response in experimental animals.

Principal routes of exposure are usually by skin contact and inhalation of generated dust.

Hypersensitivity reactions have been reported after application of preparations containing p-hydroxybenzoates to the skin. Hypersensitivity reactions have also been reported following parenteral or oral administration. Cross-sensitivity occurs between the p-hydroxybenzoates. Hypersensitivity reactions may include acute bronchospasm, hives (urticaria), deep dermal wheals (angioneurotic oedema), running nose (rhinitis) and blurred vision. Anaphylactic shock and skin rash (non-thrombocytopenic purpura) may also occur. Any individual may be predisposed to such antibody mediated reaction if other chemical agents have caused prior sensitisation (cross-sensitivity).

Chronic exposure to the salicylates (o-hydroxybenzoates) produces a range of effects

continued...

METHYL-M-HYDROXYBENZOATE

Page 9 of 9

Section 11 - TOXICOLOGICAL INFORMATION

ranging from metabolic disturbances to kidney and pancreas damage. Hypersensitivity to salicylic acid derivatives have caused reactions which include urticaria and other skin eruptions, rhinitis and severe (even fatal) bronchospasm and dyspnoea.

TOXICITY AND IRRITATION

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

No data for methyl 3-hydroxybenzoate.

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA,
IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

No regulations applicable

No data available for methyl 3-hydroxybenzoate as CAS: 19438-10-9.

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
methyl 3- hydroxybenzoate	19438- 10- 9	R43

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 12-May-2018