

## BENZYLTRIBUTYL AMMONIUM CHLORIDE

Version No:2.0  
Page 1 of 11

GHS SAFETY DATA SHEET

### Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

#### PRODUCT NAME

BENZYLTRIBUTYLAMMONIUM CHLORIDE

#### OTHER NAMES

C19-H34-Br-N.Cl, C6-H5-CH2-N((CH2)CH3)3Cl, "ammonium, benzyltributyl-, chloride", "benzenemethanaminium, N, N, N-tributyl-, chloride", "benzenemethanaminium, N, N, N-tributyl-, chloride", benzyl-tributyl-ammonium-chloride, "N, N, N-tributylbenzenemethanaminium chloride", "N, N, N-tributylbenzenemethanaminium chloride", "tributylbenzylammonium chloride", "quaternary ammonium compound"

#### PRODUCT USE

Quaternary ammonium compound; phase transfer catalyst.

#### SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

#### HAZARD RATINGS



### Section 2 - HAZARDS IDENTIFICATION

#### GHS Classification

Acute Aquatic Hazard Category 2

Respiratory Sensitizer Category 1

Skin Sensitizer Category 1

continued...

# BENZYLTRIBUTYL AMMONIUM CHLORIDE



## EMERGENCY OVERVIEW

### HAZARD

#### DANGER

Determined by using GHS criteria:

H334 H317 H401

May cause allergic or asthmatic symptoms or breathing difficulties if inhaled

May cause allergic skin reaction

Toxic to aquatic life

### PRECAUTIONARY STATEMENTS

#### Prevention

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated clothing should not be allowed out of the workplace.

In case of inadequate ventilation wear respiratory protection.

#### Response

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

If skin irritation or rash occurs, seek medical advice/attention.

If experiencing respiratory symptoms call a POISON CENTER or doctor/physician.

Specific treatment: refer to Label or MSDS.

IF ON SKIN: Gently wash with plenty of soap and water.

Wash contaminated clothing before reuse.

#### Disposal

Dispose of contents and container in accordance with relevant legislation.

---

## Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| NAME                            | CAS RN     | %   |
|---------------------------------|------------|-----|
| benzyltributylammonium chloride | 23616-79-7 | >98 |

---

## Section 4 - FIRST AID MEASURES

### SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.

- If swallowed do NOT induce vomiting.

- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

- Immediately give a glass of water.

continued...

# BENZYLTRIBUTYL AMMONIUM CHLORIDE

## EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

## SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

## INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.
- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

## NOTES TO PHYSICIAN

For exposures to quaternary ammonium compounds;

- For ingestion of concentrated solutions (10% or higher): Swallow promptly a large quantity of milk, egg whites / gelatin solution. If not readily available, a slurry of activated charcoal may be useful. Avoid alcohol. Because of probable mucosal damage omit gastric lavage and emetic drugs.
- For dilute solutions (2% or less): If little or no emesis appears spontaneously, administer syrup of Ipecac or perform gastric lavage.
- If hypotension becomes severe, institute measures against circulatory shock.
- If respiration laboured, administer oxygen and support breathing mechanically. Oropharyngeal airway may be inserted in absence of gag reflex. Epiglottic or laryngeal edema may necessitate a tracheotomy.
- Persistent convulsions may be controlled by cautious intravenous injection of diazepam or short-acting barbiturate drugs. [Gosselin et al, Clinical Toxicology of Commercial Products].

---

## Section 5 - FIRE FIGHTING MEASURES

---

### EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

### FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.

# BENZYLTRIBUTYL AMMONIUM CHLORIDE

- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

## FIRE/EXPLOSION HAZARD

- Solid which exhibits difficult combustion or is difficult to ignite.
  - Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.
  - Dry dust can also be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.
  - Build-up of electrostatic charge may be prevented by bonding and grounding.
  - Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.
  - All movable parts coming in contact with this material should have a speed of less than 1-metre/sec.
- Combustion products include: carbon monoxide (CO), nitrogen oxides (NOx) and hydrogen chloride.

## FIRE INCOMPATIBILITY

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

## Personal Protective Equipment

Gas tight chemical resistant suit.  
Limit exposure duration to 1 BA set 30 mins.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

## EMERGENCY PROCEDURES

### MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety glasses.
- Use dry clean up procedures and avoid generating dust.
- Sweep up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labelled container.

### MAJOR SPILLS

Clear area of personnel and move upwind.

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- No smoking, naked lights or ignition sources.
- Increase ventilation.

continued...

# BENZYLTRIBUTYL AMMONIUM CHLORIDE

## Section 6 - ACCIDENTAL RELEASE MEASURES

- Stop leak if safe to do so.
- Water spray or fog may be used to disperse / absorb vapour.
- Contain or absorb spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



- +: *May be stored together*  
O: *May be stored together with specific precautions*  
X: *Must not be stored together*

**Personal Protective Equipment advice is contained in Section 8 of the MSDS.**

## Section 7 - HANDLING AND STORAGE

### PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

### SUITABLE CONTAINER

- Glass container.
- Polyethylene or polypropylene container.
  - Packing as recommended by manufacturer.
  - Check all containers are clearly labelled and free from leaks.

### STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

### STORAGE REQUIREMENTS

- Keep dry.
- Store in original containers.
  - Keep containers securely sealed.
  - No smoking, naked lights or ignition sources.
  - Store in a cool, dry, well-ventilated area.
  - Store away from incompatible materials and foodstuff containers.
  - Protect containers against physical damage and check regularly for leaks.

# BENZYLTRIBUTYL AMMONIUM CHLORIDE

- Observe manufacturer's storing and handling recommendations.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE CONTROLS

The following materials had no OELs on our records

- benzyltributylammonium chloride: CAS:23616- 79- 7

### MATERIAL DATA

These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

Extensive concentrations of P.N.O.C.s may:

- seriously reduce visibility,
- cause unpleasant deposits in the eyes, ears and nasal passages,
- contribute to skin or mucous membrane injury by chemical or mechanical action, per se, or by the rigorous skin cleansing procedures necessary for their removal. [ACGIH]

This limit does not apply:

- to brief exposures to higher concentrations
- nor does it apply to those substances that may cause physiological impairment at lower concentrations but for which a TLV has as yet to be determined.

This exposure standard applies to particles which

- are insoluble or poorly soluble\* in water or, preferably, in aqueous lung fluid (if data is available) and
- have a low toxicity (i.e.. are not cytotoxic, genotoxic, or otherwise chemically reactive with lung tissue, and do not emit ionizing radiation, cause immune sensitization, or cause toxic effects other than by inflammation or by a mechanism of lung overload).

### PERSONAL PROTECTION



#### EYE

- Safety glasses with side shields.
- Chemical goggles.
- Full face shield may be required for supplementary but never for primary protection of eyes
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account

# BENZYLTRIBUTYL AMMONIUM CHLORIDE

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

### HANDS/FEET

Wear chemical protective gloves, eg. PVC.  
Wear safety footwear.

### OTHER

- Overalls.
- Eyewash unit.

### RESPIRATOR

| Protection Factor | Half- Face Respirator | Full- Face Respirator | Powered Air Respirator |
|-------------------|-----------------------|-----------------------|------------------------|
| 10 x ES           | P1 Air- line*         | - -                   | PAPR- P1 -             |
| 50 x ES           | Air- line**           | P2                    | PAPR- P2               |
| 100 x ES          | -                     | P3                    | -                      |
|                   |                       | Air- line*            | -                      |
| 100+ x ES         | -                     | Air- line**           | PAPR- P3               |

\* - Negative pressure demand \*\* - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.  
For further information consult your  
Occupational Health and Safety Advisor.

### ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

| Type of Contaminant:  | Air Speed:                     |
|---|--------------------------------|
| solvent, vapours, degreasing etc., evaporating from tank (in still air)   | 0.25- 0.5 m/s (50- 100 f/min)  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5- 1 m/s (100- 200 f/min.)   |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1- 2.5 m/s (200- 500 f/min)    |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).  | 2.5- 10 m/s (500- 2000 f/min.) |

continued...

# BENZYLTRIBUTYL AMMONIUM CHLORIDE

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

---

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

### APPEARANCE

White, hygroscopic, crystalline powder; mixes with water.

### PHYSICAL PROPERTIES

Solid.

Mixes with water.

Molecular Weight: 311.94

Melting Range (°C): 160- 164 (decomp)

Solubility in water (g/L): Miscible

pH (1% solution): Not available

Volatile Component (%vol): Negligible

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): Not available

Autoignition Temp (°C): Not available

State: Divided solid

Boiling Range (°C): Not applicable

Specific Gravity (water=1): Not available

pH (as supplied): Not applicable

Vapour Pressure (kPa): Negligible

Evaporation Rate: Not available

Flash Point (°C): Not available

Upper Explosive Limit (%): Not available

Decomposition Temp (°C): 160

---

## Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

---

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

continued...



---

## Section 11 - TOXICOLOGICAL INFORMATION

---

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

Accidental ingestion of the material may be damaging to the health of the individual. Concentrated solutions of many cationics may cause corrosive damage to mucous membranes and the oesophagus. Nausea and vomiting (sometimes bloody) may follow ingestion. Serious exposures may produce an immediate burning sensation of the mouth, throat and abdomen with profuse salivation, ulceration of mucous membranes, signs of circulatory shock (hypotension, laboured breathing, and cyanosis) and a feeling of apprehension, restlessness, confusion and weakness. Weak convulsive movements may precede central nervous system depression. Erosion, ulceration, and petechial haemorrhage may occur through the small intestine with glottic, brain and pulmonary oedema. Death may result from asphyxiation due to paralysis of the muscles of respiration or cardiovascular collapse. Fatal poisoning may arise even when the only pathological signs are visceral congestion, swallowing, mild pulmonary oedema or varying signs of gastrointestinal irritation. Individuals who survive a period of severe hypertension may develop kidney failure. Cloudy swelling, patchy necrosis and fatty infiltration in such visceral organs as the heart, liver and kidneys shows at death.

##### EYE

Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

##### SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

The material is not thought to be a skin irritant (i.e. is unlikely to produce irritant dermatitis as described in EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Many amine compounds are sensitisers and some are absorbed through intact skin.

Sensitisation may result in allergic dermatitis responses including rash, itching, hives or swelling of extremities.

Toxic effects may result from skin absorption.

##### INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

# BENZYLTRIBUTYL AMMONIUM CHLORIDE

## Section 11 - TOXICOLOGICAL INFORMATION

---

### CHRONIC HEALTH EFFECTS

Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population.

Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking.

There exists limited evidence that shows that skin contact with the material is capable either of inducing a sensitisation reaction in a significant number of individuals, and/or of producing positive response in experimental animals.

Principal routes of exposure are by accidental skin and eye contact and inhalation of generated dusts.

No human exposure data available. For this reason health effects described are based on experience with chemically related materials.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

### TOXICITY AND IRRITATION

No significant acute toxicological data identified in literature search.

---

## Section 12 - ECOLOGICAL INFORMATION

---

No data for benzyltributylammonium chloride.

---

## Section 13 - DISPOSAL CONSIDERATIONS

---

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

---

## Section 14 - TRANSPORTATION INFORMATION

---

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

---

## Section 15 - REGULATORY INFORMATION

---

### REGULATIONS

benzyltributylammonium chloride (CAS: 23616-79-7) is found on the following regulatory lists;

continued...

# BENZYLTRIBUTYL AMMONIUM CHLORIDE

Page 11 of 11

## Section 15 - REGULATORY INFORMATION

---

WHO Guidelines for Drinking-water Quality - Chemicals for which guideline values have not been established

---

## Section 16 - OTHER INFORMATION

---

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 12-May-2018