

1-BUTANESULPHONIC ACID SODIUM SALT 98%

Version No:2.0
Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

1-BUTANESULFONIC ACID, SODIUM SALT

OTHER NAMES

C4-H10-O3-S, CH₃(CH₂)₃SO₃Na, "sulfonic acid, 1-butane-, sodium salt", "sulfonic acid, 1-butane-, sodium salt", "1-butan Sulphonic acid", "1-butan Sulphonic acid"

PRODUCT USE

Intermediate in preparation of anti-static polyester fibres.
Ion-associating reagent for HPLC analysis of peptides and proteins.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Eye Irritation Category 2B

Respiratory Sensitizer Category 1

Skin Corrosion/Irritation Category 3

Skin Sensitizer Category 1

continued...

1-BUTANESULPHONIC ACID SODIUM SALT 98%

Version No:2.0

Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by

using GHS criteria:

H316 H320 H334 H317

Causes mild skin irritation

Causes eye irritation

May cause allergic or asthmatic symptoms or breathing difficulties if inhaled

May cause allergic skin reaction

PRECAUTIONARY STATEMENTS

Prevention

In case of inadequate ventilation wear respiratory protection.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Contaminated clothing should not be allowed out of the workplace.

Wash hands thoroughly after handling.

Response

If eye irritation persists, get medical advice/attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

If skin irritation or rash occurs, seek medical advice/attention.

If experiencing respiratory symptoms call a POISON CENTER or doctor/physician.

IF ON SKIN: Gently wash with plenty of soap and water.

Specific treatment: refer to Label or MSDS.

Wash contaminated clothing before reuse.

If skin irritation occurs, seek medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
1- butanesulfonic acid, sodium salt	2386-54-1	>98

continued...

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - If pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Use water delivered as a fine spray to control fire and cool adjacent area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Solid which exhibits difficult combustion or is difficult to ignite.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame

1-BUTANESULPHONIC ACID SODIUM SALT 98%

Version No:2.0

Page 4 of 10

Section 5 - FIRE FIGHTING MEASURES

or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.

- Dry dust can also be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.
- Build-up of electrostatic charge may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require additional protection measures such as explosion venting.
- All movable parts coming in contact with this material should have a speed of less than 1-metre/sec.

Combustion products include: sulfur oxides (SO_x).

FIRE INCOMPATIBILITY

Avoid contamination with strong oxidising agents as ignition may result.

Personal Protective Equipment

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety glasses.
- Use dry clean up procedures and avoid generating dust.
- Sweep up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment and dust respirator.
- Prevent spillage from entering drains, sewers or water courses.
- Avoid generating dust.
- Sweep, shovel up. Recover product wherever possible.
- Put residues in labelled plastic bags or other containers for disposal.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+



+



+



+



+



+

+: May be stored together

O: May be stored together with specific preventions

continued...

1-BUTANESULPHONIC ACID SODIUM SALT 98%

Version No:2.0

Page 5 of 10

Section 6 - ACCIDENTAL RELEASE MEASURES

X: *Must not be stored together*

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Keep dry.
- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials.
- Protect containers against physical damage.
- Check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials have no OELs on our records

- 1- butanesulfonic acid, sodium salt: CAS:2386- 54- 1

MATERIAL DATA

These "dusts" have little adverse effect on the lungs and do not produce toxic effects or organic disease. Although there is no dust which does not evoke some cellular response at sufficiently high concentrations, the cellular response caused by P.N.O.C.s has the following characteristics:

- the architecture of the air spaces remain intact,
- scar tissue (collagen) is not synthesised to any degree,
- tissue reaction is potentially reversible.

continued...

1-BUTANESULPHONIC ACID SODIUM SALT 98%

Version No:2.0

Page 6 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Extensive concentrations of P.N.O.C.s may:

- seriously reduce visibility,
- cause unpleasant deposits in the eyes, ears and nasal passages,
- contribute to skin or mucous membrane injury by chemical or mechanical action, per se, or by the rigorous skin cleansing procedures necessary for their removal. [ACGIH]


This limit does not apply:

- to brief exposures to higher concentrations
- nor does it apply to those substances that may cause physiological impairment at lower concentrations but for which a TLV has as yet to be determined.

This exposure standard applies to particles which

- are insoluble or poorly soluble* in water or, preferably, in aqueous lung fluid (if data is available) and
- have a low toxicity (i.e.. are not cytotoxic, genotoxic, or otherwise chemically reactive with lung tissue, and do not emit ionizing radiation, cause immune sensitization, or cause toxic effects other than by inflammation or by a mechanism of lung overload).

PERSONAL PROTECTION



EYE

- Safety glasses.
- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves.

OTHER

Overalls.

- Impervious protective clothing.
- Eyewash unit.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-

continued...

1-BUTANESULPHONIC ACID SODIUM SALT 98%

Version No:2.0

Page 7 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

100+ x ES

-

Air- line**

PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:

solvent, vapours, degreasing etc., evaporating from tank (in still air)

aerosols, fumes from pouring operations,

intermittent container filling, low speed

conveyer transfers, welding, spray drift,

plating acid fumes, pickling (released at low

velocity into zone of active generation)

direct spray, spray painting in shallow booths,

drum filling, conveyer loading, crusher dusts,

gas discharge (active generation into zone of

rapid air motion)

grinding, abrasive blasting, tumbling, high

speed wheel generated dusts (released at high

initial velocity into zone of very high rapid

air motion).

Air Speed:

0.25- 0.5 m/s (50- 100 f/min)

0.5- 1 m/s (100- 200 f/min.)

1- 2.5 m/s (200- 500 f/min)

2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

1: Room air currents minimal or favourable to capture

2: Contaminants of low toxicity or of nuisance value only

3: Intermittent, low production.

4: Large hood or large air mass in motion

Upper end of the range

1: Disturbing room air currents

2: Contaminants of high toxicity

3: High production, heavy use

4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

continued...

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

White powder; mixes with water.

PHYSICAL PROPERTIES

Solid.

Mixes with water.

Molecular Weight: 160.17

Melting Range (°C): >300

Solubility in water (g/L): Miscible

pH (1% solution): Not available

Volatile Component (%vol): Negligible

Relative Vapour Density (air=1): >1

Lower Explosive Limit (%): Not available

Autoignition Temp (°C): Not available

State: Divided solid

Boiling Range (°C): Not available

Specific Gravity (water=1): Not available

pH (as supplied): Not applicable

Vapour Pressure (kPa): Negligible

Evaporation Rate: Not applicable

Flash Point (°C): Not available

Upper Explosive Limit (%): Not available.

Decomposition Temp (°C): Not available.

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be damaging to the health of the individual.

Considered an unlikely route of entry in commercial/industrial environments.

Ingestion of anionic surfactants may produce diarrhoea, intestinal distension and occasional vomiting. Lethal doses in animals range from 1 to 5 gm/kg.

EYE

Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

Direct eye contact with some concentrated anionic surfactants produces corneal damage, in some cases severe. Low concentrations may produce immediate discomfort, conjunctival

hyperaemia, and oedema of the corneal epithelium. Healing may take several days. Temporary clouding of the cornea may occur.

SKIN

Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Anionic surfactants generally produce skin reactions following the removal of natural oils. The skin may appear red and may become sore. Papular dermatitis may also develop. Sensitive individuals may exhibit cracking, scaling and blistering.

Repeated skin contact with some sulfonated surfactants has produced sensitisation dermatitis in predisposed individuals.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

CHRONIC HEALTH EFFECTS

On the basis, primarily, of animal experiments, concern has been expressed by at least one classification body that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Limited evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a significant number of individuals at a greater frequency than would be expected from the response of a normal population.

Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking.

There exists limited evidence that shows that skin contact with the material is capable either of inducing a sensitisation reaction in a significant number of individuals, and/or of producing positive response in experimental animals.

Principal routes of exposure are usually by skin contact/absorption and inhalation of generated dust.

Alkyl-substituted sulfonates have mutagenic potential due to their alkylating properties. Alkylating agents may damage the stem cell which acts as the precursor to components of the blood. Loss of the stem cell may result in pancytopenia (a reduction in the number of red and white blood cells and platelets) with a latency period corresponding to the lifetime of the individual blood cells. Granulocytopenia (a reduction in granular

1-BUTANESULPHONIC ACID SODIUM SALT 98%

Version No:2.0

Page 10 of 10

Section 11 - TOXICOLOGICAL INFORMATION

leukocytes) develops within days and thrombocytopenia (a disorder involving platelets), within 1-2 weeks, whilst loss of erythrocytes (red blood cells) need months to become clinically manifest. Aplastic anaemia develops due to complete destruction of the stem cells.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

TOXICITY AND IRRITATION

No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Toxicity Fish: TLm(96)2700mg/L

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM: None

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS:UN, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

No regulations applicable

No data available for 1-butanefulfonic acid, sodium salt as CAS: 2386-54-1.

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 12-May-2018