

4-CHLOROBUTYRYL CHLORIDE

GHS Safety Data Sheet

Version No:4.1.1.1
Page 1 of 9

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

4-CHLOROBUTYRYL CHLORIDE

OTHER NAMESC4-H6-Cl2-O, Cl(CH₂)₃COCl, "butyryl chloride, 4-chloro-"**PROPER SHIPPING NAME**

TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S.(contains 4-chlorobutyryl chloride)

PRODUCT USE

Intermediate. Easily removed protecting group used in peptide synthesis.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V.Ind.Estate,

248, Worli Road,

Mumbai- 400030, India

www.sdfine.com

Telephone: 91- 22 24959898/99

Fax: 91- 22 2493 7232

Email: technical@sdfine.com

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity Category 2

Acute Toxicity Category 4

Flammable Liquid Category 4

Metal Corrosion Category 1

Serious Eye Damage Category 1

Skin Corrosion/Irritation Category 1A

**EMERGENCY OVERVIEW****HAZARD**

DANGER

Determined by using GHS criteria

H227	Combustible Liquid
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H330	Fatal if inhaled.

PRECAUTIONARY STATEMENTS**Prevention****Code**

P210

Phrase

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

continued...

4-CHLOROBUTYRYL CHLORIDE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 2 of 9

Section 2 - HAZARDS IDENTIFICATION

P234	Keep only in original container.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash ... thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well- ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	Wear respiratory protection.
Response Code	Phrase
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P320	Specific treatment is urgent (see MSDS).
P330	Rinse mouth.
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
Storage Code	Phrase
P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P403+P235	Store in a well- ventilated place. Keep cool.
P405	Store locked up.
P406	Store in corrosive resistant container or with a resistant inner liner.
Disposal Code	Phrase
P501	Dispose of contents/container to ...

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
4- chlorobutryl chloride	4635-59-0	>98
hydrolyses in water to produce hydrogen chloride	7647-01-0.	

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

EYE

- If this product comes in contact with the eyes:
- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.

SKIN

- If skin or hair contact occurs:
- Immediately flush body and clothes with large amounts of water, using safety shower if available.
- Quickly remove all contaminated clothing, including footwear.
- Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
- Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.

continued...

4-CHLOROBUTYRYL CHLORIDE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 3 of 9

Section 4 - FIRST AID MEASURES

- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.
- Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).
- As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.
- Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.

NOTES TO PHYSICIAN

- For acute or short term repeated exposures to strong acids:
 - Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
 - Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
 - Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
 - Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

Depending on the degree of exposure, periodic medical examination is indicated. The symptoms of lung oedema often do not manifest until a few hours have passed and they are aggravated by physical effort.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- DO NOT use water.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- Heating may cause expansion or decomposition leading to violent rupture of containers.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), hydrogen chloride, phosgene, other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.
- Check regularly for spills and leaks.
- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

continued...

4-CHLOROBUTYRYL CHLORIDE

GHS Safety Data Sheet

Version No:4.1.1.1
Page 4 of 9

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

PACKAGING MATERIAL INCOMPATIBILITIES

Chemical Name Container Type
" Acetal (Delrin)" , " Cast iron" , Neoprene

SUITABLE CONTAINER

- Glass container is suitable for laboratory quantities.
- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure. <</>.

All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed.

STORAGE INCOMPATIBILITY

- Hydrogen chloride:
 - reacts strongly with strong oxidisers (releasing chlorine gas), acetic anhydride, caesium cyanotridecahydrodecaborate(2-), ethylidene difluoride, hexalithium disilicide, metal acetylide, sodium, silicon dioxide, tetraselenium tetranitride, and many organic materials
 - is incompatible with alkaline materials, acetic anhydride, acetylides, aliphatic amines, alkanolamines, alkylene oxides, aluminium, aluminium-titanium alloys, aromatic amines, amines, amides, 2-aminoethanol, ammonia, ammonium hydroxide, borides, calcium phosphide, carbides, carbonates, cyanides, chlorosulfonic acid, ethylenediamine, ethyleneimine, epichlorohydrin, formaldehyde, isocyanates, metals, metal oxides, metal hydroxides, metal acetylides, metal carbides, oleum, organic anhydrides, potassium permanganate, perchloric acid, phosphides, 3-propiolactone, silicides, sulfides, sulfites, sulfuric acid, uranium phosphide, vinyl acetate, vinylidene fluoride
 - attacks most metals forming flammable hydrogen gas, and some plastics, rubbers and coatings
 - reacts with zinc, brass, galvanised iron, aluminium, copper and copper alloys.
 - Reacts with mild steel, galvanised steel / zinc producing hydrogen gas which may form an explosive mixture with air.
 - Segregate from alcohol, water.
 - Avoid strong bases.
 - Avoid reaction with oxidising agents.
 - NOTE: May develop pressure in containers; open carefully. Vent periodically.

STORAGE REQUIREMENTS

- Store in original containers.
 - Keep containers securely sealed.
 - Store in a cool, dry, well-ventilated area.
 - Store away from incompatible materials and foodstuff containers.
- Moisture sensitive.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	Peak ppm	Peak mg/m ³
India Permissible Levels of Certain Chemical Substances in Work Environment	hydrogen chloride (Hydrogen chloride)	5	7

The following materials had no OELs on our records

- 4- chlorobutyryl chloride:

CAS:4635- 59- 0

continued...

4-CHLOROBUTYRYL CHLORIDE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 5 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

MATERIAL DATA

4-CHLOROBUTYRYL CHLORIDE:

HYDROGEN CHLORIDE:

- for hydrogen chloride:

Odour Threshold Value: 0.262 ppm (detection), 10.06 ppm (recognition)

NOTE: Detector tubes for hydrochloric acid, measuring in excess of 1 ppm, are available commercially.

Hydrogen chloride is a strong irritant to the eyes, mucous membranes and skin.

4-CHLOROBUTYRYL CHLORIDE:

- No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION



RESPIRATOR

- Type B-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure
- Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- Alternatively a gas mask may replace splash goggles and face shields.

HANDS/FEET

- Elbow length PVC gloves.
 - When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.
- The selection of the suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
- Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:
- Neoprene gloves.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.

ENGINEERING CONTROLS

- Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Light-yellow liquid with unpleasant smell; hydrolyses in water.

PHYSICAL PROPERTIES

Corrosive.

Acid.

Toxic or noxious vapours/gas.

State

LIQUID

Molecular Weight

141.00

continued...

4-CHLOROBUTYRYL CHLORIDE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 6 of 9

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Melting Range (°C)	Not available	Viscosity	Not Available
Boiling Range (°C)	173- 174	Solubility in water (g/L)	Reacts
Flash Point (°C)	72	pH (1% solution)	Not available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°C)	440.00	Vapour Pressure (kPa)	0.4 @ 20 C
Upper Explosive Limit (%)	Not available	Specific Gravity (water=1)	1.258
Lower Explosive Limit (%)	Not available	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	Not available	Evaporation Rate	Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

Health hazard summary table:

Acute toxicity	Acute Tox. (inhal) 2
	Acute Tox. (oral) 4
Skin corrosion/irritation	Skin Corr. 1 A
Serious eye damage/irritation	Eye Dam. 1
Respiratory or skin sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Not applicable
Reproductive toxicity	Not applicable
STOT- single exposure	Not applicable
STOT- repeated exposure	Not applicable
Aspiration hazard	Not applicable

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
- Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident.

EYE

- If applied to the eyes, this material causes severe eye damage.
- Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely.
- Irritation of the eyes may produce a heavy secretion of tears (lachrymation).

SKIN

- Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.
- Skin contact is not thought to produce harmful health effects (as classified under EC Directives using animal models). Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
- Solution of material in moisture on the skin, or perspiration, may markedly increase skin corrosion and accelerate tissue destruction.

INHALED

- Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects.
- The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage.

continued...

4-CHLOROBUTYRYL CHLORIDE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 7 of 9

Section 11 - TOXICOLOGICAL INFORMATION

There may be dizziness, headache, nausea and weakness.

■ Inhalation hazard is increased at higher temperatures.

■ Inhalation of quantities of liquid mist may be extremely hazardous, even lethal due to spasm, extreme irritation of larynx and bronchi, chemical pneumonitis and pulmonary oedema.

■ Hydrogen chloride (HCl) vapour or fumes present a hazard from a single acute exposure.

Exposures of 1300 to 2000 ppm have been lethal to humans in a few minutes.

CHRONIC HEALTH EFFECTS

■ Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining.

Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs. Chronic exposure may inflame the skin or conjunctiva.

Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Chronic minor exposure to hydrogen chloride (HCl) vapour or fume may cause discolouration or erosion of the teeth, bleeding of the nose and gums; and ulceration of the nasal mucous membranes.

Repeated exposures of animals to concentrations of about 34 ppm HCl produced no immediate toxic effects.

Workers exposed to hydrochloric acid suffered from gastritis and a number of cases of chronic bronchitis have also been reported.

Repeated or prolonged exposure to dilute solutions of HCl may cause dermatitis.

TOXICITY AND IRRITATION

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

No significant acute toxicological data identified in literature search.

CARCINOGEN

hydrogen chloride	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3	Not classifiable as to its carcinogenicity to humans
-------------------	---	-------	---	--

SKIN

hydrogen chloride	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	(3C)
hydrogen chloride	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	3C

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
hydrogen chloride	LOW	No Data Available	LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

• Containers may still present a chemical hazard/ danger when empty.

• Return to supplier for reuse/ recycling if possible.

Otherwise:

• If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

• Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws

continued...

4-CHLOROBUTYRYL CHLORIDE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 8 of 9

Section 13 - DISPOSAL CONSIDERATIONS

operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus
- Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: TOXIC,CORROSIVE

HAZCHEM:

2XE

Land Transport UNDG:

Class or division:	6.1	Subsidiary risk:	8
UN No.:	2927	UN packing group:	I
Shipping Name:TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (contains 4-chlorobutryl chloride)			

Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	8
UN/ID Number:	2927	Packing Group:	I
Special provisions:	A4		
Cargo Only			
Packing Instructions:	657	Maximum Qty/Pack:	2.5 L
Passenger and Cargo		Passenger and Cargo	
Packing Instructions:	651	Maximum Qty/Pack:	0.5 L
Passenger and Cargo		Passenger and Cargo	
Limited Quantity		Limited Quantity	
Packing Instructions:	Forbidden	Maximum Qty/Pack:	Forbidden

Shipping name:TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S.(contains 4-chlorobutryl chloride)

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	8
UN Number:	2927	Packing Group:	I
EMS Number:	F- A, S- B	Special provisions:	274 315
Limited Quantities:	0		
Shipping name:TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S.(contains 4-chlorobutryl chloride)			

Section 15 - REGULATORY INFORMATION

REGULATIONS

4-chlorobutryl chloride (CAS: 4635-59-0) is found on the following regulatory lists;

"Acros Transport Information", "Sigma-Aldrich Transport Information", "WHO Guidelines for Drinking-water Quality - Chemicals for which guideline values have not been established"

Regulations for ingredients

continued...

4-CHLOROBUTYRYL CHLORIDE

GHS Safety Data Sheet

Version No:4.1.1.1
Page 9 of 9

Section 15 - REGULATORY INFORMATION

hydrogen chloride (CAS: 7647-01-0) is found on the following regulatory lists;

"Acros Transport Information", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "India Chemical Accidents Rules - Schedule 1: List of Hazardous Chemicals", "India Chemical Accidents Rules - Schedule 3: Named Chemicals", "India Hazardous Wastes (Management, Handling and Transboundary Movement) Rules - Schedule 2: List of Wastes Constituents with Concentration Limits", "India Manufacture, Storage and Import of Hazardous Chemical Rules - Schedule 1: List of Hazardous and Toxic Chemicals", "India Manufacture, Storage and Import of Hazardous Chemical Rules - Schedule 3: List of Hazardous Chemicals for Application of Rules 5 and 7 to 15", "India Permissible Levels of Certain Chemical Substances in Work Environment", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code) - Goods Forbidden for Transport", "International Numbering System for Food Additives", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information", "United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II", "United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control (Red List) - Table II", "WHO Guidelines for Drinking-water Quality - Chemicals for which guideline values have not been established"

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
4- chlorobutryl chloride	4635- 59- 0	Mut3; R68 Rep3; R63 Xn; R22 Xi; R38
hydrogen chloride	7647- 01- 0	Mut3; R68 Rep3; R63 Xn; R22 Xi; R38

- Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

- The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 10-Mar-2018