



CROWN ETHER/15-CROWN-6

GHS SAFETY DATA SHEET

Version No:2.0

Page 1 of 11

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

15-CROWN-5

OTHER NAMES

C10-H20-O5, "1, 4, 7, 10, 13-pentaoxacyclopentadecane", 15-crown-5-ester, "ethylene oxide cyclic pentamer", "pentadecane, 1, 4, 7, 10, 13-pentaoxacyclo-

PROPER SHIPPING NAME

TOXIC LIQUID, ORGANIC, N.O.S.

PRODUCT USE

Cyclic pentamer of ethylene oxide. Used as a phase transfer catalyst and complexing agent which solubilises alkali metals in non-polar solvents.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Oral) Category 4

continued...

CROWN ETHER/15-CROWN-6

Eye Irritation Category 2B
Skin Corrosion/Irritation Category 3



EMERGENCY OVERVIEW

HAZARD

WARNING

Determined by using GHS criteria:
H302 H316 H320
Harmful if swallowed
Causes mild skin irritation
Causes eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation occurs, seek medical advice/attention.
If eye irritation persists, get medical advice/attention.
Specific treatment: refer to Label or MSDS.

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
15- crown- 5	33100-27-5	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

For advice, contact a Poisons Information Centre or a doctor.
· If swallowed do NOT induce vomiting.
· If vomiting occurs, lean patient forward or place on left side (head-down position, if

continued...

CROWN ETHER/15-CROWN-6

possible) to maintain open airway and prevent aspiration.

- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- If pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

continued...

CROWN ETHER/15-CROWN-6

FIRE/EXPLOSION HAZARD

- Combustible.
 - Slight fire hazard when exposed to heat or flame.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
 - May emit acrid smoke.
 - Mists containing combustible materials may be explosive.
- Other combustion products include: carbon dioxide (CO₂).

FIRE INCOMPATIBILITY

Avoid reaction with oxidising agents.

Personal Protective Equipment

- Breathing apparatus.
- Gas tight chemical resistant suit.
- Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable labelled container for waste disposal.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.
- Collect recoverable product into labelled containers for recycling.
- Neutralise/decontaminate residue.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent runoff into drains.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.
- If contamination of drains or waterways occurs, advise emergency services.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+



X



+



X



0



+

CROWN ETHER/15-CROWN-6

- +: May be stored together
O: May be stored together with specific preventions
X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Avoid contact with moisture.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Packaging as recommended by manufacturer.
- Check that containers are clearly labelled.

STORAGE INCOMPATIBILITY

- Avoid oxidising agents, acids, acid chlorides, acid anhydrides.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- 15- crown- 5:

CAS:33100- 27- 5 CAS:168081- 57- 0

CROWN ETHER/15-CROWN-6

MATERIAL DATA

CEL TWA: 0.05 ppm, 0.45 mg/m³

Given the significant biological changes established for 12-crown-4 at 0.5 ppm a CEL has been proposed.

PERSONAL PROTECTION



EYE

No special equipment for minor exposure i.e. when handling small quantities.

· OTHERWISE:

· Safety glasses with side shields.

· Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Rubber Gloves.

OTHER

· Overalls.

· Eyewash unit.

RESPIRATOR

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	A- AUS P	-	A- PAPR- AUS P
50 x ES	-	A- AUS P	-
100 x ES	-	A- 2 P	A- PAPR- 2 P ^

^ - Full-face.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

continued...

CROWN ETHER/15-CROWN-6

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in specific circumstances. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear, colourless, very hygroscopic liquid; mixes with water.

CROWN ETHER/15-CROWN-6

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

Molecular Weight: 220.27
Melting Range (°C): Not available
Solubility in water (g/L): Miscible
pH (1% solution): Not available
Volatile Component (%vol): Not available
Relative Vapour Density (air=1): >1
Lower Explosive Limit (%): Not available
Autoignition Temp (°C): Not available
State: Liquid

Boiling Range (°C): 100- 135 (0.2 mm)
Specific Gravity (water=1): 1.109
pH (as supplied): Not applicable
Vapour Pressure (kPa): Not available
Evaporation Rate: Not available
Flash Point (°C): >110
Upper Explosive Limit (%): Not available
Decomposition Temp (°C): Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

As cyclic polyethers (polyethylene oxides) the crown ethers may be subject to peroxidation although no reports of peroxidation have been reported.
BREITHERICK L.: Handbook of Reactive Chemical Hazards.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Considered an unlikely route of entry in commercial/industrial environments.

Oral administration of 18-crown-6 to dogs produced transitory signs of tremulous movement and paralysis of the hind-limbs 2 to 12 hours after administration. Single oral doses of 12-crown-4 (100 mg/kg) produced CNS effects and testicular atrophy in rats. Toxic action of the crown ethers may involve the complexing of electrolytes leading to a change in the permeability of cell membranes to sodium and potassium.

EYE

Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

continued...

SKIN

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

The liquid may produce skin discomfort following prolonged contact. Defatting and/or drying of the skin may lead to dermatitis.

Open cuts, abraded or irritated skin should not be exposed to this material.

Toxic effects may result from skin absorption.

Skin absorption of 12-crown-4 produced CNS effects in rabbits. Larger macrocyclic crowns produced only skin redness.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.

INHALED

Inhalation may produce health damage*.

The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation, of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

Not normally a hazard due to non-volatile nature of product.

Inhalation of vapour is more likely at higher than normal temperatures.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures.

Long-term exposure to 12-crown-4 (0.5 and 1.0 ppm/ 7hrs/day/ 5days/week for 3 weeks) produced testicular atrophy (associated with degeneration of the germinal epithelium), atrophy of the prostate and seminal vesicles and degradation of conditioned behavioral performance, depression of food and water intake, retardation of growth and body tremors.

All effects were reversible although urogenital effects persisted for up to 4 months.

As with any chemical product, contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided by observing good occupational work practice.

TOXICITY AND IRRITATION

TOXICITY

Oral (rat) LD50: 1410 mg/kg

Intraperitoneal (rat): 530 mg/kg

Oral (mouse) LD50: 1020 mg/kg

Intraperitoneal (mouse) LD50: 514 mg/kg

Dermal (rabbit) LD50: 2520 mg/kg

Intraperitoneal (rabbit) LD50: 560 mg/kg

Behavioural effects include tremor and convulsions.

IRRITATION

Skin (rabbit): 100 mg/24h - Mild

Eye (rabbit): 50 mg - Moderate

CROWN ETHER/15-CROWN-6

Page 10 of 11

Section 11 - TOXICOLOGICAL INFORMATION

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant: Not Determined
No data for 15-crown-5.

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: TOXIC
HAZCHEM: 2X

UNDG:

Dangerous Goods Class:	6.1	Subrisk:	None
UN Number:	2810	Packing Group:	III
Shipping Name: TOXIC LIQUID, ORGANIC, N.O.S.			

Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	None
UN/ID Number:	2810	Packing Group:	III
ERG Code:	6L		
Shipping name: TOXIC LIQUID, ORGANIC, N.O.S.			

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	None
UN Number:	2810	Packing Group:	III
EMS Number:	F- A, S- A	Marine Pollutant:	Not Determined
Shipping name: TOXIC LIQUID, ORGANIC, N.O.S.			

Section 15 - REGULATORY INFORMATION

REGULATIONS

No regulations applicable
No data available for 15-crown-5 as CAS: 33100-27-5, CAS: 168081-57-0.

continued...

CROWN ETHER/15-CROWN-6

Page 11 of 11

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
15- crown- 5	33100- 27- 5, 168081- 57- 0

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 12-May-2018