

CATECHOL

GHS Safety Data Sheet

Page 1 of 14

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

CATECHOL

OTHER NAMES

C₆-H₆-O₂, C₆-H₄(OH)₂, pyrocatechol, "1, 2-benzenediol", "1, 2-benzenediol", "pyrocatectomolic acid", "oxyphenic acid", "1, 2-dihydroxybenzene", "1, 2-dihydroxybenzene", "pyrocatechinic acid", pyrocatechin, o-dihydroxybenzene, o-dihydroxybenzene, o-diphenol, o-diphenol, o-hydroxyquinone, o-hydroxyquinone, o-hydroxyphenol, o-hydroxyphenol, o-phenylenediol, o-phenylenediol,

PROPER SHIPPING NAME

TOXIC SOLID, ORGANIC, N.O.S.

PRODUCT USE

Used for fur dyeing, chemical laboratories, photography and in the manufacture of medicinals.

SUPPLIER

Company: S D FINE- CHEM LIMITED

Address:

315- 317, T.V. INDUSTRIAL ESTATE,

248, WORLI,

MUMBAI- 400030.INDIA.


technical@sdfine.com

Telephone: 91- 22- 24959898

Telephone: 91- 22- 24959899

Fax: 91- 22- 24937232

HAZARD RATINGS



continued...

CATECHOL

Section 2 - HAZARDS IDENTIFICATION

GHS Classification

Acute Toxicity (Dermal) Category 4
Acute Toxicity (Oral) Category 3
Eye Irritation Category 2A
Respiratory Irritation Category 3
Skin Corrosion/Irritation Category 2



EMERGENCY OVERVIEW

HAZARD

DANGER
Determined by using GHS criteria:
H335 H301 H312 H315 H319
May cause respiratory irritation
Toxic if swallowed
Harmful in contact with skin
Causes skin irritation
Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Wash hands thoroughly after handling.
Wash thoroughly after handling.
Wear protective gloves/clothing
Do not eat, drink or smoke when using this product.

Response

Wash contaminated clothing before reuse.
IF ON SKIN: Gently wash with plenty of soap and water.
Wear eye/face protection.
If eye irritation persists, get medical advice/attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation occurs, seek medical advice/attention.
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
Specific treatment: refer to Label or MSDS.
Call a POISON CENTER or doctor/physician if you feel unwell.
Wash/Decontaminate removed clothing before reuse.
Remove/Take off immediately all contaminated clothing

CATECHOL

Section 2 - HAZARDS IDENTIFICATION

Storage

Store locked up.

Disposal

Dispose of contents and container in accordance with relevant legislation.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
catechol	120-80-9	98

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If dust is inhaled, remove from contaminated area.
- Encourage patient to blow nose to ensure clear passage of breathing.
- If irritation or discomfort persists seek medical attention.

NOTES TO PHYSICIAN

For acute or short term repeated exposures to phenols/ cresols:

- Phenol is absorbed rapidly through lungs and skin. [Massive skin contact may result in collapse and death]*
- [Ingestion may result in ulceration of upper respiratory tract; perforation of oesophagus and/or stomach, with attendant complications, may occur. Oesophageal stricture may occur.]*
- An initial excitatory phase may present. Convulsions may appear as long as 18 hours after ingestion. Hypotension and ventricular tachycardia that require vasopressor and antiarrhythmic therapy, respectively, can occur.
- Respiratory arrest, ventricular dysrhythmias, seizures and metabolic acidosis may complicate severe phenol exposures so the initial attention should be directed towards

continued...

CATECHOL

Section 4 - FIRST AID MEASURES

stabilisation of breathing and circulation with ventilation, intubation, intravenous lines, fluids and cardiac monitoring as indicated.

- [Vegetable oils retard absorption; do NOT use paraffin oils or alcohols. Gastric lavage, with endotracheal intubation, should be repeated until phenol odour is no longer detectable; follow with vegetable oil. A saline cathartic should then be given.]*

ALTERNATIVELY: Activated charcoal (1g/kg) may be given. A cathartic should be given after oral activated charcoal.

- Severe poisoning may require slow intravenous injection of methylene blue to treat methaemoglobinaemia.

- [Renal failure may require haemodialysis.]*

- Most absorbed phenol is biotransformed by the liver to ethereal and glucuronide sulfates and is eliminated almost completely after 24 hours. [Ellenhorn and Barceloux: Medical Toxicology] *[Union Carbide]

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker who has been exposed to the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
1. Total phenol in blood	250 mg/gm creatinine	End of shift	B, NS

B: Background levels occur in specimens collected from subjects NOT exposed

NS: Non-specific determinant; also seen in exposure to other materials.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog - Large fires only.

FIRE FIGHTING

- Use water delivered as a fine spray to control fire and cool adjacent area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

FIRE/EXPLOSION HAZARD

- Solid which exhibits difficult combustion or is difficult to ignite.
- Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust may burn rapidly and fiercely if ignited.
- Dry dust can also be charged electrostatically by turbulence, pneumatic transport, pouring, in exhaust ducts and during transport.
- Build-up of electrostatic charge may be prevented by bonding and grounding.
- Powder handling equipment such as dust collectors, dryers and mills may require

continued...

CATECHOL

Section 5 - FIRE FIGHTING MEASURES

additional protection measures such as explosion venting.

- All movable parts coming in contact with this material should have a speed of less than 1-metre/sec.

Combustion products include:.

carbon monoxide (CO) phenolics and other pyrolysis products typical of burning organic material.

FIRE INCOMPATIBILITY

Avoid contamination with strong oxidising agents as ignition may result.

Personal Protective Equipment

Breathing apparatus.

Gas tight chemical resistant suit.

Limit exposure duration to 1 BA set 30 mins.

Section 6 - ACCIDENTAL RELEASE MEASURES

EMERGENCY PROCEDURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid contact with skin and eyes.
- Wear impervious gloves and safety glasses.
- Use dry clean up procedures and avoid generating dust.
- Sweep up or
- Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).
- Place spilled material in clean, dry, sealable, labelled container.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Control personal contact by using protective equipment and dust respirator.
- Prevent spillage from entering drains, sewers or water courses.
- Avoid generating dust.
- Sweep, shovel up. Recover product wherever possible.
- Put residues in labelled plastic bags or other containers for disposal.
- If contamination of drains or waterways occurs, advise emergency services.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

catechol 25 ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

catechol 25 ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

catechol 15 ppm

continued...

CATECHOL

Section 6 - ACCIDENTAL RELEASE MEASURES

The threshold concentration below which most people will experience no appreciable risk of health effects:
catechol 5 ppm


American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	$\geq 0.1\%$	Toxic (T)	$\geq 3.0\%$
R50	$\geq 0.25\%$	Corrosive (C)	$\geq 5.0\%$
R51	$\geq 2.5\%$		
else	$\geq 10\%$		

where percentage is percentage of ingredient found in the mixture

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

Avoid reaction with oxidising agents.
Avoid strong bases.

STORAGE REQUIREMENTS

- Keep dry.
- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.

continued...

CATECHOL

Section 7 - HANDLING AND STORAGE

- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials.
- Protect containers against physical damage.
- Check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records


- catechol:

CAS:120- 80- 9 CAS:37349- 32- 9 CAS:16474- 89- 8
CAS:16474- 90- 1

MATERIAL DATA

Phenol and catechol produce similar toxic actions although catechol is considerably less toxic than phenol in animal tests following inhalation. By other exposure routes catechol is considerably more toxic. The TLV-TWA is thought to be protective against the significant risk of dermal and upper respiratory tract irritation and central nervous system effects, including convulsion.

PERSONAL PROTECTION



EYE

- Safety glasses.
- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves.

CATECHOL

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OTHER

Overalls.

- Impervious protective clothing.
- Eyewash unit.

RESPIRATOR

Protection Factor	Half- Face Respirator	Full- Face Respirator	Powered Air Respirator
10 x ES	P1 Air- line*	- -	PAPR- P1 -
50 x ES	Air- line**	P2	PAPR- P2
100 x ES	-	P3	-
		Air- line*	-
100+ x ES	-	Air- line**	PAPR- P3

* - Negative pressure demand ** - Continuous flow.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

For further information consult your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood - local control only

continued...

CATECHOL

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

White to faint tan odourless powder; mixes with water.
Soluble in most organic solvents. May discolour on exposure to air and light.

PHYSICAL PROPERTIES

Solid.
Mixes with water.

Molecular Weight: 110.12
Melting Range (°C): 105
Solubility in water (g/L): Miscible
pH (1% solution): <7
Volatile Component (%vol): Not available
Relative Vapour Density (air=1): 3.79
Lower Explosive Limit (%): Not applicable
Autoignition Temp (°C): Not available.
State: Divided solid

Boiling Range (°C): 245.5
Specific Gravity (water=1): 1.34
pH (as supplied): Not applicable
Vapour Pressure (kPa): 1.33 @ 20 C
Evaporation Rate: Not available
Flash Point (°C): 127
Upper Explosive Limit (%): Not applicable
Decomposition Temp (°C): Not available
Viscosity: Not available

log Kow: 0.88-1.01

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

continued...

CATECHOL

Section 11 - TOXICOLOGICAL INFORMATION

SWALLOWED

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Considered an unlikely route of entry in commercial/industrial environments.

Some phenol derivatives may produce mild to severe damage within the gastrointestinal tract. Absorption may result in profuse perspiration, intense thirst, nausea, vomiting, diarrhoea, cyanosis (following the formation of methaemoglobin), hyperactivity, stupor, falling blood pressure, hypernea, abdominal pain, haemolysis, convulsions, coma and pulmonary oedema followed by pneumonia. Respiratory failure and kidney damage may follow. Severe phenol ingestions cause hypotension, coma, ventricular dysrhythmias, seizures and white coagulative chemical burns.

Phenol does not uncouple oxidative phosphorylation like dinitrophenol and pentachlorophenol and thus does not cause a heat exhaustion-like syndrome. Phenolic groups with ortho and para positions free from substitution are reactive; this is because the ortho and para positions on the aromatic ring are highly activated by the phenolic hydroxyl group and are therefore readily substituted.

EYE

Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.

Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.

Some phenol derivatives may produce mild to severe eye irritation with redness, pain and blurred vision. Permanent eye injury may occur; recovery may also be complete or partial.

SKIN

Skin contact with the material may be harmful; systemic effects may result following absorption.

Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.

Open cuts, abraded or irritated skin should not be exposed to this material.

The material may accentuate any pre-existing skin condition.

Phenol and some of its derivatives may produce mild to severe skin irritation on repeated or prolonged contact, producing second and third degree chemical burns. Rapid cutaneous absorption may lead to systemic toxicity affecting the cardiovascular and central nervous system. Absorption through the skin may result in profuse perspiration, intense thirst, nausea, vomiting, diarrhoea, cyanosis (following the formation of methaemoglobin), hyperactivity, stupor, falling blood pressure, hyperpnoea, abdominal pain, haemolysis, convulsions, coma and pulmonary oedema followed by pneumonia. Respiratory failure and kidney damage may follow.

CATECHOL

Section 11 - TOXICOLOGICAL INFORMATION

INHALED

Limited evidence exists, or practical experience predicts, that the material produces irritation of the respiratory system in a significant number of individuals following inhalation.

Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.

Pulmonary absorption may lead to systemic toxicity affecting the cardiovascular and central nervous system. Inhalation of phenol and some of its derivatives may produce profuse perspiration, intense thirst, nausea, vomiting, diarrhoea, cyanosis, hyperactivity, stupor, falling blood pressure, hyperpnoea, abdominal pain, haemolysis, convulsions, coma and pulmonary oedema with pneumonia. Respiratory failure and kidney damage may follow. Phenols may exhibit local anaesthetic properties and, in general, are central nervous system depressants at high concentrations. The dihydroxy derivatives act as simple phenols but their effects are largely limited to local irritation. Trihydroxy derivatives may reduce the oxygen content of blood at sufficient exposure levels. Methyl phenols (cresols) typically do not pose significant inhalation hazards due to relatively low vapour pressures and objectionable odours. Substituted phenols produce similar effects to phenol although such effects may only be evident at high levels of exposure. Alkyl substitution tends to increase toxicity.

CHRONIC HEALTH EFFECTS

Principal routes of exposure are usually by.

skin contact/absorption and inhalation of generated dust.

Prolonged exposure to some derivatives of phenol may produce dermatitis, anorexia, weight loss, weakness, muscle aches and pain, liver damage, dark urine, ochronosis, skin eruptions, diarrhoea, nervous disorders with headache, salivation, fainting, increased skin and scleral pigmentation, vertigo and mental disorders. Liver and kidney damage may also ensue. Chronic phenol toxicity was first noted in medical personnel in the late 1800s when 5 and 10% phenol was used as a skin disinfectant. The term carbolic (phenol) marasmus was given to this syndrome.

Addition of structurally related phenolic compounds to the diet of Syrian golden hamsters induced forestomach hyperplasia and tumours. These compounds included 2(3)-tert-butyl-4-methoxyphenol (BHA) (CAS RN: 25013-16-5), 2-tert-butyl-4-methylphenol (TBMP) (29759-28-2) and p-tert-butylphenol (PTBP) (98-54-4); less active were catechol (154-23-4), p-methylphenol (331-39-5), methylhydroquinone (MHQ) (95-71-6) and pyrogallol (87-66-1), whilst no activity was seen with resorcinol (108-46-3), hydroquinone (123-31-9), propylparaben (94-13-3) and tert-butylhydroquinone (TBHQ) (1948-33-0).

In autoradiographic studies, intake of BHA, TBMP, catechol, PMOP, PTBP and MHQ resulted in a significant increase in the labelling index of the forestomach epithelium, whilst PMOP induced epithelial damage and pyloric regenerative hyperplasia. Catechol, CA and PYMP induced similar but less marked alterations. Both catechol and PMOP increased the labelling index in the glandular stomach. The urinary bladder was free from histo-pathological lesions, but propylparabene, catechol, TBHQ and MHQ increased the labelling index. The authors of this study concluded that long term administration of PTBP and TBMP may be carcinogenic for hamster forestomach and that both 1-hydroxy and tert-butyl substituents may play a role in the induction of forestomach tumours.

Hiros, M., et al: Carcinogenesis, Vol 7, pp 1285-1289; 1986.

TOXICITY AND IRRITATION

TOXICITY

Oral (rat) LD50: 260 mg/kg

Dermal (rabbit) LD50: 800 mg/kg

IRRITATION

Nil Reported

continued...

CATECHOL

Section 11 - TOXICOLOGICAL INFORMATION

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant:	Not Determined
Hazardous Air Pollutant:	Yes
BCF<100:	0.88/1.01
Half- life Soil - High (hours):	168
Half- life Soil - Low (hours):	24
Half- life Air - High (hours):	26
Half- life Air - Low (hours):	2.6
Half- life Surface water - High (hours):	168
Half- life Surface water - Low (hours):	24
Half- life Ground water - High (hours):	336
Half- life Ground water - Low (hours):	48
Aqueous biodegradation - Aerobic - High (hours):	168
Aqueous biodegradation - Aerobic - Low (hours):	24
Aqueous biodegradation - Anaerobic - High (hours):	672
Aqueous biodegradation - Anaerobic - Low (hours):	96
Aqueous biodegradation - Removal secondary treatment - High (hours):	98.80%
Aqueous biodegradation - Removal secondary treatment - Low (hours):	97.50%
Photooxidation half- life water - High (hours):	3840
Photooxidation half- life water - Low (hours):	77
Photooxidation half- life air - High (hours):	26
Photooxidation half- life air - Low (hours):	2.6

log Kow: 0.88-1.01

Koc: 72

COD: 1.89

ThOD: 1.89

BCF: 3

Toxicity Fish: LC50(48)14mg/L

Toxicity invertebrate: LD0 1.6prt -90bac mg/L

Bioaccumulation: unlikely

Effects on algae and plankton: algae LD0 6mg/L

Degradation Biological: soil microflora -1 day, sig
processes Abiotic: oxid,no photol,

Section 13 - DISPOSAL CONSIDERATIONS

- Consult manufacturer for recycling options and recycle where possible .
- Consult State Land Waste Management Authority for disposal.
- Incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

CATECHOL

Section 14 - TRANSPORTATION INFORMATION



Labels Required: TOXIC
HAZCHEM: 2X

UNDG:

Dangerous Goods Class:	6.1	Subrisk:	None
UN Number:	2811	Packing Group:	III
Shipping Name: TOXIC SOLID, ORGANIC, N.O.S.			

Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	None
UN/ID Number:	2811	Packing Group:	III
ERG Code:	6L		
Shipping name: TOXIC SOLID, ORGANIC, N.O.S.			

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	None
UN Number:	2811	Packing Group:	III
EMS Number:	F- A, S- A	Marine Pollutant:	Not Determined
Shipping name: TOXIC SOLID, ORGANIC, N.O.S.			

Section 15 - REGULATORY INFORMATION

REGULATIONS

catechol (CAS: 120-80-9) is found on the following regulatory lists;
International Agency for Research on Cancer (IARC) Carcinogens
International Council of Chemical Associations (ICCA) - High Production Volume List
OECD Representative List of High Production Volume (HPV) Chemicals

No data available for catechol as CAS: 37349-32-9, CAS: 16474-89-8, CAS: 16474-90-1.

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
catechol	120- 80- 9, 37349- 32- 9, 16474 - 89- 8, 16474- 90- 1

continued...

CATECHOL

Section 16 - OTHER INFORMATION

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose private study, research, review or criticism, as permitted under the Copyright

Issue Date: 16-Jun-2018