

DI-IODOMETHANE

GHS Safety Data Sheet

Version No:4.1.1.1
Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME
DI-IODOMETHANE

OTHER NAMES
CH₂I₂, "methane, diiodo", "methylene diiodide", "MI GEE", "NSC 35804"

PROPER SHIPPING NAME
TOXIC LIQUID, ORGANIC, N.O.S.(contains methylene iodide)

PRODUCT USE
In separating mixtures of minerals. In determining the specific gravity of minerals and other substances. In the manufacture of X-ray contrast media.

SUPPLIER
Company: S D FINE- CHEM LIMITED
Address:
315- 317, T.V.Ind.Estate,
248, Worli Road,
Mumbai- 400030, India
www.sdfine.com
Telephone: 91- 22 24959898/99
Fax: 91- 22 2493 7232
Email: technical@sdfine.com

Section 2 - HAZARDS IDENTIFICATION

GHS Classification
Acute Toxicity Category 4
Acute Toxicity Category 4
Eye Irritation Category 2A
Skin Corrosion/Irritation Category 2
STOT - SE Category 3



EMERGENCY OVERVIEW

HAZARD
WARNING

Determined by using GHS criteria

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Prevention

Code	Phrase
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash ... thoroughly after handling.

continued...

DI-IODOMETHANE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 2 of 8

Section 2 - HAZARDS IDENTIFICATION

P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well- ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Response Code	Phrase
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P330	Rinse mouth.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing and wash before re- use.
Storage Code	Phrase
P403+P233	Store in a well- ventilated place. Keep container tightly closed.
P405	Store locked up.
Disposal Code	Phrase
P501	Dispose of contents/container to ...

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
methylene iodide	75-11-6	>98

Section 4 - FIRST AID MEASURES

SWALLOWED

- IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY.
- For advice, contact a Poisons Information Centre or a doctor.
- Urgent hospital treatment is likely to be needed.
- In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition.
- Avoid giving milk or oils.
- Avoid giving alcohol.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Treat symptomatically.
- for intoxication due to Freons/ Halons;
A: Emergency and Supportive Measures

continued...

DI-IODOMETHANE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 3 of 8

Section 4 - FIRST AID MEASURES

- Maintain an open airway and assist ventilation if necessary
 - Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
 - Monitor the ECG for 4-6 hours
- B: Specific drugs and antidotes:
- There is no specific antidote.
- The material may induce methaemoglobinaemia following exposure.
- Initial attention should be directed at oxygen delivery and assisted ventilation if necessary. Hyperbaric oxygen has not demonstrated substantial benefits.
 - Hypotension should respond to Trendelenburg's position and intravenous fluids; otherwise dopamine may be needed.
 - Symptomatic patients with methaemoglobin levels over 30% should receive methylene blue. (Cyanosis, alone, is not an indication for treatment). The usual dose is 1-2 mg/kg of a 1% solution (10 mg/ml) IV over 50 minutes; repeat, using the same dose, if symptoms of hypoxia fail to subside within 1 hour.
 - Thorough cleansing of the entire contaminated area of the body, including the scalp and nails, is of utmost importance.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.

FIRE/EXPLOSION HAZARD

- Combustible.
 - Slight fire hazard when exposed to heat or flame.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
- Combustion products include: carbon dioxide (CO₂), hydrogen iodide, other pyrolysis products typical of burning organic material. May emit poisonous fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

MAJOR SPILLS

- Clear area of personnel and move upwind.
 - Alert Fire Brigade and tell them location and nature of hazard.
 - Wear full body protective clothing with breathing apparatus.
 - Prevent, by any means available, spillage from entering drains or water course.
- Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.

continued...

DI-IODOMETHANE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 4 of 8

Section 7 - HANDLING AND STORAGE

- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- DO NOT use aluminium or galvanised containers.
- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure. <</>.

STORAGE INCOMPATIBILITY

■ WARNING:

May decompose violently or explosively on contact with other substances.

- This substance, or one of its components, is one of the relatively few compounds which are described as "endothermic" i.e. heat is absorbed into the compound, rather than released from it, during its formation.
- The majority of endothermic compounds are thermodynamically unstable and may decompose explosively under various circumstances of initiation.
- Many but not all endothermic compounds have been involved in decompositions, reactions and explosions and, in general, compounds with significantly positive values of standard heats of formation, may be considered suspect on stability grounds.

BREITHERICK L.: Handbook of Reactive Chemical Hazards.

Haloalkanes:

- are highly reactive:some of the more lightly substituted lower members are highly flammable; the more highly substituted may be used as fire suppressants, not always with the anticipated results.
- may react with the lighter divalent metals to produce more reactive compounds analogous to Grignard reagents.
- may produce explosive compounds following prolonged contact with metallic or other azides
- may react on contact with potassium or its alloys - although apparently stable on contact with a wide range of halocarbons, reaction products may be shock-sensitive and may explode with great violence on light impact; severity generally increases with the degree of halocarbon substitution and potassium-sodium alloys give extremely sensitive mixtures .

In the presence of moisture and at higher temperatures material breaks down generating hydroiodic, which may corrode and perforate containers.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- methylene iodide:

CAS:75- 11- 6

MATERIAL DATA

METHYLENE IODIDE:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

CEL TWA: 50 ppm, 174 mg/m³

(as analogue for methylene chloride)

PERSONAL PROTECTION



RESPIRATOR

- Type E Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

continued...

DI-IODOMETHANE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 5 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:.

- Neoprene gloves.

OTHER

- Overalls.
- Eyewash unit.
- Barrier cream.
- Skin cleansing cream.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Very heavy, highly refractive liquid; does not mix well with water (1:70). Miscible with alcohol, propanol, isopropanol, hexane, cyclohexane, ether, chloroform, benzene. Darkens on exposure to light, air and moisture.

PHYSICAL PROPERTIES

Liquid.

Does not mix with water.

Sinks in water.

State	Liquid	Molecular Weight	267.84
Melting Range (°C)	6.1	Viscosity	Not Available
Boiling Range (°C)	182	Solubility in water (g/L)	Partly miscible
Flash Point (°C)	>110	pH (1% solution)	Not available.
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not applicable
Autoignition Temp (°C)	Not available.	Vapour Pressure (kPa)	Not available.
Upper Explosive Limit (%)	Not available.	Specific Gravity (water=1)	3.325 @ 20 C
Lower Explosive Limit (%)	Not available.	Relative Vapour Density (air=1)	9.25
Volatile Component (%vol)	Not available.	Evaporation Rate	Not available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

continued...

DI-IODOMETHANE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 6 of 8

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

Health hazard summary table:

Acute toxicity	Acute Tox. (inhal) 4
	Acute Tox. (oral) 4
Skin corrosion/irritation	Skin Irrit. 2
Serious eye damage/irritation	Eye Irrit. 2A
Respiratory or skin sensitization	Not applicable
Germ cell mutagenicity	Not applicable
Carcinogenicity	Not applicable
Reproductive toxicity	Not applicable
STOT- single exposure	STOT SE 3
STOT- repeated exposure	Not applicable
Aspiration hazard	Not applicable

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
- The substance and/or its metabolites may bind to haemoglobin inhibiting normal uptake of oxygen. This condition, known as "methaemoglobinemia", is a form of oxygen starvation (anoxia).

EYE

- This material can cause eye irritation and damage in some persons.

SKIN

- This material can cause inflammation of the skin on contact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.
- The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.
- Inhalation hazard is increased at higher temperatures.
- Acute intoxication by halogenated aliphatic hydrocarbons appears to take place over two stages. Signs of a reversible narcosis are evident in the first stage and in the second stage signs of injury to organs may become evident, a single organ alone is (almost) never involved.
- Depression of the central nervous system is the most outstanding effect of most halogenated aliphatic hydrocarbons. Inebriation and excitation, passing into narcosis, is a typical reaction.
- In the case of iodised and brominated compounds, exposure effects cannot be described by simple central nervous system depression produced by other halogenated aliphatic hydrocarbons. Headache, nausea, ataxia (loss of muscle co-ordination), tremors, speech difficulties, visual disturbances, convulsions, paralysis, delirium, mania and apathy are all evidence of additional effects.
- Inhalation exposure may cause susceptible individuals to show change in heart beat rhythm i.e. cardiac arrhythmia. Exposures must be terminated.

CHRONIC HEALTH EFFECTS

- Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.
- Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Dichloromethane exposures cause liver and kidney damage in animals and this justifies consideration before exposing persons with a history of impaired liver function and/or renal disorders.
- This substance structurally bears resemblance to methylene chloride.

TOXICITY AND IRRITATION

- Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of

continued...

DI-iodomethane

GHS Safety Data Sheet

Version No:4.1.1.1

Page 7 of 8

Section 11 - TOXICOLOGICAL INFORMATION

highly irritating compound.

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
methylene iodide	HIGH	No Data Available	LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.
- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION



Labels Required: TOXIC

HAZCHEM:

2X

Land Transport UNDG:

Class or division:	6.1	Subsidiary risk:	None
UN No.:	2810	UN packing group:	III
Shipping Name: TOXIC LIQUID, ORGANIC, N.O.S. (contains methylene iodide)			

Air Transport IATA:

ICAO/IATA Class:	6.1	ICAO/IATA Subrisk:	None
UN/ID Number:	2810	Packing Group:	III
Special provisions:	A3		

Shipping name: TOXIC LIQUID, ORGANIC, N.O.S. (contains methylene iodide)

Maritime Transport IMDG:

IMDG Class:	6.1	IMDG Subrisk:	None
-------------	-----	---------------	------

continued...

DI-IODOMETHANE

GHS Safety Data Sheet

Version No:4.1.1.1

Page 8 of 8

Section 14 - TRANSPORTATION INFORMATION

UN Number:	2810	Packing Group:	III
EMS Number:	F- A, S- A	Special provisions:	223 274
Limited Quantities:	5 L		
Shipping name: TOXIC LIQUID, ORGANIC, N.O.S.(contains methylene iodide)			

Section 15 - REGULATORY INFORMATION

REGULATIONS

methylene iodide (CAS: 75-11-6) is found on the following regulatory lists;

"Acros Transport Information", "Fisher Transport Information", "India Chemical Accidents Rules - Schedule 1: List of Hazardous Chemicals", "India Hazardous Wastes (Management, Handling and Transboundary Movement) Rules - Schedule 2: List of Wastes Constituents with Concentration Limits", "Sigma-Aldrich Transport Information"

Section 16 - OTHER INFORMATION

■ Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

The above information is believed to be accurate and represent the best information currently available to us, but does not represent any warranty expressed or implied of the properties of the product. User should make their own investigation to determine the suitability of the information for their particular purpose.

Issue Date: 19-Apr-2018